CAREERTRACK DATABASE SCHEMA

MongoDB collections and relationships

Database

Default database name: careertrack. Connection string is configured with MONGO_URI.

admins

_id ObjectId; name; unique lowercase email; passwordHash (bcrypt); role; timestamps.

jobs

_id; title; company; location; employmentType; experienceLevel; salaryRange; description; responsibilities[]; qualifications[]; skills[]; benefits[]; applicationDeadline; status; createdBy (Admin reference); timestamps. Indexes: status + createdAt and text search across title/company/location.

applications

_id; job (Job reference); candidate name/email/phone/education/experience/skills/coverLetter; résumé metadata; status enum; internalNotes[] with Admin reference; timestamps. Unique compound index job + email prevents duplicate applications.

Relationships

Admin 1-to-many Job. Job 1-to-many Application. Application embeds internal notes, each optionally referencing an Admin. Candidate PII and résumé metadata must remain private.

Validation

Required candidate fields, email and phone formats, supported résumé MIME/extension, upload size, allowed job states and fixed application status values are checked in the API/model layer.

ER-style relationship

ADMIN (1) ■■■■■ (M) JOB (1) ■■■■■ (M) APPLICATION; ADMIN (1) ■■■■■ (M) APPLICATION_NOTE; APPLICATION (1) ■■■■■ (M) APPLICATION_NOTE.