
Target Ad Live (for STB)

Version 3.1 authored by  Luc Cools on 2023/06/22 13:59

Table of Contents

- Introduction 3
- NTVBE base solution 3
 - Server locations 3
 - Target Ad proxy TAP 3
 - Target Ad Server 3
 - Target Ad CDN 3
 - HW version information 4
 - TA consent 4
 - Channel enabling 4
- Impact 4
 - AVS console 4
 - UI builder 4
 - urlprov 4

Introduction

On BEP the necessary information is provided to the clients to allow them to perform TA-live functionality without further interaction with the TV backend

To maintain a similar solution when clients are connected to AVS backend similar information needs to be provided to the STB clients

NTVBE base solution

For NTVBE Target Ad Live the same approach as on BEP is chosen

Below are the adapted methods to retrieve the different information elements needed for TA live. Client processing shall be the same as when connected to BEP

Server locations

To enable the client to know where to send request for target advertisement, the address of these servers need to be provided towards those clients.

For this purpose the following server addresses will be provided

- ~~SAP channel for Target advertisements~~
- TAP server address
 - request ad replacement
- TAS server address
 - request daily ad list
- CDN address for downloading ads in unicast mode

Target Ad proxy TAP

- Server Name = TAP
- Server Type = TAP
- TAP Server Address
- TAP Server port number
- request randomization interval (in milliseconds) = randomization value for unicast based on marker download
- VAST Request Randomization = randomization to send VAST request after detecting SCTE marker
- Ad duration Tolerance = max time value difference between SCTE marker time and duration of replacement ad

Target Ad Server

- Server Name
- Server Type = TAS
- TAS Server Address
- TAS Server port number
- AdRetrievalInterval = periodicity for retrieving list of ads
- RequestRandomInterval = randomization to retrieve list after boot

Target Ad CDN

- Server Name
- External IP Address: IPV4/IPV6 or DNS name as which the CDN server is visible towards the clients on the external network (egress side of the CDN).
- External Port: port number through which the file can be fetched (default 80)
- External Protocol: http, https (default http)
- TAPublishingPath: path on the external CDN from which the target ads can be loaded.

HW version information

this is included in the config/app response

- TADTVEnabled: true
- TASTorageSize: 1024
- TAPreDownloadPercentage: 80
- TargetAdDownloadBandwidth :150
- TargetAdCutOffBandwidth
this is a new parameter: in case the totalAssignedBandwidth (for the line) from the get USER/DEVICES response is below this threshold then no support for TA live will be provided

TA consent

Consent for target ad live is contained in

"consentFlag": "Target_Adv_Enabled"

which can be retrieved via /AGL/1.6/R/ENG/ANDROIDSTB/PXS/CUSUSER/CONSENTS

Channel enabling

a Channel is enabled for TA live in case isTargetADVEnabled": true,

No distinction to be made between live and Pause live T

TargetADVInactivity will be provided on channel.extendedMetadata level (no need to provide it on asset level)

Impact

AVS console

create server definitions

UI builder

enhance STB configuration with HW information

urlprov

include isTargetADVEnabledin and TargetADVInactivity in urlprov (values taken from BEP)