

GENERAL INSTRUCTIONS FOR USAGE AND MAINTENANCE

- The Battery should be firmly secured in the cradle. Please ensure that the cable clamps are fitted tightly and properly on the terminals. A loosely held battery vibrates and bounces, causing damage to the container and the plates.
- Connections must be made in the right polarity. Apply petroleum jelly on the terminals to avoid corrosion.
- The regulator charging voltage setting measured across the battery terminals must be maintained at 14.20+ 0.20 volts.
(Excessive voltage than specified would overcharge the battery leading to loss of electrolyte and premature failure of the battery.)
(Lesser voltage than specified voltage would discharge the battery)
- Recharging is required when the horn is weak, lights are dim. Recharging would also be required when the battery/vehicle is left idle for more than 5-6 weeks.
- To get superior performance and maximum life of battery, it is advised to check the R R unit once every 3 to 4 months for maintaining the recommended output voltage
- Battery top should be kept clean & dry

CAUTION

- Avoid installing a lower Ah rating capacity battery than advised by our franchisee / retailer / application chart
- Keep away from sparks, cigarettes and open flame. These can cause an explosion
- Avoid metallic contact across the terminals, as this can result in short circuit / sparking / explosion of the battery
- It is strongly recommended not to use any form of battery additives in the battery
- Keep out of reach of children



SOLANCE INDUSTRIES

228, Vireshwar Industrial Estate, Nr. SKF Bearing,
NH- 8A, Kerala, Ta.:Bavla, Dist.: Ahmedabad, Gujarat.
Mo: +91 722 600 4444 | E: info@solance.in
W: www.solance.in

CONDITIONS OF WARRANTY

- Solance Two Wheeler Battery-Platinum VRLA batteries warranty period is as follows:

Free Replacement	Pro-rata Compensation*	
0-24 Months	25-30 Months	25%
	31-39 Months	20%
	40-48 Months	15%

*Discount applicable on prevailing MRP prices against purchase of new "Solance Platinum Series" two wheeler battery only subject to fulfilling conditions of the warranty terms.

- The liability of the company under this warranty is limited to defect arising only from defective workmanship or the use of faulty material and developing under proper use.
- If the container, covers or parts are damaged due to negligent maintenance or tampering or if these are destroyed in an accident such as fire, wreckage on explosion, the warranty becomes null and void.
- If the defects are due to faulty or spurious vehicle electrical systems, negligent maintenance or improper handling, servicing of the battery by unauthorized dealers or auto electricians, then the warranty is nullified.
- In case the battery is replaced free of charge, the defective battery being replaced with becomes the property of the company and no scrap rebate will be given for it. The warranty period on the battery being repaired, replaced, shall commence from the date of sale of the original battery as stated in the original warranty card and not from the day it is repaired / replaced.
- Recharging is not covered under the preview of this warranty and will be billed extra.
- The service record panel on the warranty card must be filled regularly as a proof of regular maintenance. Failure to do so is liable to invalidate this warranty.
- All claims have to be done by bringing the vehicle at the dealer / office premises.
- Battery used for any other application, other than the specified ones, will not be carried under warranty.
- In case a Service battery is issued, this must be returned within 7 days, failing which a nominal charge per day will be levied.
- In case a battery model is phased out, the dealer reserves the right to provide any other model of the same capacity and suited to the vehicle as settlement of warranty.

Customers are deemed to have read, understood and agreed to these terms and conditions at the time of purchase of the battery.