CC31xx IP Configuration Application

Overview

This sample application demonstrates how to configure a static IP address for CC3100. The device connects to the AP w/ the configured static IP. The IP address will be stored in the FileSystem.

Source Files briefly explained

i. main - Initializes the device, configures cc3100 for static IP and connects to AP.

Application details and Usage

• Edit values for below macros in 'main.c' for configuring the static IP address:

```
#define CONFIG_IP SL_IPV4_VAL(192,168,1,45)
```

• Edit values for below macros in 'main.c' per the APs properties:

```
#define AP_MASK SL_IPV4_VAL(255,255,255,0)

#define AP_GATEWAY SL_IPV4_VAL(192,168,1,1)

#define AP_DNS SL_IPV4_VAL(0,0,0,0)
```

• Edit following parameters in 'main.c - The device connects to this AP on getting the corresponding command from application:

```
#define SSID_NAME "<ap_name>"
```

· Build and run the application

```
The device connect to the '<ap_name>' access-point w/ the static IP defined in 'CONFIG_IP'.

The connection could be checked by pinging CC3100 on the static IP address
```

```
Pinging 192.168.1.45 with 32 bytes of data:
Reply from 192.168.1.45: bytes=32 time=245ms TTL=128
Reply from 192.168.1.45: bytes=32 time=164ms TTL=128
Reply from 192.168.1.45: bytes=32 time=42ms TTL=128
Reply from 192.168.1.45: bytes=32 time=262ms TTL=128

Ping statistics for 192.168.1.45:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 42ms, Maximum = 262ms, Average = 178ms
```

Notes

• To configure the device in DHCP mode again, call 'SL_STA_IPV4_DHCP_SET' after 'sl_Start' - Defining 'USE_DHCP' is this sample example configures the device in DHCP mode

Limitations/Known Issues

None

Article Sources and Contributors

 $\textbf{CC31xx IP Configuration Application} \ \ \textit{Source}: \\ \textbf{http://ap-fpdsp-swapps.dal.design.ti.com/index.php?oldid=188692} \ \ \textit{Contributors}: A0131814, Giansway \\ \textbf{Giansway Source}: \\ \textbf{Gianswa$

Image Sources, Licenses and Contributors

 $\textbf{Image:IP_Config_1.png} \ \ \textit{Source:} \ \text{http://ap-fpdsp-swapps.dal.design.ti.com/index.php?title=File:IP_Config_1.png} \ \ \textit{License:} \ \text{unknown} \ \ \textit{Contributors:} \ \ \text{A0131814} \ \ \text{A0131814}$