


WEEK-2 LAB OBSERVATION

SHASHANK M S – 1BM21CS201



```
Router0
Physical Config CLI
IOS Command Line Interface
IOS (tm) PT1000 Software (PT1000-I-M), Version 12.2(28), RELEASE SOFTWARE (fc5)
Technical Support: http://www.cisco.com/techsupport
Copyright (c) 1986-2005 by Cisco Systems, Inc.
Compiled Wed 27-Apr-04 19:01 by miwang


PT 1001 (PTSC2005) processor (revision 0x200) with 60416K/5120K bytes of memory
.
Processor board ID PT0123 (0123)
PT2005 processor: part number 0, mask 01
Bridging software.
X.25 software, Version 3.0.0.
4 FastEthernet/IEEE 802.3 interface(s)
2 Low-speed serial(sync/async) network interface(s)
32K bytes of non-volatile configuration memory.
63488K bytes of ATA CompactFlash (Read/Write)

--- System Configuration Dialog ---

Continue with configuration dialog? [yes/no]: no

Press RETURN to get started!

Router>enable
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#
```



```
Router0
Physical Config CLI
IOS Command Line Interface

4 FastEthernet/IEEE 802.3 interface(s)
2 Low-speed serial(sync/async) network interface(s)
32K bytes of non-volatile configuration memory.
63488K bytes of ATA CompactFlash (Read/Write)

--- System Configuration Dialog ---


Continue with configuration dialog? [yes/no]: no

Press RETURN to get started!

Router>enable
Router#configure terminal
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#interface fastEthernet 0/0
Router(config-if)#ip address 10.0.0.1 255.0.0.0
Router(config-if)#no shutdown

Router(config-if)#
%LINK-5-CHANGED: Interface FastEthernet0/0, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/0, changed state to
up
%IP-4-DUPADDR: Duplicate address 10.0.0.1 on FastEthernet0/0, sourced by
0030.F2B6.1D54
```



Command Prompt

X

```
PC>ping 10.0.0.1

Pinging 10.0.0.1 with 32 bytes of data:

Reply from 10.0.0.1: bytes=32 time=1ms TTL=255
Reply from 10.0.0.1: bytes=32 time=0ms TTL=255
Reply from 10.0.0.1: bytes=32 time=0ms TTL=255
Reply from 10.0.0.1: bytes=32 time=0ms TTL=255

Ping statistics for 10.0.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms


PC>ping 10.0.0.2

Pinging 10.0.0.2 with 32 bytes of data:

Reply from 10.0.0.2: bytes=32 time=1ms TTL=128
Reply from 10.0.0.2: bytes=32 time=0ms TTL=128
Reply from 10.0.0.2: bytes=32 time=5ms TTL=128
Reply from 10.0.0.2: bytes=32 time=0ms TTL=128

Ping statistics for 10.0.0.2:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 5ms, Average = 1ms


PC>
```



Port	Link	IP Address	IPv6 Address	MAC Address
FastEthernet0	Up	20.0.0.2/8	<not set>	0006.2A07.CD57

Gateway: 10.0.0.1
 DNS Server: <not set>
 Line Number: <not set>

Physical Location: Intercity, Home City, Corporate Office



Port	Link	IP Address	IPv6 Address	MAC Address
FastEthernet0	Up	10.0.0.2/8	<not set>	0030.F2B6.1D54

Gateway: 10.0.0.1
 DNS Server: <not set>
 Line Number: <not set>

Physical Location: Intercity, Home City, Corporate Office

