

Task

Hosting 3-tier studentapp via docker compose

Name – Shashank Sharma

1. Create EC2 instance with ubuntu image and connect it.
2. Install docker in the instance terminal using root user (sudo -i) and after installing docker start the docker using
systemctl start docker

Link - <https://docs.docker.com/engine/install/ubuntu/>

3. Firstly create data base in MySQL for this use command.

```
# docker run -d -p 3306:3306 -e MYSQL_ROOT_PASSWORD=1234
```

```
mysql:latest
```

```
# docker ps
```


```
root@ip-172-31-18-203:~# docker run -d -p 3306:3306 -e MYSQL_ROOT_PASSWORD=1234 mysql:latest
Unable to find image 'mysql:latest' locally
latest: Pulling from library/mysql
9a5c778f631f: Pull complete
9e77c3a95bf2: Pull complete
8b279a2086e0: Pull complete
c8bfbcd7882: Pull complete
d35b074b68ec: Pull complete
e6ea5014e6af: Pull complete
dc3791a61558: Pull complete
52f9323b9f0e: Pull complete
7f7391eab49b: Pull complete
8d2f04b287ee: Pull complete
Digest: sha256:9d1c923e5f66a89607285ee2641f8a53430a1ccd5e4a62b35eb8a48b74b99ff48
Status: Downloaded newer image for mysql:latest
ba77ad53be96aca5ebb3b9fe9f3c628291653d7524e409a2f7c81c206b8281f0
root@ip-172-31-18-203:~# docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
ba77ad53be96	mysql:latest	"docker-entrypoint.s..."	9 seconds ago	Up 7 seconds	0.0.0.0:3306->3306/tcp, :::3306->3306/tcp, 33060/tcp	hardcore_snyder

```
# docker exec -it <container-id> mysql -u root -p1234
```

4. After entering this command you enter into the mysql use commands to create database.

```
create database studentapp;
use studentapp;
CREATE TABLE if not exists students(student_id INT NOT NULL
AUTO_INCREMENT,
    student_name VARCHAR(100) NOT NULL,
    student_addr VARCHAR(100) NOT NULL,
    student_age VARCHAR(3) NOT NULL,
    student_qual VARCHAR(20) NOT NULL,
    student_percent VARCHAR(10) NOT NULL,
    student_year_passed VARCHAR(10) NOT NULL,
    PRIMARY KEY (student_id)
);
desc students;
exit
```



```
mysql> create database studentapp;
Query OK, 1 row affected (0.00 sec)

mysql> use studentapp;
Database changed

mysql> CREATE TABLE if not exists students(student_id INT NOT NULL AUTO_INCREMENT,
-> student_name VARCHAR(100) NOT NULL,
-> student_addr VARCHAR(100) NOT NULL,
-> student_age VARCHAR(3) NOT NULL,
-> student_qual VARCHAR(20) NOT NULL,
-> student_percent VARCHAR(10) NOT NULL,
-> student_year_passed VARCHAR(10) NOT NULL,
-> PRIMARY KEY (student_id)
-> );
Query OK, 0 rows affected (0.03 sec)
```

5. To see image ip. (mysql ip)
docker inspect <container-id> |grep "IP"
6. Copy mysql ip for the further use.


❖ Backend

1. Create repo in git or use existing and make two folder in the repo.
 - 1.frontend
 - 2.backend
2. In backend create three files.
 - 1.Dockerfile -> your image
 - 2.context.xml -> add mysql IP
 - 3.studnet.war ->
3. Make git clone and build docker image.
docker build .
docker images
Assign ip to image -> docker run -d -p 8080:8080 <image-id>
docker ps
4. Hit ip to see hosting.

❖ Frontend

1. Create two files in frontend folder.
 - 1.Dockerfile -> your image
 - 2.index.html -> paste your EC2 instance IP

- ❖ Create docker compose file with extension yaml (docker-compose.yml)
- ❖ The docker-compose.yml file must be separate as shown in photo.



studentapp-3tire-dockerimage / docker-compose.yml

shashanksharma1309 Update docker-compose.yml


Code Blame 20 lines (16 loc) · 375 Bytes Code 55% faster with GitHub Copilot

```
1
2  version: '3.8'
3
4  services:
5    frontending:
6      build: /root/studentapp-3tire-dockerimage/frontend
7      container_name: frontend
8      ports:
9        - 80:80
10     network_mode: bridge
11
12
13    backending:
14      build: /root/studentapp-3tire-dockerimage/backend
15      container_name: backend
16      ports:
17        - 8080:8080
18      network_mode: bridge
19      depends_on :
20        - "frontending"
```

2. Git push or pull
3. docker compose up -d -> use command

```
=> => Writing image sha256:3a088665d1299125a0b0038533022a60c56663731d
=> => naming to docker.io/library/studentapp-3tire-dockerimage-backend
[+] Running 2/2
✓ Container frontend Started
✓ Container backend Started
root@ip-172-31-2-106:~/studentapp-3tire-dockerimage#
```

4. Hit your instance IP.



Student Registration Form

Student Name	<input type="text"/>
Student Address	<input type="text"/>
Student Age	<input type="text"/>
Student Qualification	<input type="text"/>
Student Percentage	<input type="text"/>
Year Passed	<input type="text"/>
<input type="button" value="register"/>	

Register Student

Students List

Student ID	StudentName	Student Addr	Student Age	Student Qualification	Student Percentage	Student Year Passed	Edit	Delete
1	chashank	Pune	23	BE	7.95	2	edit	delete

[Register Student](#)

Students List

Student ID	StudentName	Student Addr	Student Age	Student Qualification	Student Percentage	Student Year Passed	Edit	Delete
1	shashank	Pune	23	BE	7.95	2023	edit	delete
2	Omkar	Pune	23	BE	8.65	2023	edit	delete
3	chinu	Pune	22	BCS	8.99	2023	edit	delete

- ❖ If you want to push files to the dockerhub provide tags to your images and then login into the dockerhub using command.
 docker login
 docker push <dockerhub-usrname>/<dockerhub-repo>:[<tag>]