SQL PROJECT ON PIZZA SALES

AN SQL-BASED ANALYSIS OF PIZZA SALES DATA USING MYSQL WORKBENCH, UNCOVERING INSIGHTS ON ORDERS, REVENUE, POPULAR PIZZAS, SIZE TRENDS, ORDER PATTERNS, AND REVENUE CONTRIBUTION. THIS PROJECT SHOWCASES THE ABILITY TO TURN RAW SALES DATA INTO ACTIONABLE BUSINESS INSIGHTS."

-- K Shashi Deep

IDENTIFY THE MOST COMMON PIZZA SIZE ORDERED.

```sql
SELECT
    pizzas.size, COUNT(order_details.quantity)
FROM
    pizzas
        JOIN
    order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizzas.size
LIMIT 1;
```

Result Grid | Filter Rows:

size	COUNT(order_details.quantity)
M	15385

IDENTIFY THE HIGHEST-PRICED PIZZA.

```sql
SELECT
    pizza_types.name, pizzas.price
FROM
    pizzas
        JOIN
    pizza_types ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1
```

Result Grid | Filter Rows:

name	price
The Greek Pizza	35.95

CALCULATE THE TOTAL REVENUE GENERATED FROM PIZZA SALES.

```sql
SELECT
    ROUND(SUM((order_details.quantity * pizzas.price)),
            2) AS total_sales
FROM
    order_details
        JOIN
    pizzas ON pizzas.pizza_id = order_details.pizza_id
```

Result Grid | Filter

total_sales
817860.05

IDENTIFY THE MOST COMMON PIZZA SIZE ORDERED.

```sql
SELECT
    pizzas.size,
    COUNT(order_details.order_details_id) AS order_count
FROM
    pizzas
        JOIN
    order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizzas.size
ORDER BY order_count DESC
LIMIT 1;
```

Result Grid | Filter Rows:

size	order_count
L	18526

LIST THE TOP 5 MOST ORDERED PIZZA TYPES ALONG WITH THEIR QUANTITIES.

```sql
SELECT
    pizza_types.name, SUM(order_details.quantity) AS sum
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY sum DESC
LIMIT 5;
```

Result Grid Filter Rows:

name	sum
The Classic Deluxe Pizza	2453
The Barbecue Chicken Pizza	2432
The Hawaiian Pizza	2422
The Pepperoni Pizza	2418
The Thai Chicken Pizza	2371

JOIN THE NECESSARY TABLES TO FIND THE TOTAL QUANTITY OF EACH PIZZA CATEGORY ORDERED.

```
SELECT
    pizza_types.category, SUM(order_details.quantity) AS cat
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY cat DESC
LIMIT 5;
```

Result Grid | Filter R

category	cat
Classic	14888
Supreme	11987
Veggie	11649
Chicken	11050

DETERMINE THE DISTRIBUTION OF ORDER BY HOUR OF THE DAY

```sql
SELECT
    HOUR(order_time), COUNT(order_id)
FROM
    orders
GROUP BY HOUR(order_time);
```

Result Grid | Filter Rows:

HOUR(order_time)	COUNT(order_id)
11	1231
12	2520
13	2455
14	1472
15	1468
16	1920
17	2336
18	2399
19	2009
20	1642
21	1198
22	663
23	28
10	8
9	1

JOIN REVALENT TABLES TO FIND THE CATEGORY WISE DISTRIBUTION OF PIZZAS

```sql
SELECT
    pizza_types.category, COUNT(pizza_types.name)
FROM
    pizza_types
GROUP BY category;
```

Result Grid | Filter Rows:

category	COUNT(pizza_types.name)
Chicken	6
Classic	8
Supreme	9
Veggie	9

GROUP THE ORDERS BY DATE AND CALCULATE THE AVERAGE NUMBER OF PIZZAS ORDERED PER DAY

```sql
SELECT
    ROUND(AVG(orders), 0)
FROM
    (SELECT
        DATE(orders.order_date),
            SUM(order_details.quantity) AS orders
    FROM
        orders
    JOIN order_details ON order_details.order_id = orders.order_id
    GROUP BY orders.order_date) AS order_quantity;
```

Result Grid | Filter Rows

	ROUND(AVG(orders), 0)
▶	138

DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE.

```sql
SELECT
    pizza_types.name,
    ROUND(SUM(order_details.quantity * pizzas.price),
            0) AS revenue
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY revenue DESC
LIMIT 3;
```

Result Grid | Filter Rows:

name	revenue
The Thai Chicken Pizza	43434
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41410

CALCULATE THE PERCENTAGE CONTRIBUTION OF EACH PIZZA TYPE TO TOTAL REVENUE

```
SELECT
    pizza_types.category,
    ROUND(SUM(order_details.quantity * pizzas.price) / (SELECT
                    ROUND(SUM(order_details.quantity * pizzas.price),
                                0)
                FROM
                    order_details
                        JOIN
                    pizzas ON order_details.pizza_id = pizzas.pizza_id) * 100,
            2) AS revenue
FROM
    pizza_types
        JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
        JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.category
ORDER BY revenue;
```

Result Grid | Filter

category	revenue
Veggie	23.68
Chicken	23.96
Supreme	25.46
Classic	26.91

ANALYZE THE CUMULATIVE REVENUE GENERATED OVER TIME.

```
select order_date , sum(revenue) over(order by order_date) as cum_revenue
from
(select orders.order_date , sum(order_details.quantity * pizzas.price) as revenue
from order_details join pizzas
on order_details.pizza_id = pizzas.pizza_id
join orders
on orders.order_id = order_details.order_id
group by orders.order_date) as sales
```

order_date	cum_revenue
2015-01-01	2713.8500000000004
2015-01-02	5445.75
2015-01-03	8108.15
2015-01-04	9863.6
2015-01-05	11929.55
2015-01-06	14358.5
2015-01-07	16560.7
2015-01-08	19399.05
2015-01-09	21526.4
2015-01-10	23990.350000000002
2015-01-11	25862.65
2015-01-12	27781.7
2015-01-13	29831.300000000003
2015-01-14	32358.700000000004
2015-01-15	34343.50000000001
2015-01-16	36937.65000000001
2015-01-17	39001.75000000001
2015-01-18	40978.600000000006
2015-01-19	43365.75000000001
2015-01-20	45763.65000000001
2015-01-21	47804.20000000001

Result 1

DETERMINE THE TOP 3 MOST ORDERED PIZZA TYPES BASED ON REVENUE FOR EACH PIZZA CATEGORY.

```sql
select name, revenue
from (
    select category, name, revenue,
           rank() over(partition by category order by revenue desc) as rn
    from (
        select pizza_types.category, pizza_types.name,
               sum((order_details.quantity) * pizzas.price) as revenue
        from pizza_types
        join pizzas
          on pizza_types.pizza_type_id = pizzas.pizza_type_id
        join order_details
          on order_details.pizza_id = pizzas.pizza_id
        group by pizza_types.category, pizza_types.name
    ) as a
) as b
where rn <= 3;
```

Result Grid | Filter Rows: | Exp

name	revenue
The Thai Chicken Pizza	43434.25
The Barbecue Chicken Pizza	42768
The California Chicken Pizza	41409.5
The Classic Deluxe Pizza	38180.5
The Hawaiian Pizza	32273.25
The Pepperoni Pizza	30161.75
The Spicy Italian Pizza	34831.25
The Italian Supreme Pizza	33476.75
The Sicilian Pizza	30940.5

THANK YOU FOR ATTENTION