

Chapter 2	Configuration Space
Chapter 3	Rigid-Body Motions
Chapter 4	Forward Kinematics
Chapter 5	Velocity Kinematics and Statics
Chapter 6	Inverse Kinematics
Chapter 7	Kinematics of Closed Chains
Chapter 8	Dynamics of Open Chains
Chapter 9	Trajectory Generation
Chapter 10	Motion Planning
Chapter 11	Robot Control
Chapter 12	Grasping and Manipulation
Chapter 13	Wheeled Mobile Robots
	13.1 Types of Wheeled Mobile Robots
	13.2 Omnidirectional Wheeled Mobile Robots
	13.3 Nonholonomic Wheeled Mobile Robots
	13.4 Odometry

Important concepts, symbols, and equations

Relationship between planar and spatial twist:

$$\mathcal{V}_{b6} = \begin{bmatrix} 0 \\ 0 \\ \mathcal{V}_b \\ 0 \end{bmatrix}$$

Important concepts, symbols, and equations (cont.)

Odometry (or dead reckoning)


1. Measure the wheel displacements, $\Delta\theta$.
2. Assume constant wheel speeds, so $\dot{\theta} = \Delta\theta/\Delta t$, $\Delta t = 1$.

3. Find $\mathcal{V}_b = F\dot{\theta} = F\Delta\theta$.

4. Integrate \mathcal{V}_{b6} for $\Delta t = 1$, $T_{b_k b_{k+1}} = e^{[\mathcal{V}_{b6}]}$.
 5. $T_{sb_{k+1}} = T_{sb_k} T_{b_k b_{k+1}}$ (or express as q_{k+1}).
-

Important concepts, symbols, and equations (cont.)


Diff-drive



$$\mathcal{V}_b = F\Delta\theta = r \begin{bmatrix} -1/(2d) & 1/(2d) \\ 1/2 & 1/2 \\ 0 & 0 \end{bmatrix} \begin{bmatrix} \Delta\theta_L \\ \Delta\theta_R \end{bmatrix}$$

Important concepts, symbols, and equations (cont.)


$$\dot{\theta} = H(0)\mathcal{V}_b \rightarrow \mathcal{V}_b = H^\dagger(0)\dot{\theta} = F\dot{\theta} = F\Delta\theta$$



$$\mathcal{V}_b = F\Delta\theta = r \begin{bmatrix} -1/(3d) & -1/(3d) & -1/(3d) \\ 2/3 & -1/3 & -1/3 \\ 0 & -1/(2 \sin(\pi/3)) & 1/(2 \sin(\pi/3)) \end{bmatrix} \Delta\theta$$

Important concepts, symbols, and equations (cont.)

$$\dot{\theta} = H(0)\mathcal{V}_b \rightarrow \mathcal{V}_b = H^\dagger(0)\dot{\theta} = F\dot{\theta} = F\Delta\theta$$



$$\mathcal{V}_b = F\Delta\theta = \frac{r}{4} \begin{bmatrix} -1/(\ell + w) & 1/(\ell + w) & 1/(\ell + w) & -1/(\ell + w) \\ 1 & 1 & 1 & 1 \\ -1 & 1 & -1 & 1 \end{bmatrix} \Delta\theta$$

Important concepts, symbols, and equations (cont.)

$$T_{b_k b_{k+1}} = e^{[\mathcal{V}_{b6}]}$$

$$T_{sb_{k+1}} = T_{sb_k} T_{b_k b_{k+1}} = T_{sb_k} e^{[\mathcal{V}_{b6}]}$$

$$\rightarrow q_{k+1}$$

or

Could instead use $SE(2)$ representations
and use a matrix exponential for $se(2)$.

$$T_{b_k b_{k+1}} = e^{[\mathcal{V}_{b6}]}$$

$$\rightarrow \Delta q_b \rightarrow \Delta q \rightarrow q_{k+1} = q_k + \Delta q$$


rotate the
linear
component


Important concepts, symbols, and equations (cont.)

“Matrix exponential” for $se(2)$ using **center of rotation (CoR)** visualization


$$\begin{aligned} \text{if } \omega_{bz} = 0, \quad \Delta q_b &= \begin{bmatrix} \Delta\phi_b \\ \Delta x_b \\ \Delta y_b \end{bmatrix} = \begin{bmatrix} 0 \\ v_{bx} \\ v_{by} \end{bmatrix}; \\ \text{if } \omega_{bz} \neq 0, \quad \Delta q_b &= \begin{bmatrix} \Delta\phi_b \\ \Delta x_b \\ \Delta y_b \end{bmatrix} = \begin{bmatrix} \omega_{bz} \\ (v_{bx} \sin \omega_{bz} + v_{by}(\cos \omega_{bz} - 1))/\omega_{bz} \\ (v_{by} \sin \omega_{bz} + v_{bx}(1 - \cos \omega_{bz}))/\omega_{bz} \end{bmatrix} \end{aligned}$$

$$(-v_{by}/\omega_{bz}, v_{bx}/\omega_{bz})$$





Draw the proper angles of the front wheels of the car-like mobile robot for the CoR shown. (Ackermann steering.) How do the rolling speeds of the rear wheels compare?



Your mobile robot is equipped with two mouse sensors for odometry. They report the velocity vectors shown. Where is the CoR?