

```
In [4]: import pandas as pd
df = pd.read_csv(r"C:\Users\user\OneDrive\Desktop\customer_shopping_behavior.csv")
```

```
In [5]: df.head()
```

```
Out[5]:
```

	Customer ID	Age	Gender	Item Purchased	Category	Purchase Amount (USD)	Location	Size	Color
0	1	55	Male	Blouse	Clothing	53	Kentucky	L	Green
1	2	19	Male	Sweater	Clothing	64	Maine	L	Marc
2	3	50	Male	Jeans	Clothing	73	Massachusetts	S	Marc
3	4	21	Male	Sandals	Footwear	90	Rhode Island	M	Marc
4	5	45	Male	Blouse	Clothing	49	Oregon	M	Turqu



```
In [6]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 3900 entries, 0 to 3899
Data columns (total 18 columns):
#   Column                                Non-Null Count  Dtype
---  -
0   Customer ID                          3900 non-null   int64
1   Age                                  3900 non-null   int64
2   Gender                              3900 non-null   object
3   Item Purchased                      3900 non-null   object
4   Category                            3900 non-null   object
5   Purchase Amount (USD)               3900 non-null   int64
6   Location                             3900 non-null   object
7   Size                                 3900 non-null   object
8   Color                               3900 non-null   object
9   Season                              3900 non-null   object
10  Review Rating                       3863 non-null   float64
11  Subscription Status                 3900 non-null   object
12  Shipping Type                      3900 non-null   object
13  Discount Applied                   3900 non-null   object
14  Promo Code Used                    3900 non-null   object
15  Previous Purchases                 3900 non-null   int64
16  Payment Method                     3900 non-null   object
17  Frequency of Purchases              3900 non-null   object
dtypes: float64(1), int64(4), object(13)
memory usage: 548.6+ KB
```

```
In [9]: df.describe(include='all')
```

Out[9]:

	Customer ID	Age	Gender	Item Purchased	Category	Purchase Amount (USD)	Location
count	3900.000000	3900.000000	3900	3900	3900	3900.000000	3900
unique	NaN	NaN	2	25	4	NaN	50
top	NaN	NaN	Male	Blouse	Clothing	NaN	Montana
freq	NaN	NaN	2652	171	1737	NaN	96
mean	1950.500000	44.068462	NaN	NaN	NaN	59.764359	NaN
std	1125.977353	15.207589	NaN	NaN	NaN	23.685392	NaN
min	1.000000	18.000000	NaN	NaN	NaN	20.000000	NaN
25%	975.750000	31.000000	NaN	NaN	NaN	39.000000	NaN
50%	1950.500000	44.000000	NaN	NaN	NaN	60.000000	NaN
75%	2925.250000	57.000000	NaN	NaN	NaN	81.000000	NaN
max	3900.000000	70.000000	NaN	NaN	NaN	100.000000	NaN

In [10]: `df.isnull().sum()`

Out[10]: Customer ID 0  
Age 0  
Gender 0  
Item Purchased 0  
Category 0  
Purchase Amount (USD) 0  
Location 0  
Size 0  
Color 0  
Season 0  
Review Rating 37  
Subscription Status 0  
Shipping Type 0  
Discount Applied 0  
Promo Code Used 0  
Previous Purchases 0  
Payment Method 0  
Frequency of Purchases 0  
dtype: int64

In [11]: `df['Review Rating'] = df.groupby('Category')['Review Rating'].transform(lambda x`

In [12]: `df.isnull().sum()`

```
Out[12]: Customer ID      0
Age      0
Gender    0
Item Purchased  0
Category   0
Purchase Amount (USD)  0
Location   0
Size       0
Color      0
Season     0
Review Rating  0
Subscription Status  0
Shipping Type  0
Discount Applied  0
Promo Code Used  0
Previous Purchases  0
Payment Method  0
Frequency of Purchases  0
dtype: int64
```

```
In [25]: df.columns = df.columns.str.lower()
df.columns = df.columns.str.replace(' ', '_')
df = df.rename(columns={'purchase_amount_(usd)': 'purchase_amount'})
```

```
In [29]: df.columns
```

```
Out[29]: Index(['customer_id', 'age', 'gender', 'item_purchased', 'category',
               'purchase_amount', 'location', 'size', 'color', 'season',
               'review_rating', 'subscription_status', 'shipping_type',
               'discount_applied', 'promo_code_used', 'previous_purchases',
               'payment_method', 'frequency_of_purchases', 'age_group'],
              dtype='object')
```

```
In [30]: # create a column for age-group
labels = ['Young Adult', 'Adult', 'Middle-aged', 'Senior']
df['age_group'] = pd.qcut(df['age'], q=4, labels=labels)
```

```
In [31]: df[['age', 'age_group']].head()
```

```
Out[31]:
```

	age	age_group
0	55	Middle-aged
1	19	Young Adult
2	50	Middle-aged
3	21	Young Adult
4	45	Middle-aged

```
In [32]: #create column for purchase_frequency_days
frequency_mapping = {
    'Fortnightly':14,
    'Weekly':7,
    'Monthly':30,
    'Quarterly':90,
    'Bi-Weekly':14,
    'Annually':365,
```

```

    'Every 3 months':90,
}
df['purchase_frequency_days']= df['frequency_of_purchases'].map(frequency_mappin

```

```
In [38]: df[['purchase_frequency_days', 'frequency_of_purchases']].head(10)
```

```
Out[38]:
```

	<b>purchase_frequency_days</b>	<b>frequency_of_purchases</b>
<b>0</b>	14.0	Fortnightly
<b>1</b>	14.0	Fortnightly
<b>2</b>	7.0	Weekly
<b>3</b>	7.0	Weekly
<b>4</b>	365.0	Annually
<b>5</b>	7.0	Weekly
<b>6</b>	90.0	Quarterly
<b>7</b>	7.0	Weekly
<b>8</b>	365.0	Annually
<b>9</b>	90.0	Quarterly

```
In [41]: df[['discount_applied', 'promo_code_used']].head(10)
```

```
Out[41]:
```

	<b>discount_applied</b>	<b>promo_code_used</b>
<b>0</b>	Yes	Yes
<b>1</b>	Yes	Yes
<b>2</b>	Yes	Yes
<b>3</b>	Yes	Yes
<b>4</b>	Yes	Yes
<b>5</b>	Yes	Yes
<b>6</b>	Yes	Yes
<b>7</b>	Yes	Yes
<b>8</b>	Yes	Yes
<b>9</b>	Yes	Yes

```
In [51]: df['discount_applied'].equals(df['promo_code_used'])
```

```
Out[51]: True
```

```
In [52]: (df['discount_applied'] == df['promo_code_used']).all()
```

```
Out[52]: np.True_
```

```
In [54]: df = df.drop('promo_code_used',axis=1)
```

```
In [58]: df.columns
```

```
Out[58]: Index(['customer_id', 'age', 'gender', 'item_purchased', 'category',  
              'purchase_amount', 'location', 'size', 'color', 'season',  
              'review_rating', 'subscription_status', 'shipping_type',  
              'discount_applied', 'previous_purchases', 'payment_method',  
              'frequency_of_purchases', 'age_group', 'purchase_frequency_days'],  
             dtype='object')
```

```
In [60]: pip install psycopg2-binary sqlalchemy
```

```
Requirement already satisfied: psycopg2-binary in c:\users\user\sql_notebook\env  
\lib\site-packages (2.9.11)  
Requirement already satisfied: sqlalchemy in c:\users\user\sql_notebook\env\lib\s  
ite-packages (2.0.43)  
Requirement already satisfied: greenlet>=1 in c:\users\user\sql_notebook\env\lib  
\site-packages (from sqlalchemy) (3.2.4)  
Requirement already satisfied: typing-extensions>=4.6.0 in c:\users\user\sql_note  
book\env\lib\site-packages (from sqlalchemy) (4.15.0)  
Note: you may need to restart the kernel to use updated packages.
```

```
[notice] A new release of pip is available: 24.3.1 -> 26.0.1
```

```
[notice] To update, run: python.exe -m pip install --upgrade pip
```

```
In [65]: from sqlalchemy import create_engine  
from urllib.parse import quote_plus  
username="postgres"  
password= quote_plus("Shasti@1369")  
host="localhost"  
port="5432"  
database="customer_behavior"  
  
engine = create_engine(f"postgresql+psycopg2://{username}:{password}@{host}:{por  
  
table_name = "customer"  
df.to_sql(table_name, engine, if_exists="replace", index=False)  
  
print(f"Data successfully loaded into table '{table_name}' in database '{databas
```

```
Data successfully loaded into table 'customer' in database 'customer_behavior'.
```

```
In [ ]:
```