

```
from google.colab import drive
drive.mount('/content/drive')

Mounted at /content/drive

from numpy import mean
from numpy import std
from matplotlib import pyplot
from sklearn.model_selection import KFold
from keras.datasets import mnist
from keras.utils import to_categorical
from keras.models import Sequential
from keras.layers import Conv2D
from keras.layers import MaxPooling2D
from keras.layers import Dense
from keras.layers import Flatten
from keras.optimizers import SGD
from keras.layers import Dropout
from keras.layers import BatchNormalization
import keras
from keras import backend as K
import matplotlib.pyplot as plt
import sklearn

path_normal = '/content/drive/MyDrive/Deep learning demo project/Normal/'
path_pneumonia = '/content/drive/MyDrive/Deep learning demo project/pneumonia/'

##Import necessary libraries
import numpy as np
import PIL
import cv2
import os
data1 = list()
data2 = list()
x = list()

##Class-1 images##

for image in os.walk(path_normal):
    data1.append(image[2])

for i in range(len(data1[0])):
    str_complete = path_normal + data1[0][i]
    img = cv2.imread(str_complete)
    img = cv2.resize(img, (224, 224))
    x.append(img)
print(i)#Ensure all images are loaded

0
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
```

```
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57

print(img.shape)

(224, 224, 3)

##Class-2 images##

for image in os.walk(path_pneumonia):
    data2.append(image[2])

for i in range(len(data2[0])):
    str_complete = path_pneumonia + data2[0][i]
    img = cv2.imread(str_complete)
    img = cv2.resize(img, (224, 224))
    x.append(img)#Ensure all images are loaded
    print(i)

44
45
```

```

90
91
92
93
94
95
96
97
98
99
100
101

data_x = np.asarray(x)

data_x.shape

(1400, 224, 224, 3)

x=data_x

y = np.zeros(1400)
y[:700] =1
y[700:1400]=2

from sklearn.model_selection import train_test_split

##Dataset Split##
from sklearn.model_selection import train_test_split
from keras.utils import to_categorical
#y = to_categorical(y)
x_train, x_test, y_train, y_test = train_test_split(data_x, y, test_size=0.2, random_state=1)
x_train, x_val, y_train, y_val = train_test_split(x_train, y_train, test_size=1/8, random_state=1)

y_tr_one_hot = np.zeros((np.array(y_train).shape[0],2))

for i in range(np.array(y_train).shape[0]):
    label = y_train[i]-1
    y_tr_one_hot[i][int(label)] = 1

y_val_one_hot = np.zeros((np.array(y_val).shape[0],2))

for i in range(np.array(y_val).shape[0]):
    label = y_val[i]-1
    y_val_one_hot[i][int(label)] = 1

y_te_one_hot = np.zeros((np.array(y_test).shape[0],2))

for i in range(np.array(y_test).shape[0]):
    label = y_test[i]-1
    y_te_one_hot[i][int(label)] = 1

from keras.models import load_model
from keras.layers import Lambda
import tensorflow as tf
from tensorflow.keras.models import Model
from tensorflow.keras.layers import GlobalAveragePooling2D, Dense

model = tf.keras.applications.VGG16(include_top=False,input_shape=(224,224,3))
# mark loaded layers as not trainable
for layer in model.layers:
    layer.trainable = False
# add new classifier layers
flat1 = Flatten()(model.layers[-1].output)
#x=Dense(1024,activation='relu')(flat1) # FC layer 1
#x=Dense(64,activation='relu')(x) # FC layer 2
output = Dense(2, activation='softmax')(flat1)
model = Model(inputs=model.inputs, outputs=output)

optimizer = tf.keras.optimizers.Adam(learning_rate=0.01)
model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accuracy'])
model.fit(x_train, y_tr_one_hot, validation_data=(x_val, y_val_one_hot), epochs=5, batch_size=200,verbose=1)

Downloading data from https://storage.googleapis.com/tensorflow/keras-applications/vgg16/vgg16\_weights\_tf\_dim\_ordering\_tf\_58889256/58889256 [=====] - 0s 0us/step
Epoch 1/5
5/5 [=====] - 483s 99s/step - loss: 4.6395 - accuracy: 0.7898 - val_loss: 0.6604 - val_accuracy:

```

```
Epoch 2/5
5/5 [=====] - 473s 97s/step - loss: 0.6921 - accuracy: 0.9694 - val_loss: 0.6225 - val_accuracy:
Epoch 3/5
5/5 [=====] - 469s 96s/step - loss: 0.1334 - accuracy: 0.9939 - val_loss: 0.2637 - val_accuracy:
Epoch 4/5
5/5 [=====] - 468s 96s/step - loss: 0.0158 - accuracy: 0.9990 - val_loss: 0.1493 - val_accuracy:
Epoch 5/5
5/5 [=====] - 490s 102s/step - loss: 5.2752e-05 - accuracy: 1.0000 - val_loss: 0.0714 - val_accu
<keras.callbacks.History at 0x7fa8f40fa820>
```

```
import sklearn
from sklearn.metrics import confusion_matrix

test_loss, test_acc = model.evaluate(np.array(x_test), np.array(y_te_one_hot), verbose=0)
print(test_acc)
##Evaluating Sensitivity, Accuracy and Kappa scores
y_prob = model.predict(x_test)
Y_pred = y_prob.argmax(axis=-1)
```

```
1.0
9/9 [=====] - 119s 13s/step
```

```
cm1 = confusion_matrix(y_test-1,Y_pred)
print("confusion matrix \n",cm1)
```

```
confusion matrix
[[137  0]
 [ 0 143]]
```

```
from sklearn.metrics import classification_report
```

```
import pandas as pd
```

```
print(pd.DataFrame(classification_report(y_test-1,Y_pred,output_dict=True)).T)
Kappa=sklearn.metrics.cohen_kappa_score(y_test-1,Y_pred)
print('Kappa=',Kappa)
```

```
precision recall f1-score support
0.0          1.0      1.0      1.0      137.0
1.0          1.0      1.0      1.0      143.0
accuracy          1.0      1.0      1.0      1.0
macro avg          1.0      1.0      1.0     280.0
weighted avg          1.0      1.0      1.0     280.0
Kappa= 1.0
```