

```
from google.colab import drive
drive.mount('/content/drive')

Drive already mounted at /content/drive; to attempt to forcibly remount, call drive.mount("/content/drive", force_remount=True)

from numpy import mean
from numpy import std
from matplotlib import pyplot
from sklearn.model_selection import KFold
from keras.datasets import mnist
from keras.utils import to_categorical
from keras.models import Sequential
from keras.layers import Conv2D
from keras.layers import MaxPooling2D
from keras.layers import Dense
from keras.layers import Flatten
from keras.optimizers import SGD
from keras.layers import Dropout
from keras.layers import BatchNormalization
import keras
from keras import backend as K
import matplotlib.pyplot as plt
import sklearn

path_normal = '/content/drive/MyDrive/Deep learning demo project/Normal/'
path_pneumonia = '/content/drive/MyDrive/Deep learning demo project/pneumonia/'

##Import necessary libraries
import numpy as np
import PIL
import cv2
import os
data1 = list()
data2 = list()
x = list()

##Class-1 images##

for image in os.walk(path_normal):
    data1.append(image[2])

for i in range(len(data1[0])):
    str_complete = path_normal + data1[0][i]
    img = cv2.imread(str_complete)
    img = cv2.resize(img, (224, 224))
    x.append(img)
    print(i)#Ensure all images are loaded
```

```
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699

print(img.shape)

(224, 224, 3)

##Class-2 images##

for image in os.walk(path_pneumonia):
    data2.append(image[2])

for i in range(len(data2[0])):
    str_complete = path_pneumonia + data2[0][i]
    img = cv2.imread(str_complete)
    img = cv2.resize(img, (224, 224))
    x.append(img)#Ensure all images are loaded
    print(i)
```

```

687
688
689
690
691
692
693
694
695
696
697
698
699

data_x = np.asarray(x)

data_x.shape

(1400, 224, 224, 3)

x=data_x

y = np.zeros(1400)
y[:700] =1
y[700:1400]=2

from sklearn.model_selection import train_test_split

##Dataset Split##
from sklearn.model_selection import train_test_split
from keras.utils import to_categorical
#y = to_categorical(y)
x_train, x_test, y_train, y_test = train_test_split(data_x, y, test_size=0.2, random_state=1)
x_train, x_val, y_train, y_val = train_test_split(x_train, y_train, test_size=1/8, random_state=1)

y_tr_one_hot = np.zeros((np.array(y_train).shape[0],2))

for i in range(np.array(y_train).shape[0]):
    label = y_train[i]-1
    y_tr_one_hot[i][int(label)] = 1

y_val_one_hot = np.zeros((np.array(y_val).shape[0],2))

for i in range(np.array(y_val).shape[0]):
    label = y_val[i]-1
    y_val_one_hot[i][int(label)] = 1

y_te_one_hot = np.zeros((np.array(y_test).shape[0],2))

for i in range(np.array(y_test).shape[0]):
    label = y_test[i]-1
    y_te_one_hot[i][int(label)] = 1

from keras.models import load_model
from keras.layers import Lambda
import tensorflow as tf
from tensorflow.keras.models import Model
from tensorflow.keras.layers import GlobalAveragePooling2D, Dense

model = tf.keras.applications.MobileNetV3Large(include_top=False,input_shape=(224,224,3))
# mark loaded layers as not trainable
for layer in model.layers:
    layer.trainable = False
# add new classifier layers
flat1 = Flatten()(model.layers[-1].output)
#x=Dense(1024,activation='relu')(flat1) # FC layer 1
#x=Dense(64,activation='relu')(x) # FC layer 2
output = Dense(2, activation='softmax')(flat1)
model = Model(inputs=model.inputs, outputs=output)

optimizer = tf.keras.optimizers.Adam(learning_rate=0.01)
model.compile(loss='categorical_crossentropy', optimizer='adam', metrics=['accuracy'])
model.fit(x_train, y_tr_one_hot, validation_data=(x_val, y_val_one_hot), epochs=5, batch_size=200,verbose=1)

```

📄 Downloading data from https://storage.googleapis.com/tensorflow/keras-applications/mobilenet_v3/weights_mobilenet_v3_large/12683000/12683000 [=====] - 0s 0us/step

```

Epoch 1/5
5/5 [=====] - 63s 12s/step - loss: 1.5030 - accuracy: 0.7929 - val_loss: 0.0066 - val_accuracy:
Epoch 2/5
5/5 [=====] - 51s 11s/step - loss: 0.0551 - accuracy: 0.9898 - val_loss: 0.2676 - val_accuracy:
Epoch 3/5
5/5 [=====] - 52s 11s/step - loss: 0.0412 - accuracy: 0.9898 - val_loss: 0.1554 - val_accuracy:
Epoch 4/5
5/5 [=====] - 55s 12s/step - loss: 0.0022 - accuracy: 0.9990 - val_loss: 0.0491 - val_accuracy:
Epoch 5/5
5/5 [=====] - 56s 12s/step - loss: 2.0873e-07 - accuracy: 1.0000 - val_loss: 0.0086 - val_accuracy:
<keras.callbacks.History at 0x7f0744a83220>

```

```

import sklearn
from sklearn.metrics import confusion_matrix

```

```

test_loss, test_acc = model.evaluate(np.array(x_test), np.array(y_test_one_hot), verbose=0)
print(test_acc)
##Evaluating Sensitivity, Accuracy and Kappa scores
y_prob = model.predict(x_test)
Y_pred = y_prob.argmax(axis=-1)

```

```

0.9964285492897034
9/9 [=====] - 13s 1s/step

```

```

cm1 = confusion_matrix(y_test-1,Y_pred)
print("confusion matrix \n",cm1)

```

```

confusion matrix
[[136   1]
 [  0 143]]

```

```

from sklearn.metrics import classification_report

```

```

import pandas as pd

```

```

print(pd.DataFrame(classification_report(y_test-1,Y_pred,output_dict=True)).T)
Kappa=s sklearn.metrics.cohen_kappa_score(y_test-1,Y_pred)
print('Kappa=',Kappa)

```

```

          precision    recall  f1-score   support

0.0          1.000000    0.992701    0.996337    137.000000
1.0          0.993056    1.000000    0.996516    143.000000
accuracy          0.996429    0.996429    0.996429    0.996429
macro avg          0.996528    0.996350    0.996426    280.000000
weighted avg          0.996453    0.996429    0.996428    280.000000
Kappa= 0.9928527670002042

```