

■ COMPLETE NOTES - TOPIC 04

CSS Typography

Fonts, Text aur Color Properties - Basic se Practical tak

Web Development Course - Shauray

font-family

font-size

font-weight

font-style

line-height

text-align

text-decoration

text-transform

letter-spacing

word-spacing

text-shadow

color

background-color

RGB / HEX / HSL

opacity

CSS Font Properties

Website ke letters ka family, size, weight aur style control karna

KYA HAI?

Font properties se hum text ka **typeface**, **size**, **thickness**, **style** aur **reading flow** control karte hain. Simple words mein: font properties decide karti hain ki text kaise dikhega aur padhne mein kitna comfortable hoga.

■ 1. font-family - Font Ka Naam

`font-family` batata hai browser ko ki text kis font mein show karna hai. Always backup fonts bhi do, kyunki user ke system mein first font available na ho sakta hai.

Browser font ko left se right check karta hai. Agar first font available hai toh wahi use hoga. Agar first font missing hai toh second font use hoga. Agar wo bhi missing hai toh generic family jaise `sans-serif` ya `serif` use hogi. Isi backup system ko **font stack** bolte hain.

font-family.css

```
/* Font family - pehle preferred font, phir fallback fonts */
body {
  font-family: Arial, Helvetica, sans-serif;
}

h1 {
  font-family: 'Times New Roman', Times, serif;
}

code {
  font-family: 'Courier New', monospace;
}
```

SERIF

Letters ke ends par chhoti strokes hoti hain.
Example: Times New Roman, Georgia. Books aur formal text mein common.

SANS-SERIF

Clean letters, extra strokes nahi. Example: Arial, Helvetica, Poppins. Websites mein sabse zyada use hota hai.

Generic Family	Look	Use Case
serif	Letters ke end par strokes	Books, formal articles, editorial layout
sans-serif	Clean aur modern letters	Websites, apps, dashboards, landing pages
monospace	Har letter ki width same	Code blocks, terminal, technical notes
cursive	Handwriting style	Decorative headings, invitations
fantasy	Highly decorative	Rare use, poster type design

■ **Deep Point:** Jis font name mein space ho, usko quotes mein likhna hota hai. Example: `'Times New Roman'`. Single word font jaise `Arial` bina quotes ke bhi chal jaata hai.

■ 2. font-size - Text Ka Size

`font-size` text ki height/size decide karta hai. Website readability ka sabse direct effect isi property se hota hai. Agar text chhota hai toh user ko padhne mein strain hoga; agar text bahut bada hai toh layout heavy aur unbalanced lagega.

CSS mein font-size fixed bhi ho sakta hai aur relative bhi. Fixed means exact value, jaise `16px`. Relative means kisi existing size ke according, jaise `1rem` root font-size ke according aur `1.2em` parent ke according.

```
/* Fixed size */  
  
p {  
    font-size: 16px;  
}  
  
/* Relative size - responsive design ke liye better */  
  
h1 {  
    font-size: 2.5rem; /* root font size ka 2.5 times */  
}  
  
small {  
    font-size: 0.875rem;  
}
```

Unit	Example	Kab Use Kare?
px	16px	Exact fixed size chahiye ho
rem	1.5rem	Most recommended for font sizes
em	1.2em	Parent ke font size ke according
%	120%	Parent size ka percentage

■ font-size Units Ko Proper Samjho

```
/* Default browser root font-size usually 16px hota hai */
html {
  font-size: 16px;
}

.title {
  font-size: 2rem;    /* 2 x 16px = 32px */
}

.card {
  font-size: 20px;
}

.card p {
  font-size: 1.2em;    /* 1.2 x parent 20px = 24px */
}
```

■ **Pro Tip:** Normal paragraph text ke liye mostly `16px` ya `1rem` comfortable hota hai. Headings ke liye `rem` use karo, responsive design clean rahega.

■ 3. font-weight - Text Ki Thickness

`font-weight` text ko light, normal, semi-bold, bold ya extra-bold banata hai. Headings mein usually heavier weight use hota hai taaki hierarchy clear ho. Paragraph text mein normal ya medium weight use hota hai taaki long reading comfortable rahe.

```
/* Keyword values */  
  
p { font-weight: normal; } /* 400 */  
strong { font-weight: bold; } /* 700 */  
  
/* Numeric values */  
  
.light { font-weight: 300; }  
.normal { font-weight: 400; }  
.medium { font-weight: 500; }  
.bold { font-weight: 700; }  
.black { font-weight: 900; }
```

Value	Name	Common Use
100	Thin	Rare, decorative large headings
300	Light	Subtle headings, elegant design
400	Normal	Paragraphs, default text
500	Medium	Labels, buttons, nav links
600	Semi Bold	Sub-headings, card titles
700	Bold	Main headings, important text
900	Black	Hero headings, poster-style text

■ **Important:** Har font family har weight support nahi karti. Agar font ke paas 600 weight file nahi hai toh browser nearest available weight use karega. Isliye Google Fonts se required weights load karna zaroori hai.

■ 4. font-style aur font-variant

font-style ka most common use italic text ke liye hota hai. Italic usually emphasis, quotes, technical terms ya special words ko highlight karne ke liye use hota hai. **font-variant: small-caps** normal lowercase letters ko capital-style small letters jaisa dikhata hai.

font-style.css

```
em {  
    font-style: italic;    /* slanted text */  
}  
  
.no-italic {  
    font-style: normal;    /* italic remove */  
}  
  
.small-caps {  
    font-variant: small-caps; /* lowercase bhi capital style mein */  
}
```

■ 5. line-height - Lines Ke Beech Space

line-height reading comfort ke liye bahut important hai. Agar line-height tight hai toh text crowded lagega, aur zyada hai toh text disconnected lagega.

Line-height actual text size ke upar extra vertical space add karta hai. Example: agar **font-size: 16px** aur **line-height: 1.6** hai, toh ek line ki total height around **25.6px** hogi. Unitless value best hoti hai kyunki child elements apne font-size ke according line-height calculate kar lete hain.

line-height.css

```
p {  
    font-size: 16px;  
    line-height: 1.6; /* best practice - unitless value */  
}  
  
h1 {  
    line-height: 1.1; /* headings ko compact rakhte hain */  
}
```

■ **Note:** Paragraphs ke liye **line-height: 1.5** se **1.8** usually best hota hai. Headings ke liye **1.1** se **1.3** clean lagta hai.

■ 6. Font Inheritance - Parent Se Child Tak

Most font properties inherited hoti hain. Matlab agar `body` par `font-family`, `font-size`, `line-height` aur `color` set kar diya, toh andar ke paragraph, list, span jaise elements automatically wahi style follow karenge, jab tak unke liye alag CSS na likhi ho.

● ● ● inheritance.css

```
body {  
    font-family: 'Poppins', sans-serif;  
    font-size: 16px;  
    line-height: 1.6;  
    color: #222;  
}  
  
/* p ko font-family alag se dene ki zaroorat nahi,  
   kyunki body se inherit ho jayega */  
p {  
    margin-bottom: 16px;  
}
```


CSS Text Properties

Text ka alignment, decoration, spacing, case aur shadow control karna

KYA HAI?

Text properties se hum letters ka font nahi, balki **text ka arrangement aur presentation** control karte hain. Jaise text center ho ya left, underline ho ya nahi, uppercase ho ya lowercase, letters ke beech kitna gap ho, etc.

■ 1. text-align - Text Ki Direction / Alignment

`text-align` text ko horizontal direction mein align karta hai. Yeh property mostly block-level elements par useful hoti hai, jaise `p`, `div`, `h1`, `section`. Agar tum inline element jaise `span` par text-align lagao, toh usually visible effect nahi dikhega kyunki inline element apni content width jitna hi space leta hai.

● ● ● text-align.css

```
h1 {
  text-align: center;
}

p {
  text-align: left;      /* default in English/Hinglish */
}

.price {
  text-align: right;     /* tables/prices ke liye useful */
}

.article {
  text-align: justify;   /* both sides equal line edge */
}
```

■ **Warning:** Long paragraphs ko mobile par `justify` karne se weird gaps aa sakte hain. Websites mein normal readable text ke liye `left` alignment safest hota hai.

Value	Meaning	Example Use
<code>left</code>	Text left side se start hota hai	Articles, paragraphs, forms
<code>center</code>	Text center mein aata hai	Hero heading, cards, short labels
<code>right</code>	Text right side align hota hai	Prices, table numbers, invoices
<code>justify</code>	Line dono sides se equal stretch hoti hai	Print-like layout, newspapers
<code>start</code>	Writing direction ke start side par	Multilingual websites
<code>end</code>	Writing direction ke end side par	RTL/LTR adaptive layouts

■ 2. text-decoration - Underline / Overline / Strike

`text-decoration` text ke upar, neeche ya beech mein line add karta hai. Links mein browser default underline deta hai. Hum underline remove bhi kar sakte hain, ya modern CSS se underline ka color, thickness aur style customize kar sakte hain.

```
/* Links ki underline remove */  
  
a {  
    text-decoration: none;  
}  
  
/* Modern detailed decoration */  
  
.special-link {  
    text-decoration-line: underline;  
    text-decoration-color: #00b4d8;  
    text-decoration-style: wavy;  
    text-decoration-thickness: 2px;  
}  
  
.old-price {  
    text-decoration: line-through;  
}
```

■ **Link Note:** Agar links ki underline remove kar rahe ho, toh hover/focus par koi clear visual signal do. Sirf color change kabhi-kabhi enough nahi hota, especially accessibility ke liye.

■ 3. text-transform - Case Change

`text-transform` actual HTML text ko change nahi karta, sirf browser mein display ka case change karta hai. Iska benefit yeh hai ki content clean rehta hai aur CSS se design control hota hai. Example: HTML mein "submit form" likha hai, CSS se button par "SUBMIT FORM" dikh sakta hai.

```
.title {  
    text-transform: uppercase;    /* HELLO WORLD */  
}  
  
.name {  
    text-transform: capitalize;    /* Hello World */  
}  
  
.quiet {  
    text-transform: lowercase;    /* hello world */  
}
```

■ **Tip:** HTML content ko manually uppercase type mat karo. CSS mein `text-transform: uppercase` use karo, taaki screen readers aur copy-paste behavior better rahe.

■ 4. letter-spacing aur word-spacing

`letter-spacing` letters ke beech ka gap control karta hai. Yeh badges, nav labels, uppercase headings jaise short text par achha lagta hai. Lekin paragraph text par zyada letter-spacing readability kharab kar sakti hai.

`word-spacing` words ke beech ka gap control karta hai. Iska use rare hota hai, kyunki default spacing usually readable hoti hai. Special typography effects ya wide layout mein use kar sakte hain.

```
.badge {  
  letter-spacing: 3px;  
  text-transform: uppercase;  
}  
  
.para {  
  word-spacing: 4px;  
}  
  
.compact {  
  letter-spacing: normal;  
  word-spacing: normal;  
}
```

■ **Common Mistake:** Uppercase text ke saath thoda letter-spacing achha lagta hai, lekin normal paragraph mein `letter-spacing: 3px` jaisa large value text ko difficult bana deta hai.

■ 5. text-indent, white-space aur overflow

`text-indent` first line ko left se andar shift karta hai. Books aur articles mein paragraph starting show karne ke liye use hota hai. Web design mein margin/padding zyada common hai, but long reading layouts mein text-indent useful ho sakta hai.

`white-space` decide karta hai ki spaces, tabs aur line breaks kaise handle honge. Normal text automatically wrap hota hai, lekin code, file paths, single-line labels ya chips mein wrapping control karna padta hai.

```

.article p {
    text-indent: 40px;      /* paragraph ki first line andar */
}

.single-line {
    white-space: nowrap;    /* text next line pe nahi jayega */
    overflow: hidden;
    text-overflow: ellipsis; /* extra text ... ban jayega */
}

pre {
    white-space: pre-wrap;  /* spaces preserve + line wrap */
}

```

white-space Value	Spaces Preserve?	Line Wrap?	Use
normal	No	Yes	Default paragraphs
nowrap	No	No	Single-line labels, nav items
pre	Yes	No	Exact formatted text
pre-wrap	Yes	Yes	Code/text preserving spaces but wrapping
pre-line	Line breaks yes	Yes	User-entered multi-line text

■ **Ellipsis Rule:** `text-overflow: ellipsis` tabhi kaam karta hai jab element ki fixed/limited width ho, `overflow: hidden` ho, aur text single line ho with `white-space: nowrap`.

■ 6. text-shadow - Text Ke Peeche Shadow

`text-shadow` text ke peeche shadow ya glow effect create karta hai. Ismein 4 cheezein hoti hain: horizontal offset, vertical offset, blur radius aur color. Positive x shadow ko right le jaata hai, positive y shadow ko down le jaata hai, blur shadow ko soft karta hai.

```
/* text-shadow: x-offset y-offset blur color; */  
h1 {  
  text-shadow: 2px 2px 6px rgba(0, 0, 0, 0.4);  
}  
  
.glow {  
  color: #00b4d8;  
  text-shadow: 0 0 12px rgba(0, 180, 216, 0.8);  
}
```

TEXT PROPERTY DEMO

text-align: center;

Yeh text center aligned hai

UPPERCASE + LETTER-SPACING

IMPORTANT BADGE TEXT

text-shadow glow

Glowing heading effect

■ 7. Text Properties Ka Real Use Case

Real website mein text properties ko isolated use nahi karte. Usually heading ke liye `text-transform`, `letter-spacing`, `font-weight` aur `line-height` saath use hote hain. Paragraph ke liye `font-size`, `line-height`, `color` aur `max-width` reading comfort decide karte hain.

```
.article {  
  max-width: 720px;  
}  
  
.article h2 {  
  font-size: 2rem;  
  line-height: 1.2;  
  text-transform: capitalize;  
}  
  
.article p {  
  font-size: 1rem;  
  line-height: 1.75;  
  color: #4b5563;  
}
```


CSS Color Properties

Text, background, border aur transparency ke colors control karna

KYA HAI?

Color properties se hum kisi bhi element ka **text color**, **background color**, **border color**, **shadow color** aur transparency set karte hain. CSS mein colors multiple formats mein likh sakte hain: name, HEX, RGB, RGBA, HSL, HSLA.

■ 1. color - Text Ka Color

`color` property element ke text ka color set karti hai. Yeh inherited property hai, matlab agar parent element par color set hai toh child text bhi wahi color inherit kar sakta hai. Isi wajah se hum often `body` par base text color set kar dete hain.

color.css

```
h1 {  
  color: white;  
}  
  
p {  
  color: #a8b2d8;  
}  
  
.error {  
  color: rgb(233, 69, 96);  
}
```

color-inheritance.css

```
body {  
    color: #1f2937; /* website ka default text color */  
}  
  
.card {  
    color: #e8eaf6; /* card ke andar ka text inherit karega */  
}  
  
.card a {  
    color: #00b4d8; /* link ka color specifically override */  
}
```

■ 2. background-color - Element Ka Background

`background-color` element ke background area ko fill karta hai. Yeh text ke peeche ka color hota hai. Button, card, navbar, footer, alert box, highlight section, badge - sab mein background-color ka heavy use hota hai.

background-color.css

```
body {  
    background-color: #0a0f1e;  
}  
  
.card {  
    background-color: #0d1b2a;  
}  
  
.highlight {  
    background-color: yellow;  
    color: black;  
}
```

■ **Note:** `color` sirf text color change karta hai. `background-color` element ke background ko color deta hai. Dono ko mix karte time contrast ka dhyan rakho.

■ 3. Color Formats in CSS

CSS colors ko multiple formats mein likh sakte hain. Output same ho sakta hai, bas writing style different hota hai. Beginners ke liye HEX easiest hota hai, RGB transparency ke liye useful hota hai, aur HSL color variations create karne ke liye bahut readable hota hai.

Format	Example	Explanation
Color Name	red	Simple predefined color name
HEX	#e94560	Most common web color format
RGB	rgb(233, 69, 96)	Red, Green, Blue values 0-255
RGBA	rgba(233, 69, 96, 0.5)	RGB + alpha transparency
HSL	hsl(350, 80%, 59%)	Hue, Saturation, Lightness
HSLA	hsla(350, 80%, 59%, 0.5)	HSL + alpha transparency

● ● ● color-formats.css

```
.name { color: crimson; }
.hex { color: #e94560; }
.rgb { color: rgb(233, 69, 96); }
.rgba { color: rgba(233, 69, 96, 0.7); }
.hsl { color: hsl(350, 80%, 59%); }
```

■ HEX, RGB aur HSL Ko Detail Mein Samjho

HEX

HEX format `#RRGGBB` hota hai. Pehle 2 digits red, next 2 green, last 2 blue. Example `#ffffff` white, `#000000` black. Short form bhi hota hai: `#fff`.

RGB / RGBA

RGB mein red, green, blue values 0 se 255 tak hoti hain. RGBA mein last value alpha hoti hai, jahan `0` fully transparent aur `1` fully visible hota hai.

HSL

HSL means Hue, Saturation, Lightness. Hue color wheel angle hai, saturation color ki intensity hai, lightness color ko dark/light banata hai.

Alpha

Alpha transparency control karta hai. Modern CSS mein `rgb(0 0 0 / 0.5)` aur `hsl(220 80% 50% / 0.4)` syntax bhi use hota hai.

modern-color-syntax.css

```
.overlay {  
  background: rgb(0 0 0 / 0.6);      /* modern RGB alpha */  
}  
  
.tag {  
  background: hsl(190 100% 42% / 0.15);  
  color:      hsl(190 100% 42%);  
}
```

COLOR SWATCHES

			
#e94560 accent	#00b4d8 blue	#06d6a0 green	#ffd166 yellow

■ 4. border-color aur outline-color

`border-color` element ke border ka color set karta hai. Border tabhi dikhega jab border style aur width bhi set ho. Sirf `border-color` likhne se border visible nahi hota agar border style missing hai.

`outline` border jaisa dikhta hai, lekin layout space occupy nahi karta. Forms, buttons aur links ke focus state mein outline important hota hai. Keyboard se website use karne wale users isi outline se samajhte hain ki current focus kahan hai.

border-outline-color.css

```
.card {  
    border: 1px solid #1e3a5f;  
}  
  
input:focus {  
    outline: 2px solid #00b4d8;  
    outline-offset: 2px;  
}
```

■ **Accessibility Tip:** Focus outline ko remove mat karo jab tak uska clear replacement na ho. Keyboard users ko pata chalna chahiye ki currently kaunsa element selected hai.

■ 5. opacity - Whole Element Transparent

`opacity` element ki overall visibility control karta hai. Value `0` ka matlab fully invisible, `1` ka matlab fully visible. Beech ki values like `0.5` element ko 50% transparent bana deti hain.

opacity.css

```
.disabled {  
    opacity: 0.5;           /* element + text + children sab fade */  
}  
  
.overlay {  
    background: rgba(0, 0, 0, 0.6); /* sirf background transparent */  
}
```

■ **Important:** `opacity` poore element ko transparent karta hai, including text aur child elements. Agar sirf background transparent chahiye toh `rgba()` ya `hsla()` use karo.

■ 6.currentColor - Text Color Ko Reuse Karna

`currentColor` ek special CSS keyword hai jo current element ke `color` value ko reuse karta hai. Isse border, icon, outline ya shadow ko same color dena easy ho jaata hai. Buttons aur icon links mein

yeh bahut useful hai.

current-color.css

```
.btn {
  color: #00b4d8;
  border: 2px solid currentColor; /* border bhi text color jaisa */
}

.btn:hover {
  color: #06d6a0; /* border automatically green */
}
```

■ 7. CSS Variables For Colors

Real projects mein same colors baar-baar use hote hain. Agar har jagah direct `#e94560` likhoge toh later brand color change karna difficult hoga. CSS variables se color ek jagah define karte hain aur poori website mein reuse karte hain.

color-variables.css

```
:root {
  --primary: #00b4d8;
  --danger: #e94560;
  --text: #e8eaf6;
  --surface: #0d1b2a;
}

body {
  color: var(--text);
}

.card {
  background: var(--surface);
  border-color: var(--primary);
}
```

■ **Pro Tip:** Color variables ko meaningful naam do, jaise `--primary`, `--text`, `--surface`. Sirf `--blue` naam rakhoge toh future mein color blue se purple ho gaya toh naam confusing ho jayega.

■ 8. Contrast - Readability Ka Rule

Color choose karte time sabse important cheez contrast hai. Light background par dark text readable hota hai; dark background par light text readable hota hai. Low contrast text stylish lag sakta hai, lekin padhne mein difficult hota hai, especially mobile screen, sunlight ya weak eyesight users ke liye.

GOOD CONTRAST

Dark background + light text. Reading clear, accessible, comfortable.

LOW CONTRAST

Dark background + dark text. Stylish ho sakta hai, par readable nahi.

Google Fonts, @font-face aur Font Shorthand

Real projects mein custom fonts kaise use karte hain

KYA HAI?

Default fonts ke alawa hum custom fonts bhi use kar sakte hain. Most beginners ke liye **Google Fonts** easiest option hai. Advanced projects mein local font files ke liye `@font-face` use hota hai.

■ 1. Google Fonts Use Karna

Google Fonts se custom fonts use karna beginner-friendly hai. Website se font select karo, required weights choose karo, phir generated `<link>` tag HTML ke `<head>` mein paste karo. Uske baad CSS mein `font-family` set kar do.

Font load hone mein thoda time lag sakta hai. Isi liye Google Fonts URL mein `display=swap` hota hai. Iska matlab: jab tak custom font load nahi hota, browser fallback font show karega; font load hone ke baad custom font swap ho jayega.

● ● ● google-fonts.html

```
<!-- HTML head ke andar Google Font Link add karo -->
<link rel="preconnect" href="https://fonts.googleapis.com">
<link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
<link href="https://fonts.googleapis.com/css2?
family=Poppins:wght@400;600;700&display=swap" rel="stylesheet">
```

● ● ● use-google-font.css

```
body {
  font-family: 'Poppins', sans-serif;
}
```

■ **Pro Tip:** Google Fonts se sirf wahi weights load karo jo use karne wale ho. Example: `400;600;700`. Extra weights website ko slow kar sakte hain.

■ 2. @font-face - Local Font File Use Karna

`@font-face` tab use hota hai jab font file project ke andar locally rakhi ho. Example: `.woff2` file assets/fonts folder mein hai. Is method mein tum font ka custom naam define karte ho, file path dete ho, phir normal `font-family` ki tarah use karte ho.

`woff2` modern web font format hai aur mostly recommended hai kyunki compressed hota hai. Large font files website loading slow kar sakti hain, isliye unnecessary font weights aur styles avoid karo.

font-face.css

```
@font-face {  
  font-family: 'MyCustomFont';  
  src: url('fonts/my-font.woff2') format('woff2');  
  font-weight: 400;  
  font-style: normal;  
}  
  
body {  
  font-family: 'MyCustomFont', Arial, sans-serif;  
}
```

■ 3. font Shorthand Property

`font` shorthand se multiple font properties ek line mein likh sakte hain. Lekin order important hota hai.

Shorthand useful hai jab tum compact CSS likhna chahte ho. Lekin beginners ke liye separate properties zyada readable hoti hain. Jab debugging kar rahe ho, separate `font-size`, `font-weight`, `line-height` likhna better hota hai.

```
/* Order:
   font-style font-variant font-weight font-size/line-height font-family
*/

p {
  font: italic small-caps 600 18px/1.6 Arial, sans-serif;
}

/* Common practical shorthand */
.card-title {
  font: 700 24px/1.2 'Poppins', sans-serif;
}
```

■ **Warning:** Font shorthand use karte time `font-size` aur `font-family` required hote hain. Agar missing hue toh rule invalid ho sakta hai.

■ 4. Practical Typography System

Real website mein typography random values se nahi banani chahiye. Ek system banao: body text ka size fixed karo, headings ke sizes decide karo, line-height consistent rakho, aur colors variables se manage karo. Isse poori website professional aur consistent lagti hai.

```
body {  
  font-family: 'Poppins', Arial, sans-serif;  
  font-size: 16px;  
  line-height: 1.6;  
  color: #222;  
}  
  
h1 { font-size: 3rem; line-height: 1.1; font-weight: 700; }  
h2 { font-size: 2rem; line-height: 1.2; font-weight: 700; }  
h3 { font-size: 1.5rem; line-height: 1.3; font-weight: 600; }  
p { font-size: 1rem; line-height: 1.7; }  
small { font-size: 0.875rem; }
```

■ 5. Typography Hierarchy - User Ki Nazar Guide Karna

Typography ka kaam sirf beautiful text banana nahi hai. Iska main kaam user ki eye guide karna hai: pehle heading dikhe, phir subheading, phir paragraph, phir button/action. Isko visual hierarchy bolte hain.

Element	Typical Style	Reason
h1	Largest, bold, tight line-height	Page ka main topic instantly clear ho
h2	Large, bold/semi-bold	Sections clearly divide ho
h3	Medium, semi-bold	Sub-section readable ho
p	16px, normal weight, 1.6 line-height	Long reading comfortable ho
small	14px ya 0.875rem	Meta info, helper text, captions
button	Medium weight, clear color contrast	Action clearly visible ho

■ 6. Common Typography Mistakes

MISTAKE

Har heading ka random size.
Paragraph line-height too tight.
Ek page mein 4-5 fonts.
Low contrast gray text.
Button text too small.

FIX

3-5 font sizes ka scale banao.
Paragraph line-height 1.5-1.8 rakho.
1-2 fonts enough hain.
Contrast clearly test karo.
Buttons 14-16px readable rakho.

■ **Golden Rule:** Design mein font, text aur color alag-alag topics lagte hain, lekin real UI mein yeh saath kaam karte hain. Good typography = readable font + proper spacing + strong hierarchy + clear contrast.

Fonts, Text and Colors - Complete Summary

Important properties ek jagah revision ke liye

Category	Property	Example	Kya Karta Hai
Font	font-family	Arial, sans-serif	Font ka typeface set karta hai
Font	font-size	16px, 1rem	Text ka size set karta hai
Font	font-weight	400, 700, bold	Text ki thickness set karta hai
Font	font-style	italic	Text ko italic ya normal karta hai
Font	font-variant	small-caps	Small capital style apply karta hai
Font	line-height	1.6	Lines ke beech vertical gap
Text	text-align	center, right	Text ko align karta hai
Text	text-decoration	underline	Underline, overline, line-through
Text	text-transform	uppercase	Text case change karta hai
Text	letter-spacing	2px	Letters ke beech space
Text	word-spacing	4px	Words ke beech space
Text	text-indent	40px	First line ko indent karta hai
Text	white-space	nowrap	Spaces aur wrapping control karta hai
Text	text-overflow	ellipsis	Overflow text ko ... banata hai
Text	text-shadow	2px 2px 5px #000	Text ke peeche shadow
Color	color	#ffffff	Text ka color
Color	background-color	#0a0f1e	Element ka background color
Color	border-color	#1e3a5f	Border ka color
Color	outline-color	#00b4d8	Outline/focus ring ka color
Color	opacity	0.5	Poora element transparent karta hai

■ Best Practices - Yaad Rakhna

DO

Use readable font sizes.
Paragraph line-height 1.5-1.8 rakho.
Font family mein fallbacks add karo.
Color contrast clear rakho.
Reusable colors ke liye CSS variables use karo.

AVOID

Too many fonts ek page par mat use karo.
Paragraphs mein excessive letter-spacing mat do.
Focus outline bina replacement ke remove mat karo.
Low contrast text avoid karo.
Har element par random color mat lagao.

> NEXT TOPICS TO COVER

CSS Units (px, rem, em, %)

Display Property

Box Sizing Revision

Flexbox

CSS Grid

Positioning

Background Images

CSS Animations

Made with ❤️ for Web Development Course learners

Shauray ke saath CSS seekhte raho 🚀 | Topic 04 - Fonts, Text and Color Properties