HAVILAND PRODUCTS COMPANY SAFETY DATA SHEET



Section 1: Identification

Product Name: ADR #1 Product Code:H000735

Haviland Products Company 421 Ann Street NW Grand Rapids, MI 49504 (616) 361-6691

Emergency Phone CHEMTREC (800) 424-9300 CHEMTREC International (703) 527-3887

Product Use: NA

Not recommended for: NA

Section 2: Hazard(s) Identification

GHS Ratings:

-			
	Corrosive to metals	1	Corrosive to metals
	Dermal Toxicity	Acute Tox. 4	Dermal>1000+<=2000mg/kg
	Skin corrosive	1A	Destruction of dermal tissue: Exposure < 3 min. Observation < 1 hour, visible necrosis in at least one animal
	Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
	Organ toxin single exposure	1	Significant toxicity in humans- Reliable, good quality human case studies or epidemiological studies, Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low exposure (guidan
	Aquatic toxicity	A3	Acute toxicity <= 10.0 but < 100 mg/l

GHS Hazards	
H290	May be corrosive to metals
H312	Harmful in contact with skin
H314	Causes severe skin burns and
	eye damage
H318	Causes serious eye damage
H370	Causes damage to organs
H402	Harmful to aquatic life

GHS Precaution	<u>18</u>
P234	Keep only in original container
P260	Do not breathe
	dust/fume/gas/mist/vapors/spray
P264	Wash face, hands, and any exposed
	skin thoroughly after handling
P270	Do not eat, drink or smoke when using
	this product
P273	Avoid release to the environment
P280	Wear protective gloves/protective
	clothing/eye protection/face protection
P310	Immediately call a POISON CENTER or
	doctor/physician
P312	Call a POISON CENTER or
	doctor/physician if you feel unwell
P321	Specific treatment (see first aid
	treatment on SDS)
P322	Specific measures (see first aid
	treatment on SDS)
P363	Wash contaminated clothing before
	reuse

SDS for: 1.H000735.DF55L.Std.3 Page 1 of 6

P390 Absorb spillage to prevent material

damage

P301+P330+P33 IF SWALLOWED: Rinse mouth. Do

NOT induce vomiting

P302+P352 IF ON SKIN: Wash with soap and water P303+P361+P35 IF ON SKIN (or hair): Remove/Take off 3 immediately all contaminated clothing.

Rinse skin with water/shower

P304+P340 IF INHALED: Remove victim to fresh air

and keep at rest in a position

comfortable for breathing

P305+P351+P33 IF IN EYES: Rinse cautiously with

> water for several minutes. Remove contact lenses if present and easy to

do - continue rinsing

P307+P311 IF exposed: Call a POISON CENTER or

doctor/physician

P405 Store locked up

P406 Store in a corrosive resistant container

with a resistant inner liner

P501 Dispose of contents/container in

accordance with

local/regional/national/international

regulations

Danger



Section 3: Composition/Information on Ingredients

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Sodium hydroxide 1310-73-2 60 to 70%	2 mg/m3 TWA	2 mg/m3 Ceiling	NIOSH: 2 mg/m3 Ceiling
Trade Secret 20 to 30%			
Trade Secret 5 to 10%			
Sodium chloride 7647-14-5 1 to 5%			

8

Section 4: First-aid Measures

Inhalation

Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

Eye Contact

Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

Skin Contact

Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing

SDS for: 1.H000735.DF55L.Std.3 Page 2 of 6

separately and clean shoes before reuse.

Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Section	5:	Fire-fighting	Measures
---------	----	---------------	----------

LEL:

UEL:

Extinguishing Media

Use media suitable for surrounding fires

Specific Hazards Arising from the Chemical

In water solution will react with amphoteric metals (such as aluminum) to generate hydrogen, which is flammable and/or explosive if ignited.

Special Protective Equipment and Precautions for Firefighters

Special Information: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

Section 6: Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASE OR SPILLED:

Remove and reclaim as much as possible (shovel up). Neutralize remaining traces with dilute acid, flush with water.

Section 7: Handling and Storage

HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Ground and bond containers when transferring material. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight.

Section 8: Exposure Control/Personal Protection

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Sodium hydroxide 1310-73-2	2 mg/m3 TWA	2 mg/m3 Ceiling	NIOSH: 2 mg/m3 Ceiling
Trade Secret N/A			
Trade Secret N/A			
Sodium chloride 7647-14-5			

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant the use of a respirator.

SKIN PROTECTION: Wear impervious protective gloves. Wear protective gear as needed - apron, suit, boots.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

SDS for: 1.H000735.DF55L.Std.3 Page 3 of 6

HYGENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

Section 9: Physical and Chemical Properties

Appearance: Off White Powder

Vapor Pressure: Unknown

Vapor Density: Unknown

Density: Unknown

Freezing point: Unknown

Boiling range: Unknown

Evaporation rate: Unknown

Explosive Limits: Unknown

Autoignition temperature: Unknown

Viscosity: Unknown

Odor: Detergent Odor

Odor threshold: Unknown

pH: 1% Solution: 12.6

Melting point: Unknown

Solubility: Very Soluble

Flash point: Unknown

Flammability: Unknown

Specific Gravity 2.01

Decomposition temperature: Unknown

Grams VOC less water: Unknown

Section 10: Stability and Reactivity

Chemical Stability:

STABLE

Incompatibile Materials

All acids, copper, magnesium, aluminum, tin, zinc (galvanized), leather, wool, strong oxidizers.

Conditions to Avoid

Unknown

Hazardous Decomposition Products

Unknown

Hazardous Polymerization

Hazardous polymerization will not occur.

Section 11: Toxicology Information

Mixture Toxicity

Dermal Toxicity LD50: 1,960mg/kg Inhalation Toxicity LC50: 24mg/L

Component Toxicity

1310-73-2 Sodium hydroxide

Dermal LD50: 1,350 mg/kg (Rabbit)

Routes of Entry:

Inhalation Ingestion Skin contact Eye contact

Eyes Skin Respiratory System

Effects of Overexposure

SDS for: 1.H000735.DF55L.Std.3 Page 4 of 6

<u>CAS Number</u> <u>Description</u> <u>% Weight</u> <u>Carcinogen Rating</u>

Section 12: Ecological Information

Component Ecotoxicity

Sodium hydroxide 96 Hr LC50 Oncorhynchus mykiss: 45.4 mg/L [static]

Trade Secret 96 Hr LC50 Lepomis macrochirus: 300 mg/L [static]; 96 Hr LC50 Pimephales

promelas: 310 - 1220 mg/L [static] 48 Hr EC50 Daphnia magna: 265 mg/L

Sodium chloride 96 Hr LC50 Lepomis macrochirus: 5560 - 6080 mg/L [flow-through]; 96 Hr LC50

Lepomis macrochirus: 12946 mg/L [static]; 96 Hr LC50 Pimephales promelas: 6020 - 7070 mg/L [static]; 96 Hr LC50 Pimephales promelas: 7050 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 6420 - 6700 mg/L [static]; 96 Hr LC50

Oncorhynchus mykiss: 4747 - 7824 mg/L [flow-through]

48 Hr EC50 Daphnia magna: 1000 mg/L; 48 Hr EC50 Daphnia magna: 340.7 -

469.2 mg/L [Static]

Section 13: Disposal Considerations

Dispose of in accordance with local, state and federal regulations.

Section 14: Transportation Informations

Refer to Bill of Lading or container label for DOT or other transportation hazard classification, if any .

Section 15: Regulatory Information

CERCLA/SARA Hazardous Substances

1310-73-2 Sodium hydroxide

TSCA 8(b) Inventory

7647-14-5 Sodium chloride Trade Secret Trade Secret 1310-73-2 Sodium hydroxide

Country Regulation All Components Listed

Section 16: Other Information

Date Prepared: 6/4/2015

Reviewer Revision

Disclaimer

The information herein is believed to be correct, but does not claim to be all inclusive and should be used only as a guide. Neither the above named supplier nor any of its affiliates or subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All chemical reagents must be handled with the recognition that their chemical, physiological, toxicological, and hazardous properties have not been fully investigated or determined. All chemical reagents should be handled only by individuals who are familiar with their potential hazards and who have been fully trained in proper safety, laboratory, and chemical handling procedures. Although certain hazards are described herein, we can not guarantee that these are the only hazards which exist. Our SDS are based only on data available at the time of shipping and are subject to change without notice as new information is obtained. Avoid long storage periods since the product is subject to degradation with age and may become more dangerous or hazardous. It is the responsibility of the user to request updated SDS for products that are stored for extended periods. Disposal of unused product must be undertaken by qualified personnel

SDS for: 1.H000735.DF55L.Std.3

who are knowledgeable in all applicable regulations and follow all pertinent safety precautions including the use of appropriate protective equipment (e.g. protective goggles, protective clothing, breathing equipment, face mask, fume hood). For proper handling and disposal, always comply with federal, state and local regulations.

SDS for: 1.H000735.DF55L.Std.3 Page 6 of 6