Introduction

- Overview. What is the Internet? What is a protocol?
- Network edge
- Network core: packet/circuit switching, internet structure
- Performance: loss, delay, throughput
- Protocol layers, service models
- Security
- History

COMPSCI 453 Computer Networks


Professor Jim Kurose

College of Information and Computer Sciences
University of Massachusetts




Class textbook: Computer Networking: A Top-Down Approach (8th ed.) J.F. Kurose, K.W. Ross Pearson, 2020

http://gaia.cs.umass.edu/kurose ross



The network core


- mesh of interconnected routers
- packet-switching: hosts break application-layer messages into packets
 - network forwards packets from one router to the next, across links on path from source to destination



Two key network-core functions

Forwarding:

- aka "switching"
- local action: move arriving packets from router's input link to appropriate router output link




Routing:

- global action: determine sourcedestination paths taken by packets
- routing algorithms





Packet-switching: store-and-forward




- packet transmission delay: takes L/R seconds to transmit (push out) L-bit packet into link at R bps
- store and forward: entire packet must arrive at router before it can be transmitted on next link

One-hop numerical example:

- *L* = 10 Kbits
- *R* = 100 Mbps
- one-hop transmission delay= 0.1 msec

Packet-switching: queueing




Queueing occurs when work arrives faster than it can be serviced:







Packet-switching: queueing




Packet queuing and loss: if arrival rate (in bps) to link exceeds transmission rate (bps) of link for some period of time:

- packets will queue, waiting to be transmitted on output link
- packets can be dropped (lost) if memory (buffer) in router fills up

Alternative to packet switching: circuit switching

end-end resources allocated to, reserved for "call" between source and destination

- in diagram, each link has four circuits.
 - call gets 2nd circuit in top link and 1st circuit in right link.
- dedicated resources: no sharing
 - circuit-like (guaranteed) performance
- circuit segment idle if not used by call (no sharing)
- commonly used in traditional telephone networks



^{*} Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive


Circuit switching: FDM and TDM


Frequency Division Multiplexing (FDM)

- optical, electromagnetic frequencies divided into (narrow) frequency bands
- each call allocated its own band, can transmit at max rate of that narrow band

Time Division Multiplexing (TDM)

- time divided into slots
- each call allocated periodic slot(s), can transmit at maximum rate of (wider) frequency band (only) during its time slot(s)






Packet switching versus circuit switching

example:

- 1 Gb/s link
- each user:
 - 100 Mb/s when "active"
 - active 10% of time



Q: how many users can use this network under circuit-switching and packet switching?

- circuit-switching: 10 users
- packet switching: with 35 users, probability > 10 active at same time is less than .0004 *

Q: how did we get value 0.0004?

A: HW problem (for those with course in probability only)

^{*} Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive


Packet switching versus circuit switching

Is packet switching a "slam dunk winner"?

- great for "bursty" data sometimes has data to send, but at other times not
 - resource sharing
 - simpler, no call setup
- excessive congestion possible: packet delay and loss due to buffer overflow
 - protocols needed for reliable data transfer, congestion control
- Q: How to provide circuit-like behavior with packet-switching?
 - "It's complicated." We'll study various techniques that try to make packet switching as "circuit-like" as possible.


Q: human analogies of reserved resources (circuit switching) versus on-demand allocation (packet switching)?

- hosts connect to Internet via access Internet Service Providers (ISPs)
- access ISPs in turn must be interconnected
 - so that *any* two hosts (anywhere!) can send packets to each other
- resulting network of networks is very complex
 - evolution driven by economics, national policies




Let's take a stepwise approach to describe current Internet structure

Question: given millions of access ISPs, how to connect them together?




Question: given millions of access ISPs, how to connect them together?




Option: connect each access ISP to one global transit ISP?


Customer and provider ISPs have economic agreement.




But if one global ISP is viable business, there will be competitors




But if one global ISP is viable business, there will be competitors who will want to be connected




... and regional networks may arise to connect access nets to ISPs



... and content provider networks (e.g., Google, Microsoft, Akamai) may run their own network, to bring services, content close to end users






At "center": small # of well-connected large networks

- "tier-1" commercial ISPs (e.g., Level 3, Sprint, AT&T, NTT), national & international coverage
- content provider networks (e.g., Google, Facebook): private network that connects its data centers to Internet, often bypassing tier-1, regional ISPs

Tier-1 ISP Network map: Sprint (2019)



Introduction

- Overview. What is the Internet? What is a protocol?
- Network edge
- Network core: packet/circuit switching, internet structure
- Performance: loss, delay, throughput
- Protocol layers, service models
- Security
- History

COMPSCI 453 Computer Networks

Professor Jim Kurose

College of Information and Computer Sciences
University of Massachusetts



Class textbook:

Computer Networking: A TopDown Approach (8th ed.)

J.F. Kurose, K.W. Ross

Pearson, 2020

http://gaia.cs.umass.edu/kurose ross

