```
4 1.013348 172.25.99.109 128.119.245.12 TCP 78
                                                                                 56670 → 80
[SYN] Seq=690321719 Win=65535 Len=0 MSS=1460 WS=32 TSval=455737275 TSecr=0 SACK PERM=1
Frame 4: 78 bytes on wire (624 bits), 78 bytes captured (624 bits) on interface 0
Ethernet II, Src: Apple 00:03:9e (2c:f0:ee:00:03:9e), Dst: JuniperN 95:0f:f0 (08:81:f4:95:0f:f0)
Internet Protocol Version 4, Src: 172.25.99.109, Dst: 128.119.245.12
Transmission Control Protocol, Src Port: 56670 (56670), Dst Port: 80 (80), Seq: 690321719, Len: 0
   Source Port: 56670
   Destination Port: 80
    [Stream index: 1]
    [TCP Seament Len: 0]
   Sequence number: 690321719
   Acknowledgment number: 0
   Header Length: 44 bytes
   Flags: 0x002 (SYN)
   Window size value: 65535
    [Calculated window size: 65535]
   Checksum: 0x1702 [validation disabled]
   Urgent pointer: 0
   Options: (24 bytes), Maximum segment size, No-Operation (NOP), Window scale, No-Operation
(NOP), No-Operation (NOP), Timestamps, SACK permitted, End of Option List (EOL)
```