

ESP32 Classical Key Exchange Benchmark

Phase A: Isolated Micro-Benchmarks (No Network Involved)

FYP Documentation: Embedded VPN Client (Deliverable 3)

Department of Computer Engineering

October 2026

1 Phase A: Isolated Micro-Benchmarks (No Network Involved)

Phase A benchmarks the raw cryptographic execution of three key exchange schemes on an ESP32-D0WDQ6 microcontroller running at 240 MHz. Tests run locally in chip memory without network stack overhead to profile pure computational cost, memory allocation, and payload footprint:

1. **X25519:** Modern Montgomery-curve Diffie-Hellman algorithm over Curve25519 (RFC 7748).
2. **ECDH P-256:** Standard NIST elliptic curve algorithm over secp256r1.
3. **Classical DH-2048:** Classic Finite Field Diffie-Hellman configured with RFC 3526 2048-bit MODP prime.

2 Key Performance Indicators (KPIs)

The evaluation profiles six Key Performance Indicators (KPIs) covering execution latency, hardware workload, wire footprint, and RAM consumption.

2.1 KPI Definitions and Operational Impact

- **KEX-1 (Key Generation Time):** Elapsed time to generate a fresh ephemeral public and private key pair. Determines the latency overhead when creating ephemeral keys for session forward secrecy.
- **KEX-2 (Public Key Size):** Encoded byte length of the public key transmitted over the network channel.
- **KEX-3 (Secret Derivation Time):** Elapsed time to compute the shared secret from the peer's public key.
- **KEX-4 (Shared Secret Size):** Encoded byte length of the derived shared secret output fed into HKDF for symmetric session key derivation.
- **KEX-5 (Total Client Compute Time):** Total on-chip processor time (KEX-1 + KEX-3) required for complete client key exchange.
- **KEX-6 (Peak Dynamic Heap Memory):** Dynamic RAM allocated from the ESP32 heap during cryptographic operations. Excessive allocations risk Out-Of-Memory (OOM) resets.
- **Hardware CPU Cycles (@ 240 MHz):** Hardware processor cycles consumed during execution. Because the ESP32 clock operates at 240 MHz (240,000,000 cycles per second), hardware cycle counts provide an exact, clock-invariant metric:

$$\text{Time (ms)} = \frac{\text{CPU Cycles}}{240,000} \quad (1)$$

2.2 Iteration Count Strategy

- **Benchmark Iterations ($N = 100$):** All three algorithms (X25519, ECDH P-256, and DH-2048) were executed 100 times to compute stable arithmetic means and cancel out OS scheduling jitter.

- **FreeRTOS Watchdog Mitigation:** In Classical DH-2048, periodic yields (`vTaskDelay(1)`) prevent Task Watchdog Timer (TWDT) resets during heavy modular exponentiation loops.

Table 1: Summary of Key Exchange Benchmarking KPIs

KPI ID	Metric Name	Unit	Operational Significance for Embedded VPN
KEX-1	Key Generation Time	ms / cycles	Time spent generating client ephemeral keypair
KEX-2	Public Key Wire Size	Bytes	Network transmission payload per session
KEX-3	Secret Derivation Time	ms / cycles	Time spent computing shared secret from peer key
KEX-4	Shared Secret Output Size	Bytes	Output size fed into HKDF key derivation
KEX-5	Total Client Compute Time	ms / cycles	Total CPU time (KEX-1 + KEX-3) per handshake
KEX-6	Peak Dynamic Heap RAM	Bytes	Dynamic RAM consumed during test

3 Comparison Tables

3.1 Performance Comparison

Table 2 summarizes the empirical metrics collected across all three algorithms on the ESP32 at 240 MHz, indicating the best performer for each parameter.

Table 2: Performance Comparison: X25519 vs. ECDH P-256 vs. Classical DH-2048

Metric	X25519	ECDH P-256	DH-2048	Winner	Performance Factor
Execution Latency (Milliseconds)					
Key Generation Time	8.47 ms	156.83 ms	31.60 ms	X25519	18.5× faster than P-256
Secret Derivation Time	16.91 ms	156.73 ms	31.44 ms	X25519	9.3× faster than P-256
Total Client Crypto Time	25.38 ms	313.56 ms	63.04 ms	X25519	12.4× faster than P-256
Hardware CPU Cycles (@ 240 MHz)					
KeyGen Cycles	2,033,095	37,638,242	7,583,754	X25519	Lowest compute workload
Derivation Cycles	4,057,917	37,615,903	7,546,518	X25519	Lowest compute workload
Total Client Cycles	6,091,012	75,254,145	15,130,272	X25519	Lowest compute workload
Communication Payload (Bytes)					
Public Key Size	32 bytes	65 bytes	256 bytes	X25519	8.0× smaller than DH-2048
Shared Secret Size	32 bytes	32 bytes	256 bytes	—	256-bit symmetric key seed
Total Data Footprint	64 bytes	97 bytes	512 bytes	X25519	8.0× smaller than DH-2048
Memory Utilization					
Peak Dynamic Heap RAM	0 bytes	348 bytes	636 bytes	X25519	Stack only (0 bytes heap)

4 Selection Rationale for X25519

X25519 was selected as the key exchange scheme for the ESP32 VPN client based on four critical technical advantages:

1. **Minimal Computation Latency (2.5x to 12.4x speed advantage):** X25519 completes key generation in **8.47 ms** and secret derivation in **16.91 ms**, totaling **25.38 ms**. In comparison, Classical DH-2048 requires **63.04 ms** (2.48× slower) and ECDH P-256 requires **313.56 ms** (12.35× slower). The entire X25519 key exchange executes in approximately 25 ms, eliminating connection setup bottlenecks.
2. **Compact Wire Payload (8x smaller than DH-2048):** X25519 requires only **32 bytes** on the wire for the public key, compared to 65 bytes for ECDH P-256 (uncompressed format) and 256 bytes for DH-2048. The compact 32-byte payload fits into single-packet envelopes,

avoids MTU fragmentation, and minimizes Wi-Fi radio transmission time to preserve battery life.

3. **Zero Heap Memory Overhead (0 bytes vs. 348 and 636 bytes):** The ESP32 has approximately 320 KB of usable RAM shared among Wi-Fi drivers, network buffers, and RTOS queues. X25519 consumes **0 bytes of dynamic heap memory**, executing purely within the local stack frame. In contrast, ECDH P-256 allocates 348 bytes and DH-2048 allocates 636 bytes for multi-precision integer contexts, introducing memory fragmentation risks.
4. **Deterministic Constant-Time Timing & Side-Channel Resistance:** X25519 utilizes the Montgomery ladder algorithm, which naturally executes in constant time regardless of the private key value, preventing timing and power side-channel attacks. Furthermore, any 32-byte array constitutes a valid Curve25519 point, eliminating point-on-curve validation checks that are prone to implementation bugs in Weierstrass curves like P-256.
5. **Rationale for Hardcoded RFC 3526 MODP Prime in DH-2048:** In Classical DH-2048, safe prime generation ($p = 2q + 1$) dynamically at runtime on an ESP32 is computationally prohibitive, requiring minutes of Miller-Rabin primality testing and causing watchdog time-outs. The standardized RFC 3526 2048-bit MODP prime is mathematically verified, provides instant initialization, and prevents small-subgroup confinement attacks.

5 Serial Monitor Output Verification

The terminal captures below confirm execution runs and heap measurements recorded on the ESP32 hardware:

5.1 Detailed Per-Algorithm Execution Capture

Figure 1 displays the serial output across 100 runs, showing exact cycle counts, converted millisecond timings, wire sizes, and peak dynamic heap RAM for X25519, ECDH P-256, and DH-2048.

5.2 Benchmark Results Summary Table Capture

Figure 2 displays the terminal output summarizing all tested algorithms across all evaluated KPIs (KEX-1 through KEX-6).

6 Graphical Benchmark Visualizations

The figures below plot the empirical metrics across execution latency, communication payload, and heap memory:

6.1 Execution Latency Comparison

Figure 3 compares key generation, secret derivation, and total compute latency on a logarithmic scale.

6.2 Handshake Communication Overhead

Figure 4 breaks down public key and shared secret output sizes in bytes.

6.3 Dynamic Heap Memory Overhead

Figure 5 illustrates the peak dynamic heap RAM consumed during algorithm execution.

```

=====
ESP32 Classical Key Exchange Micro-Benchmark (Phase A: Isolated)
Iterations: 100 | CPU Frequency: 240 MHz | Initial Free Heap: 329480 bytes
=====

[1/3] X25519 (Curve25519)
KEX-1 Key Generation Latency      : 2033095 cycles | 8.47 ms
KEX-2 Public Key Wire Size        : 32 bytes
KEX-3 Secret Derivation Latency   : 4057917 cycles | 16.91 ms
KEX-4 Shared Secret Output Size   : 32 bytes
KEX-5 Total Client Compute Time   : 6091012 cycles | 25.38 ms
KEX-6 Peak Dynamic Heap Memory    : 0 bytes

[2/3] ECDH P-256 (secp256r1)
KEX-1 Key Generation Latency      : 37638242 cycles | 156.83 ms
KEX-2 Public Key Wire Size        : 65 bytes
KEX-3 Secret Derivation Latency   : 37615903 cycles | 156.73 ms
KEX-4 Shared Secret Output Size   : 32 bytes
KEX-5 Total Client Compute Time   : 75254145 cycles | 313.56 ms
KEX-6 Peak Dynamic Heap Memory    : 348 bytes

[3/3] Classical DH-2048 (RFC 3526 MODP)
KEX-1 Key Generation Latency      : 7583754 cycles | 31.60 ms
KEX-2 Public Key Wire Size        : 256 bytes
KEX-3 Secret Derivation Latency   : 7546518 cycles | 31.44 ms
KEX-4 Shared Secret Output Size   : 256 bytes
KEX-5 Total Client Compute Time   : 15130272 cycles | 63.04 ms
KEX-6 Peak Dynamic Heap Memory    : 636 bytes

```

Figure 1: ESP32 Serial Output for Key Exchange Micro-Benchmarks (100 runs, 240 MHz).

BENCHMARK RESULTS SUMMARY				
KPI ID	Metric	X25519	ECDH P-256	DH-2048
KEX-1	Key Generation Time	8.47 ms	156.83 ms	31.60 ms
KEX-2	Public Key Wire Size	32 B	65 B	256 B
KEX-3	Secret Derivation Time	16.91 ms	156.73 ms	31.44 ms
KEX-4	Shared Secret Output Size	32 B	32 B	256 B
KEX-5	Total Client Compute Time	25.38 ms	313.56 ms	63.04 ms
KEX-6	Peak Dynamic Heap RAM	0 B	348 B	636 B

Figure 2: ESP32 Serial Output showing the automated Benchmark Results Summary Table.




Figure 3: Execution time comparison (logarithmic scale) for KeyGen, Secret Derivation, and Total Compute.




Figure 4: Key exchange communication overhead (Public Key + Shared Secret size in bytes).




Figure 5: Dynamic heap memory consumed by each key exchange algorithm on the ESP32.

7 Benchmarking Logic and Pseudocode

The pseudocode below details the measurement routine implemented on the ESP32, including cycle counter acquisition, heap profiling, and test loops for each algorithm:

7.1 Setup and Hardware Measurement Helpers

```
// Configuration: ESP32 runs at 240 MHz clock speed
const uint32_t CPU_FREQ_MHZ = 240;
const int ITERATIONS = 100;

// Reads 32-bit hardware cycle register directly from ESP32 core
static inline uint32_t read_cpu_cycles() {
    uint32_t ccount;
    __asm__ __volatile__ ("rsr %0, ccount" : "=a"(ccount));
    return ccount;
}

// Converts raw CPU clock cycles into milliseconds
float cycles_to_ms(uint32_t cycles) {
    return (float)cycles / (CPU_FREQ_MHZ * 1000.0f);
}
```

7.2 X25519 Benchmark Routine

```
// Step 1: Benchmark X25519 (Curve25519 via Libsodium)
uint8_t client_pk[32], client_sk[32], peer_pk[32], peer_sk[32], shared[32];
crypto_kx_keypair(peer_pk, peer_sk);

uint32_t heap_before = ESP.getFreeHeap();
uint32_t peak_heap = 0;

for (int i = 0; i < ITERATIONS; i++) {
    // 1. Key Generation (KEX-1)
    uint32_t t0 = read_cpu_cycles();
    crypto_kx_keypair(client_pk, client_sk);
    uint32_t t1 = read_cpu_cycles();
```

```

keygen_cycles += (t1 - t0);

// Peak Heap Profiling (KEX-6)
uint32_t used_heap = heap_before - ESP.getFreeHeap();
if (used_heap > peak_heap) peak_heap = used_heap;

// 2. Secret Derivation (KEX-3)
uint32_t t2 = read_cpu_cycles();
crypto_scalarmult(shared, client_sk, peer_pk);
uint32_t t3 = read_cpu_cycles();
deriv_cycles += (t3 - t2);
}

```

8 Conclusion and Deliverable 3 Alignment

The empirical findings from Phase A confirm that **X25519 (Curve25519)** is the optimal classical key exchange primitive for the embedded IoT VPN client. With a total cryptographic compute time of **25.38 ms**, an ultra-compact **32-byte** wire payload, **0 bytes** of dynamic heap consumption, and constant-time execution, X25519 provides the highest performance and security margin on resource-constrained microcontrollers.

These results finalize the classical baseline for Deliverable 3 (Phase A Isolated Benchmark), establishing the reference benchmark for the subsequent Post-Quantum Cryptography transition.