DAY 3

# Nmap Reconnaissance Scan Report

Hands-on Cybersecurity Lab | TCP Port & Service Discovery

| | |
|---|---|
| Scan date | 26 October 2026 (as recorded in Nmap output) |
| Tool / version | Nmap 7.95 |
| Target IP | 192.168.18.164 |
| Scan scope | TCP ports 1–1000 |
| Scan options | -sV -sC -O -p 1-1000 -oN day3-scan.txt |
| Duration | 1.86 seconds |
| Result | Host up; 1,000 scanned TCP ports reported closed; no open ports found |

## 1. Objective

Identify reachable TCP ports and attempt to determine exposed services, software versions, default-script findings, and operating-system information on an authorized lab target.

## 2. Methodology

A TCP scan of ports 1–1000 was run with service/version detection (-sV), Nmap default scripts (-sC), OS detection (-O), and normal-format output logging (-oN). The command recorded in the scan file was:

```
sudo nmap -sV -sC -O -p 1-1000 -oN day3-scan.txt 192.168.18.164
```

## 3. Results

| Scope | Observed result | Interpretation | Status |
|---|---|---|---|
| Host reachability | Host is up; ~0.000099 s latency | Target responded to discovery | Observed |
| TCP ports 1–1000 | 1,000 closed (reset) | No open TCP ports found in this range | Observed |
| Service/version detection | No services listed | No service versions identified | Not identified |
| OS detection | Too many fingerprints match | OS could not be identified confidently | Inconclusive |
| Network distance | 0 hops | Nmap reports no intervening routed hop | Observed |

## 4. Risk assessment

No exposed services or service-specific vulnerabilities were identified in the scanned TCP ports 1–1000. This is a limited-scope result, not proof that the host is secure. Ports 1001–65535, UDP services, other interfaces, application-layer issues, and host configuration were not assessed by this scan. No critical/high/medium vulnerability rating is assigned because the output contains no evidence of a specific vulnerability.

## 5. Recommendations / next steps

- Confirm that 192.168.18.164 is the intended lab target and that the scan was authorized.
- If broader TCP coverage is needed, run: sudo nmap -sV -p- --open -oN day3-all-ports.txt 192.168.18.164
- If open ports are found, run targeted service and default-script checks against only those ports.
- Consider UDP scanning only when appropriate for the lab; it may take longer.
- Record exact commands, date, scope, and outputs. Redact sensitive hostnames, public IPs, tokens, or personal data before publishing.

## 6. Evidence

Source evidence: terminal output from day3-scan.txt, including the Nmap 7.95 command and summary.

**Key output:** “Host is up”; “All 1000 scanned ports…”; “1000 closed tcp ports (reset)”; “Too many fingerprints match this host to give specific OS details.”

## 7. Conclusion

The target was reachable, but no open TCP ports were detected in the scanned range 1–1000. OS identification was inconclusive. Further testing should begin by confirming the target and expanding the authorized scan scope if required. Findings should be updated only when supported by new scan evidence.

## Portfolio publication note

This report documents a beginner reconnaissance lab and should be labelled as a learning exercise, not as a professional penetration test or proof of vulnerability discovery. Before making the raw scan output public, confirm that the target is your own lab machine and remove identifying details if necessary.