

Biomechanical modeling of soft tissue multiphysics using hybrid machine learning and finite element analysis

Seyed Shayan Sajjadinia

Faculty of Computer Science, Free University of Bozen-Bolzano, 39100 Bozen-Bolzano, Italy

CMBBE2021
7 – 9 September 2021, Bonn, Germany

17th International Symposium
on Computer Methods in Biomechanics
and Biomedical Engineering and
5th Conference on Imaging and Visualization

www.cmbbe-symposium.com

Seyed Shayan Sajjadinia



Faculty of Computer Science,
Free University of Bozen-Bolzano,
39100 Bozen-Bolzano, Italy

A PhD candidate with background in:

- Biomechanics
- Multiphysics modeling
- Finite element analysis
- Machine learning




AUTHORS & AFFILIATIONS

- **Seyed Shayan Sajjadinia** (Faculty of Computer Science, Free University of Bozen-Bolzano, 39100 Bozen-Bolzano, Italy)
- **Bruno Carpentieri** (Faculty of Computer Science, Free University of Bozen-Bolzano, 39100 Bozen-Bolzano, Italy)
- **Duraisamy Shriram** (Engineering Product Development (EPD) Pillar, Singapore University of Technology and Design (SUTD), 487372 Singapore)
- **Gerhard A. Holzapfel**: (Institute of Biomechanics, Graz University of Technology, Stremayrgasse 16/2, 8010 Graz, Austria, and Department of Structural Engineering, Norwegian University of Science and Technology (NTNU), Trondheim, Norway)



Introduction: finite element modeling




Limitations

Expensive


Complex

Methodology: surrogate modeling

Machine learning



Hybrid machine learning (HML)



Methodology: multi-fidelity modeling

High-fidelity model

$$\nabla \cdot (\boldsymbol{\sigma}_T) = 0$$


$$\nabla \cdot (\dot{\mathbf{u}} - \kappa \nabla p) = 0$$

Low-fidelity model


$$\nabla \cdot (\boldsymbol{\sigma}_{LF}) = 0$$

We use multiphysics!


Methodology: 2D models



Initial condition





Under shear loading




Under axial loading



Methodology: 2D models





Methodology: 3D model



Methodology: 3D model





Results and discussion: 2D model



Results and discussion: 3D model

#High-fidelity training samples	Surrogate model			
	DL-1	HML-1	DL-2	HML-2
13	0.055	0.009	0.033	0.015
26	0.047	0.034	0.049	0.011
39	0.174	0.049	0.060	0.016

Results and discussion: 3D model



Conclusions

Benefits	Implementation efficiency.
	Performance increase.
	8 to 19 times faster.
Limitations	Application of two numerical models.
	Longer training of the 3D model.
	Requiring tuning.

References

- [1] S. S. Sajjadinia, M. Haghpanahi, and M. Razi, “Computational simulation of the multiphasic degeneration of the bone-cartilage unit during osteoarthritis via indentation and unconfined compression tests,” *Proceedings of the Institution of Mechanical Engineers, Part H: Journal of Engineering in Medicine*, vol. 233, p. 871–882, Sep 2019.
- [2] A. Erdemir, “Open knee: Open source modeling and simulation in knee biomechanics,” *Journal of Knee Surgery*, vol. 29, p. 107–116, Oct 2014.

Thank you for your time!

Website:
www.cmbbe-symposium.com

Email:
info@cmbbe-symposium.com

Twitter:
[@cmbbesymposium](https://twitter.com/cmbbesymposium)

Facebook:
[@cmbbesymposium](https://facebook.com/cmbbesymposium)