




ECONOMY ♦ EXCELLENCE ♦ ETHICS

MERINO HANEX

SOLID SURFACES BY HYUNDAI L&C

MERINO- HANEX COLLECTION



ST - 001 (CLARA)*




ST - 002 (MARELINHO)*



D-001 (SILVER STONE)



T-089 (VOCALISE)



T-201 (FETA CHEESE)



D-025 (LIGHTSAND)



C-001 (CUBIC WHITE)



P-004 (SOLARIS)



T-201 (PURE ARCTIC)



S-008 (N-WHITE)



M-003 (M-RED)



M-006 (N-YELLOW)



M-005 (N-ORANGE)



S-022 (STEEL)



D-007 (MIST)



CC-001 (CASCADE ICE)*




CC-002 (CASCADE CREAM)*



CC-003 (CASCADE GREY)*




CC-004 (CASCADE BEIGE)*



T-216 (L-GREY)

MERINO- HANEX COLLECTION



D-024 (SILVER WHITE)




ST-201 (ROMANO)*




P-002 (METAL GREY)



U-002 (CONCRETE GREY)



T-012 (H-ELEGANCE)




S-004 (IVORY)



S-006 (GREY)



ST-005 (MORENO)*




D-003 (GOLD BROWN)



T-239 (STONE GREY)




T-243 (BROWN COOKIE)



S-019 (BROWN FEVER)



D-028 (BLACK BEAT)



M-007 (BLACK)



VM-01 (VENATO SPARKLE)*



VM-02 (VENATO SNOW)*

CARE & MAINTENANCE

Everyday cleaning: Wipe clean with a damp cloth or sponge. For basic stains, clean with mild detergents or general all purpose cleaners. Periodically go over surface with a mild abrasive cleanser to maintain a uniform appearance.

Heat damage: To prevent any damage from heat, never place hot items directly on the surface. Always use trivets with rubber feet when placing hot items on the Solid Surface.

Chemical damage: Avoid contact with strong chemicals that can cause damage to the surface such as oven cleaners, acetone, paint removers and other strong chemicals. If exposed, promptly rinse with water. Remember, prolonged contact with harsh chemicals can cause serious damage to the Solid Surface. Simple steps to avoid damage: Avoid cutting directly on the Solid Surface. Always use a cutting board. Never place hot pans directly on the Solid Surface.

Removing persistent stains: To remove persistent stains or scratches, scrub the stained area with a mild abrasive cleanser. Deep scratches and/or other damages may require professional repair. Only Hanex Joint Adhesive is recommended for use on Merino - Hanex Solid Surfaces.



CERTIFICATION & ACCREDITATION

At Merino, maintaining quality is a tradition which is lived with a passion. We encourage the adherence to safety standards, promote ease-of-application, strive to reduce installation time, and help our customers maintain their interiors with relevant usage information.



WHY MERINO - HANEX SOLID SURFACES?

Easy to fabricate: These solid surfaces can be fabricated into any shape and can be joined without visible seaming line.

Durability: Excellent in both colour and durability, these solid surfaces are the best choice as finishing materials for interiors. These are stronger than natural stone and maintain their shapes and beauty in any condition.

Stability: These solid surfaces are thermally stable. These surfaces are heat resistant, hot water resistant, chemical resistant, stain resistant, UV stable and can stand all weather changes on interior applications.

Easy to maintain and repair: These solid surfaces are water resistant, which makes them easy to maintain and a perfect fit for damp areas such as bathrooms and kitchens.

Refined design and unlimited possibilities of application: These solid surfaces offer style that is comparable to natural stone or marble and can be used in any indoor application. With a wide range of colours and patterns, they provide elegance and aesthetic interiors.

TECHNICAL SPECIFICATIONS

Specification	Tolerance	Test Standard	Hanex
Composition			(12 mm Thickness)
Aluminum	60-65%	60-65%	60-65%
Polymer	33% max	30-35%	30-35%
Additives	3-5%	4-5%	4-5%
Tensile Strength	5800 to 6200 PSI	(ASTM D638-22)	6000.0
Flexural Strength	61 to 72 MPa	(ASTM D790-17)	64.3
Flexural Modulus	10.9 to 11.5 GPa	(ASTM D790-17)	11.5 Gpa
Hardness	>85 Rockwell Scale	(ASTM D785-08)	86
Thermal Expansion	3.02 x 10-5 mm/mm/°C	ASTM D 696(EN14581)	3.04 x 10-5
Light Resistance (Xenon Arc)	No effect	(NEMA LD3)	Pass
Wear and Cleanability	Passes	(ANSI Z124.3)	Pass
Stain Resistance Sheets	Passes Rating >4	(ANSI Z124.3)	Pass
Fungus and Bacteria Resistance	Does not support Microbial Growth	(ASTM G21)	No Growth
Resistance to wet heat	No Visible Change	(JIS K 6902)	No Defects
Impact Resistance	No break	(NEMA LD3, ISO 4586-2)	Pass
Density	1.66 to 1.75	(ASTM D792-20)	1.72
Water absorption	0.02 to 0.05 %	ASTM D570-98(2010)e1	0.03%
Thickness of Sheets	12mm ± 0.8		12mm ± 0.8



SIZE MATRIX			
Thickness (MM)	Width (MM) (FT)	Length (MM) (FT)	Weight (KG)
6 MM	760 MM 2.5 Feet	2490 MM 8' Feet	20 - 21 KG
12 MM	760 MM 2.5 Feet	3680 MM 12' Feet	59 - 61 KG

HANEX IS THE REGISTERED TRADE MARK OF HYUNDAI L&C - SOUTH KOREA.

REGISTERED OFFICE

 **MERINO INDUSTRIES LIMITED**
5, Alexandra court, 60/1, Chowringhee Road,
Kolkata-70002, India
☎ 033-22901214/1215
✉ merinokol@merinoindia.com

MARKETING OFFICE

 **MERINO INDUSTRIES LIMITED**
70, KLJ Complex, 2nd Floor, Moti Nagar,
New Delhi-110015, India
☎ 011-45557000, 25107617
✉ merinodelhi@merinoindia.com

CONTACT US

 080-69056500
 www.merinolaminates.com

Scan for
E-Catalogue

Laminates | Compacts | Panels | Solid Surfaces | Plywood | Flooring | Restroom Solutions | Furniture Solutions



ECONOMY • EXCELLENCE • ETHICS