

Assignment 4, Two Dots game Specification

SFWR ENG 2AA4

April 2, 2020

This Module Interface Specification (MIS) document contains modules, types and methods for implementing a game of Two Dots

Color Module

Module

Color

Uses

N/A

Syntax

Exported Constants

None

Exported Types

Color = {R, G, B, P, Y}

//R stands for Red, G for green, B for blue, P for Purple, Y for yellow

Exported Access Programs

Routine name	In	Out	Exceptions
randomColor		Color	

Semantics

State Variables

colors: color

State Invariant

None

Access Routine Semantics

randomColor():

- transition: none

- output: $out := \text{randomVal}()$
- exception: none

Local Functions

$\text{randomVal}()$: Color

$\text{randomVal}() \equiv (i = 0 \implies \text{R} \mid i = 1 \implies \text{G} \mid i = 2 \implies \text{B} \mid i = 3 \implies \text{P} \mid i = 4 \implies \text{Y})$

Where i is a uniformly-distributed random number in the range $0 \leq i \leq 4$

Point ADT Module

Template Module

PointT

Uses

N/A

Syntax

Exported Types

PointT = ?

Exported Access Programs

Routine name	In	Out	Exceptions
PointT	\mathbb{Z}, \mathbb{Z}	PointT	
row		\mathbb{Z}	
col		\mathbb{Z}	
translate	\mathbb{Z}, \mathbb{Z}	PointT	

Semantics

State Variables

r : \mathbb{Z}

c : \mathbb{Z}

State Invariant

None

Assumptions

The constructor PointT is called for each object instance before any other access routine is called for that object. The constructor cannot be called on an existing object.

Access Routine Semantics

PointT(*row*, *col*):

- transition: $r := row, c := col$
- output: $out := self$
- exception: None

row():

- output: $out := r$
- exception: None

col():

- output: $out := c$
- exception: None

Generic Board Module

Generic Template Module

Board(T)

Uses

PointT

Syntax

Exported Types

Board(T) = ?

Exported Constants

None

Exported Access Programs

Routine name	In	Out	Exceptions
Board	\mathbb{N}, \mathbb{N}	Board	IllegalArgumentException
set	PointT, T		IndexOutOfBoundsException
get	PointT	T	IndexOutOfBoundsException
getNumRow		\mathbb{N}	
getNumCol		\mathbb{N}	

Semantics

State Variables

s : seq of (seq of T)

nRow: \mathbb{N}

nCol: \mathbb{N}

State Invariant

None

Assumptions

- The Board(T) constructor is called for each object instance before any other access routine is called for that object. The constructor can only be called once.
- $s[i][j]$ means the i th row and the j th column. The 0th row is at the top of the grid and the 0th column is at the leftmost side of the grid.

Access Routine Semantics

Board(row, col):

- transition (note that the list does not enforce an *order* in which the transitions occur, only the transitions that must occur):
 1. $nRow := row$
 2. $nCol := col$
- output: $out := self$
- exception:
 $exc := (row \leq 0) \vee (col \leq 0) \implies IllegalArgumentException$

set(p, v):

- transition: $s[p.row()][p.col()] = v$
- exception:
 $\neg \text{validPoint}(p) \implies IndexOutOfBoundsException$

get(p):

- output: $out := s[p.row()][p.col()]$
- exception:
 $\neg \text{validPoint}(p) \implies IndexOutOfBoundsException$

getNumRow():

- output: $out := nRow$
- exception: None

getNumCol():

- output: $out := nCol$
- exception: None

Local Functions

validRow: $\mathbb{N} \rightarrow \mathbb{B}$

$\text{validRow}(r) \equiv r \geq 0 \wedge (r < \text{nRow})$

validCol: $\mathbb{N} \rightarrow \mathbb{B}$

$\text{validCol}(c) \equiv (c \geq 0) \wedge (c < \text{nCol})$

validPoint: $\text{PointT} \rightarrow \mathbb{B}$

$\text{validPoint}(p) \equiv \text{validCol}(p.\text{col}()) \wedge \text{validRow}(p.\text{row}())$

BoardMoves Module

Template Module

BoardMoves is seq of PointT

Considerations

When using in Java. Use ArrayList parameterized by PointT

TwoDotsBoard Module

Template Module

TwoDotsBoard is Board(Color)

Syntax

Exported Constants

None

Exported Access Programs

Routine name	In	Out	Exceptions
validateMoves	BoardMoves	\mathbb{B}	
updateBoard	BoardMoves		

Semantics

Access Routine Semantics

validateMoves(b):

- $\text{output} : \text{out} := |b| > 1 \wedge \forall(p : \text{PointT} | p \in b : \text{validPoint}(p)) \wedge \text{validPath}(b) \wedge \text{isDistinct}(b)$
- exception: None

updateBoard(b):

- $\text{output} : \text{out} := \text{None}$
- $\text{transition} : s := p \forall(p : \text{PointT} | p \in b \forall(i : \mathbb{N} | i \in [p.\text{row()}..1]))$
- exception: None

Local Functions

validRow: $\mathbb{N} \rightarrow \mathbb{B}$

$\text{validRow}(r) \equiv r \geq 0 \wedge (r < \text{nRow})$

validCol: $\mathbb{N} \rightarrow \mathbb{B}$

$\text{validCol}(c) \equiv (c \geq 0) \wedge (c < \text{nCol})$

validPoint: $\text{PointT} \rightarrow \mathbb{B}$

$\text{validPoint}(p) \equiv \text{validCol}(p.\text{col}()) \wedge \text{validRow}(p.\text{row}())$

isDistinct: $\text{BoardMoves} \rightarrow \mathbb{B}$

$\text{isDistinct}(b) \equiv \forall(i : \mathbb{N} | i \in [0..|b| - 1] : \forall(j : \mathbb{N} | j \in [(i + 1)..|b| - 1]) : \neg(b[i].\text{row}() = b[j].\text{row}()) \wedge (b[i].\text{col}() = b[j].\text{col}()))$

validPath: $\text{BoardMoves} \rightarrow \mathbb{B}$

$\text{validPath}(b) \equiv \forall(i : \mathbb{N} | i \in [0..|b| - 2] : \text{isAdjacent}(b, i, i + 1) \wedge \text{sameColor}(b, i, i + 1)) \wedge$

$\text{sameColor} : \text{BoardMoves} \times \mathbb{N} \times \mathbb{N} \rightarrow \mathbb{B}$

$\text{sameColor}(b, i, j) \equiv s[b[i].\text{row}()][b[i].\text{col}()] = s[b[j].\text{row}()][b[j].\text{col}()]$

isAdjacent: $\text{BoardMoves} \times \mathbb{N} \times \mathbb{N} \rightarrow \mathbb{B}$

$\text{isAdjacent}(b, i, j) \equiv b[i].\text{row}() = b[j].\text{row}() \wedge b[i].\text{col}() = b[j].\text{col}() + 1$

$\vee b[i].\text{row}() = b[j].\text{row}() \wedge b[i].\text{col}() = b[j].\text{col}() - 1$

$\vee b[i].\text{row}() = b[j].\text{row}() - 1 \wedge b[i].\text{col}() = b[j].\text{col}()$

$\vee b[i].\text{row}() = b[j].\text{row}() + 1 \wedge b[i].\text{col}() = b[j].\text{col}()$

Strategy Interface Module

Interface Module

Strategy

Syntax

Exported Constants

None

Exported Access Programs

Routine name	In	Out	Exceptions
play	TwoDotsBoard		

BoardView Module

Template Module

BoardView

Syntax

Exported Constants

None

Exported Access Programs

Routine name	In	Out	Exceptions
printBoard	TwoDotsBoard	\mathbb{B}	
modePrompt		Strategy	
getInput		BoardMoves	
closeStream			
printMsg	<i>msg : string</i>		

Semantics

Environment variables

s : 2D sequence of pixels displayed on a standard Unix Shell/console

r : an object to write text out on a standard Unix Shell/console

Access Routine Semantics

printBoard(*b*):

- transition *s* := Modify the Console so that the TwoDotsBoard *b* is printed in a tabular manner. The contents of each row from *b* should be on individual line. Their should be horizontal and vertical numbering indicating each row and column from one upto and including the row and column size of the board
- exception: None

modePrompt():

- transition :

- $s :=$ Modify the console to print a message asking the user to enter “T” for the timed version of the game and “M” for the mode of the game with a set number of moves
- $r :=$ read a single line of text from the standard input. Store this value in memory and then determine what to output as follows:
 If the line read in is “T” or “t” output : $out := \text{new TimedStrategy}()$
 If the line read in is “M” or “m” output: $out := \text{new MovesStrategy}()$
 Otherwise keep reading a line from the standard input until one of the above two conditions are met

- exception: None

`getInput():`

- transition :
 - $r :=$ read a single line of text from the standard input to determine the coordinates of the dots the user would like to eliminate. Note that the desired input format is u,v w,x y,z These are pairs of natural numbers with a comma between them and each pair is separated by a space. Store this value in memory and then determine what to output as follows:
 If the line read in is in the correct format then *output* : $out := \text{new Board-Moves}()$ containing the pairs of integers
 Otherwise keep reading a line from the standard input until one of the above conditions are met

`closeStream():`

- transition : $s :=$ close the input stream

`printMsg(msg : string):`

- transition : $s :=$ Modify the output console to print out text contain in the string *msg*

Considerations

In java, closing the input stream corresponds to closing the `System.in` object

BoardController Module

Template Module

BoardController

Uses

TwoDotsBoard, BoardView, Color, PointT, BoardMoves

Syntax

Exported Constants

None

Exported Access Programs

Routine name	In	Out	Exceptions
BoardController	TwoDotsBoard, BoardView	BoardController	
get	PointT	Color	
set	PointT, Color		
validateMoves	BoardMoves	\mathbb{B}	
updateBoard	BoardMoves		
updateView			
printMsg	<i>msg : string</i>		
modePrompt		Strategy	
closeViewStream			
getInput		BoardMoves	

Semantics

State variables

m : TwoDotsBoard v : BoardView

State invariant

None

Access Routine Semantics

BoardController(*model,view*)

- output: *out* := self
- transition: *m* := model, *v* := view
- exceptions: none

get(*p*)

- output : *out* := m.get(*p*)
- transition: none
- exceptions: none

set(*p,c*)

- transition: m.set(*p,c*)
- exception : none

validateMoves(*b*)

- output : *out* := m.validateMoves(*b*)

updateBoard(*b*)

- transition: m.updateBoard(*b*)

updateView()

- transition: v.printBoard(*m*)

printMsg(*msg* : *string*):

- transition view.printMsg(*msg*)

modePrompt():

- output: *out* := v.modePrompt()

closeViewStream():

- transition :v.closeStream()

getInput():

- output: if (m.validateMoves(v.getInput())) then *out* := else *out* := getInput()

DEM Module

Template Module

DemT is Seq2D(\mathbb{Z})

Syntax

Exported Access Programs

Routine name	In	Out	Exceptions
total		\mathbb{Z}	
max		\mathbb{Z}	
ascendingRows		\mathbb{B}	

Semantics

Access Routine Semantics

total():

- output : $\text{out} := +(x, y : \mathbb{N} \mid \text{validRow}(x) \wedge \text{validCol}(y) : s[x][y])$
- exception: None

max():

- output: $\text{out} := M$ such that $\forall(x : \text{Seq of } \mathbb{Z} \mid x \in s : \forall(y : \mathbb{Z} \mid y \in x : M \geq y)) \wedge (\exists i : \mathbb{N} \mid \text{validRow}(i) : M \in s[i])$
- exception: None

ascendingRows():

- output: $\text{out} := \forall(i : \mathbb{N} \mid i \in [0..|s| - 2] : \text{sum}(s[i]) < \text{sum}(s[i + 1]))$
- exception: None

Local Functions

validRow: $\mathbb{N} \rightarrow \mathbb{B}$

$\text{validRow}(n) \equiv (n \geq 0) \wedge (n < \text{nRow})$

validCol: $\mathbb{N} \rightarrow \mathbb{B}$

$\text{validCol}(c) \equiv (c \geq 0) \wedge (c < \text{nCol})$

sum: Seq of $\mathbb{Z} \rightarrow \mathbb{Z}$

$\text{sum}(s) \equiv (+x : \mathbb{Z} \mid x \in s : x)$