LOCATION PREDICTION SYSTEM FOR DISASTER RESPONSE

A DISSERTATION

Submitted by

SHAZZ ABDUL SAMED

2021239020

in partial fulfillment for the award of the degree of

MASTER OF SCIENCE (INTEGRATED)

in

COMPUTER SCIENCE



FACULTY OF SCIENCE AND HUMANITIES

ANNA UNIVERSITY

CHENNAI 600 025

DECEMBER 2024

ANNA UNIVERSITY
CHENNAI 600 025

BONAFIDE CERTIFICATE

Certified that this dissertation titled "**LOCATION PREDICTION SYSTEM FOR DISASTER RESPONSE**" is the bonafide work of **Mr. SHAZZ ABDUL SAMED** who carried out the work under my supervision. Certified further that to the best of my knowledge the work reported herein does not form part of any other dissertation on the basis of which a degree or award was conferred on an earlier occasion on this or any other candidate.

(Dr. L. JONES TARCIUS DOSS)
PROFESSOR AND HEAD
Department of Mathematics
Anna University
Chennai 600 025

(Dr. N. SIVASANKARI)
SUPERVISOR
Teaching Fellow
Department of Mathematics
Anna University
Chennai 600 025

(Dr. S. PAULRAJ)
PROJECT COORDINATOR
Professor
Department of Mathematics
Anna University
Chennai 600 025

ABSTRACT

The project aims to develop a Location Mention Prediction system designed to identify and extract location mentions from disaster-related tweets, such as those posted during floods or cyclones. Leveraging advanced Named Entity Recognition (NER) algorithms, the system identifies location mentions in text, which are then converted into precise geographical coordinates using geocoding techniques. These locations are visualized on a live map integrated into a real-time dashboard, offering a dynamic and interactive interface for monitoring disaster scenarios.

The system empowers emergency responders to track and manage aid requests effectively by pinpointing exact locations shared on social media. This ensures the efficient allocation of resources to critical areas, particularly when traditional communication channels are unavailable or disrupted. By bridging the gap between social media information and geospatial analysis, this project offers a robust tool for enhancing disaster management and relief operations. Its scalability and potential for future enhancements, such as multilingual support and IoT integration, make it a comprehensive solution for addressing global disaster challenges.

திட்டப்பணிச்சுருக்கம

இந்த திட்டம் பேரழிவுகள் நேரத்தில் சமூக ஊடக பதிவுகளில் இருந்து இடங்களை கண்டறிந்து, அவற்றை செயல்படுத்த ஒரு இடம் குறிப்பீடு கணிப்பு அமைப்பை உருவாக்கக் குறிக்கிறது. இது வெள்ளம் அல்லது சுழல்காற்று போன்ற பேரழிவுகளைப் பற்றிய ட்வீட்களில் இடங்களை சுட்டிக்காட்டும் தகவல்களை அடையாளம் காணவும், அவற்றை நியமமான புவியியல் அடையாளங்களாக மாற்றவும் உதவுகிறது. இவை பின்னர் நேரடி டாஷ்போர்ட்டில் காணப்படும் வரைபடத்தில் காண்பிக்கப்படுகின்றன, இது பேரழிவு நிலையில் உதவிகளை நிர்வகிக்க உடனடி தகவல்களை வழங்குகிறது.

இந்த அமைப்பு அவசர கால உதவியாளர்களுக்கு குறிப்பிட்ட இடங்களை சரியாகக் கண்டறிய உதவுகிறது, இதன் மூலம் வளங்களை தேவையான பகுதிகளுக்கு குறைவான நேரத்திலேயே எளிதாக வழங்க முடியும். பொது தொடர்பு வழிகள் செயலிழக்கும் நேரங்களில் கூட, இந்த அமைப்பு பேரழிவு மேலாண்மை மற்றும் மீட்புப் பணிகளை விரைவாக செய்ய ஒரு மிகச் சிறந்த கருவியாக செயல்படுகிறது.

ACKNOWLEDGEMENT

I sincerely thank **Dr. L. JONES TARCIUS DOSS**, Professor and Head, Department of Mathematics, Anna University, Chennai, for his continuous guidance and encouragement throughout this project. His support has been a constant source of inspiration.

I am deeply grateful to my Project Coordinator, **Dr. S. PAULRAJ**, Professor, Department of Mathematics, Anna University, Chennai, for his valuable motivation and support, which have been instrumental in the success of this work.

My heartfelt thanks to my Review Faculty Member **Dr. G. SUMATHI**, Teaching Fellow, Department of Mathematics, Anna University, Chennai, for her constructive feedback and helpful suggestions during the project.

I extend my gratitude to my internal supervisor, **Dr. N. SIVASANKARI**, Teaching Fellow, Department of Mathematics, Anna University, Chennai, for her consistent guidance and practical inputs, which helped enhance the quality of the project.

I would also like to thank my project mentor, **Mr. JOHN FORTUNATE**, NGP Websmart Pvt. Ltd, Chennai, for his insightful advice and support throughout the project.

Finally, I am thankful to my parents, friends, and colleagues for their encouragement and assistance, and to the Almighty for His blessings and guidance.

CHENNAI-25

DECEMBER 2024 **SHAZZ ABDUL SAMED**

TABLE OF CONTENTS

CHAPTER NO.	TITLE	PAGE NO.
	ABSTRACT (ENGLISH)	**iv**
	ABSTRACT (TAMIL)	**v**
	LIST OF TABLES	**x**
	LIST OF FIGURES	**xi**
	LIST OF ABBREVIATIONS	**xii**
1	**INTRODUCTION**	
	1.1 ORGANIZATION PROFILE	**1**
	1.2 OBJECTIVE OF THE PROJECT	1
	1.3 PROJECT OVERVIEW	2
	1.4 ORGANIZATION OF THE REPORT	2
2	**SYSTEM ANALYSIS**	**4**
	2.1 EXISTING SYSTEM	4
	2.2 PROPOSED SYSTEM	4
	2.3 PROJECT INITIATION	5
	2.4 SYSTEM REQUIREMENTS	5
	2.4.1 Hardware Specifications	6
	2.4.2 Software Specifications	6

CHAPTER NO.	TITLE	PAGE NO.
	2.5 TOOLS AND TECHNOLOGIES USED	6
	2.5.1 Hugging Face Transformers	7
	2.5.2 Leaflet	7
	2.5.3 Vue.js	7
	2.5.4 Flask	7
	2.5.5 Nominatim API	8
3	**SYSTEM DESIGN**	**9**
	3.1 SYSTEM ARCHITECTURE	9
	3.2 UML DIAGRAMS	11
	3.2.1 Use Case Diagram	11
	3.2.2 Sequence Diagram	12
	3.3 DATA FLOW DIAGRAM	13
	3.4 ENTITY – RELATIONSHIP DIAGRAM	15
4	**SYSTEM IMPLEMENTATION AND TESTING**	**16**
	4.1 SYSTEM MODULES	16
	4.1.1 Named Entity Recognition Module	16
	4.1.1.1 Data Preprocessing	17

CHAPTER NO.	TITLE	PAGE NO.
	4.1.1.2 Model Training and Implementation	18
	4.1.1.3 Evaluation and Results	19
	4.1.2 Geocoding and Mapping Module	20
	4.1.3 Dashboard Module	20
	4.2 SCREENSHOTS	21
	4.3 TESTING	26
	4.3.1 Unit Testing	27
	4.3.2 Integration Testing	27
	4.3.3 System Testing	27
	4.4 TEST CASES	27
5	**CONCLUSION**	**31**
	5.1 LIMITATIONS	31
	5.2 FUTURE ENHANCEMENT	32
	REFERENCES	**34**

LIST OF TABLES

TABLE NO.	TABLE NAME	PAGE NO.
2.1	Hardware Specifications	6
2.2	Software Specifications	6
4.1	Evaluation of Baseline and Project Model	19
4.2	Test Cases	28

LIST OF FIGURES

FIGURE NO.	FIGURE NAME	PAGE NO.
3.1	System Architecture	10
3.2	Use Case Diagram	11
3.3	Sequence Diagram for Map Navigation	12
3.4	Data Flow Diagram	14
3.5	Entity Relationship Diagram	15
4.1	Data Preprocessing	17
4.2	Location Extracted from Disaster Related Tweet	21
4.3	Location Extracted from unrelated tweet	21
4.4	Dashboard Analytics (line plot)	22
4.5	Dashboard Analytics (bar chart)	22
4.6	Dashboard Analytics (count and numbers)	23
4.7	Report Incident	23
4.8	Details of Responders	24
4.9	Dashboard Map View	24
4.10	Assign Responders	25
4.11	Notification Section	25
4.12	Navigate to Location	26

LIST OF ABBREVIATIONS

API	Application Programming Interface
BERT	Bidirectional Encoder Representations from Transformers
CRF	Conditional Random Field
GPT	Generative Pre-trained Transformer
GHz	Gigahertz
IoT	Internet of Things
LMR	Location Mention Recognition
LOC	Location
NER	Named Entity Recognition
NLP	Natural Language Processing
OS	Operating System
RAM	Random Access Memory
REST	Representational State Transfer
RMSE	Root Mean Squared Error
RNN	Recurrent Neural Network
UML	Unified Modeling Language
GPS	Global Positioning System
WNUT	Workshop on Noisy User-generated Text

CHAPTER 1

INTRODUCTION

This chapter begins with the organization profile where the problem statement has been emerged into a project and the services provided by the company. Then followed by the overview of the project.

1.1 ORGANIZATION PROFILE

NGP Websmart is the technology division of Northern Gas and Power (NGP), a leading energy solutions provider in Europe. Established in 2012, it develops scalable software solutions for energy management, data analytics, and client services. Leveraging technologies like cloud computing and advanced web frameworks, the organization delivers secure and innovative energy solutions. With offices in the UK and India, its global team consistently drives advancements in the energy sector.

1.2 OBJECTIVE OF THE PROJECT

The objective of this project is to develop a real-time disaster response system that extracts actionable location data from tweets to aid emergency responders. The system employs a fine-tuned Named Entity Recognition (NER) model to identify location mentions in disaster-related tweets and converts them into precise geographic coordinates using geocoding services.

These locations are visualized on an interactive live map within a dashboard, providing real-time situational awareness for effective response planning. Additionally, the project explores real-time tweet streaming for continuous updates, combining machine learning and geospatial technologies to enhance disaster management and minimize response times.

1.3 PROJECT OVERVIEW

The system consists of several modules designed to efficiently manage disaster response data. The Data Collection module fetches disaster-related tweets using the Twitter API, providing real-time information. The NER Model Integration module processes these tweets, extracting location mentions with accuracy tailored to disaster-related contexts. The Geocoding module translates these mentions into precise geographical coordinates. A Dashboard Visualization module displays this data interactively on a live map, while the Responder Management module facilitates the assignment of responders to critical locations for effective resource allocation.

Key features include:

1. **Real-Time Location Extraction and Mapping:** Accurate geocoding and visualization of disaster-affected areas.
2. **Interactive Dashboard:** Displays affected zones on a user-friendly live map for monitoring and planning.
3. **Efficient Responder Assignment:** Enables quick allocation of responders to high-priority zones.
4. **Actionable Data Insights:** Provides analytics to aid decision-making during disaster response.
5. **Real-Time Tweet Processing:** Ensures continuous updates by processing incoming disaster-related tweets in real time.

1.4 ORGANIZATION OF THE REPORT

Chapter 1: This chapter describes a profile of NGP Websmart Pvt Ltd., along with the overview and the objective of the project.

Chapter 2: This chapter gives details about the system analysis that was expected to be developed. It provides the system requirements and explains in detail the various tools and technologies involved during the development of the system.

Chapter 3: This chapter explains about the overall system architecture and design.

Chapter 4: This chapter discusses the implementation of the system and explains about the project in detail. It also explains about the testing done with the developed test cases.

Chapter 5: This chapter summarises the whole project and points out the enhancements and limitations of the project. It also includes the areas of future enhancements.

CHAPTER 2

SYSTEM ANALYSIS

System analysis can be defined as the process of studying and evaluating a system's components, objectives, and requirements to understand its functionality and improve its performance. This chapter focuses on understanding the current system, identifying its limitations, and defining the requirements for the proposed system.

2.1 EXISTING SYSTEM

Existing disaster management systems primarily focus on sentiment analysis and general Named Entity Recognition (NER) for identifying broad themes in social media data. However, these systems lack the specificity needed for real-time extraction and accurate mapping of disaster-related locations. While tools analyze trends and sentiments, they do not offer integrated geolocation capabilities for immediate response. Challenges remain in processing unstructured social media text and identifying ambiguous location references, as highlighted by Behl et al. [2] and Zhang et al. [4]. Conventional geocoding systems struggle with informal and incomplete location information in disaster tweets, hindering real-time actionable insights.

2.2 PROPOSED SYSTEM

The proposed system aims to streamline disaster response by integrating three core modules: NER-based Location Prediction, Geocoding Service, and Dashboard Visualization.

- The **NER Model** processes tweets in real time, extracting location mentions with high accuracy. This transforms unstructured text into actionable geographic data.

- The **Geocoding Service** converts extracted locations into precise geographic coordinates using OpenStreetMap, providing cost-effective and flexible mapping.
- The **Dashboard** visualizes incident locations on an interactive map, coupled with key statistics and analytics.
- Additionally, the system supports assigning responders to incidents and offers navigation integration for seamless coordination. The project optimizes response time, automates data extraction, and enhances situational awareness.

2.3 PROJECT INITIATION

The project began with a focus on understanding NER techniques and training the machine learning model. The initiation included, gathering disaster-related tweets as the dataset, exploring pre-trained transformer models like BERT (Bidirectional Encoder Representations from Transformers) for NER, Designing the geocoding pipeline to leverage OpenStreetMap. Prototyping the dashboard to integrate map-based incident reporting commenced after training in Vue.js and Flask.

2.4 SYSTEM REQUIREMENTS

System requirements are the required specifications a device must have to use certain hardware or software. The system requires both hardware and software configurations to handle real-time data processing, geocoding, and visualization effectively.

2.4.1 Hardware Specifications

Table 2.1 Hardware Specification

Processor	Intel® Core™ i7-9700 or equivalent
Processor Speed	3.0 GHz
System Type	64-bit operating system, x64 based
RAM	8GB
Storage	SSD, 512 GB

Table 2.1 discusses the system resource settings allotted for the specific device i.e., lists the hardware specification as part of the configuration of the system used to run the application.

2.4.2 Software Specifications

Table 2.2 Software Specification

Web Browser	Google Chrome (Latest version), Mozilla Firefox (Latest version), Microsoft Edge (Latest version), Safari (for macOS users)
Operating System	Windows: Windows 10 or later, Mac OS: macOS Mojave (10.14) or later, Linux: Ubuntu 18.04 or later
Screen Resolution	Minimum 1280x720 for optimal display, especially for the dashboard

Table 2.2 lists the software specification i.e., the software side of the configuration of the system used to run system. The operating system, tools used come under software specification.

2.5 TOOLS AND TECHNOLOGIES USED

The proposed system has been built using the following software technologies. This section gives an overview of these tools and technologies

2.5.1 Hugging Face Transformers

Hugging Face Transformers [6] provides a wide range of pre-trained models for NLP tasks, such as Named Entity Recognition (NER). The library is instrumental in extracting location mentions from social media posts and tweets. By utilizing transformer-based models like BERT and GPT (Generative Pre-trained Transformer), it helps in improving the accuracy and efficiency of location prediction in disaster scenarios. The library's flexibility allows fine-tuning for specific needs.

2.5.2 Leaflet

Leaflet [7] is an open-source JavaScript library for creating interactive maps. It is used to visualize disaster-affected areas by plotting geospatial data on a real-time map. Leaflet integrates smoothly with other geolocation services like OpenStreetMap and Nominatim API for accurate location display. It supports various map layers and provides an intuitive interface for end-users.

2.5.3 Vue.js

Vue.js is a JavaScript framework that helps in building dynamic and responsive user interfaces. It is lightweight and offers a flexible architecture for developing scalable web applications. Vue.js enables the creation of interactive, component-based user interfaces, ideal for disaster response dashboards. It enhances real-time updates and seamless user experience.

2.5.4 Flask

Flask is a lightweight web framework for Python that facilitates the development of web applications. In this project, Flask is used to create a RESTful API that serves as the backend for handling requests related to location mention prediction. It allows the system to process data, manage routes for receiving incoming tweets, and interact with the model for location extraction. Flask ensures smooth communication between the frontend and the machine learning model, enabling real-time processing and visualization of disaster-related locations.

2.5.5 Nominatim API

The Nominatim API [5] is a geocoding tool provided by OpenStreetMap that converts addresses or place names into geographical coordinates. It is used to map the locations extracted from tweets and social media posts onto interactive maps. This API enables accurate geolocation of locations even if they are mentioned informally in disaster-related tweets. It is an open-source, cost-effective solution compared to other proprietary geocoding services.

CHAPTER 3

SYSTEM DESIGN

System design defines the architecture and components necessary to meet the project's requirements. It includes detailing the system's structure, data flow, and interactions between modules. This chapter will cover the design of key components, user interfaces, and security features, ensuring efficient processing and real-time responses. The design aims to ensure scalability, reliability, and performance in the final system.

3.1 SYSTEM ARCHITECTURE

System architecture is a conceptual model that defines the structure, behaviour, and design principles of a system. It's a key concept in engineering and technology, and can be applied to hardware, software, electronics, and electrical systems.

The System Architecture in the Figure 3.1, consists of a robust data pipeline that collects real-time data from Twitter, processes it through Natural Language Processing (NLP) for location extraction, and integrates geocoding for accurate location mapping. A backend, developed using Flask, serves model predictions and coordinates the communication with the frontend dashboard built with Vue.js and Leaflet. PostgreSQL is used to store model predictions and related data. Real-time updates are enabled through Web Sockets, ensuring responders receive timely alerts. The architecture is designed to be scalable and fault-tolerant, capable of handling high volumes of incoming social media data and providing immediate actionable insights for disaster response.




Figure 3.1 System Architecture

3.2 UML DIAGRAMS

The Unified Modelling Language (UML) is a standardized visual language used to represent the design and structure of a system through various diagrams. This project consists of following UML diagrams for virtual representation of the whole system.

- Use Case Diagram
- Sequence Diagram

3.2.1 Use Case Diagram

Use Case Diagram is a visual representation of how users interact with a system, and is a key tool in the early stages of system design.




Figure 3.2 Use Case Diagram

The Use Case Diagram in Figure 3.2, illustrates a location predictor system designed to assist emergency responders. It shows how emergency responders can view real-time disaster locations, filter and sort them, navigate to affected areas, and

generate reports. Admins can manage user access, monitor system activity, and collect disaster-related tweets. The system processes these tweets to extract location information and generate visualizations.

3.2.2 Sequence Diagram

A sequence diagram is a visual representation of how objects interact with each other in a system over time. It shows the order in which messages are exchanged between the objects, and can also illustrate control structures between them.




Figure 3.3 Sequence Diagram for Map Navigation

The sequence diagram in Figure 3.3 illustrates the steps involved in navigating from the dashboard to a disaster location. The Emergency Responder requests the map, selects a location, and the System retrieves its coordinates. Based on the availability of the responder's location, a Google Maps link is generated and opened, providing navigation directions to the disaster site.

3.3 DATA FLOW DIAGRAM

A Data Flow Diagram (DFD) is a visual representation of how data moves through a system, including the input, output, storage, and processing of data. DFDs are often used in system analysis and design, and can help identify inefficiencies and improve functionality.

This DFD (Figure 3.4) presents a high-level overview of a system that processes disaster-related tweets to generate alerts and reports.

The process begins with the collection of tweets from Twitter. These tweets undergo noise removal and text pre-processing to prepare them for further analysis. A NER model identifies disaster-related entities within the processed tweets. If a tweet is deemed disaster-related, it is validated, and its geographical coordinates are determined either through GPS or a geocoding service. The validated tweets with their respective coordinates are then stored in a database.

The system generates disaster reports based on the stored data. Additionally, it sends alerts to relevant stakeholders, such as emergency responders, to inform them about ongoing disasters. The generated reports and alerts are crucial for timely response and effective disaster management.




Figure 3.4 Data Flow Diagram

3.4 ENTITY – RELATIONSHIP DIAGRAM

An Entity-Relationship (ER) diagram is a visual tool that shows how entities, such as people, objects, or concepts, relate to each other in a system. ER diagrams are often used to design or debug relational databases.




Figure 3.5 Entity Relationship Diagram

The Figure 3.5 depicts ER Diagram of the system for managing disaster response and reporting. Users can be assigned to disaster locations to oversee or respond to incidents. Incident reports are filed for each disaster location, and tweets related to disasters are collected and associated with the relevant location.

CHAPTER 4

SYSTEM IMPLEMENTATION AND TESTING

System implementation is the process of deploying and integrating the designed system into the operational environment. This chapter outlines the steps involved in transitioning the proposed system from development to production. It covers the configuration, deployment, and initial testing phases to ensure the system operates as intended. Implementation strategies, tools, and testing protocols used for ensuring the system's functionality and reliability are discussed. Additionally, this chapter highlights the challenges encountered during deployment and the measures taken to resolve them effectively.

4.1 SYSTEM MODULES

A module is a software component or a part of a program that contains one or more routines. One or more independently developed modules make up a program. The project involves three important modules which include, NER Module, Geocoding and Mapping Module and finally the Dashboard Module.

4.1.1 Named Entity Recognition Module

NER is a subtask of Natural Language Processing (NLP) focused on identifying and categorizing entities such as locations, organizations, and individuals from unstructured text. In disaster response, it extracts location mentions from noisy social media posts for real-time geocoding and mapping, aiding emergency responders in resource allocation and improving response efficiency. By converting unstructured textual data into actionable insights, NER enhances the speed and accuracy of disaster response efforts.

4.1.1.1 Data Preprocessing

The NER model leverages two datasets for its training namely, the IDRISI dataset (Suwaileh et al. [3]), named after the geographer Muhammad al-Idrisi, and WNUT16 dataset. To enhance the consistency and accuracy of our NER model, we implemented a rigorous data preprocessing pipeline. This involved transitioning both the WNUT16 and IDRISI datasets from their original tagging schemes, BIO (Begin-Inside-Outside) and BILOU (Begin-Inside-Last-Outside-Unit), respectively to the BIOES (Begin-Inside-Outside-End-Single) tagging scheme.

- **B (Begin)**: The first token of a chunk phrase or NE.
- **I (Inside)**: Tokens inside chunk phrases or NEs.
- **O (Outside)**: Tokens that are not part of any chunk phrase or NE.
- **E (End)**: The last token of a chunk phrase or NE.
- **S (Single)**: Represents unit or single-length chunk phrases or NEs.

This change provides a more granular representation of named entities, improving model performance. Additionally, we standardized certain location-related terms like STAT, CITY, CTRY, and geo-loc to the term "LOC" to ensure consistency across datasets.




Figure 4.1 Data Preprocessing

Figure 4.1 depicts the data preprocessing where the original tags from the dataset are converted to suitable tags for training the model.

4.1.1.2 Model Training and Implementation

For the Location Mention Recognition (LMR) model, Hugging Face's transformer-based models is utilized. The model was built for Named Entity Recognition (NER) using the 'tner/deberta-v3-large-ontonotes5' model, optimized for location entity recognition.

Key steps included:

1. Data Preparation: Data was pre-processed for token-level tagging, labelling each token with location entities.
2. Embeddings: The transformer model *'tner/deberta-v3-large-ontonotes5'* was fine-tuned for this task to improve location detection.
3. Model Configuration: A **SequenceTagger** model was used, with parameters set to optimize for efficient training and inference, disabling **CRF** (Conditional Random Fields) and **RNN** (Recurrent Neural Network) layers.
4. Training: The model was trained using the **AdamW optimizer** and a **OneCycleLR scheduler**, fine-tuning the model for three epochs.

A **SequenceTagger** is a model used for tasks like NER, where each token (word) in a sentence is assigned a label. In this case, it identifies location entities like city names or landmarks (BILOU). It is used because it's designed for sequence labelling tasks. **CRF** is a model used to make predictions based on the relationship between neighbouring tokens. It helps improve labelling by considering the context of neighbouring words. In this case, using CRF might slow down training and add complexity without significant improvement for location recognition, so it's disabled.

RNN is a type of neural network that processes sequences by remembering information from previous steps. While RNNs can handle sequential data well, they are slower and less efficient for the task, which is why it is disabled it to speed up the process and simplify the model.

AdamW is an optimization algorithm that adjusts the learning rate of the model during training. It's a variation of the Adam optimizer, which combines

momentum and adaptive learning rates to speed up training and improve performance. AdamW is used because it works well for large models and datasets, especially when fine-tuning transformer models like ours.

OneCycleLR is a learning rate scheduler that adjusts the learning rate during training, starting high, decreasing, and then increasing again. It's used to help the model converge faster and avoid overshooting the optimal point. We use it because it allows for more efficient training, helping the model reach better performance with fewer epochs.

4.1.1.3 Evaluation and Results

The evaluation of the Location Prediction project employed Root Mean Squared Error (RMSE) as the primary metric to assess model performance. RMSE measures the deviation between the predicted start and end indices for location mentions and their true values in tweets. Additional metrics, including precision, recall, and F1 score, were used to evaluate the accuracy of location entity detection.

Table 4.1 Evaluation of Baseline and Project Model

Model	RMSE	Precision	Recall	F1 Score
Baseline Model	13.99	0.8237	0.8745	0.8345
Project Model	12.7	0.8869	0.9221	0.9041

The table 4.1 above compares the RMSE and F1 scores achieved by the baseline model and the project model. The project model exhibits significant improvements across all metrics, demonstrating superior performance in location prediction tasks.

These results highlight the effectiveness of the project model in accurately predicting location mentions, outperforming the baseline approach and ensuring reliable entity recognition in tweets.

4.1.2 Geocoding and Mapping Module

Geocoding, the process of converting textual addresses into geographic coordinates, is a fundamental tool in disaster response. It enables the precise visualization of affected areas, aiding in resource allocation and decision-making. This module leverages the power of Nominatim, an open-source geocoding service, to extract geographic coordinates from textual location data, primarily sourced from disaster-related tweets.

Location information is extracted from disaster tweets and fed into the Nominatim API to obtain latitude and longitude coordinates. Robust error handling mechanisms are implemented to address potential issues like rate limiting and ambiguous location descriptions. Geocoded locations are then visualized on interactive maps using libraries like Leaflet.js, employing various techniques such as markers and heatmaps to represent the severity and spatial distribution of disasters. Maps are dynamically updated as new geocoded locations are added, providing a real-time view of the evolving situation.

4.1.3 Dashboard Module

The Dashboard Module was implemented to provide real-time insights into disaster-related data through an interactive interface. Using a combination of tools like Leaflet.js and Vuejs, the module displays geographical locations of incidents and allows users to interact with the data dynamically. The map updates in real time as new disaster-related information are ingested, offering markers that represent different types of locations such as evacuation points, shelters, or damage zones. Additionally, bar charts and line graphs are used to track the frequency of incidents over time, helping users visualize patterns and trends in disaster occurrences.

The real-time data processing aspect of the module utilizes a continuous stream of geocoded tweets and other disaster-related inputs. This data is fed into the system, where it is processed and visualized on the dashboard in near-real time. The interactive features include filters that allow users to sort incidents by type, severity, or location, enabling them to focus on the most critical data. Furthermore, custom

reports and analysis are generated from the real-time dataset, providing users with insights into trends and patterns that can inform decision-making during a disaster response.

4.2 SCREENSHOTS




Figure 4.2 Location Extracted from Disaster Related Tweet

Figure 4.2 Shows how location mentioned in a disaster related tweet is extracted. Along with it the severity of the tweet is calculated using NLP techniques. The extracted location is then geocoded to coordinates.




Figure 4.3 Location Extracted from unrelated tweet

Figure 4.3 Shows how location mentioned in an unrelated tweet is extracted. The Severity is low in this case.




Figure 4.4 Dashboard Analytics (line plot)

Figure 4.4 shows the Dashboard Home View where data is presented with graph for quick insights. This plot shows the disaster related incident reports over time.




Figure 4.5 Dashboard Analytics (bar chart)

Figure 4.5 Shows another view of the dashboard where key locations are shown in the form of bar chart.




Figure 4.6 Dashboard Analytics (count and numbers)

Figure 4.6 shows the key numbers to give more insights and help in better planning of relief measures. These include numbers like assigned responders, total incidents reported.




Figure 4.7 Report Incident

Figure 4.7 is a feature in the dashboard to directly report any disaster incident through the portal which will directly go to the database without any location extractions.




Figure 4.8 Details of Responders

Figure 4.8 shows the list of responders with necessary details like last active time, their status etc.




Figure 4.9 Dashboard Map View

Figure 4.9 is the Map view where all the disaster related events is marked with two options namely ‘Navigate to Location’ and ‘Assign’.




Figure 4.10 Assign Responders

Figure 4.10 shows how responders could be assigned to a location. Multiple responders can be assigned to one location, and they are notified when they are assigned.




Figure 4.11 Notification Section

Figure 4.11 shows how real time notifications are sent to the users highlighting the location and time of the disaster report ensuring quick actions to be taken.




Figure 4.12 Navigate to Location

Figure 4.12 shows how the user is navigated to the disaster location through Google Maps from their current location to the disaster location.

4.3 TESTING

Testing is the process of evaluating a system or model to ensure it meets the required specifications and performs as expected. It involves running the system through various conditions to check for functionality, accuracy, and reliability. The objective of testing in this project is to evaluate the accuracy of the location mention

prediction model by comparing its outputs against the ground truth and ensuring its effectiveness in real-world data scenarios.

4.3.1 Unit Testing

Unit testing is a software testing technique where individual components or functions are tested in isolation to ensure they perform as expected. In this project, unit testing refers to testing smaller modules like data preprocessing, tokenization, or individual model components (such as the location mention recognition function) to verify their correctness before integrating them into the whole system.

4.3.2 Integration Testing

Integration testing involves testing the interactions between multiple components or systems to ensure they work together as expected. For this project, integration testing means ensuring that the components like the NER model, geocoding module, and the mapping system work seamlessly when integrated, providing correct location predictions and visualizations.

4.3.3 System Testing

System testing is the process of testing the entire system as a whole to verify that it behaves as expected in the complete environment. In this project, system testing means running the complete location mention prediction pipeline — from input data processing to location prediction and geocoding — to validate that the entire system functions as a unified solution.

4.4 TEST CASES

Test cases are specific conditions or inputs used to verify that a system behaves as expected, with defined expected outputs. They are created to ensure that each part of the system works correctly under different scenarios.

Key reasons for writing test cases:

- To ensure consistent execution of tests across different environments.
- To achieve comprehensive test coverage and validate all aspects of the system.

- To base the testing process on structured procedures rather than individual knowledge.
- To eliminate the need for extensive training of new testers on the product.

Table 4.2 Test Cases

Module	Test Case Summary	Expected Result	Actual Result	Status (Pass/Fail)
NER Module	Test extraction of a clear location mention in a tweet. For example, *“Flood in Chennai, near Marina Beach”*	Extract location: *"Chennai, Marina Beach."*	Extracted location correctly: *"Chennai, Marina Beach."*	Pass
NER Module	Test handling of a tweet without a location mention. Example, *"The situation is really bad, pray for us."*	Return message: *"No location found."*	Returned: *"No location found."*	Pass
NER Module	Test response to a tweet with ambiguous location mention. Example: "Flood reported near Victoria."	Return message: "Ambiguous location”	Correctly flagged as ambiguous.	Pass

Table 4.2 Test Cases (continued)

NER Module	Test processing of a tweet unrelated to disasters. Example: "I love watching sunsets on the beach!"	Return message: "No disaster-related content."	Returned: "No disaster-related content."	Pass
Geocoding Module	Test conversion of a valid location name to geographic coordinates.	Location: "Chennai, Marina Beach" Latitude: 13.0481, Longitude: 80.2822	Correct coordinates retrieved.	Pass
Geocoding Module	Test response time for geocoding a location.	Response time: < 1 second.	Response returned within acceptable limits.	Pass
Geocoding Module	Test handling of an invalid location name. Location: "Atlantis"	Return message: "Location not found."	Correctly returned: "Location not found."	Pass
Dashboard Module	Test the display of real-time incident data on the map.	Incident marker appears on the map at the correct location within 2 seconds.	Marker displayed accurately and in real-time.	Pass

Table 4.2 Test Cases (continued)

Dashboard Module	Test navigation to Google Maps from a location marker.	User is redirected to Google Maps showing directions from their current location.	Navigation link worked as expected.	Pass
Dashboard Module	Test the display of statistical charts for incidents.	Bar chart and line chart update dynamically with the given data.	Charts displayed correct values and updated dynamically.	Pass
Dashboard Module	Test contact details display for emergency responders.	Contact information (e.g., name, phone number) for responders is displayed accurately.	Information displayed correctly.	Pass
Dashboard Module	Test notification pop-up for new incidents.	Notification pop-up: "New Incident: Flood reported at (some location)"	Notification appears in real-time.	Pass

CHAPTER 5

CONCLUSION

The Location Mention Prediction system represents a novel approach to disaster management by leveraging the power of machine learning and natural language processing to extract, geocode, and visualize location mentions from social media data. This project has the potential to address a critical gap in emergency response systems by providing real-time geospatial insights during natural disasters such as floods and cyclones. The system's ability to process vast amounts of unstructured text data, identify locations, and display them on a live map equips responders with actionable intelligence, improving their ability to allocate resources effectively.

This project marks an important step forward in harnessing technology for social good. While the results demonstrate the system's capability to handle real-time data and produce accurate geocoding results, certain limitations exist, and opportunities for future enhancements remain. This chapter discusses these limitations and outlines potential directions to further refine the system, ensuring its robustness and adaptability to diverse disaster scenarios.

5.1 LIMITATIONS

Despite its promising results, the Location Mention Prediction system is not without challenges. The limitations identified during the course of this project include:

1. **Language Constraints**: The system relies on English-language datasets for training and inference, limiting its applicability in regions where social media posts during disasters are predominantly in local languages. While the current Named Entity Recognition (NER) model performs well in English, it struggles

with multilingual or non-English tweets, which could lead to missed or incorrect location mentions.

2. **Data Noise**: Social media data is inherently noisy, with posts often containing slang, abbreviations, or irrelevant information. This noise can affect the model's ability to identify precise locations, especially when tweets include ambiguous terms or incomplete address details.
3. **Geocoding Accuracy**: The geocoding process using Nominatim works effectively for well-defined locations but may struggle with vague or imprecise mentions, such as "near the river" or "in the hills." Such limitations can result in inaccurate or incomplete mapping of critical disaster locations.
4. **Scalability**: The current implementation is suited for small- to medium-scale disaster scenarios. However, handling large-scale events across multiple regions with high tweet density may require more robust infrastructure and optimized algorithms.

5.2 FUTURE ENHANCEMENT

Future enhancements to the Location Mention Prediction system focus on addressing limitations and improving functionality. Incorporating **multilingual support** through NER models trained on diverse datasets will allow the system to handle tweets in multiple languages, increasing its global applicability in disaster scenarios.

Reducing noise in social media data can be achieved by integrating **advanced pre-processing techniques**, such as semantic analysis and user-defined dictionaries. These approaches will improve the quality and relevance of extracted location mentions, minimizing false positives.

Enhanced geocoding models, combining Nominatim with machine learning-based geocoders, can improve the system's ability to interpret vague or incomplete location descriptions. This will result in more precise mapping of disaster-affected areas.

For large-scale disasters, real-time processing can be optimized by adopting **distributed computing frameworks** like Apache Kafka or Spark. These tools will enable efficient handling of high tweet volumes with minimal latency, ensuring timely updates for responders.

Integrating IoT devices and satellite data can provide additional context to social media information. This combination will offer a comprehensive view of disaster scenarios, improving decision-making for emergency response teams.

Finally, leveraging **cloud-based infrastructure** with containerization tools like Docker and Kubernetes will enhance scalability. This ensures the system can handle dense tweet traffic across multiple regions during major disasters.

REFERENCES

1. Beigi, G., Hu, X., Maciejewski, R., & Liu, H. "An Overview of Sentiment Analysis in Social Media and Its Applications in Disaster Relief." In *Sentiment Analysis and Ontology Engineering* (pp. 313-340). Springer (2016).
2. Behl, S., Rao, A., Aggarwal, S., Chadha, S., & Pannu, H.S. "Twitter for disaster relief through sentiment analysis for COVID-19 and natural hazard crises." *Safety Research* (2021).
3. Suwaileh, R., Elsayed, T., & Imran, M. "IDRISI-RE: A generalizable dataset with benchmarks for location mention recognition on disaster tweets." *Computers, Environment and Urban Systems* (2023).
4. Zhang, Y., Wang, H., & Liu, Q. "Enhancing disaster sentiment analysis with transformer-based models." *Proceedings of the International Conference on Natural Language Processing* (2022).
5. https://nominatim.org/release-docs/latest/
6. https://huggingface.co/docs
7. https://leafletjs.com/reference.html