VELORAX 20 MG FILM-COATED TABLETS - STABILITY STUDY REPORT SR-2027-014

This is a synthetic stability report and closed factual record for testing document extraction. All products, companies, people and results are fictional. Apply only the rules stated in this report; where the narrative of the report and its tables differ, the tables record the measured results.

Prepared by Halden Therapeutics AS, Quality Control Stability Unit, on 15 March 2027, and approved by Ingrid Moe, Head of Quality Control.

1 SCOPE AND BATCHES

1.1 This report presents the results of the registration stability study of Velorax (ralmetanib) 20 mg film-coated tablets up to 12 months at the long-term condition, and proposes a shelf life and a storage statement for each container closure system.

1.2 Three batches were placed on stability, one in each container closure system intended for marketing.

Table 1. Batches on stability

Batch	Scale	Container closure system	Manufactured	Placed on stability
V20-2601	Pilot, 100 000 tablets	HDPE bottle with desiccant	12 January 2026	26 January 2026
V20-2604	Production, 1 000 000 tablets	PVC/Alu blister	2 February 2026	9 February 2026
V20-2607	Production, 1 000 000 tablets	Alu/Alu blister	23 February 2026	2 March 2026

2 SPECIFICATIONS

2.1 Each batch is tested at release against the release specification, and each stability sample against the shelf-life specification. The two specifications list the same tests; their acceptance criteria differ.

Table 2. Release specification

Test	Acceptance criterion
Appearance	White, round, biconvex film-coated tablets
Assay	95.0 to 105.0 % of the label claim
Impurity D	Not more than 0.20 %
Total impurities	Not more than 0.50 %
Dissolution	Not less than 80 % (mean of 6 units) in 30 minutes
Water content	Not more than 3.0 %

Table 3. Shelf-life specification

Test	Acceptance criterion
Appearance	White, round, biconvex film-coated tablets
Assay	92.0 to 105.0 % of the label claim
Impurity D	Not more than 0.30 %
Total impurities	Not more than 1.00 %
Dissolution	Not less than 75 % (mean of 6 units) in 30 minutes
Water content	Not more than 4.0 %

2.2 A result is outside the shelf-life specification if it does not meet the acceptance criterion of Table 3 for its test. Each result outside the shelf-life specification is investigated under procedure QC-SOP-112, and the investigation is

reported in section 5.

3 STORAGE CONDITIONS AND TESTING

Table 4. Storage conditions

Condition	Storage	Time points (months)
Long-term	25 °C ± 2 °C / 60 % RH ± 5 % RH	0, 3, 6, 9, 12, then 18, 24 and 36
Intermediate	30 °C ± 2 °C / 65 % RH ± 5 % RH	0, 6, 9, 12
Accelerated	40 °C ± 2 °C / 75 % RH ± 5 % RH	0, 1, 2, 3, 6

3.1 Samples of each batch were placed at the three conditions on the day on which the batch was placed on stability (Table 1). Time 0 is that day; the initial results of a batch are those of its time 0, and apply to every condition.

3.2 The samples at the intermediate condition are tested only for a batch that shows a significant change at the accelerated condition, at each of their time points from the time point at which the significant change is found.

3.3 A significant change at the accelerated condition is any of: a change in assay of 5.0 % of the label claim or more from the initial value; a result for impurity D or for total impurities outside the shelf-life specification; a water content outside the shelf-life specification; a dissolution result outside the shelf-life specification.

3.4 Assay is reported in % of the label claim, impurity D, total impurities and water content in % (w/w), and dissolution as the mean of 6 units in % dissolved after 30 minutes. Appearance complied at every time point of every batch and condition, and is not tabulated.

4 RESULTS

4.1 BATCH V20-2601 (HDPE BOTTLE WITH DESICCANT)

Table 5. V20-2601, long-term condition (25 °C/60 % RH)

Test	Initial	3 months	6 months	9 months	12 months
Assay (%)	100.4	100.1	99.8	99.6	99.3
Impurity D (%)	0.04	0.05	0.06	0.07	0.08
Total impurities (%)	0.12	0.14	0.16	0.18	0.21
Dissolution (%)	94	93	93	92	91
Water content (%)	1.8	1.9	2.0	2.1	2.2

Table 6. V20-2601, accelerated condition (40 °C/75 % RH)

Test	Initial	1 month	2 months	3 months	6 months
Assay (%)	100.4	100.0	99.6	99.1	98.2
Impurity D (%)	0.04	0.07	0.10	0.13	0.21
Total impurities (%)	0.12	0.18	0.24	0.31	0.48
Dissolution (%)	94	93	92	91	89
Water content (%)	1.8	2.1	2.3	2.5	2.9

4.1.1 V20-2601 meets the shelf-life specification at every time point, and shows no significant change at the accelerated condition.

4.2 BATCH V20-2604 (PVC/ALU BLISTER)

Table 7. V20-2604, long-term condition (25 °C/60 % RH)

Test	Initial	3 months	6 months	9 months	12 months

Test	Initial	3 months	6 months	9 months	12 months
Assay (%)	100.9	100.5	100.0	99.6	99.1
Impurity D (%)	0.05	0.07	0.09	0.11	0.13
Total impurities (%)	0.14	0.17	0.20	0.23	0.27
Dissolution (%)	95	94	92	91	89
Water content (%)	2.0	2.4	2.7	3.0	3.3

Table 8. V20-2604, accelerated condition (40 °C/75 % RH)

Test	Initial	1 month	2 months	3 months	6 months
Assay (%)	100.9	99.8	98.9	97.6	95.1
Impurity D (%)	0.05	0.11	0.17	0.24	0.41
Total impurities (%)	0.14	0.29	0.45	0.63	1.12
Dissolution (%)	95	92	89	86	79
Water content (%)	2.0	3.1	3.8	4.4	5.6

Table 9. V20-2604, intermediate condition (30 °C/65 % RH)

Test	Initial	6 months	9 months	12 months
Assay (%)	100.9	99.4	98.8	98.1
Impurity D (%)	0.05	0.14	0.18	0.22
Total impurities (%)	0.14	0.32	0.40	0.49
Dissolution (%)	95	90	88	86
Water content (%)	2.0	3.4	3.7	3.9

4.2.1 V20-2604 showed a significant change at the accelerated condition at 6 months (section 5). Its samples at the intermediate condition were tested from 6 months, and meet the shelf-life specification up to 12 months.

4.3 BATCH V20-2607 (ALU/ALU BLISTER)

Table 10. V20-2607, long-term condition (25 °C/60 % RH)

Test	Initial	3 months	6 months	9 months	12 months
Assay (%)	100.2	100.0	99.9	99.7	99.5
Impurity D (%)	0.03	0.04	0.04	0.05	0.06
Total impurities (%)	0.10	0.11	0.12	0.14	0.15
Dissolution (%)	96	96	95	95	94
Water content (%)	1.6	1.6	1.7	1.7	1.7

Table 11. V20-2607, accelerated condition (40 °C/75 % RH)

Test	Initial	1 month	2 months	3 months	6 months
Assay (%)	100.2	99.9	99.5	99.0	98.0
Impurity D (%)	0.03	0.08	0.14	0.19	0.31
Total impurities (%)	0.10	0.17	0.25	0.33	0.52
Dissolution (%)	96	95	95	94	93
Water content (%)	1.6	1.6	1.7	1.7	1.8

4.3.1 V20-2607 meets the shelf-life specification at every time point, and shows no significant change at the accelerated condition.

5 RESULTS OUTSIDE THE SHELF-LIFE SPECIFICATION

5.1 Investigation INV-26-031 was opened on 18 August 2026 for the 6-month results of V20-2604 at the accelerated condition, the first results of the study outside the shelf-life specification: impurity D, total impurities and water content.

5.2 The results were confirmed by retesting retained samples. A laboratory error was excluded: the system suitability, the reference standards and the sample preparation met their requirements.

5.3 Root cause: moisture ingress through the PVC film of the blister at 75 % RH. The water content of the tablets rose with the time of storage, and impurity D, a hydrolysis product, rose with it. At its intended storage of 25 °C/60 % RH the same batch stays within the shelf-life specification.

5.4 Corrective action: the PVC/Alu blister is not to be stored above 25 °C, and its storage statement requires protection from moisture. No action is needed for the HDPE bottle with desiccant or for the Alu/Alu blister.

5.5 INV-26-031 was closed on 30 September 2026. No other result of the study was outside the shelf-life specification.

6 EVALUATION AND PROPOSED SHELF LIFE

6.1 Where no significant change occurs at the accelerated condition, the shelf life may be extrapolated to twice the period covered by the long-term data, and not beyond 24 months.

6.2 Where a significant change occurs at the accelerated condition and no significant change occurs at the intermediate condition, the shelf life may be extrapolated to one and a half times the period covered by the long-term data, and not more than 6 months beyond it.

6.3 Where a significant change occurs at the intermediate condition, or where it occurs at the accelerated condition and the intermediate condition has not been tested, the shelf life is not extended beyond the period covered by the long-term data.

6.4 A significant change at the intermediate condition is defined as at the accelerated condition (3.3).

6.5 The long-term data cover 12 months for each batch. The assay of each batch at the long-term condition decreases by no more than 0.15 % of the label claim per month, so that the assay of no batch is expected to fall below the shelf-life specification within 24 months.

Table 12. Proposed shelf lives and storage statements

Container closure system	Batch	Proposed shelf life	Storage statement
HDPE bottle with desiccant	V20-2601	24 months	Do not store above 30 °C.
PVC/Alu blister	V20-2604	18 months	Do not store above 25 °C. Store in the original package in order to protect from moisture.
Alu/Alu blister	V20-2607	24 months	Do not store above 30 °C.

7 COMMITMENTS

7.1 The long-term study of the three batches continues to 36 months, and the results at 18, 24 and 36 months will be reported in updates of this report.

7.2 The first three production batches of each container closure system will be placed on stability at the long-term and accelerated conditions after approval.

7.3 The shelf life of each container closure system will be confirmed against the long-term data as they become available, and a result outside the shelf-life specification will be reported to the competent authorities within 30 days.

ANNEX A - ANALYTICAL METHODS

Table A1. Analytical methods

Test	Method	Reporting threshold
Assay	HPLC with UV detection, AM-201	Not applicable
Impurity D	HPLC with UV detection, AM-202	0.02 %
Total impurities	HPLC with UV detection, AM-202	0.02 %
Dissolution	Paddle apparatus at 50 rpm, 900 ml of pH 6.8 buffer, AM-203	Not applicable
Water content	Coulometric Karl Fischer titration, AM-204	Not applicable