

Implement Client Script & UI Policy (Incident)

Milestone 3: Create on Change Client Script

Activity 1: Create Client Script

Description

1. Navigate to Client Scripts:

Go to System UI → Client Scripts.

2. Click New to create a new Client Script.

3. Fill in the details:

- **Name: Auto set urgency for high impact – clearly shows the purpose.**
- **Table: Incident – the script runs only on Incident records.**
- **Type: onChange – executes when a field value changes.**
- **Field name: Impact – triggers the script when Impact is updated.**
- **Active: true – ensures the script runs immediately.**

4. Paste the script in the script editor section.

5. Go to System UI → Client Scripts.

6. Verify: Open an Incident record and change the Impact field to High. The Urgency field should update automatically.

7. Click Submit.

servicenow							
Client Scripts							
All Favorites History Workspaces							
Client Scripts for text Search							
Actions on selected rows...							
New							
All > Class = Client Script							
Name	Active	Table	Application	View	Type	Updated	
Maximum Duration Range Check	true	Transaction Quota Rule [sysrule_quota]	Global		onChange	2012-05-30 14:47:01	
Create default value	true	Response Template Channel [sn_templated_snip_channel]	Templated Snippets		onChange	2020-09-22 17:06:27	
Show overlap field based on data labels	true	Widgets [pa_widgets]	Global		onChange	2021-04-23 02:59:51	
Set protocol based on auth type	false	HTTP(s) Connection [http_connection]	Global		onChange	2017-06-02 15:49:24	
Set default values for OIDC PKCE flow	true	OAuth OIDC Entity [oauth_oidc_entity]	Global		onChange	2020-02-28 00:59:58	
Make notification read only	true	Additional Notification Recipients [sys_notification_recipient]	Global		onLoad	2021-02-05 22:42:13	
Deprecated - SN - Make serial number man	false	Asset [alm_asset]	Global		onChange	2025-03-06 00:42:54	
Validate StatefulSet Name	true	MID K8s Deployment Request [mid_k8s_deployment]	Global		onChange	2022-10-09 23:18:07	
Set Use current record if delete	true	Action item [sys_sg_write_back_action_item]	Global		onChange	2019-04-14 07:30:02	

servicenow

All Favorites History

Client Script - Auto set urgency for h...

Search

Client Script

Auto set urgency for high impact

Update Delete

Current View: Default view (click me for other views)

DOM access disabled. Access to jQuery, prototype and the window object are likewise disabled. To disable this on a per-script basis, configure this form and add the "Disable Script Host" to disable this feature. For all new globally-scoped client-side scripts set the system property "glide.script.block.client.globals" to false.

Name

Auto set urgency for high impact

Table

Incident [incident]

UI Type

Desktop

Type

onChange

Field name

-- None --

Application

Global

Active

☒

Inherited

☐

Global

☒

Description

Messages

Script

```

1 function onChange(control, oldValue, newValue, isLoading) {
2   if (isLoading || newValue == '') {
3     return;
4   }
5
6   if (newValue == '1') {

```