

Threat Intelligence Report

Case: "Tusk Infostealer" — Crypto Wallet Theft Investigation

Report Type:	Malware / Threat Intelligence Analysis
Case Number:	TI-001
Examiner:	Muhammad Shoaib
Date of Analysis:	29 August 2026
Client / Scenario:	Blockchain Development Company (Practice Lab — CyberDefenders)
Evidence Provided:	MD5 hash of suspicious file (E5B8B2CF5B244500B22B665C87C11767)
Tools Used:	VirusTotal (static analysis, sandbox behavior, file relations)

1. Scenario

A blockchain development company detected unusual activity after an employee was redirected to an unfamiliar website while accessing a DAO management platform. Shortly after, multiple cryptocurrency wallets linked to the organization were drained. This report documents the analysis of a suspicious file hash provided as part of the investigation, tracing the malware family, its behavior, and its position within a larger multi-stage infection chain.

Severity: Critical — confirmed infostealer malware associated with cryptocurrency theft.

2. Initial Indicator

MD5 Hash provided: **E5B8B2CF5B244500B22B665C87C11767**

This hash was submitted to VirusTotal for identification and further pivoting.

3. Malware Identification

3.1 Primary Sample: madHcNet.dll

Field	Value
SHA-256	523d4eb71af86090d2d8a6766315a027fdec842041d668971bfbbd1fe826722
File Name	madHcNet.dll
File Type	Win32 DLL
File Size	921.36 KB
Detection Rate	44 / 71 security vendors
Popular Threat Label	trojan.rugmi/jaik
Threat Categories	Trojan, Downloader
Family Labels	rugmi, jaik, malgent
Notable Tags	invalid-signature, checks-user-input, overlay

3.2 Parent Loader: wdrvvtmoevsvki.exe

Field	Value
SHA-256	141ee34a8afb8f5a9d47e4910395bc70098a40ab46eb65bf3fb0b8e7c415c956
File Type	Win32 EXE
File Size	427.00 KB
Detection Rate	59 / 71 security vendors
Popular Threat Label	trojan.strab/jaik
Family Labels	strab, jaik, rhadamanthys
Notable Tags	checks-usb-bus, detect-debug-environment, spreader, long-sleeps

3.3 Root Dropper: snss2.exe

Identified as the execution parent of wdrvvtmoevsvki.exe, with a detection rate of 37/65 security vendors. This file represents the earliest stage of the infection chain observed in this analysis and is the likely initial payload delivered to the victim.

4. Malware Family: Rhadamanthys

The parent loader is associated with the Rhadamanthys malware family, a well-documented commercial information-stealer ("stealer-as-a-service") active since 2022. Rhadamanthys is specifically known for targeting:

- Browser-saved credentials and session cookies
- Cryptocurrency wallet files and browser extension data (e.g., MetaMask)
- Clipboard content, including cryptocurrency address substitution ("clipper" behavior)
- System screenshots and general reconnaissance data

This capability set directly aligns with the scenario's reported outcome: credential theft followed by drainage of multiple organizational cryptocurrency wallets.

5. Infection Chain Summary

Stage	File	Detection	Role
1 (Root)	snss2.exe	37/65	Initial dropper delivered to victim
2	wdrvvtmoevsvki.exe	59/71	Rhadamanthys loader
3	madHcNet.dll	44/71	Downloader / secondary payload
Related	datastate.dll	46/72	Dropped file — highest detection in set
Related	mdnsresponder.exe	1/71	Dropped file masquerading as legitimate Apple service

6. Notes on Network Indicators

Contacted domains and IP addresses observed during sandbox execution (e.g., Microsoft/Akamai/Fastly CDN infrastructure) were determined to be legitimate background system traffic and not attacker-controlled

infrastructure. No dedicated command-and-control domain was captured in the available sandbox telemetry for this sample set; this is a known limitation of static/sandbox-only analysis, as Rhadamanthys is known to use encrypted, rotating C2 infrastructure that may not always trigger during a short sandbox run.

7. Conclusion

The analyzed hash corresponds to a component of a multi-stage Rhadamanthys infostealer infection chain. The malware's known capabilities (credential theft, cryptocurrency wallet targeting, and clipboard hijacking) are consistent with the reported incident, in which an employee was redirected to a malicious site and the organization's cryptocurrency wallets were subsequently drained.

8. Recommendations

1. Treat all cryptocurrency wallets and credentials used on the affected endpoint as compromised; rotate keys and migrate funds to new wallets from a known-clean device.
2. Block the identified file hashes (madHcNet.dll, wdrvvtmoevsvki.exe) across endpoint protection and EDR tooling.
3. Reimage the affected endpoint rather than attempting in-place remediation, given Rhadamanthys's use of anti-analysis and persistence techniques.
4. Review browser extension permissions and clipboard-monitoring alerts organization-wide for signs of similar clipper activity.
5. Educate employees on verifying URLs before entering credentials on DAO/wallet management platforms, given the phishing redirect vector reported in this incident.

Disclaimer: This report was produced as part of a training exercise using the "Tusk Infostealer" practice case provided by CyberDefenders.org. All indicators were sourced from publicly available threat intelligence (VirusTotal). This report demonstrates threat intelligence and malware triage methodology for portfolio purposes and does not represent a real client engagement.