

# for Loops

---

CSC 116 – Section 002  
February 16, 2005

---

© 2005 Sarah E. Smith

## for Loops

---

- Ideal loop for count-controlled loops
- Syntax:  

```
for(<initialization>; <Boolean expression>;  
    <increment>) {  
    <loop body>  
}
```

---

© 2005 Sarah E. Smith

## for Loops (2)

---

- Ex: Sum numbers from 1 to 100

```
int sum = 0;
for(int i = 1; i <= 100; i++) {
    sum += i;
}
```

- *i* is the control variable. You can declare it outside of the loop or in the initialization statement.
- 

© 2005 Sarah E. Smith

## <initialization> Component

---

- Initialized the control variable to some value
- The value is usually 0 or 1, but can be anything

---

© 2005 Sarah E. Smith

## <Boolean expression> Component

---

- The for loop executes as long as the Boolean expression is true.
- The Boolean expression is evaluated before the loop is started

---

© 2005 Sarah E. Smith

## <increment> Component

---

- We can increment or decrement the control value
- Need to increment or decrement in such a way that you will eventually break out of the loop.

---

© 2005 Sarah E. Smith

## Sample Decrement for Loop

---

```
int sum = 0;
for(int i = 100; i > 0; i--) {
    sum += i;
}
```

---

© 2005 Sarah E. Smith

## Variable Scope

---

- Local variables can only be used in the block of code which they are declared
- Remember blocks are defined by { }s
- If you declare the control variable inside of the for loop declaration, the control variable only has scope inside of the loop
- If you want the control variable to have scope outside of the for loop, declare the variable before the for loop

---

© 2005 Sarah E. Smith

## Variable Scope (2)

---

- Ex:

```
for(int i = 0; i < 10; i++) {  
    System.out.println(i);  
}  
System.out.println(i);    //Can't use i here  
                           //out of scope
```

---

© 2005 Sarah E. Smith

## References

---

- Jason Schwarz's Lecture 12 slides:  
<http://courses.ncsu.edu/csc116/>

---

© 2005 Sarah E. Smith