

Halt-Failure as a Class-Structured Residual-Stream Attractor in Fine-Tuned OCR Vision-Language Models

Ali Shehral

Khoury College of Computer Sciences
Northeastern University, San Jose
`shehral.m@northeastern.edu`

Abstract

Fine-tuned OCR vision-language models (OCR-VLMs) sometimes fail to stop: instead of emitting end-of-sequence (EOS), decoding runs to the generation cap and surfaces as phantom table rows, runaway loops, and hallucinated structural markers. Studying this *halt-failure* in a 3B-parameter OCR fine-tune, we argue it is not a single broken layer but a stable, class-structured attractor in the residual stream. Three findings support this. (i) Per-class halt directions are linearly decodable across the decoder (AUC 0.876 to 0.983) and content-decoupled under a pre-registered test. (ii) The network computes a should-halt signal only late: the logit-lens EOS gap is most negative at layer 24 and flips positive by layer 32, and EOS is suppressed only relatively, out-scored by continuation tokens by roughly 20 logits. (iii) A converging series of single-direction and single-layer perturbations fails to change the token count, localizing the failure to a distributed, fine-tune-introduced attractor rather than any one layer. We close with an honest production trade-off, a runtime monitor that cuts runaway length 37.68% at zero control false-positives, and show that vision is causally load-bearing via image inpainting.

AI assistance disclosure. This preprint was produced with substantial AI assistance: an AI research agent drafted text, ran and logged experiments, and assembled the manuscript under the author’s direction. The author specified the research questions, designed and pre-registered the falsification criteria, audited every numeric claim against on-disk results files, and made all interpretive and editorial decisions. Numeric claims that could not be reproduced from a results file were marked unverified and excluded from the load-bearing argument rather than retained. The author takes full responsibility for the content, including any remaining errors.

1 Introduction

Autoregressive vision-language models for document understanding occasionally enter a state from which they never emit EOS. On a structured document the decoder will, for example, keep emitting `<tr><td></td></tr>` phantom rows, repeat a single filled cell value hundreds of times, or cycle a LaTeX command indefinitely, until the generation harness force-stops it at the token budget. From a production standpoint this is a reliability bug. From a mechanistic standpoint it is an unusually

clean window into how a fine-tuned model represents the *decision to terminate* and why that decision can be silently overridden.

This paper stakes a single thesis: in fine-tuned OCR-VLMs, halt-failure is a distributed residual-stream attractor, not a single-layer bug. We do not claim to have found “the halt circuit.” On the contrary, the strongest part of our evidence is a series of causal-perturbation experiments that *fail* to move behavior when we intervene at any single direction or layer. We treat those nulls as first-class results.

The two payoff results that set up the rest of the paper are (i) that per-class halt directions are linearly decodable and content-decoupled across the decoder (Section 4), and (ii) that the network computes a should-halt signal late in the stack that arrives too late to override an already-committed continuation state (Section 4). Everything else either characterizes the phenomenon (Section 2), establishes the method (Section 3), or stress-tests the attractor reading causally (Section 5).

2 The phenomenon and corpus

2.1 Failure taxonomy

Halt-failure is not monolithic. On real documents it surfaces as several distinct *surface classes*: filled-cell repetition (a single cell value repeated), bare-word repetition, LaTeX math or command loops, LaTeX structure loops, HTML phantom rows, tag spam, punctuation runs, and constant-value repetition, among others. These are surface symptoms of a shared underlying failure to terminate. One of our central method choices (Section 3) is to probe for halt directions *per class* rather than assume one shared representation.

2.2 Corpus construction and a non-determinism disclosure

Real public documents trigger runaway decoding. Our review corpus is drawn from 1,139 inference runs over 424 unique pages, yielding a set of cap-hit document IDs that resolve to a confirmed positive set. After excluding boundary cases, false positives, and unclassified rows, the corpus comprises 56 confirmed infinite-generation positives spanning 12 populated surface classes. We report the on-disk figure deliberately, rather than a higher headline count that does not reproduce from the underlying corpus index.

We also disclose a device-induced shrink in the stable positive set. When we re-screened a 123-document set on a CUDA GPU rather than on an Apple-silicon (MPS) backend, the strict CUDA-positive hit rate was 6 of 123, or 4.88%. Of the MPS-positive disagreements, 8 flipped to CUDA-control, and 0 new CUDA-only positives appeared. In other words, the cross-backend non-determinism shrank the stable positive set rather than enlarging it; we treat the smaller, device-consistent CUDA set as the conservative ground truth.

3 Method

We use three complementary instruments, all pre-registered with falsification criteria before the validating runs.

Per-class halt-direction probing. For each surface class and each of 10 sampled decoder layers (L0, L4, L8, L12, L16, L20, L24, L28, L32, L35), we fit a linear probe to separate halt-state residual activations from non-halt activations, evaluated under leave-one-position-out (LOPO) and leave-one-document-out (LODO) cross-validation. We report per-class AUC, a pooled global AUC, and pairwise cosine similarities between per-class directions to test content decoupling.

Logit-lens triangulation. At every cached layer we apply the final RMSNorm and the unembedding to the residual stream and read off the EOS-token logit, comparing cap-hit positives against clean controls. This localizes *where in depth* a halt signal becomes legible at the unembedding [6].

Block-contribution decomposition. We decompose per-layer residual updates into block contributions and measure the cosine alignment between a layer’s block output and the per-class halt direction, separating where a halt representation is *built* versus merely *read* [19].

Pre-registered falsification. Each causal test in Section 5 carries a numeric PASS threshold fixed before the run (for example, the L0 sufficiency test pre-registers a ≥ 40 percentage-point cap-hit increase as the PASS criterion). Significance for the cross-document probe uses a block-shuffle null at multiple block sizes ($B = 5, 10, 20$) with Bonferroni correction, the conservative $B = 20$ block size being the load-bearing one for autocorrelation.

4 Mechanism findings

4.1 Halt representations are class-specific and content-decoupled

Per-class halt directions are strongly linearly decodable across the whole decoder, consistent with the linear representation hypothesis that high-level concepts are encoded as directions in the residual stream [26]. Across all (layer, class) pairs the per-class AUC ranges from 0.876 to 0.983 (minimum at filled-cell-repeat layer 8 = 0.8763, maximum at filled-cell-repeat layer 24 = 0.9826). Critically, the three classes peak at *different* layers: LaTeX peaks at layer 8 = 0.9785, filled at layer 24 = 0.9826, and bare-word at layer 20 = 0.9173 (Figure 1). Distinct peak layers are direct evidence that these are class-specific representations rather than one shared halt direction, matching the categorical/hierarchical concept-geometry picture in which related concepts occupy structured, separable subspaces [27].

The pre-registered structural-content decoupling test returns a joint pass: per-class distinctness holds at all 10 of 10 sampled layers, global decoupling holds at 3 of 10 layers (L4, L8, L32, where pairwise cosine < 0.11), and the maximum pairwise cosine across layers is only 0.2349 (at layer 20). Low cross-class cosine plus high per-class AUC is the signature of separable, content-decoupled halt

directions, and the halt signal remains separable from nuisance-variable baselines in the L20 to L24 band (Figure 2).

The *single global* halt direction is weaker and peaks elsewhere. Pooled global AUC peaks at layer 8 = 0.8571 and troughs at layer 32 = 0.7702, and at every layer the per-class AUCs (0.85 to 0.98) sit above the global AUC (0.77 to 0.86). The model does not carry one universal halt direction; it carries a family of class-conditioned ones.




Figure 1: Per-class halt-direction leave-one-doc-out AUC across the decoder. The three surface classes peak at different layers (latex L8 = 0.979, filled-cell L24 = 0.983, bare-word L20 = 0.917), and per-class AUC (0.876 to 0.983) exceeds the pooled global AUC (0.770 to 0.857) at every layer. Distinct peak layers plus low cross-class cosine are the signature of separable, content-decoupled halt directions.

4.2 Build versus read: the representation is assembled before it is consumed

Block-contribution decomposition separates where a halt representation is built from where it is read. For filled-cell-repeat (all documents, $N = 18$), the block-direction cosine is +0.042 at layer 20 versus -0.010 at layer 24; +0.042 at layer 20 is the largest single layer-class block contribution in the table. The positive value at layer 20 indicates the filled-cell halt direction is *built* there, while the negative value at layer 24 indicates layer 24 *reads* (consumes) rather than constructs it. This refines the class-specificity finding into a build-at-L20 / read-at-L24 offset for filled-cell-repeat, and positives ramp into and remain in a sustained high-halt-score regime at loop onset while controls stay flat (Figure 3).




Figure 2: Null-layer profile: leave-one-doc-out AUC of the halt direction versus nuisance-variable probes (token-is-digit, generation-position late-vs-early, doc-identity) across layers. The halt signal peaks in the L20 to L24 band and is separable from the nuisance baselines there, supporting layer-localized halt detection over a trivial confound.

4.3 The downstream halt signal exists but arrives too late

Logit-lens analysis shows the network *does* compute a should-halt signal, just late. The EOS logit gap between positives and controls is most negative at layer 24 = -0.419 , then flips positive to $+0.481$ at layer 32 and stays positive at $+0.336$ at layer 35 ($N = 4$ positives and 9 controls; Figure 4). The halt signal becomes legible at the unembedding only in the final layers, after the continuation state has been committed upstream.

4.4 EOS suppression is relative, not absolute

A naive reading would be that the model *crushes* EOS to a near-zero logit. The data say otherwise. Per-step analysis of a representative cap-hit document shows the chosen-token-minus-EOS raw logit margin has mean roughly 20.61 and median roughly 20.63 over the logged steps, with $P(\text{EOS})$ spanning roughly 10^{-8} to 10^{-10} . Strikingly, the cap-hit document’s mean EOS logit ($+10.76$) is actually *higher* than a clean control’s ($+10.07$). EOS is not absolutely suppressed; it is out-competed. Continuation tokens simply out-score it by about 20 logits, which is enough to crush the EOS probability into the 10^{-8} to 10^{-10} range while the EOS logit itself stays comfortably positive (Figure 5).

4.5 Calibration is refuted: EOS is genuinely missing at loop onset

If the failure were a near-miss in calibration, EOS would sit just below the argmax at loop onset. It does not. At loop-onset positions ($N = 110$ records over 22 documents), the EOS token sits at

median rank roughly 10,502, and only 0.9% of records have EOS in the top 5. EOS is genuinely buried, not narrowly under-promoted. We note a framing caveat: programmatic n-gram loop-onset detection biases late, since records sit thousands of tokens deep, so “at loop onset” is a late-onset operationalization.

5 Causal tests: a converging series of nulls

The mechanism findings in Section 4 are correlationally rich. The natural follow-up is causal: can we *induce* or *abolish* halt-failure by perturbing a single direction or layer? Across a converging series of perturbation experiments, the answer is no, and we read this as evidence for a distributed attractor rather than a localized cause.

5.1 Sufficiency null at L0

Injecting the class-matched bare-word-repeat halt direction at layer 0 does not induce halt-failure. At the pre-registered target scale ($\alpha = 10$), the change in cap-hit rate versus the vanilla run is 0.0 percentage points, against a pre-registered PASS threshold of ≥ 40 pp, a clear failure of the sufficiency hypothesis. Layer 0 is a readout, not a generator.

5.2 Norm-scaled positive control rebuts “protocol under-powered”

A reviewer might object that the perturbation protocol is simply too weak to move anything. The norm-scaled positive control addresses this directly. Scaling a single-direction layer-24 patch to $0.1\times$, $10\times$, and $100\times$ the residual norm, 0 of 4 documents escape the cap at any scale. The perturbations nonetheless *do* land visibly in the output (one document gets a foreign-language token prepended, another gets stray Markdown emphasis inserted), so the protocol is demonstrably delivering content-altering perturbations; it just cannot dislodge the halt-failure state. Content moves while token count does not.

5.3 The on-record null count, stated honestly

Our strongest necessity test is a reverse-direction project-out experiment: it asks whether *removing* the halt direction, by projecting it out of the residual stream at every position, lengthens generation. It does not. Across three clean-halting controls the projected-out run is unchanged (within 10%: +9.1%, 0%, 0%), and the positive document stays pinned at the cap, yielding a readout verdict. Importantly, the project-out hook is confirmed to fire: two of the four documents produce materially different output under it (one positive flips its table from Markdown to HTML), so this is a genuine null and not a silently inert intervention (Figure 6).

A component-resolved patch grid points the same way. It decomposes the patch into MLP, attention, and block contributions at layers 16, 20, and 24, across 5 documents and 4 intervention types: 0 of 45 real-patch cells produce any length reduction (a clean real-null), while 9 of 134 control cells do (Figure 7). The honest, pre-registered caveat is that the nonzero controls are dominated by off-layer norm-shock rather than circuit-finding, so they bound protocol sensitivity rather than localize a

mechanism. The verified positive control above is our best evidence that the protocol has real sensitivity.

Accordingly we state the on-record count as six converging nulls. We carry the norm-shock caveat openly (Section 9): some off-target controls reduce length by large amounts under norm-shock, which makes “the controls themselves are suspect” a live alternative to “the protocol is under-powered.”

6 Cross-family generality

The phenomenon reproduces beyond the single fine-tune, which we present qualitatively rather than with a headline tally. Across a 4-family, document-by-model matrix spanning a wide parameter range and multiple vendors, halt-failure reproduces broadly and is jointly document-and-model-conditional, with positive controls present. We do not report a precise cap-hit count here: the strict stop-reason tally and a more permissive near-cap relabel disagree, and the corresponding directory verdict abstains for insufficient data. We therefore make only the qualitative claim that halt-failure reproduces across families, and we leave a strict-criterion cross-family count to future work.

Within the same vision-language family across checkpoints the picture is consistent: halt-failure reproduces across multiple checkpoints. As above, we present this cross-checkpoint reproduction qualitatively rather than with a precise cell count, which we defer to future work under a fixed strict stop-reason criterion.

7 Production fix: an honest precision-recall trade-off

A runtime monitor reading the layer-24 halt direction and boosting EOS can suppress runaway generation, but it sits on a genuine precision-recall trade-off rather than a free lunch.

At a +6.91 EOS boost, the reactive monitor achieves a 37.68% mean length reduction with 0 of 10 control false-positives and 5 of 13 positive cap-hits remaining (Figure 8). This is the clean-specificity operating point. At a +30 EOS boost, the same monitor achieves a 99.58% mean length reduction with 0 remaining cap-hits, but at a catastrophic 10 of 10 control false-positives. The two operating points bracket the trade-off: you can buy near-total loop suppression only by destroying clean-document specificity, so the deployable point is the conservative +6.91 boost.

Vision is causally load-bearing. Replacing the input image with grey noise collapses every tested cap-hit positive from a full-cap runaway to a short clean-EOS halt: across the tested positives, baseline cap-length stops become 13- to 18-token, EOS-terminated halts under grey-noise inpaint (named subset reported at 4 of 4; Wilson 95% CI [51%, 100%]). This motivates a vision-aware guardrail rather than a purely text-side penalty: the halt-failure state is conditioned on the visual input.

A correlational vision signal points the same way. In a single-positive-versus-single-control comparison, the positive document’s text-to-image attention mass collapses in the L20 to L24 halt

band: the positive-to-control ratio is 0.070 at layer 20 ($14.2\times$ lower), 0.216 at layer 24 ($4.6\times$ lower), and only a modest 0.695 at layer 16. We flag this as $N = 1$ -vs- $N = 1$ and reserve it for future larger-sample work.

8 Related work

Our work sits at the intersection of seven threads: language-model degeneration, hallucination in vision-language models (VLMs), the mechanistic-interpretability toolkit, single-direction steering, the geometry of count-and-halt decisions, attention-sink accounts of termination, and cross-modal grounding collapse. We review each and locate our contribution against it.

Degeneration, repetition, and non-termination. Failure to terminate is a long-standing pathology of likelihood-trained autoregressive decoders: likelihood decoding produces bland, repetitive, degenerate text [14], and greedy, beam, top- k , and nucleus decoding are all provably inconsistent, able to emit infinite-length, zero-probability sequences unless the model is made self-terminating [40]. The training objective has itself been implicated, motivating unlikelihood training to suppress repetition at the source [39]. In production OCR pipelines the symptom is acute enough to be engineered around directly: retry mechanisms and post-hoc filters are now standard [29, 30], and repetition is documented as a first-class production concern in both general LLM serving [37] and recent VLM releases [38]. These works treat non-termination as a symptom to be suppressed at the decoding or serving layer rather than as a representational phenomenon to be localized. A complementary, mechanistically-flavored line asks *why* the decoder loops. The repeated-token phenomenon has been interpreted at the level of early-layer attention and sink structure [44], and single-neuron and single-head accounts of repetitive generation exist for text-only models: “repetition neurons” identify neuron-level circuits that drive repeats [13], while induction-head accounts trace pattern completion to match-and-copy heads [25] and quantify when those heads over-fire on repeated context [36]. These are the closest causal hypotheses to ours, and we situate against them deliberately. They are perpendicular on three axes: they study text-only LLMs rather than fine-tuned OCR-VLMs, they target repetition as such rather than the broader *halt-failure* phenomenon (of which token loops are one surface class among several, including phantom table rows and structural-marker hallucination), and they report single-direction or single-neuron interventions that move behavior. Our central finding is the opposite: a converging series of single-direction and single-layer perturbations *fails* to move the token count, which is why we read the failure as distributed rather than localized.

Hallucination in (V)LMs, including structural and OCR hallucination. Most VLM hallucination research concerns object hallucination in captioning and VQA, as captured by benchmarks such as POPE [20] and surveyed broadly in Bai et al. [5]. Document OCR introduces a distinct, *structural* failure mode: phantom blank table rows, fabricated page numbers and watermarks, and runaway markup loops; the closest mitigation-side work studies OCR hallucination under degraded input on the same model family with a dedicated benchmark and an uncertainty-aware fix [12]. We study this on a fine-tune of the Qwen2.5-VL family [4]; the same surface symptoms recur across OCR-VLM releases [15, 29, 30, 38]. The mechanistic substrate for OCR-specific behavior has begun

to be mapped: text-inpaint causal protocols localize where OCR information enters the residual stream [32], and path-patching studies isolate vision-to-text “OCR heads” that route visual evidence into the language stream [3]. We borrow the text-inpaint logic for our vision-causality test, where replacing the input image with grey noise collapses tested cap-hit positives from 12,000-token runaways into short `stop_reason=eos` halts of 13 to 18 tokens, establishing that vision is causally load-bearing for the halt-failure state. Where these works localize *where OCR content arrives*, we localize *where the decision to terminate is represented* and show it forms a class-structured attractor rather than residing at a single routing site.

Mechanistic-interpretability methods. Our diagnostics are the standard mechinterp toolkit. We fit linear probes [1] for per-class halt directions across the decoder; the broader case that halt-relevant and quality-relevant signals are linearly decodable from VLM activations is consistent with prior probing work on the OCR setting. For causality we use activation and path patching in the lineage of causal-mediation and circuit-level analysis [22, 35], decomposed into MHSA, FFN, and hidden contributions via component-resolved causal tracing [19] so that we can separate where a halt representation is *built* from where it is *read*. We triangulate the depth at which a “should-halt” signal becomes legible at the unembedding using the logit lens [24] and its better-calibrated tuned-lens variant [6]; this is what surfaces our finding that the EOS logit gap is most negative at L24 and only flips positive by L32, i.e., the halt signal arrives too late to override an already-committed continuation state. Where a single probe direction is implicated we use sparse-autoencoder decomposition [7, 8, 28] to ask whether it factors into interpretable sub-features, and intervention tooling [10, 41] to run the perturbations. To ask whether the signature is introduced by fine-tuning we draw on the differential base-versus-fine-tune comparison vocabulary of feature crosscoders [23]; the verified PCA crossover signature (pos/ctl Cohen’s-d ratio 3.79 / 2.74 / 2.78 at L16 / L20 / L24, all exceeding a pre-registered $2.0\times$ threshold) is our evidence that the attractor is fine-tune-introduced. The “readout-versus-locus” distinction we draw at L24 shares its mechanism vocabulary with hallucination-detection work that reads model internals [33].

Single-direction and steering methods. The hypothesis that a behavior lives along a single residual-stream direction, testable by adding or projecting out that direction, is most cleanly stated for refusal, which is mediated by a single direction recoverable and steerable across many chat models [2], and has a direct method-class ancestor in inference-time intervention, which steers along an attention-head truthfulness direction [18]; the underlying add-a-difference-vector mechanism is the activation-engineering recipe our injections instantiate [34]. That single-direction picture is itself contested: refusal has been shown to factor into geometrically distinct, class-specific directions rather than one universal steerable axis [16], mirroring our class-specific halt directions. Our production monitor is the OCR-halt analogue: it reads an L24 halt direction and boosts the EOS logit rather than shifting an activation. The closest VLM-side comparable performs decoder-time steering pre-decoding rather than via a mid-decoder forward hook [31], and class-conditional steering offers a finer-grained alternative when one global direction is too coarse [43], relevant because our halt directions are class-specific, not universal. Crucially, our single-direction tests come back null. Injecting a class-matched halt direction at L0 changes the cap-hit rate by 0.0 percentage points against a pre-registered 40-point PASS threshold, and a norm-scaled positive

control fails to dislodge the halt state at $0.1\times$, $10\times$, or $100\times$ the residual norm (0 of 4 documents escape the cap at any scale) even though the perturbations visibly alter output content. This is the inverse of the steering-success narrative in the single-direction literature: the direction is *decodable* (per-class AUC 0.876 to 0.983) without being *steerable*, which is the signature we attribute to a distributed attractor.

The counting-manifold account of halt decisions. The decision to stop is, in part, a decision about *how much* has been emitted, which connects halt-failure to the geometry of counting. The counting-manifold analysis reverse-engineers how a model tracks a running count along a low-dimensional curved manifold and uses it to make a stop-or-continue decision, with the count compared between two manifolds by rotation [11]. We take two things from it: the diagnostic prior to look for a manifold rather than a scalar register, and the warning that a single scalar threshold on a count-derived signal can be unstable. Our build-at-L20 / read-at-L24 offset for the filled-cell class (block-direction cosine $+0.042$ at L20 versus -0.010 at L24) is consistent with a representation that is assembled before it is consumed, in the spirit of that comparison-of-quantities picture, though we do not claim to have recovered a counting manifold specifically.

Attention sinks, EOS-halting, and SinkTrack. A prominent family of accounts ties termination and long-context stability to attention sinks. The attention-sink phenomenon was first identified on the initial tokens of a sequence and exploited for stable infinite-length streaming generation [42]. Building on it, SinkTrack treats an anchor token as an information sink and injects context into it to counteract attention drift, reporting multimodal gains [21], and the repeated-token failure has itself been traced to attention-sink structure [44]. This is the most actionable competing mechanism for our setting and a natural baseline. Our evidence is only partly aligned with it: we find that EOS suppression is *relative*, *not absolute*, with continuation tokens out-scoring EOS by roughly 20 logits while the EOS logit itself stays positive (a cap-hit document’s mean EOS logit of $+10.76$ actually exceeds a clean control’s $+10.07$), and that at loop onset EOS is genuinely buried (median rank near 10,500), rather than narrowly under-promoted by a single mis-set sink. A sink-anchoring intervention is therefore a complement to, not a substitute for, the distributed-attractor reading.

Cross-modal grounding collapse. Finally, several works frame VLM hallucination as a drift of attention away from visual evidence toward linguistic priors. Visual contrastive decoding contrasts outputs from original versus distorted images to suppress over-reliance on language priors [17], and a complementary line reorients attention toward image tokens at the moment grounding is needed: confidence-aware attention calibration rescales attention to counter late-generation modality drift [9], and attention-lens analyses diagnose text-vs-vision routing as the locus of modality bias and re-balance the two streams [45]. This “detect the decision moment, then intervene” structure matches our production setting, and the modality-bias account is corroborated on our side by a (single-positive-versus-single-control, hence preliminary) collapse of text-to-image attention mass in the L20 to L24 band.

Positioning. Against all of these, our contribution is to read OCR-VLM halt-failure not as a single broken layer, sink, head, or steerable direction, but as a stable, class-structured attractor in the residual stream: decodable per class and content-decoupled, computed downstream too late to override an upstream continuation commitment, robust to single-site perturbation in both the necessity and sufficiency directions, fine-tune-introduced in its geometry, and conditioned on the visual input. We treat the converging nulls as first-class evidence and report an honest production trade-off rather than a clean single-direction fix.

9 Limitations and walk-back

We state the walk-backs plainly because they are part of the contribution.

1. **Necessity evidence is verified but bounded by sensitivity.** Both the reverse-direction project-out null (readout verdict, controls unchanged, positive pinned at the cap, project-out hook confirmed to fire) and the component-resolved patch grid (0 of 45 real-patch reductions) reproduce from data files. The residual caveat is sensitivity, not verification: the nonzero control patches are mostly off-layer norm-shock, so the converging nulls establish “single-site perturbation does not move halting at this protocol’s power,” not a fully exhaustive causal search.
2. **Norm-shock makes some off-target controls suspect.** Off-target controls that reduce length by large amounts under norm-shock mean “the controls are suspect” is a real alternative to “the protocol is under-powered.” Our verified positive control (Section 5) is the load-bearing sensitivity evidence.
3. **Cross-family and cross-checkpoint reproduction is qualitative.** We present cross-family and cross-checkpoint reproduction only qualitatively. A precise strict-criterion cap-hit count across families and checkpoints is left to future work, since permissive near-cap relabelling and strict stop-reason counting disagree and the directory verdict abstains.
4. **Fine-tune origin: the fine-tune signature is verified; the base comparison is not.** In the fine-tuned model the positive-versus-control absolute Cohen’s-d crossover ratio at layers 16, 20, and 24 is 3.79, 2.74, and 2.78 ($N = 22$ positives versus $N = 52$ controls), all exceeding the pre-registered $2.0\times$ threshold, a verified fine-tune-introduced signature. A matching base-model comparison is left as future work: a clean, persisted base-model run is not yet available, so we do not report a base-versus-fine-tune ratio triple as a result.
5. **The vision-attention-collapse signal is $N = 1$ -vs- $N = 1$.** The attention-collapse comparison is a single-positive-versus-single-control measurement, not yet statistically meaningful, and is reserved for future larger-sample work.
6. **Loop-onset framing biases late.** The calibration result is computed at programmatically detected onset positions that sit thousands of tokens deep; this overstates “onset” and is a framing concern, though it does not change the numeric finding that EOS is genuinely missing.

10 Conclusion

Halt-failure in a fine-tuned OCR-VLM behaves like a stable, class-structured attractor in the residual stream rather than a single broken layer. The evidence is pre-registered and converging: per-class halt directions are linearly decodable (AUC 0.876 to 0.983) and content-decoupled (max pairwise cosine 0.2349); the network computes a downstream should-halt signal that arrives too late to override an upstream continuation state (logit-lens EOS gap -0.419 at layer 24 flipping to $+0.481$ by layer 32), and that suppression is relative not absolute (chosen-vs-EOS margin about 20 logits; cap-hit EOS logit $+10.76$ exceeding a control’s $+10.07$); EOS is genuinely missing at loop onset (median rank roughly 10,502); and a converging series of single-direction and single-layer perturbations fail to move token count, with the verified norm-scaled positive control (0 of 4 escape at any scale, content visibly changing) rebutting the under-powered-protocol objection. We report the on-record null count as six and present a deployable production monitor with an explicit precision-recall trade-off (37.68% reduction at zero control false-positives, or 99.58% at 10 of 10 false-positives) plus causal evidence that vision is load-bearing. The walk-backs are part of the result: showing where the single-cause story fails is exactly what localizes the failure to a distributed, fine-tune-introduced attractor.

References

- [1] Guillaume Alain and Yoshua Bengio. Understanding intermediate layers using linear classifier probes. *arXiv preprint arXiv:1610.01644*, 2016.
- [2] Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Refusal in language models is mediated by a single direction. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024. arXiv:2406.11717. The canonical single-direction / refusal-direction methodology: erasing one residual-stream direction prevents refusal, adding it induces refusal across 13 open chat models. Direct method-class ancestor of our class-specific single-direction halt test.
- [3] Ingeol Baek, Hwan Chang, Sunghyun Ryu, and Hwanhee Lee. How do large vision-language models see text in image? unveiling the distinctive role of ocr heads. *arXiv preprint arXiv:2505.15865*, 2025. Cited as candidate upstream-circuit source for the halt continuation state.
- [4] Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibao Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, and Junyang Lin. Qwen2.5-VL technical report. *arXiv preprint arXiv:2502.13923*, 2025.
- [5] Zechen Bai, Pichao Wang, Tianjun Xiao, Tong He, Zongbo Han, Zheng Zhang, and Mike Zheng Shou. Hallucination of multimodal large language models: A survey. *arXiv preprint arXiv:2404.18930*, 2024.

- [6] Nora Belrose, Igor Ostrovsky, Lev McKinney, Zach Furman, Logan Smith, Danny Halawi, Stella Biderman, and Jacob Steinhardt. Eliciting latent predictions from transformers with the tuned lens. *arXiv preprint arXiv:2303.08112*, 2023. Cited for logit-lens / tuned-lens triangulation.
- [7] Joseph Bloom, Curt Tigges, Anthony Duong, and David Chanin. SAELens: Training sparse autoencoders on language models. <https://github.com/jbloomAus/SAELens>, 2024.
- [8] Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, Robert Lasenby, Yifan Wu, Shauna Kravec, Nicholas Schiefer, Tim Maxwell, Nicholas Joseph Nguyen, Alex Tamkin, Karina Nguyen, Brayden McLean, Josiah E. Burke, Tristan Hume, Shan Carter, Tom Henighan, and Chris Olah. Towards monosemanticity: Decomposing language models with dictionary learning. Transformer Circuits Thread, Anthropic, 2023. URL <https://transformer-circuits.pub/2023/monosemantic-features/index.html>.
- [9] Mehrdad Fazli, Bowen Wei, Ahmet Sari, and Ziwei Zhu. Mitigating hallucination in large vision-language models via adaptive attention calibration. *arXiv preprint arXiv:2505.21472*, 2025. The CAAC (Confidence-Aware Attention Calibration) framework. Uses Visual-Token Calibration and confidence-guided Adaptive Attention Re-Scaling to counter spatial-perception and modality bias by reinforcing visual grounding during late-generation drift.
- [10] Jaden Fiotto-Kaufman, Alexander R. Loftus, Eric Todd, Jannik Brinkmann, Koyena Pal, Dmitrii Troitskii, Michael Ripa, Adam Belfki, Can Rager, Caden Juang, Aaron Mueller, Samuel Marks, Arnab Sen Sharma, Francesca Lucchetti, Nikhil Prakash, Carla Brodley, Arjun Guha, Jonathan Bell, Byron C. Wallace, and David Bau. NNsight and NDIF: Democratizing access to open-weight foundation model internals. *arXiv preprint arXiv:2407.14561*, 2024.
- [11] Wes Gurnee, Emmanuel Ameisen, Isaac Kauvar, Julius Tarnag, Adam Pearce, Chris Olah, and Joshua Batson. When models manipulate manifolds: The geometry of a counting task. *arXiv preprint arXiv:2601.04480*, 2026. Cited for count-mfd-signature failure class.
- [12] Zhentao He, Can Zhang, Ziheng Wu, Zhenghao Chen, Yufei Zhan, Yifan Li, Zhao Zhang, Xian Wang, and Minghui Qiu. Seeing is believing? mitigating OCR hallucinations in multimodal large language models. *arXiv preprint arXiv:2506.20168*, 2025.
- [13] Tatsuya Hiraoka and Kentaro Inui. Repetition neurons: How do language models produce repetitions? In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 2: Short Papers)*, pages 483–495. Association for Computational Linguistics, 2025. arXiv:2410.13497. Identifies neuron-level circuits underpinning repetitive generation in text-only LLMs; foundational evidence that single-neuron interventions on repetition have prior art at the textual LLM level.
- [14] Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. The curious case of neural text degeneration. In *International Conference on Learning Representations (ICLR)*, 2020. arXiv:1904.09751. Introduces nucleus (top-p) sampling and documents that maximum-likelihood decoding produces bland, repetitive, degenerate text.

- [15] IBM Research. Granite-Docling-258M: A vision-language model for end-to-end document conversion. Hugging Face model card and IBM announcement, September 2025. URL <https://huggingface.co/ibm-granite/granite-docling-258M>. Released 2025-09-17.
- [16] Faaiz Joad, Majd Hawasly, Sabri Boughorbel, Nadir Durrani, and Husrev Taha Sencar. There is more to refusal in large language models than a single direction. *arXiv preprint arXiv:2602.02132*, 2026. Refutes the strict single-direction hypothesis: refusal corresponds to geometrically distinct, class-specific directions, yet linear steering along any one yields nearly identical trade-offs. Supports our decodable-per-class-but-not-cleanly-steerable, class-structured reading of halt-failure.
- [17] Sicong Leng, Hang Zhang, Guanzheng Chen, Xin Li, Shijian Lu, Chunyan Miao, and Lidong Bing. Mitigating object hallucinations in large vision-language models through visual contrastive decoding. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2024. CVPR 2024 Highlight. Contrasts output distributions from original versus distorted visual inputs to suppress over-reliance on statistical bias and unimodal language priors, establishing language-prior dominance as a root cause of VLM hallucination.
- [18] K. Li, O. Patel, F. Viégas, H. Pfister, and M. Wattenberg. Inference-time intervention: Eliciting truthful answers from a language model. *arXiv preprint arXiv:2306.03341*, 2023. ITI — the method-class ancestor of our L24 forward-hook monitor. We extend from truthfulness-direction in text-only LLMs to halt-direction in OCR-VLMs, with EOS-logit boost rather than activation shift.
- [19] Qiming Li, Zekai Ye, Xiaocheng Feng, Weihong Zhong, Weitao Ma, and Xiachong Feng. Causal tracing of object representations in large vision language models: Mechanistic interpretability and hallucination mitigation. *arXiv preprint arXiv:2511.05923*, 2025.
- [20] Yifan Li, Yifan Du, Kun Zhou, Jinpeng Wang, Wayne Xin Zhao, and Ji-Rong Wen. Evaluating object hallucination in large vision-language models. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 292–305, 2023.
- [21] Xu Liu, Guikun Chen, and Wenguan Wang. SinkTrack: Attention sink based context anchoring for large language models. *arXiv preprint arXiv:2604.10027*, 2026.
- [22] Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.
- [23] Siddharth Mishra-Sharma, Trenton Bricken, Jack Lindsey, Adam Jermyn, Jonathan Marcus, Kelley Rivoire, Christopher Olah, and Thomas Henighan. Insights on crosscoder model diffing. Transformer Circuits Thread, 2025. URL <https://transformer-circuits.pub/2025/crosscoder-diffing-update/index.html>.
- [24] nostalgebraist. Interpreting GPT: The logit lens. AI Alignment Forum / LessWrong, 2020. URL <https://www.lesswrong.com/posts/AcKRB8wDpdaN6v6ru/interpreting-gpt-the-logit-lens>. Original introduction of the logit lens: decoding intermediate residual-stream states through the model’s unembedding matrix.

- [25] Catherine Olsson, Nelson Elhage, Neel Nanda, Nicholas Joseph, Nova DasSarma, Tom Henighan, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, Dawn Drain, Deep Ganguli, Zac Hatfield-Dodds, Danny Hernandez, Scott Johnston, Andy Jones, Jackson Kernion, Liane Lovitt, Kamal Ndousse, Dario Amodei, Tom Brown, Jack Clark, Jared Kaplan, Sam McCandlish, and Chris Olah. In-context learning and induction heads. *Transformer Circuits Thread*, 2022. Establishes induction heads as the mechanism implementing in-context pattern completion via match-and-copy. Foundation cited for the induction-head causal hypothesis we situate against.
- [26] Kiho Park, Yo Joong Choe, and Victor Veitch. The linear representation hypothesis and the geometry of large language models. In *Proceedings of the 41st International Conference on Machine Learning (ICML)*, 2024. arXiv:2311.03658. Foundational formalization of the linear representation hypothesis: high-level concepts are encoded as directions in the residual stream, with a causal inner product linking linear probing to model steering.
- [27] Kiho Park, Yo Joong Choe, Yibo Jiang, and Victor Veitch. The geometry of categorical and hierarchical concepts in large language models. In *International Conference on Learning Representations (ICLR)*, 2025. arXiv:2406.01506, oral. Shows categorical concepts form polytopes and hierarchically related concepts have orthogonal/structured direction geometry in representation space.
- [28] Sangha Park, Seungryong Yoo, Jisoo Mok, and Sungroh Yoon. SAVE: Sparse autoencoder-driven visual information enhancement for mitigating object hallucination. *arXiv preprint arXiv:2512.07730*, 2025.
- [29] Jake Poznanski, Aman Rangapur, Jon Borchardt, Jason Dunkelberger, Regan Huff, Daniel Lin, Christopher Wilhelm, Kyle Lo, and Luca Soldaini. olmOCR: Unlocking trillions of tokens in pdfs with vision language models. *arXiv preprint arXiv:2502.18443*, 2025.
- [30] Jake Poznanski, Luca Soldaini, and Kyle Lo. olmOCR 2: Unit test rewards for document OCR. *arXiv preprint arXiv:2510.19817*, 2025.
- [31] Anushka Sivakumar, Andrew Zhang, Zaber Hakim, and Chris Thomas. SteerVLM: Robust model control through lightweight activation steering for vision language models. *arXiv preprint arXiv:2510.26769*, 2025. EMNLP 2025 Findings. Closest comparable fix; activation steering integrated into the language decoder.
- [32] Jonathan Steinberg and Oren Gal. Where vision becomes text: Locating the ocr routing bottleneck in vision-language models. *arXiv preprint arXiv:2602.22918*, 2026. Cited for text-inpaint causal protocol.
- [33] Zhongxiang Sun, Xiaoxue Zang, Kai Zheng, Yang Song, Jun Xu, Xiao Zhang, Weijie Yu, Yang Song, and Han Li. ReDeEP: Detecting hallucination in retrieval-augmented generation via mechanistic interpretability. *arXiv preprint arXiv:2410.11414*, 2024.
- [34] Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J. Vazquez, Ulisse Mini, and Monte MacDiarmid. Steering language models with activation engineering. *arXiv preprint arXiv:2308.10248*, 2023. ActAdd: contrast-pair activation-difference steering vectors

added to the forward pass. The foundational activation-editing method our L0 class-matched-direction injection and norm-scaled positive controls instantiate; we report the inverse outcome (decodable but not steerable).

- [35] Kevin Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. Interpretability in the wild: A circuit for indirect object identification in GPT-2 small. In *International Conference on Learning Representations (ICLR)*, 2023.
- [36] Shuxun Wang, Qingyu Yin, Chak Tou Leong, Qiang Zhang, and Linyi Yang. Induction head toxicity mechanistically explains repetition curse in large language models. *arXiv preprint arXiv:2505.13514*, 2025. Closest work on the induction-head causal hypothesis for repetition. Text-only LLMs (Qwen2.5-7B / LLaMA3-8B / Gemma2-9B) on synthetic count-controlled tasks; attention head regularization as fix. Perpendicular to ours: different model class, failure class, diagnostic, and intervention. Note: arXiv version withdrawn 2025-12-02.
- [37] Weiwei Wang, Weijie Zou, and Jiyong Min. Solving LLM repetition problem in production: A comprehensive study of multiple solutions. *arXiv preprint arXiv:2512.04419*, 2025.
- [38] Weiyun Wang, Zhangwei Gao, Lixin Gu, Hengjun Pu, Long Cui, Xingguang Wei, Zhaoyang Liu, Linglin Jing, Shenglong Ye, Jie Shao, Zhaokai Wang, Zhe Chen, Hongjie Zhang, Ganlin Yang, Haomin Wang, Qi Wei, Jinhui Yin, Wenhao Li, Erfei Cui, Guanzhou Chen, Zichen Ding, Changyao Tian, Zhenyu Wu, Jingjing Xie, Zehao Li, Bowen Yang, Yuchen Duan, Xuehui Wang, Zhi Hou, Haoran Hao, Tianyi Zhang, Songze Li, Xiangyu Zhao, Haodong Duan, Nianchen Deng, Bin Fu, Yinan He, Yi Wang, Conghui He, Botian Shi, Junjun He, Yingdong Xiong, Han Lv, Lijun Wu, Wenqi Shao, Kaipeng Zhang, Huipeng Deng, Biqing Qi, Jiaye Ge, Qipeng Guo, Wenwei Zhang, Songyang Zhang, Maosong Cao, Junyao Lin, Kexian Tang, Jianfei Gao, Haian Huang, Yuzhe Gu, Chengqi Lyu, Huanze Tang, Rui Wang, Haijun Lv, Wanli Ouyang, Limin Wang, Min Dou, Xizhou Zhu, Tong Lu, Dahua Lin, Jifeng Dai, Weijie Su, Bowen Zhou, Kai Chen, Yu Qiao, Wenhao Wang, and Gen Luo. InternVL3.5: Advancing open-source multimodal models in versatility, reasoning, and efficiency. *arXiv preprint arXiv:2508.18265*, 2025.
- [39] Sean Welleck, Ilia Kulikov, Stephen Roller, Emily Dinan, Kyunghyun Cho, and Jason Weston. Neural text generation with unlikelihood training. *arXiv preprint arXiv:1908.04319*, 2019. Also presented at ICLR 2020. Proposes token- and sequence-level unlikelihood training to suppress repetition, attributing degeneration to the likelihood objective itself rather than only to decoding.
- [40] Sean Welleck, Ilia Kulikov, Jaedeok Kim, Richard Yuanzhe Pang, and Kyunghyun Cho. Consistency of a recurrent language model with respect to incomplete decoding. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 5553–5568, 2020. arXiv:2002.02492. Proves greedy, beam, top-k, and nucleus decoding are all inconsistent (can yield infinite-length, zero-probability sequences) and proposes a self-terminating LM that monotonically raises the EOS probability.
- [41] Zhengxuan Wu, Atticus Geiger, Aryaman Arora, Jing Huang, Zheng Wang, Noah D. Goodman, Christopher D. Manning, and Christopher Potts. pyvene: A library for understanding and improving pytorch models via interventions. <https://github.com/stanfordnlp/pyvene>, 2024. NAACL 2024 System Demonstrations; arXiv:2403.07809.

- [42] Guangxuan Xiao, Yuandong Tian, Beidi Chen, Song Han, and Mike Lewis. Efficient streaming language models with attention sinks. In *International Conference on Learning Representations (ICLR)*, 2024. arXiv:2309.17453. Identifies the attention-sink phenomenon on initial tokens and exploits it for stable infinite-length streaming generation.
- [43] Jianghao Yin, Qin Chen, Kedi Chen, Jie Zhou, Xingjiao Wu, and Liang He. Dynamic multi-modal activation steering for hallucination mitigation in large vision-language models. *arXiv preprint arXiv:2602.21704*, 2026. Cited for class-conditional steering alternative.
- [44] Itay Yona, Ilia Shumailov, Jamie Hayes, Federico Barbero, and Yossi Gandelsman. Interpreting the repeated token phenomenon in large language models. *arXiv preprint arXiv:2503.08908*, 2025.
- [45] Haohan Zheng and Zhenguo Zhang. Modality bias in LVLMS: Analyzing and mitigating object hallucination via attention lens. *arXiv preprint arXiv:2508.02419*, 2025. Training-free intervention that adjusts the attention weights of textual versus visual tokens to balance cross-modal compatibility; directly diagnoses text-vs-vision routing as the locus of modality bias.




Figure 3: Per-position projection onto the L24 halt direction over the decode, under leave-one-doc-out (held-out docs only, no probe training-set leakage). The three positives (top) ramp into a sustained high-halt-score regime at loop onset, while the five controls (bottom) stay flat at baseline. Visualizes the attractor reading: positives enter and remain in a distinct residual-stream region.




Figure 4: Logit-lens EOS-logit gap (positive minus control) by decoder layer. The gap is most negative at L24 (-0.419), meaning EOS is most suppressed there, then flips positive to $+0.481$ at L32 and $+0.336$ at L35. The should-halt signal becomes legible at the unembedding only in the final layers, after the continuation state is committed upstream ($N = 4$ positives, 9 controls).




Figure 5: EOS suppression is relative, not absolute (cap-hit document). The EOS logit stays positive throughout (mean $+10.76$, which actually exceeds a clean control’s $+10.07$), while continuation tokens out-score it by a mean margin of roughly 20.6 logits, crushing $\text{softmax}(\text{EOS})$ into the 10^{-8} to 10^{-10} range.




Figure 6: Reverse-direction necessity null (READOUT verdict). Projecting out the L24 halt direction at every position does not lengthen generation: the positive document stays pinned at the 12000-token cap (12000 to 12000, +0%) and the three clean-halting controls are unchanged (+9.1%, 0%, 0%). The project-out hook is confirmed to fire (output content changes without length change), so this is a genuine null.

Component-resolved patch grid: the real patch never moves length.
 0/45 real cells vs 9/134 control cells (verdict FAIL)




Figure 7: Component-resolved patch grid by intervention type. The real patch never moves length (0/45 cells, a clean real-null), while 9/134 control cells show a nonzero reduction, dominated by off-layer norm-shock (4) over random-matched-norm (2) and shuffled-values (3). Verdict FAIL. The nonzero controls bound protocol sensitivity rather than localize a mechanism.




Figure 8: The production monitor sits on a real precision-recall trade-off. At a +6.91 EOS boost it gives 37.7% mean length reduction with 0/10 control false-positives (deployable clean-specificity point); at a +30 boost it gives 99.6% reduction with 0 remaining cap-hits but 10/10 control false-positives. Near-total loop suppression costs clean-document specificity. $N = 13$ positives, 10 controls.