Name: SHEIKH WASIMUDDIN
Roll No: IOT-73
Branch: CSE(IOT)

LAB 02	
Aim:	Create a class with using new object for various method.
Theory:	**1. Creating a Class:** • A class is created to define the blueprint or structure for an object. It can contain data members (attributes) and member functions (methods) that describe the behavior of the object. • The class is created once, and many objects can be instantiated from it. • To create a class, you define its name and include any necessary methods and attributes. **2. Creating Objects Using the new Keyword:** • An object is an instance of a class. To create an object in Java, you use the new keyword followed by the constructor of the class. • The constructor is a special method used to initialize objects when they are created. It typically sets initial values for the data members of the object. • When an object is created, the class defines how it will behave and what data it will hold. **3. Using the Object to Call Various Methods:** • Once an object is created, you can use it to access and invoke the methods (member functions) defined within the class. • Methods are used to perform specific actions or operations on the object. • You call methods using the object, often followed by the dot (.) operator.

Program:	i)
	
	//SHEIKH WASIMUDDIN 23071044 CSEIOT-73
	public class car {
	private String model;
	private int year;
	private double price;
	public void setModel(String model) {
	this.model = model;
	}
	public void setYear(int year) {
	this.year = year;
	}
	public void setPrice(double price) {
	this.price = price;
	}
	public String getModel() {
	return model;
	}
	public int getYear() {

Name: SHEIKH WASIMUDDIN
Roll No: IOT-73
Branch: CSE(IOT)

```
        return year;
    }
    public double getPrice() {
        return price;
    }
    public static void main(String[] args) {
        car mycar = new car();
        mycar.setModel("Audi");
        mycar.setYear(2025);
        mycar.setPrice(1500000);
        System.out.println("Model of the car: " + mycar.getModel());
        System.out.println("Year of the car: " + mycar.getYear());
        System.out.println("Price of the car: Rs" + mycar.getPrice());
    }
}
```

ii)

```
//SHEIKH WASIMUDDIN 23071044 CSEIOT-73
public class animal {
    private String name;
    private int age;
    private double weight;
    public void setName(String name) {
        this.name = name;
    }
    public void setAge(int age) {
        this.age = age;
    }
    public void setWeight(double weight) {
        this.weight = weight;
    }
    public String getName() {
        return name;
    }
    public int getAge() {
        return age;
    }
    public double getWeight() {
        return weight;
    }
    public static void main(String[] args) {
        animal myanimal = new animal();
        myanimal.setName("Cow");
        myanimal.setAge(15);
        myanimal.setWeight(160);
        System.out.println("Name of Animal is: "+myanimal.getName());
        System.out.println("Age of Animal is: "+myanimal.getAge());
        System.out.println("Weight of Animal is: "+myanimal.getWeight()+" Kgs");
    }
}
```

Name: SHEIKH WASIMUDDIN
Roll No: IOT-73
Branch: CSE(IOT)

Output:

i).

car.java

car.java > Language Support for Java(TM) by Red Hat > car

```java
//SHEIKH WASIMUDDIN 23071044 CSEIOT-73
public class car {
    private String model;
    private int year;
    private double price;
    public void setModel(String model) {
        this.model = model;
    }
    public void setYear(int year) {
        this.year = year;
    }
    public void setPrice(double price) {
        this.price = price;
    }
    public String getModel() {
        return model;
    }
```

PROBLEMS OUTPUT TERMINAL DEBUG CONSOLE PORTS

```
PS C:\Users\sheik\OneDrive\Desktop\New folder>
PS C:\Users\sheik\OneDrive\Desktop\New folder>  c:; cd 'c:\Users\shei
InExceptionMessages' '-cp' 'C:\Users\sheik\AppData\Roaming\Code\User\
Model of the car: Audi
Year of the car: 2025
Price of the car: Rs.1500000.0
PS C:\Users\sheik\OneDrive\Desktop\New folder>
```

ii)

Name: SHEIKH WASIMUDDIN
Roll No: IOT-73
Branch: CSE(IOT)

animal.java

animal.java > Language Support for Java(TM) by Red Hat > animal >

```java
//SHEIKH WASIMUDDIN 23071044 CSEIOT-73
public class animal {
    private String name;
    private int age;
    private double weight;
    public void setName(String name) {
        this.name = name;
    }
    public void setAge(int age) {
        this.age = age;
    }
    public void setWeight(double weight) {
        this.weight = weight;
    }
    public String getName() {
        return name;
    }
```

PROBLEMS OUTPUT TERMINAL DEBUG CONSOLE PORTS

```
PS C:\Users\sheik\OneDrive\Desktop\New folder>  & 'C:\Program
aming\Code\User\workspaceStorage\fa87ad616b65db608eedb6800adf
Name of Animal is: Cow
Age of Animal is: 15
Weight of Animal is: 160.0 Kgs
PS C:\Users\sheik\OneDrive\Desktop\New folder>
```

Conclusion	Create a class with using new object for various method executed successfully.
Name Of Faculty:	Prof. Akhil Jajulwar