

Ctrl K

**Documentation**

Components


Templates


Screencasts


Playground


Resources


Community

## Getting Started

Installation

Editor Setup

Using with Preprocessors

Optimizing for Production

command to generate both  
`tailwind.config.js` and  
`postcss.config.js`.

### 3 Configure your template paths

Add the paths to all of your template files in  
your `tailwind.config.js` file.

```
> npx tailwindcss init -p
```

tailwind.config.js

```
module.exports = {
  content: [
    './src/**/*.js', './src/**/*.ts', './src/**/*.tsx',
  ],
  theme: {
    extend: {},
  },
  plugins: [],
}
```

index.css

```
@tailwind base;
```

### 4 Add the Tailwind directives to your CSS

Add the `@tailwind` directives for each of  
Tailwind's layers to your `./src/index.css`  
file.

FileEditSelectionViewGoRunTerminalHelp

tailwind.config.js - ckryptonft - Visual Studio Code

EXPLORER

CKRYPTONFT

.git

client

node\_modules

src

-p

package-lock.json

package.json

postcss.config.js

tailwind.config.js

vite.config.js

smart\_contract

tailwind.config.js U

client > tailwind.config.js > ...

1 module.exports = {  
2 content: [  
3 "./src/\*\*/\*.js,jsx,ts,tsx",  
4 ],  
5 theme: {  
6 extend: {},  
7 },  
8 plugins: [],  
9 }

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PS C:\Users\CS\OneDrive\Desktop\ckryptonft\client> npx tailwindcss init -p  
npm WARN config global '--global', '--local' are deprecated. Use '--location=global' instead.  
  
Created Tailwind CSS config file: tailwind.config.js  
Created PostCSS config file: postcss.config.js  
PS C:\Users\CS\OneDrive\Desktop\ckryptonft\client>

+ v ^ x

> powershell

> powershell

main\*

0 0

Ln 9, Col 2

Spaces: 2

UTF-8

LF

Babel JavaScript

Prettier

Quick search... Ctrl K

 Documentation

 Components

 Templates

 Screencasts

 Playground

 Resources

 Community

## Getting Started

Installation

Editor Setup

Using with Preprocessors

Optimizing for Production

4 **Add the Tailwind directives to your CSS**

Add the `@tailwind` directives for each of Tailwind's layers to your `./src/index.css` file.

5 **Start your build process**

Run your build process with `npm run start`.

6 **Start using Tailwind in your project**

Start using Tailwind's utility classes to style your content.

index.css

```
@tailwind base;
@tailwind components;
@tailwind utilities;
```

Terminal

```
> npm run start
```

App.js

```
export default function App() {
  return (
    <h1 className="text-3xl font-bold underline">
      Hello world!
    </h1>
  )
}
```



FileEditSelectionViewGoRunTerminalHelp

index.css - ckryptonft - Visual Studio Code

EXPLORER

CKRYPTONFT

.git

client

node\_modules

src

.gitignore

App.css

App.jsx

favicon.svg

index.css

index.html

logo.svg

main.jsx

-p

package-lock.json

package.json

postcss.config.js

tailwind.config.js

vite.config.js

smart\_contract

OUTLINE

TIMELINE

tailwind.config.js

index.css

client > src > index.css

1

@tailwind base;

2

@tailwind components;

3

@tailwind utilities;

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PS C:\Users\CS\OneDrive\Desktop\ckryptonft\client> npx tailwindcss init -p

npm WARN config global '--global', '--local' are deprecated. Use '--location=global' instead.

Created Tailwind CSS config file: tailwind.config.js

Created PostCSS config file: postcss.config.js

PS C:\Users\CS\OneDrive\Desktop\ckryptonft\client>

+ ^ ^ x

> powershell

> powershell

main\*

0 0

Ln 3, Col 21

Spaces: 2

UTF-8

LF

PostCSS

Prettier

Quick search... Ctrl K

 Documentation

 Components

 Templates

 Screencasts

 Playground

 Resources

 Community

## Getting Started

Installation

Editor Setup

Using with Preprocessors

Optimizing for Production

### 5 Start your build process

Run your build process with ``npm run start``.

### 6 Start using Tailwind in your project

Start using Tailwind's utility classes to style your content.

Terminal

```
> npm run start
```

App.js

```
export default function App() {  
  return (  
    <h1 className="text-3xl font-bold underline">  
      Hello world!  
    </h1>  
  )  
}
```

FileEditSelectionViewGoRunTerminalHelp

App.jsx - ckryptonft - Visual Studio Code

EXPLORER

CKRYPTONFT

.git

client

node\_modules

src

.gitignore

App.css

App.jsx

favicon.svg

index.css

index.html

logo.svg

main.jsx

-p

package-lock.json

package.json

postcss.config.js

tailwind.config.js

vite.config.js

smart\_contract

OUTLINE

TIMELINE

tailwind.config.js U

index.css M

App.jsx X

client > src > App.jsx > ...

1

2

3

4

5

6

7

8

9

10

11

12

13

const App =() => {

return (

<div className="App">

<h1 className="text-3xl font-bold underline">

Hello world!

</h1>

</div>

)

}

export default App

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PS C:\Users\CS\OneDrive\Desktop\ckryptonft\client> npx tailwindcss init -p

npm WARN config global '--global', '--local' are deprecated. Use '--location=global' instead.

Created Tailwind CSS config file: tailwind.config.js

Created PostCSS config file: postcss.config.js

PS C:\Users\CS\OneDrive\Desktop\ckryptonft\client>

+ v ^ x

> powershell

> powershell

Ln 13, Col 1


Spaces: 2

UTF-8

LF

{ } Babel JavaScript

✓ Prettier



Navbar

Welcome

Services

Transactions

Navbar





ckryptonft  
*Send Crypto across the world*

Market

Exchange

Tutorials

Wallets

Welcome

Services

Transactions

Navbar



Market

Exchange

Tutorials

Wallets

Login

Welcome

Services

Transactions

Navbar