


[⇒ Show Sidebar](#)[Fork on Github](#)

Cufflinks in Python

An overview of cufflinks, a library for easy interactive Pandas charting with Plotly.

Cufflinks binds [Plotly](#) directly to [pandas](#) dataframes.


[⇒ Show Sidebar](#)[Fork on Github](#)**Out[1]:**[EDIT CHART](#)

Packages

Run ! `pip install cufflinks --upgrade` to install Cufflinks. In addition to [Plotly](#), [pandas](#) and Cufflinks, this tutorial will also use [NumPy](#).



⇒ Show Sidebar

 Fork on Github

```
import numpy as np
print cf.__version__
```


0.8.2

Dataframes


With Plotly's Python library, you can describe figures with DataFrame's series and index's

[⇒ Show Sidebar](#)[Fork on Github](#)


```
'x': df.index,  
'y': df[col],  
'name': col  
} for col in df.columns], filename='cufflinks/simple-line')
```

Out[3]:[EDIT CHART](#)

But with cufflinks, you can plot them directly

[⇒ Show Sidebar](#)[Fork on Github](#)[EDIT CHART](#)

Almost every chart that you make in `cufflinks` will be created with just one line of code.

[⇒ Show Sidebar](#)[Fork on Github](#)**Out[6]:**[EDIT CHART](#)

Charts created with cufflinks are synced with your online Plotly account. You'll need to [configure your credentials](#) to get started. cufflinks can also be configured to work offline in IPython notebooks with [Plotly Offline](#). To get started with Plotly Offline, [download a trial library](#) and run `cf.go_offline()`.

In [14]:

```
cf.go_online() # switch back to online mode, where graphs are saved on your  
online plotly account
```

[⇒ Show Sidebar](#)[Fork on Github](#)

In [15]:

```
df.a.iplot(kind='histogram', world_readable=False)
```

Out[15]:

4 4

Plot twist!

There's nothing here...

You might need to [sign in](#) to see this plot.

[Chart Studio](#) is free to view plots that have been shared with you.

Only *you* (the creator) will be able to see this chart, or change the global, default settings with `cf.set_config_file`

In [16]:

```
cf.set_config_file(offline=False, world_readable=True, theme='ggplot')
```


[⇒ Show Sidebar](#)[Fork on Github](#)

LINE CHARTS


In [17]:

```
df = pd.DataFrame(np.random.randn(1000, 2), columns=['A', 'B']).cumsum()  
df.iplot(filename='cufflinks/line-example')
```

Out[17]:

[EDIT CHART](#)

Plot one column vs another with x and y keywords

[⇒ Show Sidebar](#)[Fork on Github](#)[EDIT CHART](#)

Bar Charts

Download some civic data. A time series log of the 311 complaints in NYC.

In []:

```
df = pd.read_csv('https://raw.githubusercontent.com/plotly/widgets/master/ip  
ython-examples/311_150k.csv', parse_dates=True, index_col=1)  
df.head(3)
```


[⇒ Show Sidebar](#)[Fork on Github](#)

Plot a series directly

In [18]:


```
series.iplot(kind='bar', yTitle='Number of Complaints', title='NYC 311 Compl  
aints',  
             filename='cufflinks/categorical-bar-chart')
```

Out[18]:



[⇒ Show Sidebar](#)[Fork on Github](#)

```
df = pd.DataFrame(np.random.rand(10, 4), columns=['A', 'B', 'C', 'D'])  
row = df.ix[5]  
row.iplot(kind='bar', filename='cufflinks/bar-chart-row')
```


Out[19]:[EDIT CHART](#)

Call `iplot(kind='bar')` on a dataframe to produce a grouped bar chart



Show Sidebar

Fork on Github




EDIT CHART




⇒ Show Sidebar

Fork on Github


Out[21]:



EDIT CHART

[⇒ Show Sidebar](#)[Fork on Github](#)

Make your bar charts horizontal with `kind='barh'`


[⇒ Show Sidebar](#)[Fork on Github](#)[EDIT CHART](#)

Themes

cufflinks ships with a few themes. View available themes with `cf.getThemes`, apply them with `cf.set_config_file`



⇒ Show Sidebar

 Fork on Github

```
['pearl', 'white', 'ggplot', 'solar', 'space']
```


In [24]:

```
cf.set_config_file(theme='pearl')
```

Histograms

[⇒ Show Sidebar](#)[Fork on Github](#)

```
df.iplot(kind='histogram', filename='cufflinks/basic-histogram')
```

Out[4]:[EDIT CHART](#)


[⇒ Show Sidebar](#)[Fork on Github](#)

- `bins(int)`
- `histnorm('' | 'percent' | 'probability' | 'density' | 'probability density')`
- `histfunc('count' | 'sum' | 'avg' | 'min' | 'max')`

In [27]:

```
df.iplot(kind='histogram', barmode='stack', bins=100, histnorm='probability',  
         , filename='cufflinks/customized-histogram')
```

Out[27]:


[EDIT CHART](#)

[⇒ Show Sidebar](#)[Fork on Github](#)


In [28]:

```
df.iplot(kind='histogram', subplots=True, shape=(3, 1), filename='cufflinks/  
histogram-subplots')
```

Out[28]:

[EDIT CHART](#)

Box Plots

[⇒ Show Sidebar](#)[Fork on Github](#)**Out[29]:**[EDIT CHART](#)

Area Charts

To produce stacked area plot, each column must be either all positive or all negative values.


When input data contains NaN, it will be automatically filled by 0. If you want to drop or fill by different values, use `dataframe.dropna()` or `dataframe.fillna()` before calling `plot`.

[⇒ Show Sidebar](#)[Fork on Github](#)


In [31]:

```
df.iplot(kind='area', fill=True, filename='cufflinks/stacked-area')
```

Out[31]:

[EDIT CHART](#)

For non-stacked area charts, set kind=scatter with fill=True

[⇒ Show Sidebar](#)[Fork on Github](#)[EDIT CHART](#)


Scatter Plot

Set x and y as column names. If x isn't supplied, `df.index` will be used.

[⇒ Show Sidebar](#)[Fork on Github](#)

```
df2007 = df[df.year==2007]  
df1952 = df[df.year==1952]
```

```
df2007.iplot(kind='scatter', mode='markers', x='gdpPercap', y='lifeExp', filename='cufflinks/simple-scatter')
```


Out[5]:[EDIT CHART](#)

Plotting multiple column scatter plots isn't as easy with cufflinks. Here is an example with Plotly's native syntax


[⇒ Show Sidebar](#)
[Fork on Github](#)

```
'mode': 'markers', 'name': '2007'},
    {'x': df1952.gdpPercap, 'y': df1952.lifeExp, 'text': df1952.country,
 'mode': 'markers', 'name': '1952'}
],
'layout': {
    'xaxis': {'title': 'GDP per Capita', 'type': 'log'},
    'yaxis': {'title': "Life Expectancy"}
}
}
py.iplot(fig, filename='cufflinks/multiple-scatter')
```

Out[35]:




Grouping isn't as easy either. But, with Plotly's native syntax:


[⇒ Show Sidebar](#)
[Fork on Github](#)

```
{
    'x': df[df['year']==year]['gdpPercap'],
    'y': df[df['year']==year]['lifeExp'],
    'name': year, 'mode': 'markers',
} for year in [1952, 1982, 2007]
],
'layout': {
    'xaxis': {'title': 'GDP per Capita', 'type': 'log'},
    'yaxis': {'title': "Life Expectancy"}
}
}, filename='cufflinks/scatter-group-by')
```

Out[36]:




[⇒ Show Sidebar](#)[Fork on Github](#)

In [37]:

```
df2007.iplot(kind='bubble', x='gdpPercap', y='lifeExp', size='pop', text='country',  
             xTitle='GDP per Capita', yTitle='Life Expectancy',  
             filename='cufflinks/simple-bubble-chart')
```

Out[37]:




Subplots

[⇒ Show Sidebar](#)[Fork on Github](#)





In [38]:

```
df=cf.datagen.lines(4)
df.iplot(subplots=True, shape=(4,1), shared_xaxes=True, fill=True, filename=
'cufflinks/simple-subplots')
```


Out[38]:

[EDIT CHART](#)


Add subplot titles with `subplot_titles` as a list of titles or `True` to use column names.

[⇒ Show Sidebar](#)[Fork on Github](#)[EDIT CHART](#)

Scatter matrix

[⇒ Show Sidebar](#)[Fork on Github](#)**Out[40]:**[EDIT CHART](#)

Heatmaps


[⇒ Show Sidebar](#)[Fork on Github](#)**Out[41]:**[EDIT CHART](#)

Lines and Shaded Areas


Use `hline` and `vline` for horizontal and vertical lines.

In [42]:


```
df=cf.datagen.lines(3,columns=['a','b','c'])
```

[⇒ Show Sidebar](#)[Fork on Github](#)[EDIT CHART](#)

Draw shaded regions with `hspan`

[⇒ Show Sidebar](#)[Fork on Github](#)[EDIT CHART](#)

Extra parameters can be passed in the form of dictionaries, width, fill, color, fillcolor, opacity

[⇒ Show Sidebar](#)[Fork on Github](#)**Out[45]:**[EDIT CHART](#)



⇒ Show Sidebar

🔗 Fork on Github

cufflinks is designed for simple one-line charting with Pandas and Plotly. All of the Plotly chart attributes are not directly assignable in the `df.iplot` call signature.

To update attributes of a cufflinks chart that aren't available, first convert it to a figure (`asFigure=True`), then tweak it, then plot it with `plotly.plotly.iplot`.

Here is an example of a simple plotly figure. You can find more examples in [our online python documentation](#).


[⇒ Show Sidebar](#)[Fork on Github](#)

```
Bar(**{
    'x': [1, 2, 3],
    'y': [3, 1, 5],
    'name': 'first trace',
    'type': 'bar'
}),
Bar(**{
    'x': [1, 2, 3],
    'y': [4, 3, 6],
    'name': 'second trace',
    'type': 'bar'
})
],
'layout': Layout(**{
    'title': 'simple example'
})
}, filename='cufflinks/simple-plotly-example')
```



⇒ Show Sidebar

Fork on Github




EDIT CHART

cufflinks generates these figure's that describe plotly graphs. For example, this graph:



⇒ Show Sidebar

Fork on Github



EDIT CHART

has this description:


[⇒ Show Sidebar](#)[Fork on Github](#)

```
Figure(  
    data=Data([  
        Scatter(  
            x=['2015-01-01', '2015-01-02', '2015-01-03', '2015-01-04', '..'  
        ],  
            y=array([ 5.35393544e-01, -3.51020567e-01, -1.34207933e+00,  
                ...  
            ],  
            mode='lines',  
            name='a',  
            line=Line(  
                color='rgba(255, 153, 51, 1.0)',  
                width='1.3'  
            )  
        )  
    ])
```

So, if you want to edit any attribute of a Plotly graph from cufflinks, first convert it to a figure and then edit the figure objects. Let's add a yaxis title, tick suffixes, and new legend names to this example:

[⇒ Show Sidebar](#)[Fork on Github](#)

```
py.iplot.figure, filename='cufflinks/customized-chart')
```

Out[50]:[EDIT CHART](#)

See more examples of Plotly graphs or view the entire reference of valid attributes

Cufflinks Reference

Cufflinks is [open source on github!](#)


[⇒ Show Sidebar](#)
[Fork on Github](#)

Help on method `_iplot` in module `cufflinks.plotlytools`:

```
_iplot(self, data=None, layout=None, filename='', world_readable=None, kind='scatter', title='', xTitle='', yTitle='', zTitle='', theme=None, colors=None, colorscale=None, fill=False, width=None, mode='lines', symbol='dot', size=12, barmode='', sortbars=False, bargap=None, bargroupgap=None, bins=None, histnorm='', histfunc='count', orientation='v', boxpoints=False, annotations=None, keys=False, bestfit=False, bestfit_colors=None, categories='', x='', y='', z='', text='', gridcolor=None, zerolinecolor=None, margin=None, subplots=False, shape=None, asFrame=False, asDates=False, asFigure=False, asImage=False, dimensions=(1116, 587), asPlot=False, asUrl=False, online=None, **kwargs) method of pandas.core.frame.DataFrame instance
```

Returns a plotly chart either as inline chart, image of Figure object

Still need help?

Contact Us

community.plot.ly

support.plot.ly

github.com/plotly

For guaranteed 24 hour response
turnarounds, upgrade to a Developer
Support Plan.

[⇒ Show Sidebar](#)[Fork on Github](#)

[Dash DAQ](#)
[Dash Deployment Server](#)

[Customer Contact](#)
[#plotlylife](#)
[Twitter](#)
[GitHub](#)

[Community Support](#)
[Documentation](#)

GRAPHING LIBRARIES

[Dash](#)
[Plotly.js](#)
[Plotly.py](#)
[Plotly.R](#)

EMBEDDED BI/OEM


[Chart Studio](#)
[Dashboards](#)

JOIN THE DASH CLUB

Dash Club is a no-fluff, twice-a-month email with links and notes on the latest Dash developments and community happenings.




 Show Sidebar

 Fork on Github




 Show Sidebar

 Fork on Github




 Show Sidebar

 Fork on Github




 Show Sidebar

 Fork on Github




 Show Sidebar

 Fork on Github




 Show Sidebar

 Fork on Github



 Show Sidebar

 Fork on Github
