


StorageResource Class

Methods for Finding and Storing

Finding and Processing Data

- You've seen code for finding start and stop codons: simple extension to finding genes
 - What if genes must have 50+ nucleotides?
 - What if genes must have CG content $> 60\%$?
 - How do we process all the genes



Finding and Processing Data

- You've seen code for finding start and stop codons: simple extension to finding genes
 - What if genes must have 50+ nucleotides?
 - What if genes must have CG content $> 60\%$?
 - How do we process all the genes
- Simple extension to web crawling
 - How do we find links in a web page
 - Search for href=".." instead of ATG..TAA

Finding All Genes

- Printing all genes found in DNA
 - **findStopIndex()** discussed in earlier lesson

```
public void printAll(String dna){  
    int start = 0;  
    while (true){  
        int tag = dna.indexOf("atg",start);  
        if (tag == -1) {  
            break;  
        }  
        int end = findStopIndex(dna,tag+3);  
  
        if (end != dna.length()) {  
            System.out.println(dna.substring(tag,end+3));  
            start = end+3;  
        }  
        else {  
            start = start + 3;  
        }  
    }  
}
```


Finding All Genes

- Printing all genes found in DNA
 - **findStopIndex()** discussed in earlier lesson

```
public void printAll(String dna){  
    int tag = dna.indexOf("atg", start);  
    if (tag == -1) {  
        break;  
    }  
    if (end != dna.length()) {  
        System.out.println(dna.substring(tag, end+3));  
        start = end+3;  
    }  
    else {  
        start = start + 3;  
    }  
}
```

Finding All Genes

- Printing all genes found in DNA
 - **findStopIndex()** discussed in earlier lesson

```
public void printAll(String dna){  
    int start = 0;  
    while (true){  
        int tag = dna.indexOf("atg",start);  
        if (tag == -1) {  
            int end = findStopIndex(dna,tag+3);  
  
            if (end != dna.length()) {  
                System.out.println(dna.substring(tag,end+3));  
                start = end+3;  
            }  
            else {  
                start = start + 3;  
            }  
        }  
    }  
}
```

Storing Strings: Post-Processing

- Modifying the gene finding/printing code
 - To find/print genes that are long
 - To find/print genes that are good
 - Combines finding and printing, separating hard
- StorageResource class helps here
 - Can add strings with `.add(str)`
 - Can ask for count of added with `.size()`
 - Can use as iterable with `.data()`

Post-Processing Example

- If we had stored all genes in a StorageResource object we could ...
 - Print those long enough

```
public void printGenes(StorageResource sr){  
    for(String gene : sr.data()){  
        if (gene.length() > 60) {  
            System.out.println(gene.length()+"\t"+gene);  
        }  
    }  
}
```


Post-Processing Example

- If we had stored all genes in a StorageResource object we could ...
 - Print those long enough
 - Print those rich enough in CG content

```
public void printGenes(StorageResource sr){  
    for(String gene : sr.data()){  
        if (cgRatio(gene) > 0.35) {  
            System.out.println(gene.length()+"\t"+gene);  
        }  
    }  
}
```

Adding to a StorageResource

- Adding words to StorageResource object
 - Simply call `.add()` to add String to collection
 - Suppose tracking only words not seen before?

```
public StorageResource getWords(){  
    FileResource fr = new FileResource("/data/confucius.txt");  
    StorageResource store = new StorageResource();  
    for(String w : fr.words()){  
        if (! store.contains(w)){  
            store.add(w);  
        }  
    }  
    return store;  
}
```