

Discovery Executive Summary

Project: discovery-15july-01 · Generated: 15/07/2026, 19:47:53

EXECUTIVE SUMMARY

This report consolidates the overall ratings, key findings, and recommended actions from the 4 discovery analyses run across this codebase (frontend and backend). Each section below reproduces that analysis's executive view; full evidence and diagrams live in the individual reports.

Portfolio Overview

#	Analysis	Overall Rating	Hotspot Score
1	Architecture & Design Analysis	HIGH RISK	—
2	Code Quality & Complexity Analysis	HIGH RISK	45 / 100 — Moderate
3	Frontend Modernization Analysis	HIGH RISK	—
4	Backend Modernization Analysis	HIGH RISK	—

1. Architecture & Design Analysis

OVERALL CODEBASE RATING — ARCHITECTURE & DESIGN

High Risk

Driven by High-Risk Missing Service Layer (H2), Missing Repository Pattern (H3), Domain Boundary Violations (H8), Shared Database Coupling (H9), and Parallel API Runtimes (H10).

EXECUTIVE SUMMARY

Analysis covered **backend** (15 PHP application files: 6 API controllers, 4 Eloquent models, 2 injectable services, 0 repositories), **frontend** (15 TS/TSX/JSX source files across pages, components, hooks, and store), and **dev-api** (6 JS files mirroring 18 Laravel routes) from `shende-shweta/FSDKC@main` via GitHub REST API (tree + raw content fetch). The Klearcom monorepo runs three parallel runtimes with no repository layer and thin service coverage. Backend layering is the dominant risk: **25 controller-to-model Eloquent access points** bypass application services, **71 persistence access points** occur outside any repository abstraction (32 Eloquent + 39 MongoDB/in-memory store delegations across Laravel and dev-api), and **8 cross-domain query sites** in `DashboardController::kpis` couple Discovery and Connect models without an anti-corruption layer. Four of five MariaDB tables lack domain-exclusive ownership (**80% shared-table coupling**), and Laravel + `dev-api` duplicate reachability KPI math, IVR `buildTree`, and dashboard aggregation in

parallel. Frontend architecture is comparatively healthy (avg **86 LOC** per view component, centralized `api/client.ts`, max prop-drilling depth **2**), but one legacy class component lacks lifecycle cleanup. Overall verdict: **High Risk**, driven by H2, H3, H8, H9, and H10.

1.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	Fat Controllers	Avg LOC per controller	<150	150–300	>300	74 LOC avg	GOOD
H2	Missing Service Layer	Controllers accessing repos/models	<10	10–20	>20	25 access points	HIGH RISK
H3	Missing Repository Pattern	Direct DB access points	<10	10–20	>20	71 access points	HIGH RISK
H4	Circular Dependencies	Dependency cycles	0	1–3	>3	0	GOOD
H5	Shared Utility Abuse	Utility files w/ business logic	0	1–5	>5	4 (<code>extract</code> sites)	MODERATE
H6	Direct SQL in Controllers	ORM compliance %	>90%	60–90%	<60%	100% ORM	GOOD
H7	God Classes	Classes >1000 LOC	0	1–3	>3	0 (max 276 LOC)	GOOD
H8	Domain Boundary Violations	Cross-domain access points	0	1–5	>5	8	HIGH RISK
H9	Shared Database Coupling	Tables shared across domains	<10%	10–30%	>30%	80% (4/5 tables)	HIGH RISK
F1	Business Logic in Components	Avg LOC per component	<150	150–300	>300	86 LOC avg	GOOD
F2	Missing Frontend Service/Data Layer	Components w/ inline API calls	<10	10–20	>20	0 inline fetch/axios	GOOD
F3	God / Oversized Components	Components >400 LOC	0	1–3	>3	0	GOOD
F4	Prop Drilling / Global State Abuse	Max prop-drilling depth	≤2	3–4	>4	2 levels	GOOD

F5	Legacy / Inconsistent Component Patterns	Legacy-pattern components	0	1–10	>10	1 class component	MODERATE
H10	Parallel API Runtimes (additional)	Duplicate API implementations across runtimes	0	1	≥2	2 (Laravel + dev-api)	HIGH RISK

No additional hotspots beyond the standard set were observed beyond H10 (Parallel API Runtimes).

1.4 Actions Required

Hotspot	Action	Rating	Priority
H2 — Missing Service Layer	Introduce <code>ConnectMonitorService</code> , <code>DiscoveryJobService</code> , and <code>DashboardKpiService</code> ; move all 25 controller model-access points into application services with constructor DI.	HIGH RISK	CRITICAL
H3 — Missing Repository Pattern	Create repository interfaces for all 4 Eloquent models and 3 MongoDB collections; route 71 persistence access points through injected repository implementations.	HIGH RISK	CRITICAL
H5 — Shared Utility Abuse	Replace <code>extract(\$filters)</code> with typed DTO mappers; extract shared <code>IvrTreeBuilder</code> from duplicated <code>buildTree</code> in <code>LegacyReportController</code> , <code>DiscoveryController</code> , and <code>dev-api/src/store.js</code> .	MODERATE	MEDIUM
H8 — Domain Boundary Violations	Split cross-domain access in <code>DashboardController</code> and <code>LegacyReportController</code> ; enforce Discovery/Connect bounded contexts with published read APIs.	HIGH RISK	CRITICAL
H9 — Shared Database Coupling	Assign table ownership per domain in <code>docker/mariadb/init.sql</code> ; introduce per-domain migration files and integration views for cross-domain KPIs.	HIGH RISK	CRITICAL
H10 — Parallel API Runtimes	Deprecate <code>dev-api</code> duplicate runtime; consolidate to Laravel API with Docker Compose for local dev, or generate dev-api from OpenAPI spec.	HIGH RISK	CRITICAL
F5 — Legacy Component Patterns	Rewrite <code>LegacyMonitorPoller.jsx</code> as function component with <code>useEffect</code> cleanup; add Error Boundary around <code>LegacyDashboardWidget</code> .	MODERATE	MEDIUM

1.5 Expected Outcomes

- **Testable business logic:** Application services and repositories enable unit tests without HTTP or database bootstrapping, cutting test setup time for Connect reachability and Discovery tree workflows.
- **Independent domain evolution:** Bounded contexts with owned schemas let Discovery and Connect teams ship schema changes without cross-module regressions in dashboard KPIs.
- **Single source of truth:** Eliminating the parallel `dev-api` runtime removes behavioral drift between local development and production Laravel deployments.

- **Reduced change amplification:** Centralizing reachability calculation and IVR tree building in one service eliminates the current four-way duplication across controllers, services, and Node handlers.
- **Frontend stability:** Migrating the legacy class component and adding Error Boundaries prevents interval leaks and uncaught render errors during SPA navigation.

2. Code Quality & Complexity Analysis

OVERALL CODEBASE RATING — CODE QUALITY & COMPLEXITY

High Risk

Driven by High-Risk cyclomatic complexity in frontend page components (H1), oversized `ConnectPage` function (H3), cross-runtime business-logic duplication (H4), parallel Laravel/dev-api workflow copies (H9), and PHP `extract()` dynamic variables (H11).

EXECUTIVE SUMMARY

Analysis covered **backend** (16 PHP application files, 807 SLOC), **frontend** (14 TS/TSX/JSX files, 874 SLOC), and **dev-api** (6 JS files, 720 SLOC) — **36 files / 2,401 SLOC** total — from `shende-shweta/FSDKC@main` via GitHub REST API (public tree + raw content + Commits API). No cyclomatic-complexity linter (`eslint-plugin-complexity`, `phpmd`, Sonar) is configured; metrics were derived by manual branch/loop counting on fetched source. The dominant risks are **frontend page-level complexity** (`ConnectPage.tsx` cyclomatic complexity **44**, **201 LOC** default-export function), **cross-runtime business-logic duplication** (~**13.2%** of codebase duplicated between Laravel and `dev-api` for KPI aggregation, realtime test orchestration, and IVR `buildTree`), and **three** `extract()` **dynamic-variable sites** in legacy PHP code. No files exceed 1,000 LOC (largest: `dev-api/src/server.js` at **224 SLOC**). Git history is shallow (**3 commits**, single author `ksabai-gl` since June 2026), so churn and ownership signals are healthy but low-confidence. Overall verdict: **High Risk**, driven by H1, H3, H4, H9, and H11.

2.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	High Cyclomatic Complexity	Max complexity per method	<10	10–20	>20	44 (<code>ConnectPage</code>)	HIGH RISK
H2	Large Classes	Largest class LOC	<300	300–1000	>1000	224 LOC (<code>dev-api/src/server.js</code>)	GOOD
H3	Large Functions	Largest function LOC	<50	50–200	>200	201 LOC (<code>ConnectPage</code>)	HIGH RISK

H4	Business Logic Duplication	Duplicated business logic %	<5%	5–10%	>10%	13.2% (317 / 2,401 LOC)	HIGH R
H5	Duplicate Code (general)	Overall duplicate code %	<5%	5–10%	>10%	8.6% (206 / 2,401 LOC)	MODER
H6	High Churn Areas	Monthly changes (top files)	<5	5–10	>10	2 changes/mo (top app files)	GOOD
H7	Defect-Prone Files	Fix commits (hottest file)	1–3	4–5	>5	1 fix commit (<code>frontend/src/App.tsx</code>)	GOOD
H8	Ownership Issues	Top-author ownership %	>80%	60–80%	<60%	100% (1 author / 3 commits)	GOOD
H9	Parallel Runtime Duplication (additional)	Duplicated workflow LOC across Laravel + dev-api / backend LOC	<5%	5–15%	>15%	20.8% (317 / 1,527 backend+dev-api LOC)	HIGH R
H10	God Page Components (additional)	Largest page component LOC (UI + data + realtime)	<150	150–300	>300	208 LOC (<code>ConnectPage.tsx</code>)	MODER
H11	PHP extract() Dynamic Variables (additional)	<code>extract()</code> call sites in application code	0	1–2	>2	3 (<code>LegacyReportController</code> , <code>LegacyDataMapper</code> ×2)	HIGH R

Hotspot Score breakdown

Component	Weight	Sub-score (0–100)	Weighted
Cyclomatic Complexity	25%	82	20.5
Code Churn	25%	10	2.5
Defect Density	20%	15	3.0
Class/Function Size	15%	75	11.25
Business Logic Duplication	10%	78	7.8
Developer Ownership Risk	5%	5	0.25
Hotspot Score	100%		45 / 100

2.5 Actions Required

Hotspot	Action	Rating	Priority
H1 — High Cyclomatic Complexity	Extract <code>useModulePageQueries</code> hook; split <code>ConnectPage</code> and <code>DiscoveryPage</code> into ≤ 80 LOC sub-components; enable ESLint complexity rule (max 15) on <code>frontend/src/pages/</code> .	HIGH RISK	CRITICAL
H3 — Large Functions	Decompose <code>ConnectPage</code> (201 LOC) into <code>useConnectPageState.ts</code> + 3 presentational components; apply same pattern to <code>DiscoveryPage</code> (154 LOC).	HIGH RISK	HIGH
H4 — Business Logic Duplication	Create <code>DashboardKpiCalculator</code> and shared test-step definitions in Laravel; remove duplicated KPI and realtime blocks from <code>dev-api/src/server.js</code> and <code>dev-api/src/realtime.js</code> .	HIGH RISK	CRITICAL
H5 — Duplicate Code	Extract <code>TreeBuilder</code> utility from four <code>buildTree</code> copies; add <code>jscpd</code> / <code>phpcpd</code> CI gate at 5% threshold.	MODERATE	MEDIUM
H9 — Parallel Runtime Duplication	Deprecate <code>dev-api</code> runtime or auto-generate from Laravel OpenAPI; add contract tests until removal.	HIGH RISK	CRITICAL
H10 — God Page Components	Introduce <code>ModulePageLayout</code> , <code>EntityForm</code> , and <code>TestSessionPanel</code> shared components; cap page files at 120 LOC.	MODERATE	MEDIUM
H11 — PHP <code>extract()</code> Dynamic Variables	Replace <code>extract(\$filters)</code> with typed <code>CarrierSummaryFilter</code> DTO; refactor <code>LegacyDataMapper</code> to explicit key access; add PHPStan <code>extract()</code> ban.	HIGH RISK	HIGH

2.6 Expected Outcomes

- **Lower defect rate on UI changes:** Splitting `ConnectPage` / `DiscoveryPage` and extracting shared hooks reduces cyclomatic complexity from 44 to a testable target of <15 per function.
- **Single source of truth for KPIs and test pipelines:** Consolidating dashboard and realtime logic in Laravel eliminates the $\sim 13\%$ duplicated business-rule surface between production and `dev-api`.
- **Safer refactors:** Extracting `TreeBuilder` and domain services lets IVR tree and reachability changes propagate from one module instead of four `buildTree` copies.
- **Eliminated dynamic-variable risk:** Replacing `extract()` with typed DTOs enables PHPStan static analysis and prevents variable-injection bugs in legacy report endpoints.
- **Faster reviews:** Smaller page components and a complexity lint gate keep new features from re-expanding god components.

3. Frontend Modernization Analysis

OVERALL CODEBASE RATING — FRONTEND MODERNIZATION

High Risk

Driven by High-Risk UI Component Duplication (H1), Global State Dependencies (H4), Inline Styles Without Design Tokens (H6), and Missing Accessibility Roles (H7).

EXECUTIVE SUMMARY

Analysis covered **14 frontend source files** (8 view components across `pages/` and `components/`) from `shende-shweta/FSDKC@main` via GitHub REST API (tree + raw content fetch). The Klearcom SPA is predominantly modern — function components, TanStack React Query v5, Zustand v5, and React Router v7 — with a centralized `api/client.ts` and reusable `useRealtimeTest` hook. However, `ConnectPage.tsx` and `DiscoveryPage.tsx` duplicate an identical workbench shell (entity form, live feed, two-column grid, transcript panel), inflating UI duplication to **25%**. Six of eight view components depend on shared global state (Zustand, React Query cache, or the singleton `api` client), and **30 inline `style={{}}` occurrences** bypass the CSS token system in `index.css`. One legacy class component (`LegacyMonitorPoller.jsx`) lacks `componentWillUnmount` cleanup and leaks intervals; two orphan legacy modules coexist with the React Query stack. Zero `aria-*` / `role` attributes were found across all view components. Overall verdict: **High Risk**, driven by H1 (UI duplication), H4 (global state coupling), H6 (inline styles), and H7 (missing accessibility).

3.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	UI Component Duplication	Duplicate components %	<5%	5–10%	>10%	25.0% (2/8)	HIGH RISK
H2	Legacy Class-Based Components	Modern component adoption %	>90%	70–90%	<70%	87.5% (7/8)	MODERATE
H3	Massive Components	Largest component LOC	<200	200–500	>500	222 (<code>ConnectPage.tsx</code>)	MODERATE
H4	Global State Dependencies	Components reading global state %	<30%	30–60%	>60%	75.0% (6/8)	HIGH RISK
H5	Complex State Management	Max prop-drilling depth	<3	3–5	>5	2 levels	GOOD
H6	Inline Styles / No Design Tokens (additional)	Total <code>style={{}}</code> occurrences (target <10)	<10	10–20	>20	30 across 7 files	HIGH RISK

H7	Missing Accessibility Roles (additional)	Components with <code>aria-*</code> or <code>role</code> (target >80%)	>80%	50–80%	<50%	0% (0/8)	HIGH RISK
----	--	--	------	--------	------	----------	-----------

3.5 Actions Required

Hotspot	Action	Rating	Priority
H1 — UI Component Duplication	Extract <code>DomainWorkbenchPage</code> , <code>EntityFormCard</code> , and <code>TranscriptPanel</code> from <code>ConnectPage.tsx</code> and <code>DiscoveryPage.tsx</code> ; reduce duplicate shell to domain hooks only.	HIGH RISK	CRITICAL
H2 — Legacy Class-Based Components	Convert <code>LegacyMonitorPoller.jsx</code> to <code>useMonitorReachability</code> hook; migrate <code>LegacyDashboardWidget.tsx</code> to React Query or delete both orphan modules.	MODERATE	MEDIUM
H3 — Massive Components	Split <code>ConnectPage.tsx</code> (222 LOC) and <code>DiscoveryPage.tsx</code> (176 LOC) into container hooks + presentational sub-components; target <150 LOC per page.	MODERATE	MEDIUM
H4 — Global State Dependencies	Replace <code>useUiStore</code> selection with URL search params; add <code>frontend/src/api/queryKeys.ts</code> ; scope query invalidation to domain keys.	HIGH RISK	HIGH
H6 — Inline Styles	Add CSS utility classes to <code>index.css</code> ; migrate 30 inline <code>style={{}}</code> occurrences (18 in domain pages) to token-based classes.	HIGH RISK	HIGH
H7 — Missing Accessibility	Add <code>aria-live</code> to <code>LiveTestFeed</code> , keyboard-accessible row selection in domain tables, and <code>htmlFor</code> on form labels.	HIGH RISK	HIGH

3.6 Expected Outcomes

- **Shared component library** eliminates the 25% duplicate page-shell pattern; Connect and Discovery fixes ship once via `DomainWorkbenchPage` and `TranscriptPanel`.
- **Hooks-first migration** of `LegacyMonitorPoller` removes interval leaks and aligns all data access on React Query with testable custom hooks.
- **Scoped state** (URL params + domain query keys) reduces cross-feature invalidation fan-out and makes monitor/job selection shareable via deep links.
- **Design-token consistency** from replacing 30 inline styles lowers theming cost and aligns with the existing `:root` token system in `index.css`.
- **Accessibility baseline** (`aria-live`, keyboard rows, label associations) makes realtime test feeds and data tables operable for keyboard and screen-reader users in an operations-focused product.

Deliverables saved:

- Full report: `target/docs/discovery/03-frontend-modernization.md`

- Pipeline summary: `agent - runs/20260715T193441_nth87z/03-frontend-modernization-summary.md`

4. Backend Modernization Analysis

OVERALL CODEBASE RATING — BACKEND MODERNIZATION

High Risk

Driven by Direct SQL/ORM Outside Data Layer (H3), Missing Service Layer (H5), API Sprawl (H6), Missing API Governance (H7), and Parallel API Runtimes (H8).

EXECUTIVE SUMMARY

Analysis covered **24 controllers/handlers** (6 Laravel API controllers + 18 Express route handlers), **37 REST endpoints**, and **2 injectable service classes** (0 repositories) from `shende-shweta/FSDKC@main` via GitHub REST API (recursive tree + raw content fetch). The Klearcom backend runs two parallel API runtimes: Laravel 12 uses constructor injection for `MongoService` and `RealTimeTestService`, but **25 of 32 Eloquent access points (78%)** remain in controllers with no repository layer, and four controllers embed KPI math, IVR tree building, and reachability calculations inline. Three PHP `extract()` calls — including one on raw `$request->all()` — create untyped variable scope from user input. The Node `dev-api` holds all relational state in a module-level mutable `store` singleton with **18 inline route handlers** mirroring Laravel. No OpenAPI spec, API versioning, or contract tests exist; CI runs PHPUnit and frontend build only. Overall verdict: **High Risk**, driven by data-layer bypass (H3), missing service tier across dual runtimes (H5), API sprawl and zero governance (H6–H7), and parallel API implementations (H8).

4.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	Dynamic Variable Creation	Dynamic-var-from-input occurrences	0	1–10	>10	3 (<code>extract()</code> calls)	MODERATE
H2	Global Mutable State	Globals / mutable static state	0	1–5	>5	2 module-level stores	MODERATE
H3	Direct SQL Outside Data Layer	Data-layer compliance %	>90%	60–90%	<60%	22% (7/32 Eloquent in services)	HIGH RISK
H4	Static / Singleton Abuse	Business-logic static/singleton classes	0	1–5	>5	0	GOOD

H5	Missing Service Layer	Handlers with inline business logic	<10	10–20	>20	22 (4 Laravel controllers + 18 dev-api routes)	HIGH RISK
H6	API Sprawl	Documented & governed endpoints %	>90%	80–90%	<80%	15% single-source (3/20 capabilities); 0% governed	HIGH RISK
H7	Missing API Governance	Governance compliance %	100%	90–99%	<90%	0% (no spec, versioning, or contract tests)	HIGH RISK
H8	Parallel API Runtimes (additional)	Capabilities with duplicate Laravel + dev-api handlers (target 0)	0	1–5	>5	17 duplicated capabilities	HIGH RISK
H9	Missing Input Validation on dev-api (additional)	POST/PUT routes without schema validation (target 0)	0	1–3	>3	4 unvalidated write routes	HIGH RISK

4.5 Actions Required

Hotspot	Action	Rating	Priority
H1 — Dynamic Variable Creation	Replace <code>extract(\$filters)</code> in <code>LegacyReportController</code> with validated request DTO; refactor <code>LegacyDataMapper</code> to explicit field access; add CI ban on <code>extract()</code> .	MODERATE	HIGH
H2 — Global Mutable State	Encapsulate <code>dev-api/src/store.js</code> in an injectable repository; eliminate module-level business mutation or retire dev-api.	MODERATE	MEDIUM
H3 — Direct SQL Outside Data Layer	Create Eloquent repositories for all four models; move 25 controller ORM calls into repositories; target >90% data-layer compliance.	HIGH RISK	CRITICAL
H5 — Missing Service Layer	Add <code>DashboardService</code> , <code>DiscoveryService</code> , <code>ConnectService</code> ; move KPI/tree/reachability logic out of controllers and dev-api routes.	HIGH RISK	CRITICAL
H6 — API Sprawl	Consolidate 17 duplicated capabilities under Laravel; deprecate overlapping dev-api routes; publish canonical endpoint list.	HIGH RISK	HIGH
H7 — Missing API Governance	Author <code>docs/openapi.yaml</code> ; add <code>/api/v1/</code> versioning; introduce contract tests in CI via schemathesis or equivalent.	HIGH RISK	HIGH
H8 — Parallel API Runtimes	Retire or proxy <code>dev-api</code> to Laravel; eliminate triplicated reachability and dashboard KPI logic.	HIGH RISK	CRITICAL
H9 — Missing Input Validation on dev-api	Add express-validator schemas on all POST routes; remove or secure <code>bulk-import</code> endpoint.	HIGH RISK	HIGH

4.6 Expected Outcomes

- **Repository layer** moves 25 controller Eloquent calls behind testable boundaries, raising data-layer compliance from 22% to >90% and enabling mocked persistence in PHPUnit feature tests.
- **Application services** (`DashboardService` , `DiscoveryService` , `ConnectService`) eliminate triplicated KPI, tree, and reachability logic — fixes ship once and propagate to all entry points.
- **Retiring parallel dev-api routes** removes 17 duplicate handlers and the module-level `store` singleton, halving API surface area and integration drift risk.
- **OpenAPI spec + contract tests** catch breaking response-shape changes before merge, giving the React SPA a machine-verifiable integration contract.
- **Replacing `extract()` with typed DTOs** closes the variable-scope injection vector in legacy reporting and aligns with AGENTS.md engineering standards.