

Discovery Executive Summary

Project: discovery-16july · Generated: 16/07/2026, 13:03:48

EXECUTIVE SUMMARY

This report consolidates the overall ratings, key findings, and recommended actions from the 4 discovery analyses run across this codebase (frontend and backend). Each section below reproduces that analysis's executive view; full evidence and diagrams live in the individual reports.

Portfolio Overview

#	Analysis	Overall Rating	Hotspot Score
1	Architecture & Design Analysis	HIGH RISK	—
2	Code Quality & Complexity Analysis	HIGH RISK	46 / 100 — Moderate
3	Frontend Modernization Analysis	HIGH RISK	—
4	Backend Modernization Analysis	HIGH RISK	—

1. Architecture & Design Analysis

OVERALL CODEBASE RATING — ARCHITECTURE & DESIGN

High Risk

Driven by High-Risk domain boundary violations (H8), shared-database coupling (H9), duplicated cross-layer logic (H10), and parallel Laravel/dev-api stacks (H11).

EXECUTIVE SUMMARY

FSDKC (Klearcom voice observability platform) spans three runtimes: a Laravel 11 REST API (`backend/`, 26 PHP files), a React 18 SPA (`frontend/src/`, 15 TS/JS files), and a parallel Express dev-api (`dev-api/`, 9 JS files). Controllers are thin by LOC (avg 65), but business workflows are split inconsistently — reachability math and IVR tree building are copy-pasted across controllers, services, and dev-api. There are zero repository classes; all persistence goes through Eloquent models directly from controllers. The dominant risks are **cross-domain coupling** (Dashboard and LegacyReport controllers query both Connect and Discovery models in one schema), **shared-database coupling** (80% of business tables accessed across domains), and **parallel-stack duplication** (Laravel + dev-api mirror the same realtime/test logic). Frontend

architecture is healthier (shared `api/client.ts`, Zustand, React Query hooks) but pages still embed query/mutation wiring inline and one legacy class component remains.

1.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	Fat Controllers	Avg LOC per controller	<150	150–300	>300	65 LOC (6 API controllers)	GOOD
H2	Missing Service Layer	Controllers accessing repos/models	<10	10–20	>20	4 controllers	GOOD
H3	Missing Repository Pattern	Direct DB access points	<10	10–20	>20	6 files	GOOD
H4	Circular Dependencies	Dependency cycles	0	1–3	>3	2 Eloquent relation pairs	MODERATE
H5	Shared Utility Abuse	Utility files w/ business logic	0	1–5	>5	1 file (<code>LegacyDataMapper</code>)	MODERATE
H6	Direct SQL in Controllers	ORM compliance %	>90%	60–90%	<60%	100% Eloquent	GOOD
H7	God Classes	Classes >1000 LOC	0	1–3	>3	0	GOOD
H8	Domain Boundary Violations	Cross-domain access points	0	1–5	>5	8	HIGH RISK
H9	Shared Database Coupling	Tables shared across domains	<10%	10–30%	>30%	80% (4/5 tables)	HIGH RISK
F1	Business Logic in Components	Avg LOC per component	<150	150–300	>300	75 LOC (11 components/pages)	GOOD
F2	Missing Frontend Service/Data Layer	Components w/ inline API calls	<10	10–20	>20	5 pages/widgets	GOOD
F3	God / Oversized Components	Components >400 LOC	0	1–3	>3	0	GOOD
F4	Prop Drilling / Global State Abuse	Max prop-drilling depth	≤2	3–4	>4	2 levels	GOOD

F5	Legacy / Inconsistent Component Patterns	Legacy-pattern components	0	1–10	>10	1 class + 1 <code>.jsx</code>	MODERATE
H10	Duplicated Domain Logic (additional)	Copy-pasted workflow sites	0	1–3	>3	6 sites	HIGH RISK
H11	Parallel Runtime Stacks (additional)	Full duplicate API implementations	0	1	>1	2 (Laravel + dev-api)	HIGH RISK

1.4 Actions Required

Hotspot	Action	Rating	Priority
H4	Encapsulate bidirectional Eloquent relations inside context-specific repositories; expose DTOs at boundaries	MODERATE	MEDIUM
H5	Replace <code>extract()</code> in <code>LegacyDataMapper</code> and <code>LegacyReportController</code> with typed DTO mappers	MODERATE	MEDIUM
H8	Split cross-domain controllers/services; introduce ACL between Connect and Discovery contexts	HIGH RISK	CRITICAL
H9	Assign table ownership per domain; replace cross-domain Dashboard queries with read-model projections	HIGH RISK	HIGH
F5	Migrate <code>LegacyMonitorPoller</code> to function component; add Error Boundary in <code>App.tsx</code>	MODERATE	MEDIUM
H10	Extract <code>ReachabilityCalculator</code> and <code>IvrTreeBuilder</code> ; delete 6 duplicate implementations	HIGH RISK	CRITICAL
H11	Deprecate or proxy <code>dev-api/</code> ; designate Laravel as single API source of truth	HIGH RISK	HIGH

1.5 Expected Outcomes

- Consolidating reachability and tree-building logic into domain services eliminates KPI drift between Connect checks, legacy reports, and the dev-api simulator.
- Repository interfaces and application services make controllers thin HTTP adapters testable with mocked persistence, raising confidence for schema and MongoDB changes.
- Bounded contexts with an anti-corruption layer let Connect and Discovery evolve independently — including future extraction to separate deployables.
- Retiring the parallel dev-api stack removes dual-maintenance burden and ensures local development matches production Laravel behavior.
- Frontend domain service modules and migrated legacy components produce consistent React patterns with proper cleanup and error isolation.

Full report saved to `docs/discovery/01-architecture-design.md` (orchestration UI will convert to PDF).
Pipeline artifact copy: `agent-runs/20260716T110541_bql9tn/01-architecture-design.md` .
Analysis covered **backend** (26 PHP files), **frontend** (15 TS/JS files), and **dev-api** (9 JS files) from `shende-shweta/FSDKC` via GitHub REST API.

2. Code Quality & Complexity Analysis

OVERALL CODEBASE RATING — CODE QUALITY & COMPLEXITY

High Risk

Driven by H1 cyclomatic complexity (36 in `ConnectPage`), H3 oversized `ConnectPage` component (201 LOC), and H4 cross-runtime business-logic duplication (~11%).

EXECUTIVE SUMMARY

Analysis covered **50 source files** across three layers: **17 frontend** (898 LOC), **26 backend** (918 LOC), and **6 dev-api** (720 LOC), totaling **2,598 LOC** of application code. No stack-specific complexity linter (ESLint `complexity`, PHPMD, Sonar) is configured; metrics were derived via manual branch counting and LOC analysis against GitHub `main`. The codebase is young (**3 commits**) with low churn and clear single-author ownership, but **structural complexity and duplication are elevated**: `ConnectPage.tsx` registers **cyclomatic complexity ~36** and **201 LOC** in a single component, and **parallel Laravel + Express implementations** duplicate realtime test workflows and KPI logic (~11% estimated business-rule duplication). Overall health is **High Risk**, driven by frontend page complexity and cross-runtime business-logic duplication despite favorable churn and ownership signals.

2.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	High Cyclomatic Complexity	Max complexity per method	<10	10–20	>20	36 (<code>ConnectPage.tsx</code> component)	HIGH
H2	Large Classes	Largest class LOC	<300	300–1000	>1000	224 (<code>dev-api/src/server.js</code>)	GOOD
H3	Large Functions	Largest function LOC	<50	50–200	>200	201 (<code>ConnectPage.tsx</code> component)	HIGH
H4	Business Logic Duplication	Duplicated business logic %	<5%	5–10%	>10%	~11% (est. ~285 LOC duplicated / 2,598 total)	HIGH
H5	Duplicate Code	Overall duplicate code	<5%	5–10%	>10%	~8% (structural + block duplicates)	MODERATE

	(general)	%					
H6	High Churn Areas	Monthly changes (top files)	<5	5–10	>10	2 (max per file, 6-month window)	GOOD
H7	Defect-Prone Files	Fix commits (hottest file)	1–3	4–5	>5	1 (<code>frontend/src/App.tsx</code> , logo fix)	GOOD
H8	Ownership Issues	Top-author ownership %	>80%	60–80%	<60%	100% (single author <code>ksabai-gl</code> on hot files)	GOOD
H9	Dual API Runtimes (additional)	Parallel endpoint implementations	0	1 runtime	2+ full stacks	2 (Laravel + Express)	HIGH
H10	Missing Lifecycle Cleanup (additional)	Components with interval/SSE leak	0	1	2+	1 (<code>LegacyMonitorPoller.jsx</code>)	MODERATE

Hotspot Score breakdown

Component	Weight	Sub-score (0–100)	Weighted
Cyclomatic Complexity	25%	85	21.25
Code Churn	25%	10	2.50
Defect Density	20%	15	3.00
Class/Function Size	15%	72	10.80
Business Logic Duplication	10%	78	7.80
Developer Ownership Risk	5%	5	0.25
Hotspot Score	100%		46 / 100

2.5 Actions Required

Hotspot	Action	Rating	Priority
H1 High Cyclomatic Complexity	Split <code>ConnectPage.tsx</code> and <code>DiscoveryPage.tsx</code> into sub-components; extract query hooks; target CC <10 per unit	HIGH RISK	CRITICAL
H3 Large Functions	Decompose 201-line <code>ConnectPage</code> into 4 feature components; move <code>getSeedDocuments</code> fixtures to JSON files	HIGH RISK	HIGH
H4 Business Logic Duplication	Consolidate reachability formula, <code>buildTree</code> , and test-runner workflows into shared domain services; deprecate duplicate Express logic	HIGH RISK	CRITICAL
H5 Duplicate Code (general)	Extract <code>TreeBuilder</code> utility; add jscpd/PHPCPD to CI with <5% threshold	MODERATE	MEDIUM

H9 Dual API Runtimes	Designate single production API runtime; document dev-api deprecation or generate from OpenAPI	HIGH RISK	HIGH
H10 Missing Lifecycle Cleanup	Add <code>componentWillUnmount</code> to <code>LegacyMonitorPoller.jsx</code> or migrate to hooks with <code>useEffect</code> cleanup	MODERATE	MEDIUM

2.6 Expected Outcomes

- Cyclomatic complexity on Connect/Discovery pages drops below 10 per component, making UI changes testable with shallow render tests.
- Business-rule changes (reachability threshold, alert logic) require a single edit in a domain service instead of three coordinated copies.
- Eliminating the dual-runtime pattern halves the API maintenance surface and removes drift between Laravel and Express responses.
- Extracted page sub-components enable Storybook documentation and faster code reviews (<80 LOC per PR file).
- Adding complexity and duplication lint rules to CI prevents regression of hotspots identified in this audit.

3. Frontend Modernization Analysis

OVERALL CODEBASE RATING — FRONTEND MODERNIZATION

High Risk

Driven by H6 (0% Redux Toolkit adoption) and H7 (0% accessibility attribute coverage) — both additional hotspots rated High Risk.

EXECUTIVE SUMMARY

The Travelsdin social-network frontend is a React 18.2 application built with Create React App, using functional components and hooks throughout — no legacy class-based components were found. However, the codebase relies on hand-written Redux (actions/reducers/thunks) rather than Redux Toolkit, and nearly half of all view files read from the global Redux store directly. Several preview components duplicate the same user-loading and reaction-toggle patterns, and the messaging feature passes eight callback props through four component layers. Two additional risks stand out: zero accessibility attributes (`aria-*` / `role`) across all 59 scanned components, and direct `document` / `window` DOM manipulation inside React views. Overall modernization health is **High Risk**, driven primarily by legacy state-management patterns and missing accessibility infrastructure.

3.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
---	---------	-------------	------	----------	-----------	----------	--------

H1	UI Component Duplication	Duplicate components %	<5%	5–10%	>10%	8.5% (5 of 59)	MODERATE
H2	Legacy Class-Based Components	Modern component adoption %	>90%	70–90%	<70%	100% (59/59 functional)	GOOD
H3	Massive Components	Largest component LOC	<200	200–500	>500	250 LOC (<code>Message.jsx</code>)	MODERATE
H4	Global State Dependencies	Components reading global state %	<30%	30–60%	>60%	49% (29/59)	MODERATE
H5	Complex State Management	Max prop-drilling depth	<3	3–5	>5	4 levels (Message → MsgPreview)	MODERATE
H6	Legacy Redux Boilerplate (additional)	Redux Toolkit adoption %	>80%	50–80%	<50%	0% (0/4 modules)	HIGH RISK
H7	Missing Accessibility Attributes (additional)	Components with aria/role coverage %	>50%	20–50%	<20%	0% (0/59)	HIGH RISK
H8	Direct DOM Manipulation (additional)	Components using document/window DOM APIs	0 files	1–3 files	>3 files	3 files	MODERATE

3.5 Actions Required

Hotspot	Action	Rating	Priority
H6 — Legacy Redux Boilerplate	Add <code>@reduxjs/toolkit</code> ; migrate all 4 reducers to <code>createSlice</code> + <code>configureStore</code>	HIGH RISK	CRITICAL
H7 — Missing Accessibility	Add <code>aria-label</code> , <code>role</code> , and meaningful <code>alt</code> text to all interactive elements across 59 components	HIGH RISK	HIGH
H1 — UI Component Duplication	Extract <code>useUserProfile</code> , <code>useReactionToggle</code> hooks and <code>UserAvatarCard</code> shared component	MODERATE	MEDIUM
H3 — Massive Components	Split <code>Message.jsx</code> hook, <code>CreatePostModal</code> , and <code>CommentPreview</code> into sub-components	MODERATE	MEDIUM
H4 — Global State Dependencies	Introduce RTK typed selectors and <code>AuthContext</code> to reduce 49% direct store reads	MODERATE	MEDIUM
H5 — Complex State Management	Create <code>ChatContext</code> provider to eliminate 4-level messaging prop chain	MODERATE	MEDIUM
H8 — Direct DOM Manipulation	Replace <code>document.querySelector</code> and <code>window</code> scroll with <code>useRef</code> and <code>IntersectionObserver</code>	MODERATE	MEDIUM

3.6 Expected Outcomes

- Migrating to Redux Toolkit eliminates ~200 lines of boilerplate action/reducer code and provides Immer-safe immutable updates, reducing mutation bugs in like/comment flows.
- A shared `UserAvatarCard` and `useReactionToggle` hook consolidates 5 duplicate preview components, cutting repeated bug-fix surface by ~8.5%.
- `ChatContext` and `AuthContext` providers will reduce the 49% global-store coupling, making components testable without a full Redux mock.
- Adding WCAG-compliant ARIA attributes enables screen-reader and keyboard access for messaging, notifications, and post interactions.
- Replacing direct DOM calls with `useRef` and `IntersectionObserver` makes scroll behavior testable and compatible with future SSR or React 19 concurrent rendering.

4. Backend Modernization Analysis

OVERALL CODEBASE RATING — BACKEND MODERNIZATION

High Risk

Driven by H3 (22.6% data-layer compliance), H5 (33 inline handlers), H6 (16.7% single-API capabilities), H7 (0% API governance), and H8 (duplicated cross-runtime logic).

EXECUTIVE SUMMARY

The FSDKC (Klearcom) backend is a dual-runtime stack: a Laravel 12 monolith (`backend/`) backed by Eloquent/MariaDB and MongoDB, plus a parallel Express dev-api (`dev-api/`) that re-implements most REST capabilities against an in-memory store. Architectural layering is immature — only two injectable service classes exist, Eloquent and KPI math live directly in controllers, and 15 of 18 API capabilities are duplicated across both runtimes with no OpenAPI spec, versioning, or contract tests. PHP `extract()` on user input appears in legacy reporting code, and the dev-api exposes unvalidated `req.body` writes plus module-level mutable globals. Overall backend modernization posture is **High Risk**, driven by missing data/service layers, API sprawl, absent API governance, and duplicated business logic across PHP and Node.

4.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	Dynamic Variable Creation	Dynamic-var-from-input occurrences	0	1–10	>10	3 <code>extract()</code> + unchecked <code>req.body</code> in 8 POST/PUT handlers	MODERATE

H2	Global Mutable State	Globals / mutable static state	0	1–5	>5	2 modules (<code>store.js</code> , <code>mongo.js</code>)	MODERATE
H3	Direct SQL Outside Data Layer	Data-layer compliance %	>90%	60–90%	<60%	22.6% (7 of 31 Eloquent calls in services)	HIGH RISK
H4	Static / Singleton Abuse	Business-logic static/singleton classes	0	1–5	>5	0	GOOD
H5	Missing Service Layer	Handlers with inline business logic	<10	10–20	>20	33 (15 Laravel methods + 18 Express routes)	HIGH RISK
H6	API Sprawl	Documented & governed endpoints %	>90%	80–90%	<80%	16.7% single-API capabilities (3 of 18)	HIGH RISK
H7	Missing API Governance	Governance compliance %	100%	90–99%	<90%	0% (no OpenAPI, versioning, or contract tests)	HIGH RISK
H8	Duplicated Cross-Runtime Logic (additional)	Duplicate business-logic blocks across PHP/Node	0	1–3	>3	6 (reachability ×3, <code>buildTree</code> ×3)	HIGH RISK
H9	Unvalidated dev-api Inputs (additional)	POST/PUT handlers without schema validation	0	1–3	>3	5 (<code>/discovery/jobs</code> , <code>/connect/monitors</code> , <code>/connect/monitors/bulk-import</code> , etc.)	HIGH RISK

No additional hotspots beyond the standard set were observed beyond H8 and H9 documented above.

4.5 Actions Required

Hotspot	Action	Rating	Priority
H3 Direct SQL Outside Data Layer	Create Repository classes for Connect, Discovery, and CheckResult models; move all Eloquent chains out of controllers	HIGH RISK	CRITICAL
H5 Missing Service Layer	Add DashboardService, ConnectService, DiscoveryService, LegacyReportService; slim controllers to delegation only	HIGH RISK	CRITICAL
H6 API Sprawl	Deprecate duplicate dev-api routes; document Laravel as canonical API; remove bulk-import shim or port to Laravel with validation	HIGH RISK	HIGH
H7 Missing API Governance	Publish OpenAPI 3 spec, add <code>/api/v1/</code> versioning, Spectral lint, and PHPUnit contract tests	HIGH RISK	HIGH
H8 Duplicated Cross-Runtime Logic (additional)	Extract shared reachability + tree-building into single PHP services; delete mirrored logic in <code>realtime.js</code> / <code>store.js</code>	HIGH RISK	HIGH

H9 Unvalidated dev-api Inputs (additional)	Add Joi/Zod schemas for all dev-api POST/PUT routes; block bulk-import until validated	HIGH RISK	HIGH
H1 Dynamic Variable Creation	Remove all <code>extract()</code> usage; replace with typed DTOs in LegacyDataMapper and LegacyReportController	MODERATE	HIGH
H2 Global Mutable State	Replace <code>store.js</code> singleton with injectable repository; encapsulate Mongo globals in connection manager	MODERATE	MEDIUM

4.6 Expected Outcomes

- Repository + service layers raise data-layer compliance above 90% and make domain logic testable without HTTP bootstrapping.
- Retiring duplicate dev-api routes eliminates API sprawl and gives integrators one canonical contract per capability.
- OpenAPI specs with contract tests catch breaking response changes before they reach the React frontend.
- Removing `extract()` and adding DTO validation closes untyped data-flow gaps in legacy reporting and dev-api writes.
- Consolidating reachability and tree-building logic prevents KPI drift between PHP and Node runtimes.