

3. Frontend Modernization Hotspots Analysis

Objective: Modernize the frontend using idiomatic hooks/composables and a shared component library.

Date: July 15, 2026 | **Scope:** shende-shweta/FSDKC@main — React 19.2.3 / Vite 6.0.3 / TypeScript 5.7 SPA

Executive Summary

EXECUTIVE SUMMARY

Analysis covered **14 frontend source files** (8 view components across `pages/` and `components/`) from `shende-shweta/FSDKC@main` via GitHub REST API (tree + raw content fetch). The Klearcom SPA is predominantly modern — function components, TanStack React Query v5, Zustand v5, and React Router v7 — with a centralized `api/client.ts` and reusable `useRealtimeTest` hook. However, `ConnectPage.tsx` and `DiscoveryPage.tsx` duplicate an identical workbench shell (entity form, live feed, two-column grid, transcript panel), inflating UI duplication to **25%**. Six of eight view components depend on shared global state (Zustand, React Query cache, or the singleton `api` client), and **30 inline `style={{}}` occurrences** bypass the CSS token system in `index.css`. One legacy class component (`LegacyMonitorPoller.jsx`) lacks `componentWillUnmount` cleanup and leaks intervals; two orphan legacy modules coexist with the React Query stack. Zero `aria-*` / `role` attributes were found across all view components. Overall verdict: **High Risk**, driven by H1 (UI duplication), H4 (global state coupling), H6 (inline styles), and H7 (missing accessibility).

14

COMPONENTS/FILES
SCANNED

1

LEGACY CLASS-BASED
COMPONENTS

0

COMPONENTS OVER 500 LOC

3

GLOBAL/SHARED STATE
MODULES

OVERALL CODEBASE RATING — FRONTEND MODERNIZATION

High Risk

Driven by High-Risk UI Component Duplication (H1), Global State Dependencies (H4), Inline Styles Without Design Tokens (H6), and Missing Accessibility Roles (H7).

3.1 Benchmark Ratings Summary

#	Hotspot	Primary KPI	GOOD	MODERATE	HIGH RISK	Measured	Rating
H1	UI Component Duplication	Duplicate components %	<5%	5–10%	>10%	25.0% (2/8)	HIGH RISK

H2	Legacy Class-Based Components	Modern component adoption %	>90%	70–90%	<70%	87.5% (7/8)	MODERATE
H3	Massive Components	Largest component LOC	<200	200–500	>500	222 (<code>ConnectPage.tsx</code>)	MODERATE
H4	Global State Dependencies	Components reading global state %	<30%	30–60%	>60%	75.0% (6/8)	HIGH RISK
H5	Complex State Management	Max prop-drilling depth	<3	3–5	>5	2 levels	GOOD
H6	Inline Styles / No Design Tokens (additional)	Total <code>style={{}}</code> occurrences (target <10)	<10	10–20	>20	30 across 7 files	HIGH RISK
H7	Missing Accessibility Roles (additional)	Components with <code>aria-*</code> or <code>role</code> (target >80%)	>80%	50–80%	<50%	0% (0/8)	HIGH RISK

3.2 Hotspot-by-Hotspot Evidence

H1. UI Component Duplication CRITICAL

Benchmark: `Duplicate components % = 25.0% (2/8)` → falls in the **High Risk** band (Good <5% · Moderate 5–10% · High Risk >10%).

`ConnectPage.tsx` and `DiscoveryPage.tsx` share 11 of 11 structural patterns (page header, entity form card, `LiveTestFeed` section, two-column grid layout, transcript panel). Each page re-implements the same workbench shell with only domain-specific query keys and form fields differing — a near-copy pattern across 25% of view components.

`frontend/src/pages/ConnectPage.tsx:63-101` :

```
return (
  <>
    <header className="page-header">
      <h1>Connect</h1>
      <p>TFN reachability testing with live MongoDB event streaming</p>
    </header>

    <section className="card" style={{ marginBottom: '1.5rem' }}>
      <div className="card-header">
```

```

        <strong>Add TFN Monitor</strong>
      </div>
      <form onSubmit={handleSubmit} style={{ padding: '1.25rem' }}>
        <div className="form-grid">
          ...
        </div>
      </form>
    </section>

    <section style={{ marginBottom: '1.5rem' }}>
      <LiveTestFeed events={events} isRunning={isRunning} progress={progress}
      title="Connect – Live Reachability Test" />
    </section>

    <div style={{ display: 'grid', gridTemplateColumns: '1fr 1fr', gap:
    '1.5rem' }}>

```

frontend/src/pages/DiscoveryPage.tsx:59-95 :

```

return (
  <>
    <header className="page-header">
      <h1>Discovery</h1>
      <p>Automated IVR discovery with real-time MongoDB event streaming</p>
    </header>

    <section className="card" style={{ marginBottom: '1.5rem' }}>
      <div className="card-header">
        <strong>New Discovery Job</strong>
      </div>
      <form onSubmit={handleSubmit} style={{ padding: '1.25rem' }}>
        <div className="form-grid">
          ...
        </div>
      </form>
    </section>

    <section style={{ marginBottom: '1.5rem' }}>
      <LiveTestFeed events={events} isRunning={isRunning} progress={progress}
      title="Discovery – Live IVR Test" />
    </section>

    <div style={{ display: 'grid', gridTemplateColumns: '1fr 1fr', gap:
    '1.5rem' }}>

```

Why it matters here: Any UX fix to the workbench layout (form spacing, grid breakpoints, transcript panel styling) must be applied twice. New domain modules (e.g., Alerts, Reports) would likely copy this shell again, compounding drift and maintenance cost in a product expected to grow beyond two domains.

Recommended approach:

1. Extract `DomainWorkbenchPage` layout shell with slots for form, feed, left panel, right panel, and transcript footer.
2. Create `EntityFormCard` and `TranscriptPanel` shared components used by both pages.
3. Reduce `ConnectPage.tsx` and `DiscoveryPage.tsx` to domain-specific hooks and column render props only.

No files matched `frontend/src/pages/*.tsx` containing `style=\{\{\ display: 'grid', gridTemplateColumns: '1fr 1fr'`.

H2. Legacy Class-Based Components MEDIUM

Benchmark: `Modern component adoption % = 87.5% (7/8)` → falls in the **Moderate** band (Good >90% · Moderate 70–90% · High Risk <70%).

One of eight view components is a class-based React component. `LegacyMonitorPoller.jsx` uses `componentDidMount` to start a polling interval but deliberately omits `componentWillUnmount`, creating an interval leak anti-pattern. The file is not imported in `App.tsx` but remains in the codebase as dead legacy code.

`frontend/src/components/LegacyMonitorPoller.jsx:17-33` :

```
export default class LegacyMonitorPoller extends Component<Props, State> {
  intervalId: ReturnType<typeof setInterval> | null = null;

  state: State = { reachability: null, error: null };

  componentDidMount() {
    this.intervalId = setInterval(() => {
      api.get<{ computed?: { reachability_pct: number } }>
        (`/connect/monitors/${this.props.monitorId}/checks`)
        .then((res) => {
          const pct = res.computed?.reachability_pct ?? null;
          this.setState({ reachability: pct, error: null });
          if (pct !== null) this.props.onUpdate?.(pct);
        })
        .catch((err: Error) => this.setState({ error: err.message }));
    }, 3000);
    // Intentionally no componentWillUnmount – EventSource/interval leak for
    audit finding
  }
}
```

`frontend/src/pages/LegacyDashboardWidget.tsx:16-44` also uses imperative `useEffect` + `Promise.all` + `setInterval` instead of React Query, duplicating data-fetch patterns found in `DashboardPage.tsx` and domain pages:

```

useEffect(() => {
  let cancelled = false;

  Promise.all([
    api.get<DashboardKpis>('/dashboard/kpis'),
    api.get<{ data: DiscoveryJob[] }>('/discovery/jobs'),
    api.get<{ data: ConnectMonitor[] }>('/connect/monitors'),
  ])
    .then(([kpiRes, jobRes, monitorRes]) => { ... });

  const timer = setInterval(() => {
    api.get<DashboardKpis>('/dashboard/kpis').then((k) => { ... });
  }, 10000);

  return () => { cancelled = true; clearInterval(timer); };
}, []);

```

Why it matters here: If `LegacyMonitorPoller` is mounted during a refactor or test harness, intervals persist after unmount and continue hitting `/connect/monitors/{id}/checks`. The parallel legacy fetch pattern in `LegacyDashboardWidget` bypasses React Query cache invalidation used by domain pages, causing stale dashboard data when tests complete.

Recommended approach:

1. Convert `LegacyMonitorPoller.jsx` to a `useMonitorReachability(monitorId)` hook with `useEffect` cleanup.
2. Migrate `LegacyDashboardWidget.tsx` to `useQuery` hooks matching `DashboardPage.tsx` query keys.
3. Delete both legacy modules or gate them behind a feature flag once migration is verified.

No files matched `frontend/src/**/*.tsx,jsx` containing `class\s+\w\s+extends\s+(React\.)?Component`.

H3. Massive Components MEDIUM

Benchmark: `Largest component LOC = 222 (ConnectPage.tsx)` → falls in the **Moderate** band (Good <200 · Moderate 200–500 · High Risk >500).

No component exceeds 500 LOC, but `ConnectPage.tsx` (222 LOC) and `DiscoveryPage.tsx` (176 LOC) each mix form state, three React Query hooks, mutation handlers, SSE orchestration, table rendering, and transcript display in a single file.

`ConnectPage.tsx` alone contains 11 inline style blocks and four separate query/mutation definitions.

`frontend/src/pages/ConnectPage.tsx:9-56` :

```

export default function ConnectPage() {
  const queryClient = useQueryClient();
  const selectedId = useUiStore((s) => s.selectedMonitorId);
  const setSelectedId = useUiStore((s) => s.setSelectedMonitorId);
  const { events, isRunning, progress, startConnectCheck } =

```

```

useRealtimeTest('connect');

const [form, setForm] = useState({ name: '', toll_free_number: '',
country_code: 'US', carrier: '' });

const monitorsQuery = useQuery({ queryKey: ['connect', 'monitors'], ... });
const checksQuery = useQuery({ queryKey: ['connect', 'checks', selectedId],
... });
const transcriptsQuery = useQuery({ queryKey: ['mongodb', 'transcripts',
'connect', selectedId], ... });

const createMutation = useMutation({ ... });

const handleRunCheck = async (monitorId: number) => {
  setSelectedId(monitorId);
  await startConnectCheck(monitorId);
  queryClient.invalidateQueries({ queryKey: ['connect'] });
  queryClient.invalidateQueries({ queryKey: ['mongodb'] });
  queryClient.invalidateQueries({ queryKey: ['dashboard'] });
};

```

Why it matters here: Testing individual concerns (form validation, table selection, check history rendering) requires mounting the entire page. As domain logic grows (bulk test runs, export, filtering), these files will cross the 500 LOC High Risk threshold without structural intervention.

Recommended approach:

1. Extract `useConnectPage` container hook encapsulating queries, mutations, and handlers.
2. Split presentational sub-components: `MonitorTable`, `CheckHistoryTable`, `ConnectEntityForm`.
3. Target <150 LOC per page file with composition over monolith.

No files matched `frontend/src/pages/ConnectPage.tsx` containing `useQuery`(.

H4. Global State Dependencies HIGH

Benchmark: `Components reading global state % = 75.0% (6/8)` → falls in the **High Risk** band (Good <30% · Moderate 30–60% · High Risk >60%).

Six of eight view components read from shared global modules: Zustand `useUiStore`, TanStack React Query (`useQuery` / `useMutation` / `useQueryClient`), or the singleton `api` client. Selection state (`selectedMonitorId`, `selectedDiscoveryId`) lives in a global Zustand store rather than URL params, and query invalidation fans out across `['connect']`, `['discovery']`, `['mongodb']`, and `['dashboard']` keys from multiple pages.

`frontend/src/store/uiStore.ts:10-15` :

```

export const useUiStore = create<UiState>((set) => ({
  selectedDiscoveryId: null,
  selectedMonitorId: null,

```

```

    setSelectedDiscoveryId: (id) => set({ selectedDiscoveryId: id }),
    setSelectedMonitorId: (id) => set({ selectedMonitorId: id }),
  }));

```

`frontend/src/pages/ConnectPage.tsx:50-56` :

```

const handleRunCheck = async (monitorId: number) => {
  setSelectedId(monitorId);
  await startConnectCheck(monitorId);
  queryClient.invalidateQueries({ queryKey: ['connect'] });
  queryClient.invalidateQueries({ queryKey: ['mongodb'] });
  queryClient.invalidateQueries({ queryKey: ['dashboard'] });
};

```

`frontend/src/components/MongoStatus.tsx:5-10` :

```

export default function MongoStatus() {
  const { data, isLoading, isError } = useQuery({
    queryKey: ['mongodb', 'status'],
    queryFn: () => api.get<MongoHealth>('/mongodb/status'),
    refetchInterval: 15_000,
  });
}

```

Why it matters here: Broad `invalidateQueries` calls from Connect and Discovery pages trigger refetches in unrelated components (`MongoStatus` , `DashboardPage`). Global Zustand selection is lost on page refresh and cannot be shared via deep links — a significant gap for an operations dashboard where users need to bookmark a specific monitor or job.

Recommended approach:

1. Replace Zustand selection with URL search params (`/connect?monitor=42` , `/discovery?job=7`).
2. Add `frontend/src/api/queryKeys.ts` with typed, domain-scoped query key factories.
3. Scope invalidation to the specific domain key prefix instead of fan-out to `['dashboard']` and `['mongodb']` .

No files matched `frontend/src/**/*.tsx,jsx` containing `useUiStore|useQuery|useQueryClient|useMutation|from [\"']\.\./api/client` .

H5. Complex State Management LOW

Benchmark: `Max prop-drilling depth = 2 levels` → falls in the **Good** band (Good <3 · Moderate 3–5 · High Risk >5).

Prop passing is shallow: pages pass data directly to child components (`LiveTestFeed` , `IvrTree`) with at most one intermediate hop. `IvrTree` recursively renders `TreeNode` children but receives all data from a single `nodes` prop at depth 1 from `DiscoveryPage` . No context chains or five-level prop tunnels were observed.

`frontend/src/pages/DiscoveryPage.tsx:151-152` :

```

) : treeQuery.data?.tree.length ? (
  <IvrTree nodes={treeQuery.data.tree} />

```

frontend/src/components/IvrTree.tsx:7-14 :

```

export default function IvrTree({ nodes }: Props) {
  return (
    <div className="tree-view">
      {nodes.map((node) => (
        <TreeNode key={node.id} node={node} />
      ))}
    </div>
  );
}

```

Evidence: Not observed — prop-drilling depth stays at 2 levels (page → **IvrTree** → **TreeNode**), well within the Good threshold. React Query and Zustand already centralize server and selection state without deep prop chains.

H6. Inline Styles / No Design Tokens (additional) HIGH

Benchmark: **Total style={{}} occurrences = 30 across 7 files** → falls in the **High Risk** band (Good <10 · Moderate 10–20 · High Risk >20).

Despite a comprehensive **:root** token system in **index.css** (colors, radius, surfaces), 30 inline **style={{}}** blocks appear across 7 source files. Domain pages account for 18 of 30 (11 in **ConnectPage.tsx** , 7 in **DiscoveryPage.tsx**), duplicating spacing, grid, and typography values that should be utility classes.

frontend/src/index.css:1-17 :

```

:root {
  --bg: #0b0f1a;
  --surface: #121829;
  --surface-2: #1a2238;
  --border: #2a3555;
  --text: #e8ecf4;
  --muted: #8b95ad;
  --accent: #3b82f6;
  ...
}

```

frontend/src/pages/ConnectPage.tsx:99-103 :

```

<div style={{ display: 'grid', gridTemplateColumns: '1fr 1fr', gap:
'1.5rem' }}>
  <section className="card">

```

```
<div className="card-header">
  <strong>TFN Monitors</strong>
```

frontend/src/components/IvrTree.tsx:21-28 :

```
{node.dtmf_option && (
  <span style={{ color: 'var(--accent-2)', marginRight: '0.5rem' }}>
    [{node.dtmf_option}]
  </span>
)}
<span style={{ color: 'var(--muted)', fontSize: '0.75rem' }}>
{node.node_type}</span>
```

Why it matters here: Inline styles cannot be themed, overridden by media queries, or linted consistently. The duplicated grid layout in both domain pages will drift if one page adjusts `gap` or `gridTemplateColumns` without the other, undermining the existing design-token investment in `index.css` .

Recommended approach:

1. Add utility classes to `index.css` : `.grid-2col` , `.mb-section` , `.text-muted-sm` , `.row-selected` .
2. Migrate 30 inline occurrences starting with the 18 in domain pages.
3. Add an ESLint rule or stylelint check to block new `style={{}}` in TSX files.

No files matched `frontend/src/**/*.{tsx,jsx}` containing `style=\{\{` .

H7. Missing Accessibility Roles (additional) HIGH

Benchmark: `Components with aria-* or role = 0% (0/8)` → falls in the **High Risk** band (Good >80% · Moderate 50–80% · High Risk <50%).

Zero view components contain `aria-*` attributes or `role` properties. Interactive table rows use `onClick` without keyboard handlers or `tabIndex` . Form labels lack `htmlFor` associations (7 unlinked labels across domain pages).

`LiveTestFeed` renders dynamic realtime events without `aria-live` regions for screen-reader announcements.

frontend/src/pages/ConnectPage.tsx:76-78 :

```
<div className="form-group">
  <label>Monitor Name</label>
  <input required value={form.name} onChange={(e) => setForm({
...form, name: e.target.value })} />
```

frontend/src/pages/ConnectPage.tsx:121-126 :

```
<tr
  key={m.id}
  onClick={() => setSelectedId(m.id)}
```

```

        style={{ cursor: 'pointer', background: selectedId === m.id
? 'var(--surface-2)' : undefined }}
      >

```

`frontend/src/components/LiveTestFeed.tsx:32-49` :

```

    <div className="live-events">
      {events.map((doc, i) => (
        <div key={doc._id ?? i} className={`live-event live-
event-${doc.event?.type ?? 'step'}`}>
          ...
        </div>
      ))}
      {isRunning && <div className="live-event live-event-pending">Waiting
for next event...</div>}
    </div>

```

Why it matters here: Klearcom is an operations-focused voice observability platform where users monitor live test feeds and select monitors/jobs from data tables. Without keyboard-accessible row selection and live-region announcements, operators relying on assistive technology cannot navigate the primary workflows.

Recommended approach:

1. Add `aria-live="polite"` to `LiveTestFeed` event container.
2. Convert selectable table rows to `<button>` rows or add `role="button"` , `tabIndex={0}` , and `onKeyDown` handlers.
3. Add `htmlFor` / `id` pairs on all form labels in domain pages.

No files matched `frontend/src/{pages, components}/*.{tsx, jsx}` .


3.3 State Management & Dependency Evidence

H4 and H5 above cover the state management hotspots. Additional observations:


- **Three global modules** serve all features: `store/uiStore.ts` (Zustand), `api/client.ts` (singleton fetch wrapper), and TanStack React Query cache (configured in `main.tsx`).
- `useRealtimeTest` is a well-structured domain hook with proper `EventSource` cleanup — a positive pattern to extend for other side-effect concerns.
- **Cross-domain invalidation** in `handleRunCheck` / `handleStart` creates hidden coupling: completing a Connect test refetches Discovery-unrelated dashboard and MongoDB queries.

3.4 Diagrams


Current UI data flow



Target component + state layout



Improvement roadmap



3.5 Actions Required

Hotspot	Action	Rating	Priority
---------	--------	--------	----------

H1 — UI Component Duplication	Extract <code>DomainWorkbenchPage</code> , <code>EntityFormCard</code> , and <code>TranscriptPanel</code> from <code>ConnectPage.tsx</code> and <code>DiscoveryPage.tsx</code> ; reduce duplicate shell to domain hooks only.	HIGH RISK	CRITICAL
H2 — Legacy Class-Based Components	Convert <code>LegacyMonitorPoller.jsx</code> to <code>useMonitorReachability</code> hook; migrate <code>LegacyDashboardWidget.tsx</code> to React Query or delete both orphan modules.	MODERATE	MEDIUM
H3 — Massive Components	Split <code>ConnectPage.tsx</code> (222 LOC) and <code>DiscoveryPage.tsx</code> (176 LOC) into container hooks + presentational sub-components; target <150 LOC per page.	MODERATE	MEDIUM
H4 — Global State Dependencies	Replace <code>useUiStore</code> selection with URL search params; add <code>frontend/src/api/queryKeys.ts</code> ; scope query invalidation to domain keys.	HIGH RISK	HIGH
H6 — Inline Styles	Add CSS utility classes to <code>index.css</code> ; migrate 30 inline <code>style={{}}</code> occurrences (18 in domain pages) to token-based classes.	HIGH RISK	HIGH
H7 — Missing Accessibility	Add <code>aria-live</code> to <code>LiveTestFeed</code> , keyboard-accessible row selection in domain tables, and <code>htmlFor</code> on form labels.	HIGH RISK	HIGH

3.6 Expected Outcomes

- **Shared component library** eliminates the 25% duplicate page-shell pattern; Connect and Discovery fixes ship once via `DomainWorkbenchPage` and `TranscriptPanel` .
- **Hooks-first migration** of `LegacyMonitorPoller` removes interval leaks and aligns all data access on React Query with testable custom hooks.
- **Scoped state** (URL params + domain query keys) reduces cross-feature invalidation fan-out and makes monitor/job selection shareable via deep links.
- **Design-token consistency** from replacing 30 inline styles lowers theming cost and aligns with the existing `:root` token system in `index.css` .
- **Accessibility baseline** (`aria-live` , keyboard rows, label associations) makes realtime test feeds and data tables operable for keyboard and screen-reader users in an operations-focused product.