

Rajalakshmi Engineering College

Name: Shenlin Samuel
Email: 240801317@rajalakshmi.edu.in
Roll no: 240801317
Phone: 7904912962
Branch: REC
Department: I ECE AF
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 2

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Priya is developing a simple student management system. She wants to store roll numbers in a hash table using Linear Probing, and later search for specific roll numbers to check if they exist.

Implement a hash table using linear probing with the following operations:

Insert all roll numbers into the hash table. For a list of query roll numbers, print "Value x: Found" or "Value x: Not Found" depending on whether it exists in the table.

Input Format

The first line contains two integers, n and $table_size$ — the number of roll numbers to insert and the size of the hash table.

The second line contains n space-separated integers — the roll numbers to insert.

The third line contains an integer q — the number of queries.

The fourth line contains q space-separated integers — the roll numbers to search for.

Output Format

The output print q lines — for each query value x, print: "Value x: Found" or "Value x: Not Found"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5 10
21 31 41 51 61
3
31 60 51

Output: Value 31: Found
Value 60: Not Found
Value 51: Found

Answer

```
#include <stdio.h>

#define MAX 100
```

```
void initializeTable(int table[], int size) {
    for (int i = 0; i < size; i++) {
        table[i] = -1;
    }
}
```

```
int linearProbe(int table[], int size, int num) {
    int idx = num % size;
```

```
    if (idx < 0) idx += size;
    while (table[idx] != -1) {
        idx = (idx + 1) % size;
    }
    return idx;
}
```

```
void insertIntoHashTable(int table[], int size, int arr[], int n) {
    for (int i = 0; i < n; i++) {
        int num = arr[i];
        int idx = num % size;
        if (idx < 0) idx += size;

        if (table[idx] == -1) {
            table[idx] = num;
        } else {
            table[linearProbe(table, size, num)] = num;
        }
    }
}
```

```
int searchInHashTable(int table[], int size, int num) {
    int idx = num % size;
    if (idx < 0) idx += size;
    int probed = 0;

    while (probed < size && table[idx] != -1) {
        if (table[idx] == num) {
            return 1;
        }
        idx = (idx + 1) % size;
        probed++;
    }
    return 0;
}
```

```
int main() {
    int n, table_size;
    scanf("%d %d", &n, &table_size);
```

```
int arr[MAX], table[MAX];
for (int i = 0; i < n; i++)
    scanf("%d", &arr[i]);

initializeTable(table, table_size);
insertIntoHashTable(table, table_size, arr, n);

int q, x;
scanf("%d", &q);
for (int i = 0; i < q; i++) {
    scanf("%d", &x);
    if (searchInHashTable(table, table_size, x))
        printf("Value %d: Found\n", x);
    else
        printf("Value %d: Not Found\n", x);
}

return 0;
}
```

Status : Correct

Marks : 10/10