

Placement

Yicheng Shen

Aug 6, 2024

Note: the github repo for this work is: <https://github.com/sheny2/Placement>

Q1

Task 1: Read the data Scrape the wikipedia page on natural disasters

```
url <- "https://en.wikipedia.org/wiki/List_of_natural_disasters_by_death_toll"

webpage <- read_html(url)

tables <- webpage %>% html_nodes("table.wikitable")

# 20th and 21st century data are the 2nd and 3rd table of this page
table_20th <- tables[[2]] %>% html_table(fill = TRUE)
table_21st <- tables[[3]] %>% html_table(fill = TRUE)

disasters <- rbind(table_20th, table_21st) %>% as_tibble()

head(disasters)
```

```
## # A tibble: 6 x 6
##   Year 'Death toll' Event                'Countries affected' Type Date
##   <int> <chr>      <chr>                <chr>                <chr> <chr>
## 1  1900 6,000-12,000 1900 Galveston hurricane United States Trop~ Sept~
## 2  1901 9,500      1901 eastern United State~ United States Heat~ June~
## 3  1902 29,000      1902 eruption of Mount Pe~ Martinique Volc~ Apri~
## 4  1903 3,500      1903 Manzikert earthquake Turkey Eart~ Apri~
## 5  1904 400        1904 Sichuan earthquake China Eart~ Augu~
## 6  1905 20,000+    1905 Kangra earthquake India Eart~ Apri~
```

Task 2: Clean the data Convert the death toll to numbers using the midpoints when a range is given and the bound when an upper or lower bound is given.

```
disasters_clean = disasters

disasters_clean$`Death toll` = disasters$`Death toll` %>%
  str_remove_all(",") %>%
  str_remove_all("\\[.*?\\]") %>%
  str_remove_all("\\(.*?\\)") %>%
  str_remove_all("[a-zA-Z]") %>%
  str_trim()
```

```
# which entries need special attention to clean
list_of_clean = is.na(as.numeric(gsub(",", "", disasters_clean$`Death toll`)))
disasters$`Death toll`[list_of_clean]
```

```
## [1] "6,000-12,000"      "20,000+"           "12,000-15,000"
## [4] "75,000-82,000"     "6,000-8,000"       "50,000-220,000"
## [7] "942-1,900"         "29,978-32,610"     "2,000-10,000"
## [10] "258,707-273,407"   "50,000-100,000+"    "105,385-142,800"
## [13] "4,112+"            "3,257-3,800"       "2,000-8,000"
## [16] "422,499-4,000,000" "3,103+"             "6,865-9,300"
## [19] "10,700-12,000"     "5,000+"             "715+"
## [22] "32,700-32,968"     "2,824-5,000"        "10,000-110,000"
## [25] "1,023+"            "300,000-500,000"    "2,175-2,204"
## [28] "8,210+"            "26,000-240,000"     "242,419-655,000"
## [31] "10,000-50,000"     "15,000-25,000"      "2,633-5,000"
## [34] "25,000-50,000"     "35,000-45,000"      "17,126-18,373"
## [37] "700-800"           "13,805-20,023"      "86,000-87,351"
## [40] "5,749-5,778"       "100,000-316,000"    "3,951+"
## [43] "59,259-62,013"     "320-600(estimate)"
```

```
# use regular expression here
convert_death_toll <- function(toll) {
  if (str_detect(toll, "\\d+\\s*-\\s*\\d+")) {
    nums <- str_extract_all(toll, "\\d+")[1] %>% as.numeric()
    return(mean(nums))
  } else if (str_detect(toll, "\\d+\\s*-\\s*\\d+")) {
    nums <- str_extract_all(toll, "\\d+")[1] %>% as.numeric()
    return(mean(nums))
  } else if (str_detect(toll, ">\\s*\\d+")) {
    return(as.numeric(str_extract(toll, "\\d+")))
  } else if (str_detect(toll, "\\d+")) {
    return(as.numeric(str_extract(toll, "\\d+")))
  }
}

death_toll_clean = round(sapply(disasters_clean$`Death toll`, convert_death_toll))
death_toll_clean[list_of_clean] # check the results of those irregular ones
```

```
##      6000-12000      20000+      12000-15000      75000-82000      6000-8000
##           9000          20000          13500          78500          7000
##      50000-220000      942-1900      29978-32610      2000-10000      258707-273407
##           135000          1421          31294          6000          266057
##      50000-100000+      105385-142800          4112+          3257-3800          2000-8000
##           75000          124092          4112          3528          5000
##      422499-4000000          3103+          6865-9300      10700-12000          5000+
##           2211250          3103          8082          11350          5000
##           715+      32700-32968          2824-5000      10000-110000          1023+
##           715          32834          3912          60000          1023
##      300000-500000          2175-2204          8210+      26000-240000      242419-655000
##           400000          2190          8210          133000          448710
##           10000-50000          15000-25000          2633-5000          25000-50000          35000-45000
##           30000          20000          3816          37500          40000
##           17126-18373          700-800          13805-20023          86000-87351          5749-5778
```

```
##          17750          750          16914          86676          5764
## 100000-316000      3951+   59259-62013      320-600
##          208000          3951          60636          460
```


```
disasters_clean$`Death toll` = death_toll_clean
disasters_clean
```

```
## # A tibble: 125 x 6
##   Year 'Death toll' Event 'Countries affected' Type Date
##   <int>      <dbl> <chr>      <chr>              <chr> <chr>
## 1 1900         9000 1900 Galveston hurricane United States Trop~ Sept~
## 2 1901         9500 1901 eastern United Stat~ United States Heat~ June~
## 3 1902        29000 1902 eruption of Mount P~ Martinique Volc~ Apri~
## 4 1903         3500 1903 Manzikert earthquake Turkey Eart~ Apri~
## 5 1904          400 1904 Sichuan earthquake China Eart~ Augu~
## 6 1905        20000 1905 Kangra earthquake India Eart~ Apri~
## 7 1906        15000 1906 Hong Kong typhoon Hong Kong,China Trop~ Sept~
## 8 1907        13500 1907 Qaratog earthquake Uzbekistan Eart~ Octo~
## 9 1908        78500 1908 Messina earthquake Italy Eart~ Dece~
## 10 1909         7000 1909 Borujerd earthquake Iran Eart~ Janu~
## # i 115 more rows
```

Task 3: Plot the data


```
# Convert the year to numeric
disasters_clean <- disasters_clean %>%
  mutate(Year = as.numeric(gsub("[^0-9]", "", `Year`)))

# Plot the death toll by year, color-coded by kind of disaster
ggplot(disasters_clean, aes(x = Year, y = `Death toll`, color = Type)) +
  geom_point() +
  labs(title = "Death Toll of Natural Disasters by Year",
       x = "Year",
       y = "Death Toll",
       color = "Kind of Disaster")
```



```
ggplot(disasters_clean %>% filter(Event != "1931 China floods"),
  aes(x = Year, y = `Death toll`, color = Type)) +
  geom_point() +
```

```
labs(title = "Death Toll of Natural Disasters by Year without one outlier",
     x = "Year",
     y = "Death Toll",
     color = "Kind of Disaster")
```



Q2

First we derive the form of gradient by computing the derivative:

$$\frac{\partial ||y - bx||^2}{\partial b} = 2 \left(\frac{\partial \sum (y_i - bx_i)}{\partial b} \right) = 2 \left(\frac{-x_i \sum (y_i - bx_i)}{n} \right)$$

```
# write the gradient descent function
gradient_descent <- function(x, y, learning_rate, num_iter) {
  b <- 0
  n <- length(x)

  for (i in 1:num_iter) {
    gradient <- -2 * sum(x * (y - b * x)) / n # compute gradient
    b <- b - learning_rate * gradient # update here
  }

  return(b)
}

# Test the function using randomly generated normal vectors
set.seed(8848)
n <- 100
x <- rnorm(n)
b <- 2
y <- b * x + rnorm(n)

S <- 1000

b_estimated <- gradient_descent(x, y, learning_rate = 0.01, num_iter = S)

# Compare
b
```

```
## [1] 2
```

```
b_estimated
```

```
## [1] 2.015827
```

```
b_est_all = c()

# To test different learning rates
test_learning_rates <- function(x, y, b, learning_rates, num_iter) {
  results <- data.frame(learning_rate = c(), estimated_b = c())

  for (lr in learning_rates) {
    b_est <- gradient_descent(x, y, lr, num_iter)
    # error <- abs(b - b_est)
    results <- rbind(results, data.frame(learning_rate = lr, estimated_b = b_est))
  }

  return(results)
}
```

Findings: The algorithm can perform well as long as we choose a reasonable value for the learning rate.

We can see from below that the learning rate should not be too small. A too-small step size can make it inefficient for the algorithm to explore and reach convergence or get stuck at a local min instead of global mean.

Meanwhile, we also do not want the step size to be too large at each update, which could cause our estimate to oscillate too much and miss the optimal point.

```
learning_rates <- seq(0.001, 0.1, by = 0.001)
results <- test_learning_rates(x, y, b_true, learning_rates, num_iter = S)

# Plot the results
ggplot(results, aes(x = learning_rate, y = estimated_b)) +
  geom_line() +
  labs(title = "Estimate vs Learning Rate", x = "Learning Rate", y = "Estimate")
```

