

322. Coin Change

Medium

5580

169

Add to List

Share

You are given coins of different denominations and a total amount of money *amount*. Write a function to compute the fewest number of coins that you need to make up that amount. If that amount of money cannot be made up by any combination of the coins, return *-1*.

You may assume that you have an infinite number of each kind of coin.

Example 1:

Input: coins = [1,2,5], amount = 11

Output: 3

Explanation: 11 = 5 + 5 + 1

Example 2:

Input: coins = [2], amount = 3

Output: -1

Example 3:

Input: coins = [1], amount = 0

Output: 0

Example 4:

Input: coins = [1], amount = 1

Output: 1

Example 5:

Input: coins = [1], amount = 2

Output: 2

Def: $dp[i] = \text{min coins to make up } i \text{ amount}$

Init: $dp[0] = 0$ $dp[i] = -1, i < 0$

Transition:

$dp[i] = \min_{\text{coin} \in \text{coins}} (dp[i - \text{coin}] + 1), i > 0$

Answer: $dp[n]$

Time Complexity: $O(n \times \# \text{coins})$

Space Complexity: $O(n \times \# \text{coins})$


```
1 class Solution {
2 public:
3     int coinChange(vector<int>& coins, int amount) {
4         vector<int> dp(amount + 1, INT_MAX);
5
6         // dp[0] = 0
7         dp[0] = 0;
8
9         // dp[i] = min(dp[i - coin] + 1 | coin \in coins), i > 0
10        for (int i = 1; i <= amount; i++) {
11            for (int coin : coins) {
12                if (i - coin < 0 || dp[i - coin] == -1) {
13                    continue;
14                }
15                dp[i] = min(dp[i], dp[i - coin] + 1);
16            }
17            if (dp[i] == INT_MAX) {
18                dp[i] = -1;
19            }
20        }
21
22        return dp[amount];
23    }
24};
```