

# Recaps of CHAPTER 1 Databases and Database Users

- **Database**
- **Database Management System (DBMS)**
- **Database System**

# Typical DBMS Functionality

- Define Database
- Manipulating
- Sharing & Concurrent access
- Protection or Security
- Maintenance
- Data Presentation and Visualization

# Main Characteristics of the Database Approach

- Self-describing
- Insulation between programs and data (program-data independence)
- Data Abstraction
- Support of multiple views of the data
- Sharing of data and multi-user transaction processing

# Database Users

- Actors on the Scene
  - Database administrators
  - Database Designers
  - End-users
  - System Analysts and Application Developers (software engineer)
- Workers behind the Scene
  - System Designers and Implementors
  - Tool Developers
  - Operators and Maintenance Personnel

# Recaps of CHAPTER 2 Database System Concepts and Architecture

- Data Model
  - Constructs
  - Constraints
  - Operations
- Categories of Data Models
  - Conceptual (high-level, semantic) data models
  - Physical (low-level, internal) data models
  - Implementation (or representational) data model
  - Self-Describing Data Models

# Schemas versus Instances

- Three-Schema Architecture
  - Internal schema
  - Conceptual schema
  - External schema
- Data Independence
  - Logical Data Independence
  - Physical Data Independence

# DBMS Languages and interfaces

- Languages
  - Data Definition Language (DDL)
  - Data Manipulation Language (DML)
- Interfaces
  - Stand-alone query language interfaces
  - Programmer interfaces for embedding DML in programming languages
  - User-friendly interfaces
  - Apps for Mobile devices

# Architectures

- Centralized
- Client-Server Architectures
  - Two-tier
  - Three-tier



# CHAPTER 5

## The Relational Data Model and Relational Database Constraints

# Chapter Outline


- Relational Model Concepts
- Relational Model Constraints and Relational Database Schemas
- Update Operations and Dealing with Constraint Violations

# Relational Model Concepts

- The relational Model of Data is based on the concept of a *Relation*
  - The strength of the relational approach to data management comes from the formal foundation provided by the theory of relations
- We review the essentials of the *formal relational model* in this chapter
- In *practice*, there is a *standard model* based on SQL – this is described in Chapters 6 and 7 as a language
- Note: There are several important differences between the *formal* model and the *practical* model, as we shall see

# Relational Model Concepts

- A Relation is a mathematical concept based on the ideas of sets
- The model was first proposed by Dr. E.F. Codd of IBM Research in 1970 in the following paper:
  - "A Relational Model for Large Shared Data Banks," Communications of the ACM, June 1970



Edgar Frank Codd,  
PhD, University of  
Oxford,  
University of  
Michigan, IBM

# Relational Model Concepts (cont.)


- This paper caused a major revolution in the field of database management and earned Dr. Codd the coveted ACM Turing Award in 1981

# Informal Definitions

- Informally, a **relation** looks like a **table** of values.
- A relation typically contains a **set of rows**.
- The data elements in each **row** represent certain facts that correspond to a real-world **entity** or **relationship**
  - In the formal model, rows are called **tuples**

# Example of a Relation

- Each **column** has a column header that gives an indication of the meaning of the data items in that column
  - In the formal model, the column header is called an **attribute name** (or just **attribute**)



**Figure 5.1**

The attributes and tuples of a relation STUDENT.

# Relation

- ✗ A relation is a named, two-dimensional table of data.
- ✗ A table consists of rows (records) and columns (attribute or field).
- ✗ Requirements for a table to qualify as a relation:
  - + It must have a unique name.
  - + Every attribute value must be atomic (not multivalued, not composite).
  - + Every row must be unique (can't have two rows with exactly the same values for all their fields).
  - + Attributes (columns) in tables must have unique names.
  - + The order of the columns must be irrelevant.
  - + The order of the rows must be irrelevant.



# Informal Definitions of Key

- Key of a Relation:
  - Each row has a value of a data item (or set of items) that uniquely identifies that row in the table
    - Called the *key*
  - Sometimes row-ids or sequential numbers are assigned as keys to identify the rows in a table
    - Called *artificial key* or *surrogate key*

# Informal Definitions of Key (cont.)

- In the STUDENT table, which attribute (a set of attributes) can be used as key?

Name	Ssn	Home_phone	Address	Office_phone	Age	Gpa
Benjamin Bayer	305-61-2435	373-1616	2918 Bluebonnet Lane	NULL	19	3.21
Chung-cha Kim	381-62-1245	375-4409	125 Kirby Road	NULL	18	2.89
Dick Davidson	422-11-2320	NULL	3452 Elgin Road	749-1253	25	3.53
Rohan Panchal	489-22-1100	376-9821	265 Lark Lane	749-6492	28	3.93
Barbara Benson	533-69-1238	839-8461	7384 Fontana Lane	NULL	19	3.25

# Formal Definitions - Schema

- The **Schema** (or description) of a Relation R:
  - Denoted by  $R(A_1, A_2, \dots, A_n)$
  - R is the **name** of the relation
  - The **attributes** of the relation are  $A_1, A_2, \dots, A_n$
- Example:  
***CUSTOMER (Cust-id, Cust-name, Address, Phone#)***
  - CUSTOMER is the relation name
  - Defined over the four attributes: Cust-id, Cust-name, Address, Phone#
- Each attribute has a **domain** or a set of valid values.
  - For example, the domain of Cust-id is 6 digit numbers.

# Formal Definitions - Tuple

- A **tuple** is an ordered set of values (enclosed in angled brackets '< ... >')
- Each value is derived from an appropriate *domain*.
- A row in the CUSTOMER relation is a 4-tuple and would consist of four values, for example:
  - <632895, "John Smith", "101 Main St. Atlanta, GA 30332", "(404) 894-2000">
  - This is called a 4-tuple as it has 4 values
  - A tuple (row) in the CUSTOMER relation.
- A relation is a **set** of such tuples (rows)

# Formal Definitions - Domain

- A **domain** has a logical definition:
  - Example: “USA\_phone\_numbers” are the set of 10 digit phone numbers valid in the U.S.
- A domain also has a data-type or a format defined for it.
  - The USA\_phone\_numbers may have a format: (ddd)ddd-dddd where each d is a decimal digit.
  - Dates have various formats such as year, month, date formatted as yyyy-mm-dd, or as dd mm,yyyy etc.
- The attribute name designates the role played by a domain in a relation:
  - Used to interpret the meaning of the data elements corresponding to that attribute
  - Example: The domain Date may be used to define two attributes named “Invoice-date” and “Payment-date” with different meanings

# Formal Definitions - State

- The **relation state** is a subset of the Cartesian product of the domains of its attributes
  - each domain contains the set of all possible values the attribute can take.
- Example: attribute Cust-name is defined over the domain of character strings of maximum length 25
  - $\text{dom}(\text{Cust-name})$  is `varchar(25)`
- The role these strings play in the CUSTOMER relation is that of the *name of a customer*.

# Formal Definitions - Example

- Let  $R(A1, A2)$  be a relation schema:
  - Let  $\text{dom}(A1) = \{0,1\}$
  - Let  $\text{dom}(A2) = \{a,b,c\}$
- Then:  $\text{dom}(A1) \times \text{dom}(A2)$  is all possible combinations:

# Formal Definitions - Example

- Let  $R(A1, A2)$  be a relation schema:
  - Let  $\text{dom}(A1) = \{0,1\}$
  - Let  $\text{dom}(A2) = \{a,b,c\}$
- Then:  $\text{dom}(A1) \times \text{dom}(A2)$  is all possible combinations:  
 $\{ \langle 0,a \rangle , \langle 0,b \rangle , \langle 0,c \rangle , \langle 1,a \rangle , \langle 1,b \rangle , \langle 1,c \rangle \}$
- Let  $r(R) = \{ \langle 0,a \rangle , \langle 0,b \rangle , \langle 1,c \rangle \}$
- Is  $r(R)$  a state of  $R$ , i.e.,  $r(R) \subset \text{dom}(A1) \times \text{dom}(A2)$ ?



# Formal Definitions - Example

- Let  $R(A1, A2)$  be a relation schema:
  - Let  $\text{dom}(A1) = \{0,1\}$
  - Let  $\text{dom}(A2) = \{a,b,c\}$
- Then:  $\text{dom}(A1) \times \text{dom}(A2)$  is all possible combinations:  
 $\{ \langle 0,a \rangle , \langle 0,b \rangle , \langle 0,c \rangle , \langle 1,a \rangle , \langle 1,b \rangle , \langle 1,c \rangle \}$
- The relation state  $r(R) \subset \text{dom}(A1) \times \text{dom}(A2)$
- For example:  $r(R) = \{ \langle 0,a \rangle , \langle 0,b \rangle , \langle 1,c \rangle \}$ 
  - this is one possible state (or “population” or “extension”)  $r$  of the relation  $R$ , defined over  $A1$  and  $A2$ .
  - It has three 2-tuples:  $\langle 0,a \rangle , \langle 0,b \rangle , \langle 1,c \rangle$

# Formal Definitions - Summary

- Formally,
  - Given  $R(A_1, A_2, \dots, A_n)$
  - $r(R) \subset \text{dom}(A_1) \times \text{dom}(A_2) \times \dots \times \text{dom}(A_n)$
- $R$  is the **name** of the relation
- $R(A_1, A_2, \dots, A_n)$  is the **schema** of the relation
- $A_1, A_2, \dots, A_n$  are the **attributes** of the relation
- $r(R)$ : a specific **state** (or "value" or "population") of relation  $R$  – this is a *set of tuples* (rows)
  - $r(R) = \{t_1, t_2, \dots, t_n\}$  where each  $t_i$  is an  $n$ -tuple
  - $t_i = \langle v_1, v_2, \dots, v_n \rangle$  where each  $v_j$  *element-of*  $\text{dom}(A_j)$

# Definition Summary

<u>Informal Terms</u>		<u>Formal Terms</u>
Table		Relation
Column Header		Attribute
All possible Column Values		Domain
Row		Tuple
Table Definition		Schema of a Relation
Populated Table		State of the Relation

# Revisit relation STUDENT

Relation Name

**STUDENT**

Attributes

Name	Ssn	Home_phone	Address	Office_phone	Age	Gpa
Benjamin Bayer	305-61-2435	373-1616	2918 Bluebonnet Lane	NULL	19	3.21
Chung-cha Kim	381-62-1245	375-4409	125 Kirby Road	NULL	18	2.89
Dick Davidson	422-11-2320	NULL	3452 Elgin Road	749-1253	25	3.53
Rohan Panchal	489-22-1100	376-9821	265 Lark Lane	749-6492	28	3.93
Barbara Benson	533-69-1238	839-8461	7384 Fontana Lane	NULL	19	3.25

Tuples

**Figure 5.1**  
The attributes and tuples of a relation STUDENT.

# Characteristics Of Relations

- Ordering of tuples in a relation  $r(R)$ :
  - The tuples are *not considered to be ordered*, even though they appear to be in the tabular form.
- Ordering of attributes in a relation schema  $R$  (and of values within each tuple):
  - We will consider the attributes in  $R(A_1, A_2, \dots, A_n)$  and the values in  $t = \langle v_1, v_2, \dots, v_n \rangle$  to be ordered .
    - (However, a more general alternative definition of relation does not require this ordering. It includes both the name and the value for each of the attributes ).
    - Example:  $t = \{ \langle \text{name}, \text{"John"} \rangle, \langle \text{SSN}, 123456789 \rangle \}$
    - This representation may be called as “self-describing”.

# Same state as previous Figure (but with different order of tuples)

**Figure 5.2**

The relation STUDENT from Figure 5.1 with a different order of tuples.

**STUDENT**

Name	Ssn	Home_phone	Address	Office_phone	Age	Gpa
Dick Davidson	422-11-2320	NULL	3452 Elgin Road	749-1253	25	3.53
Barbara Benson	533-69-1238	839-8461	7384 Fontana Lane	NULL	19	3.25
Rohan Panchal	489-22-1100	376-9821	265 Lark Lane	749-6492	28	3.93
Chung-cha Kim	381-62-1245	375-4409	125 Kirby Road	NULL	18	2.89
Benjamin Bayer	305-61-2435	373-1616	2918 Bluebonnet Lane	NULL	19	3.21

# Characteristics Of Relations

- Values in a tuple:
  - All values are considered atomic (indivisible).
  - Each value in a tuple must be from the domain of the attribute for that column
    - If tuple  $t = \langle v_1, v_2, \dots, v_n \rangle$  is a tuple (row) in the relation state  $r$  of  $R(A_1, A_2, \dots, A_n)$
    - Then each  $v_i$  must be a value from  $dom(A_i)$
- A special **null** value is used to represent values that are unknown or not available or inapplicable in certain tuples.

# Characteristics Of Relations

- Notation:
  - We refer to **component values** of a tuple  $t$  by:
    - $t[A_i]$  or  $t.A_i$
    - This is the value  $v_i$  of attribute  $A_i$  for tuple  $t$
  - Similarly,  $t[A_u, A_v, \dots, A_w]$  refers to the subtuple of  $t$  containing the values of attributes  $A_u, A_v, \dots, A_w$ , respectively in  $t$



# CONSTRAINTS

Constraints determine which values are permissible and which are not in the database.

They are of three main types:

1. **Inherent or Implicit Constraints:** These are based on the data model itself. (E.g., relational model does not allow a list as a value for any attribute)
2. **Schema-based or Explicit Constraints:** They are expressed in the schema by using the facilities provided by the model. (E.g., max. cardinality ratio constraint in the ER model)
3. **Application based or semantic constraints:** These are beyond the expressive power of the model and must be specified and enforced by the application programs.

# Relational Integrity Constraints

- Constraints are **conditions** that must hold on **all** valid relation states.
- There are three *main types* of (explicit schema-based) constraints that can be expressed in the relational model:
  - **Key** constraints
  - **Entity integrity** constraints
  - **Referential integrity** constraints
- Another schema-based constraint is the **domain** constraint
  - Every value in a tuple must be from the *domain of its attribute* (or it could be **null**, if allowed for that attribute)

# Key Constraints

- **Superkey of R:**
  - Is a set of attributes SK of R with the following condition:
    - No two tuples in any valid relation state  $r(R)$  will have the same value for SK
    - That is, for any distinct tuples  $t1$  and  $t2$  in  $r(R)$ ,  $t1[SK] \neq t2[SK]$
    - This condition must hold in *any valid state*  $r(R)$

# Revisit Student Relation

Name	Ssn	Home_phone	Address	Office_phone	Age	Gpa
Benjamin Bayer	305-61-2435	373-1616	2918 Bluebonnet Lane	NULL	19	3.21
Chung-cha Kim	381-62-1245	375-4409	125 Kirby Road	NULL	18	2.89
Dick Davidson	422-11-2320	NULL	3452 Elgin Road	749-1253	25	3.53
Rohan Panchal	489-22-1100	376-9821	265 Lark Lane	749-6492	28	3.93
Barbara Benson	533-69-1238	839-8461	7384 Fontana Lane	NULL	19	3.25

# Key Constraints (cont.)

- A superkey can have redundant attributes. A more useful concept is that of a *key*, which has no redundancy.
- **Key of R:**
  - A "minimal" superkey
  - That is, a key is a superkey  $K$  such that removal of any attribute from  $K$  results in a set of attributes that is not a superkey (does not possess the superkey uniqueness property)

# Questions

- Which of the following are correct?
  - *Any key is a superkey*
  - *Any superkey is a key*
  - *Any set of attributes that includes a key is a superkey*
  - *A minimal superkey is also a key*

# Key Constraints (continued)

**CAR**

<u>License_number</u>	Engine_serial_number	Make	Model	Year
Texas ABC-739	A69352	Ford	Mustang	02
Florida TVP-347	B43696	Oldsmobile	Cutlass	05
New York MPO-22	X83554	Oldsmobile	Delta	01
California 432-TFY	C43742	Mercedes	190-D	99
California RSK-629	Y82935	Toyota	Camry	04
Texas RSK-629	U028365	Jaguar	XJS	04

**Figure 5.4**

The CAR relation, with two candidate keys: License\_number and Engine\_serial\_number.

# Key Constraints (continued)

- If a relation has several **candidate keys**, one is chosen arbitrarily to be the **primary key**.
  - The primary key attributes are underlined.
- Example: Consider the CAR relation schema:
  - CAR(State, Reg#, SerialNo, Make, Model, Year)
  - We chose SerialNo as the primary key
- The primary key value is used to *uniquely identify* each tuple in a relation
  - Provides the tuple identity
- Also used to *reference* the tuple from another tuple
  - General rule: Choose as primary key the smallest of the candidate keys (in terms of size)
  - Not always applicable – choice is sometimes subjective



# CAR table with two candidate keys – LicenseNumber chosen as Primary Key

**CAR**

<u>License_number</u>	Engine_serial_number	Make	Model	Year
Texas ABC-739	A69352	Ford	Mustang	02
Florida TVP-347	B43696	Oldsmobile	Cutlass	05
New York MPO-22	X83554	Oldsmobile	Delta	01
California 432-TFY	C43742	Mercedes	190-D	99
California RSK-629	Y82935	Toyota	Camry	04
Texas RSK-629	U028365	Jaguar	XJS	04

**Figure 5.4**

The CAR relation, with two candidate keys: License\_number and Engine\_serial\_number.

# Relational Database Schema

- **Relational Database Schema:**
  - A set  $S$  of relation schemas that belong to the same database.
  - $S$  is the name of the whole **database schema**
  - $S = \{R_1, R_2, \dots, R_n\}$  and a set of integrity constraints  $IC$ .
  - $R_1, R_2, \dots, R_n$  are the names of the individual **relation schemas** within the database  $S$
- Following slide shows a COMPANY database schema with 6 relation schemas

# COMPANY Database Schema

## EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
-------	-------	-------	------------	-------	---------	-----	--------	-----------	-----

## DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
-------	----------------	---------	----------------

## DEPT\_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
----------------	------------------

## PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
-------	----------------	-----------	------

## WORKS\_ON

<u>Essn</u>	<u>Pno</u>	Hours
-------------	------------	-------

## DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
-------------	-----------------------	-----	-------	--------------

**Figure 5.5**  
Schema diagram for  
the COMPANY  
relational database  
schema.

# Relational Database State

- A **relational database state** DB of S is a set of relation states  $DB = \{r_1, r_2, \dots, r_m\}$  such that each  $r_i$  is a state of  $R_i$  and such that the  $r_i$  relation states satisfy the integrity constraints specified in IC.
- A relational database *state* is sometimes called a relational database *snapshot* or *instance*.
- We will not use the term *instance* since it also applies to single tuples.
- A database state that does not meet the constraints is an invalid state

# Populated database state

- Each *relation* will have many tuples in its current relation state
- The *relational database state* is a union of all the individual relation states
- Whenever the database is changed, a new state arises
- Basic operations for changing the database:
  - INSERT a new tuple in a relation
  - DELETE an existing tuple from a relation
  - MODIFY an attribute of an existing tuple
- Next slide (Fig. 5.6) shows an example state for the COMPANY database schema shown in Fig. 5.5.

One possible database state for the COMPANY relational database schema.

# Populated database state for COMPANY

## EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

## DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

## DEPT\_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

## WORKS\_ON

<u>Essn</u>	<u>Pno</u>	Hours
123456789	1	32.5
123456789	2	7.5
666884444	3	40.0
453453453	1	20.0
453453453	2	20.0
333445555	2	10.0
333445555	3	10.0
333445555	10	10.0
333445555	20	10.0
999887777	30	30.0
999887777	10	10.0
987987987	10	35.0
987987987	30	5.0
987654321	30	20.0
987654321	20	15.0
888665555	20	NULL

## PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
ProductX	1	Bellaire	5
ProductY	2	Sugarland	5
ProductZ	3	Houston	5
Computerization	10	Stafford	4
Reorganization	20	Houston	1
Newbenefits	30	Stafford	4

## DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
333445555	Alice	F	1986-04-05	Daughter
333445555	Theodore	M	1983-10-25	Son
333445555	Joy	F	1958-05-03	Spouse
987654321	Abner	M	1942-02-28	Spouse
123456789	Michael	M	1988-01-04	Son
123456789	Alice	F	1988-12-30	Daughter
123456789	Elizabeth	F	1967-05-05	Spouse

# Entity Integrity

## ■ Entity Integrity:

- The *primary key attributes* PK of each relation schema R in S cannot have null values in any tuple of  $r(R)$ .
  - This is because primary key values are used to *identify* the individual tuples.
  - $t[PK] \neq \text{null}$  for any tuple  $t$  in  $r(R)$
  - If PK has several attributes, null is not allowed in any of these attributes
- Note: Other attributes of R may be constrained to disallow null values, even though they are not members of the primary key.

# Referential Integrity

- A constraint involving **two** relations
  - The previous constraints involve a single relation.
- Used to specify a **relationship** among tuples in two relations:
  - The **referencing relation** and the **referenced relation**.



One possible database state for the COMPANY relational database schema.

# Referential Integrity Constraints for COMPANY database

## EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

## DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

## DEPT\_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

## WORKS\_ON

<u>Essn</u>	<u>Pno</u>	Hours
123456789	1	32.5
123456789	2	7.5
666884444	3	40.0
453453453	1	20.0
453453453	2	20.0
333445555	2	10.0
333445555	3	10.0
333445555	10	10.0
333445555	20	10.0
999887777	30	30.0
999887777	10	10.0
987987987	10	35.0
987987987	30	5.0
987654321	30	20.0
987654321	20	15.0
888665555	20	NULL

## PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
ProductX	1	Bellaire	5
ProductY	2	Sugarland	5
ProductZ	3	Houston	5
Computerization	10	Stafford	4
Reorganization	20	Houston	1
Newbenefits	30	Stafford	4

## DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
333445555	Alice	F	1986-04-05	Daughter
333445555	Theodore	M	1983-10-25	Son
333445555	Joy	F	1958-05-03	Spouse
987654321	Abner	M	1942-02-28	Spouse
123456789	Michael	M	1988-01-04	Son
123456789	Alice	F	1988-12-30	Daughter
123456789	Elizabeth	F	1967-05-05	Spouse


# Referential Integrity

- Tuples in the **referencing relation** R1 have attributes FK (called **foreign key** attributes) that reference the primary key attributes PK of the **referenced relation** R2.
  - A tuple t1 in R1 is said to **reference** a tuple t2 in R2 if  $t1[FK] = t2[PK]$ .
- A referential integrity constraint can be displayed in a relational database schema as a directed arc from R1.FK to R2.

# Referential Integrity Constraints for COMPANY database

**Figure 5.7**

Referential integrity constraints displayed on the COMPANY relational database schema.



# Referential Integrity (or foreign key) Constraint

- Statement of the constraint
  - The value in the foreign key column (or columns) FK of the the **referencing relation** R1 can be **either**:
    - (1) a value of an existing primary key value of a corresponding primary key PK in the **referenced relation** R2, or
    - (2) a **null**.
- In case (2), the FK in R1 should **not** be a part of its own primary key.

# Exercise

- Consider the following relations for a database that keeps track of business trips of salespersons in a sales office:

SALESPERSON (SSN, Name, Start\_Year, Dept\_No)

TRIP (SSN, From\_City, To\_City, Departure\_Date, Return\_Date, Trip\_ID)

EXPENSE (Trip\_ID, Account#, Amount)

- Specify the foreign keys for this schema, stating any assumptions you make.


# Displaying a relational database schema and its constraints

- Each relation schema can be displayed as a row of attribute names
- The name of the relation is written above the attribute names
- The primary key attribute (or attributes) will be underlined
- A foreign key (referential integrity) constraints is displayed as a directed arc (arrow) from the foreign key attributes to the referenced table
  - Can also point the the primary key of the referenced relation for clarity
- Next slide shows the COMPANY relational schema diagram with referential integrity constraints

# Referential Integrity Constraints for COMPANY database

**Figure 5.7**

Referential integrity constraints displayed on the COMPANY relational database schema.



# Other Types of Constraints

- Semantic Integrity Constraints:
  - based on application semantics and cannot be expressed by the model per se
  - Example: “the max. no. of hours per employee for all projects he or she works on is 56 hrs per week”
- A **constraint specification** language may have to be used to express these
- SQL-99 allows **CREATE TRIGGER** and **CREATE ASSERTION** to express some of these semantic constraints
- Keys, Permissibility of Null values, Candidate Keys (Unique in SQL), Foreign Keys, Referential Integrity etc. are expressed by the **CREATE TABLE** statement in SQL.



# Update Operations on Relations

- INSERT a tuple.
- DELETE a tuple.
- MODIFY a tuple.
- Integrity constraints should not be violated by the update operations.
- Several update operations may have to be grouped together.
- Updates may **propagate** to cause other updates automatically. This may be necessary to maintain integrity constraints.

# Update Operations on Relations

- In case of integrity violation, several actions can be taken:
  - Cancel the operation that causes the violation (RESTRICT or REJECT option)
  - Perform the operation but inform the user of the violation
  - Trigger additional updates so the violation is corrected (CASCADE option, SET NULL option)
  - Execute a user-specified error-correction routine

# Possible violations for each operation

- INSERT may violate any of the constraints:
  - Domain constraint:
    - if one of the attribute values provided for the new tuple is not of the specified attribute domain
  - Key constraint:
    - if the value of a key attribute in the new tuple already exists in another tuple in the relation
  - Referential integrity:
    - if a foreign key value in the new tuple references a primary key value that does not exist in the referenced relation
  - Entity integrity:
    - if the primary key value is null in the new tuple

One possible database state for the COMPANY relational database schema.

## Discuss *all* integrity constraints violated by following operations

■(a) Insert < 'Robert', 'F', 'Scott', '943775543', '21-JUN-42', '2365 Newcastle Rd, Bellaire, TX', M, 58000, '888665555', 1 > into EMPLOYEE.

■(b) Insert < 'ProductA', 4, 'Bellaire', 2 > into PROJECT.

■(c) Insert < 'Production', 4, '943775543', '01-OCT-88' > into DEPARTMENT.

■(d) Insert < '677678989', null, '40.0' > into WORKS\_ON.

■(e) Insert < '453453453', 'John', M, '12-DEC-60', 'SPOUSE' > into DEPENDENT.

EMPLOYEE

Fname	Minit	Lname	Ssn	Bdate	Address	Sex	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

DEPARTMENT

Dname	Dnumber	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

DEPT\_LOCATIONS

Dnumber	Dlocation
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

WORKS\_ON

Essn	Pno	Hours
123456789	1	32.5
123456789	2	7.5
666884444	3	40.0
453453453	1	20.0
453453453	2	20.0
333445555	2	10.0
333445555	3	10.0
333445555	10	10.0
333445555	20	10.0
999887777	30	30.0
999887777	10	10.0
987987987	10	35.0
987987987	30	5.0
987654321	30	20.0
987654321	20	15.0
888665555	20	NULL

PROJECT

Pname	Pnumber	Plocation	Dnum
ProductX	1	Bellaire	5
ProductY	2	Sugarland	5
ProductZ	3	Houston	5
Computerization	10	Stafford	4
Reorganization	20	Houston	1
Newbenefits	30	Stafford	4

DEPENDENT

Essn	Dependent_name	Sex	Bdate	Relationship
333445555	Alice	F	1986-04-05	Daughter
333445555	Theodore	M	1983-10-25	Son
333445555	Joy	F	1958-05-03	Spouse
987654321	Abner	M	1942-02-28	Spouse
123456789	Michael	M	1988-01-04	Son
123456789	Alice	F	1988-12-30	Daughter
123456789	Elizabeth	F	1967-05-05	Spouse

# Possible violations for each operation

- DELETE may violate only referential integrity:
  - If the primary key value of the tuple being deleted is referenced from other tuples in the database
    - Can be remedied by several actions: RESTRICT, CASCADE, SET NULL (see Chapter 6 for more details)
      - RESTRICT option: reject the deletion
      - CASCADE option: propagate the new primary key value into the foreign keys of the referencing tuples
      - SET NULL option: set the foreign keys of the referencing tuples to NULL
  - One of the above options must be specified during database design for each foreign key constraint

One possible database state for the COMPANY relational database schema.

## Discuss *all* integrity constraints violated by following operations

■ (f) Delete the WORKS\_ON tuples with ESSN='333445555'.

■

■ (g) Delete the EMPLOYEE tuple with SSN='987654321'.

■

■ (h) Delete the PROJECT tuple with PNAME='ProductX'.

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

DEPT\_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

WORKS\_ON

<u>Essn</u>	<u>Pno</u>	Hours
123456789	1	32.5
123456789	2	7.5
666884444	3	40.0
453453453	1	20.0
453453453	2	20.0
333445555	2	10.0
333445555	3	10.0
333445555	10	10.0
333445555	20	10.0
999887777	30	30.0
999887777	10	10.0
987987987	10	35.0
987987987	30	5.0
987654321	30	20.0
987654321	20	15.0
888665555	20	NULL

PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
ProductX	1	Bellaire	5
ProductY	2	Sugarland	5
ProductZ	3	Houston	5
Computerization	10	Stafford	4
Reorganization	20	Houston	1
Newbenefits	30	Stafford	4

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
333445555	Alice	F	1986-04-05	Daughter
333445555	Theodore	M	1983-10-25	Son
333445555	Joy	F	1958-05-03	Spouse
987654321	Abner	M	1942-02-28	Spouse
123456789	Michael	M	1988-01-04	Son
123456789	Alice	F	1988-12-30	Daughter
123456789	Elizabeth	F	1967-05-05	Spouse

# Possible violations for each operation

- UPDATE may violate domain constraint and NOT NULL constraint on an attribute being modified
- Any of the other constraints may also be violated, depending on the attribute being updated:
  - Updating the primary key (PK):
    - Similar to a DELETE followed by an INSERT
    - Need to specify similar options to DELETE
  - Updating a foreign key (FK):
    - May violate referential integrity
  - Updating an ordinary attribute (neither PK nor FK):
    - Can only violate domain constraints



One possible database state for the COMPANY relational database schema.

## Discuss *all* integrity constraints violated by following operations

- (i) Modify the MGRSSN and MGRSTARTDATE of the DEPARTMENT tuple with DNUMBER=5 to '123456789' and '01-OCT-88', respectively.
- 
- (j) Modify the SUPERSSN attribute of the EMPLOYEE tuple with SSN= '999887777' to '943775543'.
- 
- (k) Modify the HOURS attribute of the WORKS\_ON tuple with ESSN= '999887777' and PNO= 10 to '5.0'.

EMPLOYEE

Fname	Minit	Lname	<u>Ssn</u>	Bdate	Address	Sex	Salary	Super_ssn	Dno
John	B	Smith	123456789	1965-01-09	731 Fondren, Houston, TX	M	30000	333445555	5
Franklin	T	Wong	333445555	1955-12-08	638 Voss, Houston, TX	M	40000	888665555	5
Alicia	J	Zelaya	999887777	1968-01-19	3321 Castle, Spring, TX	F	25000	987654321	4
Jennifer	S	Wallace	987654321	1941-06-20	291 Berry, Bellaire, TX	F	43000	888665555	4
Ramesh	K	Narayan	666884444	1962-09-15	975 Fire Oak, Humble, TX	M	38000	333445555	5
Joyce	A	English	453453453	1972-07-31	5631 Rice, Houston, TX	F	25000	333445555	5
Ahmad	V	Jabbar	987987987	1969-03-29	980 Dallas, Houston, TX	M	25000	987654321	4
James	E	Borg	888665555	1937-11-10	450 Stone, Houston, TX	M	55000	NULL	1

DEPARTMENT

Dname	<u>Dnumber</u>	Mgr_ssn	Mgr_start_date
Research	5	333445555	1988-05-22
Administration	4	987654321	1995-01-01
Headquarters	1	888665555	1981-06-19

DEPT\_LOCATIONS

<u>Dnumber</u>	<u>Dlocation</u>
1	Houston
4	Stafford
5	Bellaire
5	Sugarland
5	Houston

WORKS\_ON

<u>Essn</u>	<u>Pno</u>	Hours
123456789	1	32.5
123456789	2	7.5
666884444	3	40.0
453453453	1	20.0
453453453	2	20.0
333445555	2	10.0
333445555	3	10.0
333445555	10	10.0
333445555	20	10.0
999887777	30	30.0
999887777	10	10.0
987987987	10	35.0
987987987	30	5.0
987654321	30	20.0
987654321	20	15.0
888665555	20	NULL

PROJECT

Pname	<u>Pnumber</u>	Plocation	Dnum
ProductX	1	Bellaire	5
ProductY	2	Sugarland	5
ProductZ	3	Houston	5
Computerization	10	Stafford	4
Reorganization	20	Houston	1
Newbenefits	30	Stafford	4

DEPENDENT

<u>Essn</u>	<u>Dependent_name</u>	Sex	Bdate	Relationship
333445555	Alice	F	1986-04-05	Daughter
333445555	Theodore	M	1983-10-25	Son
333445555	Joy	F	1958-05-03	Spouse
987654321	Abner	M	1942-02-28	Spouse
123456789	Michael	M	1988-01-04	Son
123456789	Alice	F	1988-12-30	Daughter
123456789	Elizabeth	F	1967-05-05	Spouse



# Summary

- Presented Relational Model Concepts
  - Definitions
  - Characteristics of relations
- Discussed Relational Model Constraints and Relational Database Schemas
  - Domain constraints
  - Key constraints
  - Entity integrity
  - Referential integrity
- Described the Relational Update Operations and Dealing with Constraint Violations

# Reading

- Chapter 8 The Relational Algebra and Relational Calculus

# In-Class Exercise

(Taken from Exercise 5.15)

Consider the following relations for a database that keeps track of student enrollment in courses and the books adopted for each course:

STUDENT(SSN, Name, Major, Bdate)

COURSE(Course#, Cname, Dept)

ENROLL(SSN, Course#, Quarter, Grade)

BOOK\_ADOPTION(Course#, Quarter, Book\_ISBN)

TEXT(Book\_ISBN, Book\_Title, Publisher, Author)

**Draw a relational schema diagram specifying the foreign keys for this schema.**