

Structural Materials & Resilience Summary

INVESTOR TIER 2 · STRUCTURAL & MATERIALS

Structural Materials & Resilience Summary

A summary of the structural strategy, primary materials, and resilience philosophy adopted across all four SHER residential product types. This is a design-intent summary — not a structural engineer's report or independent certification.

Professional limitation: This document is a design-intent summary drawn from SHER's owner-approved Gate 4 technical documents (CTA-005, VTA-004, CNA-004). It does not constitute structural engineering certification, an engineer's opinion, or confirmation of regulatory compliance. Detailed structural design, geotechnical assessment, and professional certification will be completed as part of the DCA planning submission and construction documentation process.

1. Structural Philosophy

SHER's structural approach is governed by four principles embedded in the Design Charter (SHER-DNA-001-R02):

- Hurricane resilience** — every structure must sustain a continuous, engineered load path from roof to foundation, designed to the Saint Lucia Building Code wind load requirements. No decorative element may compromise the structural load path.
- Low site impact** — foundation systems are selected to minimise site disturbance, soil compaction, and drainage impact. Raised-floor or pier-and-pad systems are preferred where ground conditions allow.
- Authentic natural materials** — structural and finish materials are selected for ecological compatibility, long-term durability in a tropical marine environment, and honest weathering. Synthetic cladding systems are excluded.
- Maintainability** — all structural and MEP assemblies must be inspectable, accessible for maintenance, and repairable without specialist plant. No embedded systems that cannot be replaced within normal operational maintenance.

2. Cottage Type A — Structural Strategy

Hillside Cottage (Type A) · 6 Units · C-01 to C-06

GATE 4 COMPLETE

PRIMARY STRUCTURE

Frame: Marine-protected modular steel posts and beams — hot-dip galvanised or zinc-rich primer + marine epoxy + UV topcoat. Bolted connections, inspectable, isolated from incompatible materials to prevent galvanic corrosion.

Secondary frame: Treated timber or engineered timber — softens the steel, supports wall panels, decking, ceilings, and screens.

Foundation: Light-touch piers, pads, or micro-piles — type confirmed by geotechnical and structural engineer per plot. Raised construction to protect terrain and drainage.

ROOF & ENVELOPE

Roof form: Butterfly or split-butterfly — the signature Cottage Type A roof language. Standing-seam or concealed-fix metal in dark bronze, charcoal, or green-black tone. Deep overhangs for shade and wall protection.

Hurricane connections: Engineer-designed uplift connections at every rafter/purlin-to-frame junction. No reliance on gravity or adhesive-only connections at roof level.

Wall system: Natural stone base, lime/mineral render panels, or stone/timber combination. No synthetic cladding.

Primary finish materials: Butterfly roof (metal) · Marine steel primary frame · Timber secondary frame and deck · Natural stone / locally sourced stone · Lime render or mineral plaster · Premium hardwood or thermally modified timber · Engineered timber floors

3. Villa Type A — Structural Strategy

Villa Type A · 5 Units · V-01 to V-05

GATE 4 COMPLETE

PRIMARY STRUCTURE

Frame: Marine-grade structural system — steel, reinforced masonry, or hybrid as determined by structural engineer for hurricane-rated performance. Primary structural strategy to be confirmed by engineer based on slope, soil, and drainage conditions at each villa plot.

Foundation: Confirmed by geotechnical survey per plot. Continuous load path from roof to foundation required.

ROOF & ENVELOPE

Roof form: Butterfly or mono-pitch — confirmed in detailed design. Hurricane-tied structure with engineer-designed uplift connections. Metal standing-seam or concealed-fix finish in dark bronze or charcoal tone.

Wall system: Natural stone base, lime/mineral render, or stone/timber combination. All exterior materials to weather authentically.

Pool: Private plunge or lap pool at each villa position. Pool edge, overflow, and landscape integration confirmed in detailed design.

Primary finish materials: Metal roof · Timber frame and cladding · Natural stone · Lime/mineral render · Clay brick (where structurally appropriate) · Engineered timber floors · Stone or porcelain slab bathrooms

4. Condo Type A — Structural Strategy

Condo Type A · 8 Units · Lot E

GATE 4 COMPLETE

PRIMARY STRUCTURE — STEEL I-BEAM FRAME

The Condo Type A adopts a **concealed steel I-beam primary frame** — the structural strategy that distinguishes it from the cottage and villa products. The I-beam frame provides maximum clear-span flexibility for the open-plan living areas while achieving the hurricane load path required for a multi-storey residential building in Saint Lucia's wind zone.

The steel frame is entirely concealed within the building envelope. All visible materials — stone, timber, render — are secondary finish systems applied over the primary steel structure.

ENVELOPE & FINISHES

Roof: Butterfly or flat/mono-pitch form — appropriate to the stepped courtyard multi-storey configuration. Hurricane-engineered connections throughout.

Cladding: Natural stone, lime render, and timber — consistent with the cottage and villa language. The condo's greater scale is expressed through architectural articulation and landscape setting, not different materials.

Balconies: Covered private terraces at each unit level — screened for privacy and insect protection without closing the nature connection.

Primary structural materials: Concealed steel I-beam primary frame (defining structural strategy for Condo Type A) · Secondary timber framing and cladding · Natural stone and lime render · Metal roof · Engineered timber or premium stone floors

5. Flagship Villa Type B — Structural Basis

Flagship Villa Type B · 1 Unit · V-06

INDIVIDUAL BRIEF

The Flagship Villa (V-06) is individually designed with its own structural brief. The same hurricane-resilience and natural-materials principles apply. The full structural strategy for V-06 is part of the individual buyer/investor brief available at Tier 3. The structural system will be confirmed by the appointed structural engineer as part of the DCA submission.

6. Hurricane Resilience — Cross-Product Requirements

Requirement	Application
Continuous load path	Required for all product types — roof structure tied to wall frame tied to foundation. No break in the structural load path at any connection.
Uplift connections	Engineer-designed mechanical uplift connections at all roof-to-frame and frame-to-foundation junctions
Marine protection	All exposed steel — hot-dip galvanised or zinc-rich primer system + marine epoxy + UV topcoat; inspectable connections; isolated from dissimilar metals
Opening protection	Hurricane-rated glazing systems (sliding, folding, or fixed) with rated frame systems and tested impact resistance. Removable screen systems for insect exclusion.
Roof cladding	Standing-seam or concealed-fix metal roof systems — no exposed fasteners that can be lifted by negative pressure under hurricane conditions
Debris management	Minimal loose external elements; no lightweight decorative features that become projectiles; landscape planting selected for wind resilience

SHER-INV-004-R01 · Revision R01

Issued 11 July 2026 · Confidential — Investor Tier 2 · Investor Confidential
Safeport Security Services Limited · Reg. 2016-C251 · Saint Lucia · shersanctuary.com

This document is provided for preliminary information purposes only and does not constitute a prospectus, securities offering, regulated financial promotion, investment advice, or representation of fact. All financial figures, projections, and development information are preliminary, unaudited, and subject to independent verification. Prospective investors must obtain independent financial, legal, and tax advice before making any investment decision. Governed by the laws of Saint Lucia.