

AI Wardrobe API — Complete Reference

Base URL: `https://appworkspiro.com` | Prefix: `/api/v1` | Envelope: `{ "data", "error" }`

1. Response envelope

```
Success: { "data": { ... }, "error": null }
Failure: { "data": null, "error": { "code": "UNAUTHORIZED", "message": "..." } }
```

2. Access token (~10 min) & interceptor

Item	Value
Access token TTL	600 seconds (10 minutes) — env <code>ACCESS_TOKEN_TTL_SECONDS</code>
Refresh token TTL	30 days — rotates on each refresh
Header	<code>Authorization: Bearer <access_token></code>

App must implement

1. **Proactive:** call `POST /auth/refresh` ~1 min before access expires.
2. **Reactive:** on **401**, refresh once, retry request once (mutex so only one refresh runs).
3. Save **new** `refresh_token` every time.
4. Refresh returns 401 → clear storage → login screen.

```
POST /api/v1/auth/refresh
{ "refresh_token": "..." }

200 data: { "access_token", "refresh_token", "expires_at", "token_type": "Bearer" }
```

OkHttp: skip interceptor for

`/auth/login`, `/auth/register`, `/auth/google`, `/auth/refresh`, `/auth/admin/login`

3. Authentication APIs

Method	Path	Auth	Body / notes	Success data
POST	/auth/register	Public	email, password (8+), display_name?	access_token, refresh_token, expires_at, user
POST	/auth/login	Public	email, password (app users only)	same session shape
POST	/auth/google	Public	id_token, device_id?	same + photo_url
POST	/auth/refresh	Public	refresh_token	new tokens
POST	/auth/logout	Optional	refresh_token?	{ logged_out: true }
POST	/auth/forgot-password	Public	email	{ message }
POST	/auth/reset-password	Public	token, new_password	success message
POST	/auth/admin/login	Public	email, password	admin session (dashboard only)

```
POST /auth/google
{ "id_token": "<Google SDK>", "device_id": "optional" }

POST /auth/login
{ "email": "user@mail.com", "password": "*****" }
```

4. Public content (no token)

GET	Path	Query	data shape (summary)
	/app/metadata	locale?	app_name, version, feature_flags, privacy_url, ...
	/languages		languages[]
	/onboarding/pages		pages[{ title, body, image_url }]
	/home/feed	gender=men women	sections[{ items[{ style_id, thumbnail_url }]}]
	/catalog/{categoryId}	tab, gender	items[{ id, image_url, name }] — id = style_id
	/wardrobe/categories	gender	categories[]
	/files/{path}		binary image

Headers: X-App-Locale: en Or Accept-Language

5. User profile (Bearer)

Method	Path	Action	Body	data
GET	/users/me	Read profile	—	id, email, display_name, preferences
PATCH	/users/me	Edit name	display_name	id, display_name
DELETE	/users/me	Delete account	—	deleted
GET	/users/me/preferences	Read prefs	—	theme_mode, language_id, style_gender_preference
PATCH	/users/me/preferences	Edit prefs	notifications_enabled, language_id, ...	updated prefs
POST	/users/me/avatar	Upload avatar	multipart image	photo_url
POST	/users/me/fcm-token	FCM register	fcm_token, platform, device_id?	device_id, registered_at

6. Devices & push

POST	/devices/register	fcm_token, platform (android ios web), device_id?, app_version?
------	-------------------	---

7. Virtual try-on (generate)

Method	Path	Description
POST	/try-on/generate	Start job
GET	/try-on/jobs/{jobId}	Poll status (2–3s interval)
DELETE	/try-on/jobs/{jobId}	Cancel

```
POST /try-on/generate
{
  "source_image_base64": "data:image/jpeg;base64,...",
  "style_id": "style-01",
  "category_id": "virtual_try_on",
  "width": 768,
  "height": 1024
}

200: { "job_id", "polling_url", "status": "queued" }

GET /try-on/jobs/{id}
200: {
  "job_id", "status": "queued|processing|completed|failed",
  "result_image_absolute_url": "https://appworkspro.com/uploads/...",
  "error": null
}
```

8. History / saved looks (CRUD)

Method	Path	Action	Body
GET	/history?page&limit&favorites	List	—
POST	/history	Add look	image_url, style_id?, saved_to_wardrobe?, try_on_job_id?
GET	/history/{id}	Read one	—
PATCH	/history/{id}	Edit favorite	is_favorite
DELETE	/history/{id}	Delete one	—
DELETE	/history	Clear all (user)	—

```
GET /history?page=1&limit=20
200: { "items": [{ "id", "image_absolute_url", "is_favorite", "created_at" }], "meta": { page, limit, total } }

POST /history
{ "image_url": "https://appworkspro.com/uploads/.../result.png", "style_id": "style-01",
  "saved_to_wardrobe": true }
```

9. Wardrobe looks

GET	/wardrobe/looks?page&limit	User saved wardrobe items (auth)
-----	----------------------------	----------------------------------

10. Admin APIs (dashboard — role admin)

Login: POST /auth/admin/login . All below need Authorization: Bearer .

GET	/admin/overview, /admin/me, /admin/users, /admin/devices, /admin/tokens
GET	/admin/looks-history, /admin/try-on-jobs, /admin/broadcast, /admin/system-status
GET/PATCH	/admin/catalog/categories, /admin/catalog/styles, /admin/home-feed, /admin/app-content
GET	/admin/users/{id}/detail, /jobs, /looks, /sessions
POST	/admin/broadcast (push campaign)
DELETE	/admin/users/{id}, /admin/devices/{id}, tokens, sessions

11. HTTP status quick reference

Code	When
200	OK — check error is null
401	Bad/expired access → refresh or re-login
422	Validation — missing fields
429	Rate limit
502	Try-on / BFL failed

