Lesson plan · for the teacher

Parsons problems

Programming · Level 3 · Lesson 2

Time
40 min

Materials
Printed or handwritten program lines; Scissors, or pre-cut paper strips; One phone to run the answer

Learning goals

- Explain what a Parsons problem is and why it works.
- Design one with good distractors and indentation.
- Run it on paper strips, with no devices.

Activity: Strips on the desk

1. Warm-up (5 min): Give pairs three shuffled lines of a recipe to order. Ask how they knew which came first: each step needed the one before.
2. Teach (5 min): Show a shuffled four-line program on the board and order it together, saying why each line goes where it does, indents included.
3. Solve (15 min): Give each pair a set of strips with one distractor. They arrange the lines and show indentation by shifting strips to the right.
4. Explain (10 min): Pairs explain their order to another pair. Reveal the distractor and ask which misconception it was built on.
5. Wrap-up (5 min): Run the correct program on your phone. Then give the exit ticket.

Prepare strip sets in envelopes and reuse them with every class. Darsi's worksheets print this lesson's Parsons problems ready to cut.

Discussion

- Why must a Parsons problem have exactly one correct order?
- Which distractor worked best, and why?
- When would you move pupils from Parsons to writing code?

Exit ticket

- Write one distractor for a loop that counts to 10, and the misconception behind it.

Try it in class tomorrow
Write a five-line program on paper, cut it into strips and add one distractor. Pairs put it in order and indent it; then check together on the board.

Worksheet · for pupils

Parsons problems

Programming · Level 3 · Lesson 2

Name _____ Class _____ Date _____

1 **Two lines in your Parsons problem could go in either order and the program would still work. Is that fair to pupils?**

◯ Yes: any order is fine ◯ No: only one order is marked right

2 **A Parsons problem you could use with a class: swap the first two marks if they are in the wrong order, then print the list. One line doesn't belong.**

Number the lines in order (1, 2, 3…). Cross out any line that doesn't belong.

☐ `marks[0] = marks[1]`

☐ `marks[1] = temp`

☐ `print(marks)`

☐ `if marks[0] > marks[1]:`

☐ `temp = marks[0]`

☐ `marks[1] = marks[0]`

☐ `marks = [14, 9, 17]`

3 **Fill the gaps in one pass of bubble sort: it swaps any neighbours that are in the wrong order.**

```
marks = [14, 9, 17, 11]
for i in _________(len(marks) - 1):
    if marks[i] _________ marks[i + 1]:
        marks[i], marks[i + 1] = marks[i + 1], marks[i]
print(marks)
```

Word bank: `>` `range` `len` `<`

4 **A pupil arranged the strips like this. What does the program print?**

```
total = 0
for m in [4, 6]:
    total = total + m
    print(total)
```

◯ 10 ◯ 4, then 10 ◯ 0

5 A first Parsons problem for beginners: print the 3 times table from 3 x 1 to 3 x 5, then Done.

Number the lines in order (1, 2, 3…). Cross out any line that doesn't belong.

- [ ] `print(n, "x", i, "=", n * i)`
- [ ] `print("Done")`
- [ ] `n = 3`
- [ ] `for i in range(1, 6):`

✎ **Which program from your next lesson would make a good Parsons problem? Which distractor would you add, and which misconception does it test?**