Lesson notes · for you

Standard deviation and outliers

Data science · Level 2 · Lesson 2

Time	Materials
30 min	A notebook and a pencil; A phone or tablet with Darsi, for the lab

Learning goals

- Read a standard deviation.
- Flag outliers with the IQR rule.
- Check outliers before acting.

Activity: Outlier detectives

1. Warm-up (5 min): Compare two lists with the same mean but very different spreads.
2. Find (10 min): With a partner, work out the quartiles and the fences for a list of journey times.
3. Investigate (10 min): For each outlier, decide what could explain it and how to check.
4. Wrap-up (5 min): Say your finding in one sentence with a number in it, then fill in the exit ticket.

Discussion

- What does a big standard deviation mean?
- Why not delete outliers?
- Which outlier surprised you?

Check yourself

- Q1 is 20 and Q3 is 30. Write the two fences.

Try it this week

Write down how long your journeys take for a week, then find the values that stand out. Is each one a mistake, or something real?

Worksheet

Standard deviation and outliers

Data science · Level 2 · Lesson 2

Name _____ Class _____ Date _____

1 **Class C has a standard deviation of 2, class D of 6. Which has more mixed marks?**

◯ Class C ◯ Class D ◯ They are the same

2 **Two lists with the same mean always have the same spread.**

◯ True ◯ False

3 **Print every mark more than two standard deviations above the mean.**

```
from ulab import numpy as np
m = np.array([11, 12, 12, 13, 12, 30])
avg = np.mean(m)
sd = np.std(m)
print(avg)
```

Write your program:

4 **Use the IQR rule.**

Q1 = 10 and Q3 = 14, so the IQR is _____ and the upper fence is _____.

Word bank: 4 · 6 · 18 · 20

5 **A journey time of 300 minutes appears in your data. What do you do first?**

◯ Check whether it is a mistake or real ◯ Delete it ◯ Use it as the average

✎ **Think of a time when you were the outlier. What would an average have hidden about you?**