Review notes · for you

Working with an agent safely: unit check

AI agents · Lower secondary · Unit check

Time	Materials
20 min	Paper and a pen. No device needed.

Learning goals

- Inside an agent
- Check what it did
- Ask before it acts
- Your data, your bundle

Activity: Agent safety poster

1. Warm-up (3 min): Write one habit from each of the four lessons, in your own words.
2. Plan (7 min): Divide a page into four boxes: the loop, checking a call, asking first, and data and cost.
3. Make (7 min): In each box, draw one picture and write one rule, such as “Read the call before it runs”.
4. Share (3 min): Show your poster to a partner, and explain the box you think will help you most.

Paper and pens are enough. Use only made-up names in your examples.

Discussion

- Which habit from this unit will you keep?
- What surprised you most about how agents make mistakes?
- How would you explain asking first to a younger student?

Check yourself

- My most useful habit from this unit, and when I’ll use it.

Try it this week

Pick the habit from this unit you need most (reading the call, checking it against your words, saying yes only after reading, or keeping private things off the cloud) and use it every day this week.

Quiz sheet

Working with an agent safely: unit check

AI agents · Lower secondary · Unit check

Name _____ Class _____ Date _____

1 **What makes an AI agent different from a chatbot?**

- ◯ It is always bigger
- ◯ It always gives the right answer
- ◯ It can use tools to act, not just write text
- ◯ It never needs a person

2 **A tool call is the tool's name followed by its details.**

- ◯ True
- ◯ False

3 **Put the agent loop in order.**

- ☐ Result from the app
- ☐ Request
- ☐ Answer
- ☐ Tool call
- ☐ Plan

4 **Which of these should stop a call before it runs? Choose all that apply.**

- ☐ The agent sounds unsure
- ☐ A time of 25:00
- ☐ A class in the call that wasn't in the request
- ☐ A message nobody approved

5 **What does this program print?**

```
call = 'route{"from":"Kafi","to":"Dala"}'
print(call.split("{")[0])
```

- ◯ Dala
- ◯ route
- ◯ Kafi

6 **Match each action to its permission level.**

Look up tomorrow's timetable	• • • •	Never
Post a photo to the class group	• • • •	Read only
Hand over your password	• • • •	Ask first

7 **Complete the check so the message is sent only after a yes.**

```
reply = input("Send it? ")
if reply __________ "yes":
    print("SENT")
else:
    print("NOT SENT")
```

Word bank: `=` `==` `!=`

8 **If an agent asks politely before sending, the app doesn't need to check in code.**

◯ True ◯ False

9 **You have no signal and no data left. Which agent can still help with a simple timetable question?**

◯ A big model in the cloud ◯ Neither ◯ A small model already on your phone

10 **This check should send only after a yes, but it sends after a no. Which line is wrong?**

Circle the line with the mistake. Write it correctly:

```
1  reply = input("Send it? ")
2  if reply != "yes":
3      print("SENT")
4  else:
5      print("NOT SENT")
```

Check your answers

Working with an agent safely: unit check

AI agents · Lower secondary · Unit check

1 **It can use tools to act, not just write text**

An agent is a language model in a loop with tools: it can ask for a timetable, the weather or a message to be sent.

2 **True**

For example weather{"place":"Kafi","day":"tomorrow"}: the name, weather, then the details in curly brackets, written as JSON.

3 **Top to bottom: 4, 1, 5, 3, 2**

The model plans, writes a call, the app runs the tool and adds the result, and the model answers from it.

4 **A class in the call that wasn't in the request; A time of 25:00; A message nobody approved**

A name from nowhere, a detail with the wrong shape and an action nobody approved all break a checker's rules.

5 **route**

split("{") cuts the call at the first curly bracket, and [0] is the piece before it: the tool's name, route.

6 **Look up tomorrow's timetable — Read only**
Post a photo to the class group — Ask first
Hand over your password — Never

Reading is low risk; posting changes the world and needs your yes; a password is never for an agent.

7

```
reply = input("Send it? ")
if reply == "yes":
    print("SENT")
else:
    print("NOT SENT")
```

== compares the reply with "yes". != would send on everything except yes, and a single = assigns instead of comparing, which is an error in an if.

8 **False**

A model's asking is learned behaviour and can fail, as «نعم، أرسلها.» on its own shows.

9 **A small model already on your phone**

A model on the phone needs no signal and no data once it is downloaded.

10 **Line 2: `if reply == "yes":`**

!= means "is not", so line 2 sends for every reply except yes.