

ALETH STRIP

Wax & Sealant Stripper (Concentrate)

|              |         |            |                    |                |
|--------------|---------|------------|--------------------|----------------|
| DOCUMENT NO. | VERSION | SUPERSEDES | ISSUED             | EMERGENCY (US) |
| SDS-AL-09    | 1.1     | 1.0        | September 23, 2026 | 1-800-222-1222 |

Uncontrolled when printed — verify the current revision on the ALETH website or with ALETH Chemical Co. Composition disclosed at class level under trade-secret claim (29 CFR 1910.1200(i)). Hazard information fully disclosed.

1 IDENTIFICATION

|                    |                                                                                                                                                                          |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product identifier | ALETH STRIP — Wax & Sealant Stripper (Concentrate)                                                                                                                       |
| Other means of ID  | STRIP · SDS-AL-09                                                                                                                                                        |
| Recommended use    | Removes wax, sealant and polymer protection from automotive paintwork to prepare a clean bonding surface. Dilute before use per the label dilution ladder (1:1 to 1:10). |
| Restrictions       | Not for use on interior surfaces, glass, trim or sensitive plastics. Not for internal use. Not for use on hot surfaces or in direct sunlight.                            |
| Supplier           | ALETH Chemical Co., Charlotte, NC, USA                                                                                                                                   |
| Contact            | Inquiries: via the ALETH website or the contact details on the product label                                                                                             |
| Emergency phone    | US Poison Control: 1-800-222-1222                                                                                                                                        |

2 HAZARD(S) IDENTIFICATION

DANGER

GHS CLASSIFICATION OF THE MIXTURE



GHS02 · FLAME



GHS05 · CORROSION



GHS07 · EXCLAMATION



GHS09 · ENVIRONMENT

H314 — Causes severe skin burns and eye damage

H318 — Causes serious eye damage

H317 — May cause an allergic skin reaction

H335 — May cause respiratory irritation

H227 — Combustible liquid

H400 — Very toxic to aquatic life

H410 — Very toxic to aquatic life with long lasting effects

| HAZARD CLASS                                     | CATEGORY | H-CODE | STATEMENT                               |
|--------------------------------------------------|----------|--------|-----------------------------------------|
| Skin corrosion                                   | 1A       | H314   | Causes severe skin burns and eye damage |
| Serious eye damage                               | 1        | H318   | Causes serious eye damage               |
| Skin sensitization                               | 1        | H317   | May cause an allergic skin reaction     |
| Specific target organ toxicity — single exposure | 3        | H335   | May cause respiratory irritation        |

|                                                |   |      |                                                      |
|------------------------------------------------|---|------|------------------------------------------------------|
| Flammable liquid                               | 4 | H227 | Combustible liquid                                   |
| Hazardous to the aquatic environment — acute   | 1 | H400 | Very toxic to aquatic life                           |
| Hazardous to the aquatic environment — chronic | 1 | H410 | Very toxic to aquatic life with long lasting effects |

#### Precautionary statements (summary)

- **P210** — Keep away from heat, sparks, open flames and hot surfaces. No smoking
- **P260** — Do not breathe mist or vapours
- **P280** — Wear protective gloves, protective clothing and eye/face protection
- **P301+P330+P331** — If swallowed: rinse mouth. Do NOT induce vomiting
- **P302+P352** — If on skin: immediately wash with plenty of water. Remove all contaminated clothing
- **P305+P351+P338** — If in eyes: rinse cautiously with water for several minutes; remove contacts
- **P304+P340** — If inhaled: remove to fresh air, keep at rest
- **P310** — Immediately call a poison centre or physician
- **P273** — Avoid release to the environment

**Other hazards:** This preparation is strongly alkaline (pH about 13) and is corrosive — contact with skin, eyes or mucous membranes causes severe, potentially irreversible injury. Skin sensitisation is a permanent hazard — a sensitised person can react on re-exposure at very low concentration; nitrile gloves are mandatory, latex is not adequate protection against this preparation. Combustible — keep away from ignition sources; the product has a comparatively low flash point and can ignite if heated or sprayed onto a hot surface. Very toxic to aquatic life with long lasting effects — never allow concentrate to reach drains, soil or open water. Never mix with bleach, acids or other cleaning products — a violent reaction and hazardous gases can result.

### 3 COMPOSITION / INFORMATION ON INGREDIENTS

| COMPONENT                                      | CAS NO.      | WEIGHT % | GHS CLASSIFICATION                                                                        |
|------------------------------------------------|--------------|----------|-------------------------------------------------------------------------------------------|
| Proprietary blend of solvents                  | Trade secret | 15 – 18  | Flam. Liq. 4, H227 · Skin Sens. 1, H317 · Aquatic Acute 1, H400 · Aquatic Chronic 1, H410 |
| Proprietary blend of alkaline agents           | Trade secret | 7 – 9    | Skin Corr. 1A, H314 · Eye Dam. 1, H318                                                    |
| Water                                          | 7732-18-5    | 55 – 60  | Not classified                                                                            |
| Proprietary blend of surfactants and additives | Trade secret | 15 – 18  | Skin Irrit. 2, H315 · Eye Irrit. 2A, H319                                                 |

**Trade secret statement (OSHA 29 CFR 1910.1200(i)):** The specific chemical identities and/or actual concentrations or actual concentration ranges of the proprietary components are being withheld as trade secrets under the US regulation 29 CFR 1910.1200(i). Concentration ranges above are intentionally broad. Hazard information is fully disclosed throughout this SDS. Component identities are disclosed to treating physicians and other persons designated by them as required by 29 CFR 1910.1200(i)(4).

### 4 FIRST-AID MEASURES

|                     |                                                                                                                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Inhalation</b>   | Move to fresh air. Rest if breathing is difficult. Get medical attention at once if symptoms persist.                                                                                            |
| <b>Skin contact</b> | <b>Immediate medical attention.</b> Remove all contaminated clothing at once. Flood skin with water 20+ minutes. Do not delay. Seek medical attention for any subsequent allergic skin reaction. |
| <b>Eye contact</b>  | <b>Immediate medical attention.</b> Rinse cautiously with water 20+ minutes, lifting lids. Remove contacts after 5 minutes, continue rinsing. Do not delay.                                      |

|                                |                                                                                                                                                                                                                                    |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Ingestion</b>               | <b>Immediate medical attention.</b> Rinse mouth. Do NOT induce vomiting. Give water or milk if conscious. Never give anything by mouth to an unconscious person.                                                                   |
| <b>Most important symptoms</b> | Severe chemical burns to skin and eyes. Permanent eye injury possible. Allergic skin reaction in sensitised persons. Respiratory irritation from mist.                                                                             |
| <b>Note to physician</b>       | Treat as a strong alkali corrosive injury with solvent exposure. Do not neutralise on tissue. For component identities in an emergency, contact ALETH Chemical Co. (disclosure to treating physicians per 29 CFR 1910.1200(i)(4)). |

## 5 FIRE-FIGHTING MEASURES

- **Suitable extinguishing media:** Alcohol-resistant foam, dry chemical, carbon dioxide, water fog.
- **Unsuitable:** A direct water jet may scatter burning liquid.
- **Specific hazards:** Vapours may travel to a distant ignition source and flash back. Closed containers may rupture in fire. Toxic and irritant fumes and mists may form if heated or in a fire. Do not breathe smoke.
- **Firefighting PPE:** Full protective clothing and self-contained breathing apparatus (SCBA).
- **Flash point:** To be determined — ASTM D93 (Pensky–Martens closed cup), test scheduled.

## 6 ACCIDENTAL RELEASE MEASURES

- **Personal precautions:** Full PPE including chemical suit and SCBA for large spills. Eliminate all ignition sources. Evacuate non-essential personnel. Do not walk through spilled material.
- **Containment:** Dike with inert absorbent (sand, vermiculite, dry earth). Prevent entry into drains.
- **Cleanup:** Neutralise cautiously with a dilute acid spray from a distance, then absorb and containerise. Rinse residue with large volumes of water.
- **Environmental precautions:** Prevent entry into drains and watercourses at all costs (see Section 12).

## 7 HANDLING AND STORAGE

- **Handling:** Use with good ventilation. Full PPE including eye and face protection. Avoid breathing mist and vapours. Avoid all skin contact. Keep away from ignition sources. Eyewash and safety shower immediately to hand.
- **Storage:** Store in the original container as supplied, tightly closed, in a cool, dry, well-ventilated area away from heat, sparks and open flame. Store in a flammable-liquid storage area with corrosion-resistant secondary containment. Protect from freezing.
- **Incompatibilities:** Acids (violent exothermic reaction), bleach and hypochlorite solutions (chlorine gas), oxidisers.

## 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

**Occupational exposure limits:** Component-specific occupational exposure limits are withheld as trade secrets per 29 CFR 1910.1200(i). As conservative internal controls, keep airborne vapour below **400 ppm (TWA)** and airborne mist below **2 mg/m<sup>3</sup> (ceiling)**. The product is corrosive to skin and eyes regardless of airborne exposure.

- **Respiratory:** Use an organic-vapour / acid-gas combination respirator if mist or vapour levels exceed the internal control. Use a full-face respirator or SCBA for large spills.
- **Hands:** Heavy nitrile or neoprene gloves (NOT latex) for the full contact period. Change immediately if contaminated.
- **Eyes/Face:** Chemical splash goggles **and** full face shield. Mandatory.
- **Body:** Chemical-resistant apron or suit; closed-toe footwear. Suitable eyewash and safety shower immediately to hand.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

| PROPERTY   | VALUE                  |
|------------|------------------------|
| Appearance | Uniform milky emulsion |

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Odor           | Mild, characteristic odor                                                                          |
| pH             | 12.5 – 13.5 (strongly alkaline — corrosive)                                                        |
| Boiling point  | ~100°C (aqueous emulsion)                                                                          |
| Melting point  | Not determined (liquid)                                                                            |
| Flash point    | To be determined — ASTM D93 (Pensky–Martens closed cup)                                            |
| Vapor pressure | Elevated (volatile solvent content)                                                                |
| Density        | ~1.0 g/mL (approximate)                                                                            |
| Solubility     | Emulsifiable in water                                                                              |
| VOC content    | Moderate — solvent-containing system (formal value pending the flash-point and VOC test programme) |

## 10 STABILITY AND REACTIVITY

- **Stability:** Conditionally stable. This preparation is an emulsion and can separate in storage; a separated or broken emulsion is not fit for use.
- **Hazardous polymerisation:** Does not occur.
- **Conditions to avoid:** Heat, sparks, open flame, contact with acids and bleach.
- **Incompatible materials:** Acids (violent, exothermic), bleach and hypochlorite solutions (chlorine gas), oxidisers.
- **Hazardous decomposition products:** Toxic and irritant fumes and mists may form in fire. Contact with acid releases a large amount of heat. Contact with bleach releases chlorine gas.

## 11 TOXICOLOGICAL INFORMATION

- **Skin corrosion:** Category 1A (H314) — severe, irreversible injury on contact. (*Sub-category 1A is assigned under the additivity rule: the summed corrosive load clears the 5% line and no corrosive ingredient carries a documented sub-category below 1A. Held on the safe side until each supplier sub-class is on file.*)
- **Serious eye damage:** Category 1 (H318) — severe, irreversible injury possible.
- **Skin sensitisation:** Category 1 (H317). Contains potent dermal sensitisers (identities withheld — trade secrets). Once sensitised, re-exposure may cause allergic contact dermatitis at very low concentration.
- **Specific target organ toxicity — single exposure:** Category 3 (H335) — mist may cause respiratory irritation.
- **Flammable liquid:** Category 4 (H227). Flash point not yet confirmed by test.
- **Acute toxicity (mixture):** Not classified separately; corrosivity is the governing hazard for ingestion.
- **Carcinogenicity:** No components listed as carcinogens by IARC, OSHA or NTP at or above reportable levels (identities withheld as trade secrets).
- **Aspiration hazard:** Not classified.
- **Target organs:** Skin, eyes, respiratory tract, GI tract (if ingested).

## 12 ECOLOGICAL INFORMATION

- **Aquatic toxicity (mixture):** Very toxic to aquatic life (H400). Very toxic to aquatic life with long lasting effects (H410). Contains components that are persistent and bioaccumulative in the aquatic environment.
- **Persistence/degradability:** The surfactant fraction is substantially biodegradable; the solvent fraction is inherently biodegradable but acutely toxic to aquatic organisms at low concentration.
- **Mobility:** Emulsifiable in water and mobile.
- **Other adverse effects:** Do not release concentrate or washings to drains, soil or open water. Dispose of through an appropriate waste contractor.

## 13 DISPOSAL CONSIDERATIONS

---

- **Disposal:** Neutralise, then dispose of in accordance with federal, state and local regulations through a licensed waste contractor. Do not discharge concentrate or washings to drain, soil or open water.
- **Container:** Empty thoroughly; do not re-use. Rinse thoroughly (triple rinse); recycle where available.
- **RCRA status:** Not a listed hazardous waste as formulated; manage in accordance with local wastewater discharge limits for high-pH, high-solvent streams.

## 14 TRANSPORT INFORMATION

---

|                        |                                                                                                                                        |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| UN number              | UN 1760                                                                                                                                |
| Proper shipping name   | Corrosive liquid, n.o.s.                                                                                                               |
| Transport hazard class | 8 (with a subsidiary flammable-liquid risk)                                                                                            |
| Packing group          | II                                                                                                                                     |
| Marine pollutant       | Present — see Section 12                                                                                                               |
| Special provisions     | Corrosive and combustible — ship in corrosion-resistant packaging with absorbent and secondary containment, away from ignition sources |

**Technical names under 49 CFR 172.203(k):** component identities are withheld under a trade-secret claim permitted for n.o.s. entries; the claim is recorded with the shipping papers.

**Note:** Ground transport only for bulk quantities. Small retail bottles ship as routine Consumer Commodity ground freight. Confirmed at quote time per carton. The transport classification is provisional pending the ASTM D93 flash-point result — a result at or below 60°C will move the primary hazard to Class 3.

## 15 REGULATORY INFORMATION

---

- **US Federal:** OSHA Hazard Communication Standard (29 CFR 1910.1200). TSCA — all components listed or exempt; identities withheld as trade secrets.
- **CERCLA/SARA:** Components may be subject to SARA 313 and CERCLA reportable-quantity reporting; identities and thresholds withheld as trade secrets per 29 CFR 1910.1200(i). Release-reporting obligations are tracked internally by ALETH Chemical Co.
- **State:** CA Prop 65 — status under internal review at launch; potential to contain a listed chemical (identity withheld as trade secret). Final determination at label lock.
- **WHMIS 2015 (Canada):** Classified per Hazardous Products Regulations — Corrosive (D1), Flammable (B2), Sensitization (D2A). Label elements per official bilingual requirements at launch.
- **EU REACH:** Not placed on the EU market at this time. SDS formatted per 29 CFR 1910.1200 Appendix D.
- **Trade-secret note:** Specific chemical identities and/or exact concentrations of proprietary components withheld per 29 CFR 1910.1200(i)(1); hazard information fully disclosed.

## 16 OTHER INFORMATION

---

- **Prepared by:** ALETH Chemical Co. — formulation & compliance team
- **Date of issue:** September 23, 2026 · **Version 1.1** (classification pass)
- **Revision history:** Version 1.0 (September 23, 2026): initial issue. Version 1.1 (September 23, 2026): classification pass — every hazard category re-derived against the published mixture-classification rules after an independent review, and each claim those rules do not support removed. Mixture classification derived by the additivity method from component hazard classifications; composition disclosed at class level under the trade-secret provisions of 29 CFR 1910.1200(i). The skin-corrosion sub-class and the flash point are carried conservatively pending the sharper determinations scheduled in the review.
- **Next scheduled review:** September 23, 2027, or upon any formulation or regulatory change.

- **SDS sources:** Component classifications derived from supplier SDS library + UN GHS Rev. 9 mixture classification rules. Supplier and component names intentionally omitted.
- **Disclaimer:** Information provided as-is for hazard communication. User assumes responsibility for safe use under their specific conditions.