

ALETH CAUSTRA Heavy-Duty Alkaline Degreaser (Concentrate)

DOCUMENT NO.	VERSION	SUPERSEDES	ISSUED	EMERGENCY (US)
SDS-AL-02	1.1	1.0	September 23, 2026	1-800-222-1222

Uncontrolled when printed — verify the current revision on the ALETH website or with ALETH Chemical Co. Composition disclosed at class level under trade-secret claim (29 CFR 1910.1200(i)). Hazard information fully disclosed.

1 IDENTIFICATION

Product identifier	ALETH CAUSTRA — Heavy-Duty Alkaline Degreaser (Concentrate)
Other means of ID	CAUSTRA · SDS-AL-02
Recommended use	Heavy-duty alkaline degreaser concentrate for engines, machinery, workshop floors, tyres and industrial grime. Dilute before use per the product label.
Restrictions	Not for use on bare aluminium, anodised surfaces, soft metals, painted alloy or glass. Not for use on hot surfaces. Not for internal use.
Supplier	ALETH Chemical Co., Charlotte, NC, USA
Contact	Inquiries: via the ALETH website or the contact details on the product label
Emergency phone	US Poison Control: 1-800-222-1222

2 HAZARD(S) IDENTIFICATION

DANGER

GHS CLASSIFICATION OF THE MIXTURE



GHS02 · FLAME



GHS05 · CORROSION



GHS07 · EXCLAMATION



GHS09 · ENVIRONMENT

H314 — Causes severe skin burns and eye damage

H318 — Causes serious eye damage

H290 — May be corrosive to metals

H317 — May cause an allergic skin reaction

H335 — May cause respiratory irritation

H227 — Combustible liquid

H400 — Very toxic to aquatic life

H410 — Very toxic to aquatic life with long lasting effects

HAZARD CLASS	CATEGORY	H-CODE	STATEMENT
Skin corrosion	1A	H314	Causes severe skin burns and eye damage
Serious eye damage	1	H318	Causes serious eye damage
Corrosive to metals	1	H290	May be corrosive to metals

Skin sensitization	1	H317	May cause an allergic skin reaction
Specific target organ toxicity — single exposure	3	H335	May cause respiratory irritation
Flammable liquid	4	H227	Combustible liquid
Hazardous to the aquatic environment — acute	1	H400	Very toxic to aquatic life
Hazardous to the aquatic environment — chronic	1	H410	Very toxic to aquatic life with long lasting effects

Precautionary statements (summary)

- **P210** — Keep away from heat, sparks, open flames and hot surfaces. No smoking
- **P260** — Do not breathe mist or vapours
- **P280** — Wear protective gloves, protective clothing and eye/face protection
- **P301+P330+P331** — If swallowed: rinse mouth. Do NOT induce vomiting
- **P302+P352** — If on skin: immediately wash with plenty of water. Remove all contaminated clothing
- **P305+P351+P338** — If in eyes: rinse cautiously with water for several minutes; remove contacts
- **P304+P340** — If inhaled: remove to fresh air, keep at rest
- **P310** — Immediately call a poison centre or physician
- **P273** — Avoid release to the environment

Other hazards: This preparation is extremely alkaline (pH 14) and is corrosive — contact with skin, eyes or mucous membranes causes severe, potentially irreversible injury; dilution reduces but does not eliminate the hazard. Never dwell on bare aluminium — this preparation will stain and etch bare aluminium and soft metals on contact. Skin sensitisation is a permanent hazard — a sensitised person can react on re-exposure at very low concentration; nitrile or neoprene gloves are mandatory, latex is not adequate protection. Combustible — keep away from ignition sources; can ignite if heated or sprayed onto a hot surface. Very toxic to aquatic life with long lasting effects — never allow concentrate to reach drains, soil or open water. Never mix with bleach, acids or other cleaning products — a violent reaction and hazardous gases can result.

3 COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS NO.	WEIGHT %	GHS CLASSIFICATION
Water	7732-18-5	30 – 35	Not classified
Proprietary blend of alkaline agents and builders	Trade secret	25 – 30	Skin Corr. 1A, H314 · Eye Dam. 1, H318 · Met. Corr. 1, H290
Proprietary blend of solvents	Trade secret	17 – 20	Flam. Liq. 4, H227 · Skin Sens. 1, H317 · Aquatic Acute 1, H400 · Aquatic Chronic 1, H410
Proprietary blend of surfactants and additives	Trade secret	18 – 22	Skin Irrit. 2, H315 · Eye Irrit. 2A, H319 · Skin Sens. 1, H317 · STOT SE 3, H335

Trade secret statement (OSHA 29 CFR 1910.1200(i)): The specific chemical identities and/or actual concentrations or actual concentration ranges of the proprietary components are being withheld as trade secrets under the US regulation 29 CFR 1910.1200(i). Concentration ranges above are intentionally broad. Hazard information is fully disclosed throughout this SDS. Component identities are disclosed to treating physicians and other persons designated by them as required by 29 CFR 1910.1200(i)(4).

4 FIRST-AID MEASURES

Inhalation	Move to fresh air. Rest if breathing is difficult. Get medical attention at once if symptoms persist.
Skin contact	Immediate medical attention. Remove all contaminated clothing at once. Flood skin with water 20+ minutes. Do not delay. Seek medical attention for any subsequent allergic skin reaction.

Eye contact	Immediate medical attention. Rinse cautiously with water 20+ minutes, lifting lids. Remove contacts after 5 minutes, continue rinsing. Do not delay.
Ingestion	Immediate medical attention. Rinse mouth. Do NOT induce vomiting. Give water or milk if conscious. Never give anything by mouth to an unconscious person.
Most important symptoms	Severe chemical burns to skin and eyes. Permanent eye injury possible. Allergic skin reaction in sensitised persons. Respiratory irritation from mist.
Note to physician	Treat as a strong alkali corrosive injury with solvent exposure. Do not neutralise on tissue. For component identities in an emergency, contact ALETH Chemical Co. (disclosure to treating physicians per 29 CFR 1910.1200(i)(4)).

5 FIRE-FIGHTING MEASURES

- **Suitable extinguishing media:** Alcohol-resistant foam, dry chemical, carbon dioxide, water fog.
- **Unsuitable:** A direct water jet may scatter burning liquid.
- **Specific hazards:** Vapours may travel to a distant ignition source and flash back. Closed containers may rupture in fire. Toxic and irritant fumes and mists may form if heated or in a fire. Do not breathe smoke. The product is corrosive and can damage firefighting equipment.
- **Firefighting PPE:** Full protective clothing and self-contained breathing apparatus (SCBA).
- **Flash point:** To be determined — ASTM D93 (Pensky–Martens closed cup), test scheduled.

6 ACCIDENTAL RELEASE MEASURES

- **Personal precautions:** Full PPE including chemical suit and SCBA for large spills. Eliminate all ignition sources. Evacuate non-essential personnel. Do not walk through spilled material.
- **Containment:** Dike with inert absorbent (sand, vermiculite, dry earth). Prevent entry into drains.
- **Cleanup:** Neutralise cautiously with a dilute acid spray from a distance, then absorb and containerise. Rinse residue with large volumes of water.
- **Environmental precautions:** Prevent entry into drains and watercourses at all costs (see Section 12).

7 HANDLING AND STORAGE

- **Handling:** Use with good ventilation. Full PPE including eye and face protection. Avoid breathing mist and vapours. Avoid all skin contact. Keep away from ignition sources. Never allow dwell on bare aluminium. Eyewash and safety shower immediately to hand.
- **Storage:** Store in the original container as supplied, tightly closed, in a cool, dry, well-ventilated area away from heat, sparks and open flame. Store in a flammable-liquid storage area with corrosion-resistant secondary containment. Protect from freezing and from cold crystallisation.
- **Incompatibilities:** Acids (violent exothermic reaction), bleach and hypochlorite solutions (chlorine gas), aluminium and soft metals, ammonium salts (ammonia gas), oxidisers.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits: Component-specific occupational exposure limits are withheld as trade secrets per 29 CFR 1910.1200(i). As conservative internal controls, keep airborne vapour below **400 ppm (TWA)** and airborne mist below **2 mg/m³ (ceiling)**. The product is corrosive to skin and eyes regardless of airborne exposure.

- **Respiratory:** Use an organic-vapour / acid-gas combination respirator if mist or vapour levels exceed the internal control. Use a full-face respirator or SCBA for large spills.
- **Hands:** Heavy nitrile or neoprene gloves (NOT latex) for the full contact period. Change immediately if contaminated.
- **Eyes/Face:** Chemical splash goggles **and** full face shield. Mandatory.
- **Body:** Chemical-resistant apron or suit; closed-toe footwear. Suitable eyewash and safety shower immediately to hand.

9 PHYSICAL AND CHEMICAL PROPERTIES

PROPERTY	VALUE
Appearance	Uniform liquid
Odor	Mild, characteristic odor
pH	14.0 (ceiling — extremely alkaline, corrosive)
Boiling point	~100°C (aqueous)
Melting point	Not determined (liquid)
Flash point	To be determined — ASTM D93 (Pensky–Martens closed cup)
Vapor pressure	Elevated (volatile solvent content)
Density	~1.1–1.2 g/mL (approximate)
Solubility	Soluble in water
VOC content	Moderate — solvent-containing system (formal value pending the flash-point and VOC test programme)

10 STABILITY AND REACTIVITY

- **Stability:** Conditionally stable. This preparation is a near-saturated alkaline system and can crystallise if chilled or evaporated in storage; crystallised material is not fit for use.
- **Hazardous polymerisation:** Does not occur.
- **Conditions to avoid:** Cold, evaporation, contact with acids and bleach.
- **Incompatible materials:** Acids (violent, exothermic), bleach and hypochlorite solutions (chlorine gas), aluminium and soft metals, ammonium salts (ammonia gas), oxidisers.
- **Hazardous decomposition products:** Toxic and irritant fumes and mists may form in fire. Contact with acid releases a large amount of heat. Contact with bleach releases chlorine gas.

11 TOXICOLOGICAL INFORMATION

- **Skin corrosion:** Category 1A (H314) — severe, irreversible injury on contact.
- **Serious eye damage:** Category 1 (H318) — severe, irreversible injury possible.
- **Corrosive to metals:** Category 1 (H290).
- **Skin sensitisation:** Category 1 (H317). Contains potent dermal sensitisers (identities withheld — trade secrets). Once sensitised, re-exposure may cause allergic contact dermatitis at very low concentration.
- **Specific target organ toxicity — single exposure:** Category 3 (H335) — mist may cause respiratory irritation.
- **Acute toxicity (mixture):** Not classified separately; corrosivity is the governing hazard for ingestion.
- **Carcinogenicity:** No components listed as carcinogens by IARC, OSHA or NTP at or above reportable levels (identities withheld as trade secrets).
- **Aspiration hazard:** Not classified.
- **Target organs:** Skin, eyes, respiratory tract, GI tract (if ingested).

12 ECOLOGICAL INFORMATION

- **Aquatic toxicity (mixture):** Very toxic to aquatic life (H400). Very toxic to aquatic life with long lasting effects (H410). Contains components that are persistent and bioaccumulative in the aquatic environment.

- **Persistence/degradability:** The surfactant fraction is substantially biodegradable; the solvent fraction is inherently biodegradable but acutely toxic to aquatic organisms at low concentration.
- **Mobility:** Soluble in water and mobile.
- **Other adverse effects:** Do not release concentrate or washings to drains, soil or open water. Dispose of through an appropriate waste contractor.

13 DISPOSAL CONSIDERATIONS

- **Disposal:** Neutralise, then dispose of in accordance with federal, state and local regulations through a licensed waste contractor. Do not discharge concentrate or washings to drain, soil or open water.
- **Container:** Empty thoroughly; do not re-use. Rinse thoroughly (triple rinse); recycle where available.
- **RCRA status:** Not a listed hazardous waste as formulated; manage in accordance with local wastewater discharge limits for high-pH, high-solvent streams.

14 TRANSPORT INFORMATION

UN number	UN 1760
Proper shipping name	Corrosive liquid, n.o.s.
Transport hazard class	8 (with a subsidiary flammable-liquid risk)
Packing group	II
Marine pollutant	Present — see Section 12
Special provisions	Corrosive and combustible — ship in corrosion-resistant packaging with absorbent and secondary containment, away from ignition sources

Technical names under 49 CFR 172.203(k): component identities are withheld under a trade-secret claim permitted for n.o.s. entries; the claim is recorded with the shipping papers.

Note: Ground transport only for bulk quantities. Small retail bottles ship as routine Consumer Commodity ground freight. Confirmed at quote time per carton. The transport classification is provisional pending the ASTM D93 flash-point result — a result at or below 60°C will raise the subsidiary risk to a primary Class 3 hazard.

15 REGULATORY INFORMATION

- **US Federal:** OSHA Hazard Communication Standard (29 CFR 1910.1200). TSCA — all components listed or exempt; identities withheld as trade secrets.
- **CERCLA/SARA:** Components may be subject to SARA 313 and CERCLA reportable-quantity reporting; identities and thresholds withheld as trade secrets per 29 CFR 1910.1200(i). Release-reporting obligations are tracked internally by ALETH Chemical Co.
- **State:** CA Prop 65 — status under internal review at launch; potential to contain a listed chemical (identity withheld as trade secret). Final determination at label lock.
- **WHMIS 2015 (Canada):** Classified per Hazardous Products Regulations — Corrosive (D1), Flammable (B2), Sensitization (D2A). Label elements per official bilingual requirements at launch.
- **EU REACH:** Not placed on the EU market at this time. SDS formatted per 29 CFR 1910.1200 Appendix D.
- **Trade-secret note:** Specific chemical identities and/or exact concentrations of proprietary components withheld per 29 CFR 1910.1200(i)(1); hazard information fully disclosed.

16 OTHER INFORMATION

- **Prepared by:** ALETH Chemical Co. — formulation & compliance team
- **Date of issue:** September 23, 2026 · **Version 1.1** (classification pass)

- **Revision history:** Version 1.0 (September 23, 2026): initial issue. Version 1.1 (September 23, 2026): the product scope, pH and composition bands were corrected against internal formulation records; hazard classes unchanged in substance. Mixture classification derived by the additivity method from component hazard classifications; composition disclosed at class level under the trade-secret provisions of 29 CFR 1910.1200(i).
- **Next scheduled review:** September 23, 2027, or upon any formulation or regulatory change.
- **SDS sources:** Component classifications derived from supplier SDS library + UN GHS Rev. 9 mixture classification rules. Supplier and component names intentionally omitted.
- **Disclaimer:** Information provided as-is for hazard communication. User assumes responsibility for safe use under their specific conditions.