After the Decision: Learning to Adapt from Delayed Outcomes

Internal pre-results review; empirical cells are intentionally unfilled

Anonymous Author(s)
Submission Id: INTERNAL PRE-RESULTS REVIEW

Abstract

Scientific agents increasingly face menus of overlapping tools whose errors depend on the input. A returned value can be syntactically valid yet chemically wrong, while the label needed to improve the next decision is available only for the selected call and may arrive after other decisions. We study this capability ceiling as an outcome-aware tool-routing problem. MIRA-Relay combines a discriminative provider-reliability surface, a contextual choice rule, a low-dimensional online adapter, and a release ledger that keeps runtime failure separate from chemical correctness. The same evidence state supports a first call, a post-call decision to accept, refuse, or request another tool, and a delayed update for later tasks. We evaluate the primary one-call contract and a bounded evidence extension on public BBB truth with 33 concrete pharmaceutical providers, scaffold-disjoint splits, selected-only feedback, and delays $D \in \{0, 1, 4\}$. The frozen comparison will report **[RESULT]** system success versus **[RESULT]** for the strongest matched control, with paired cluster intervals and call/update costs; the mechanism table will report **[RESULT]** rescued and **[RESULT]** harmed decisions. This internal draft fixes the method, baselines, and experiment matrix; only frozen receipts and their reconciled values remain to be inserted.

CCS Concepts


• **Computing methodologies** → **Multi-agent planning**; *Reinforcement learning*; Machine learning.

Keywords

tool selection, online learning, delayed feedback, scientific agents, molecular property prediction

ACM Reference Format:
Anonymous Author(s). 2027. After the Decision: Learning to Adapt from Delayed Outcomes: Internal pre-results review; empirical cells are intentionally unfilled. In *Proc. of the 26th International Conference on Autonomous Agents and Multiagent Systems (AAMAS 2027), Hanoi, Vietnam, 3–7 May 2027*, IFAAMAS, 8 pages.

INTERNAL PRE-RESULTS DRAFT. This manuscript is a design draft, not evidence that MIRA-Relay beats any baseline. Cells marked TBD require frozen receipts, independent recovery, and author review.



This work is licensed under a Creative Commons Attribution International 4.0 License.

Proc. of the 26th International Conference on Autonomous Agents and Multiagent Systems (AAMAS 2027), M. Baldoni, F. Fang, W. Yeoh, N. Yorke-Smith (eds.), 3–7 May 2027, Hanoi, Vietnam. © 2027 International Foundation for Autonomous Agents and Multiagent Systems (www.ifaamas.org).

1 Introduction

A scientific agent must decide which tool's prediction to use when several providers estimate the same property. That choice matters even when every call completes: execution success establishes that an answer was returned, while usefulness depends on whether the answer is correct for the input. Molecular property prediction makes this distinction measurable because provider outputs can be checked against independently recorded endpoint labels.

Valid responses can disagree on the same molecule. In our frozen BBB development panel, molecule `z000282` has benchmark label 1: `admet_ai_1_4_0` returns 0, while `b3clf_dtree_common` returns 1, both with successful runtime status. The example establishes a selection problem; it does not establish which provider is best on the next molecule. During evaluation, the agent sees neither unselected outputs nor the current correctness label before choosing.

Outcome feedback creates two obstacles: sparse coverage and delayed release. A fixed policy cannot use new evidence. A selected-only learner sees feedback only from chosen providers, leaving alternatives sparsely observed; delay postpones when feedback is usable. These constraints motivate our transfer hypothesis but do not prove that any bandit fails. We therefore compare matched online controls and test whether sharing changes later decisions.

We hypothesize that a released outcome can inform later choices through a shared context residual. A local update need not transfer to related providers; provider bias preserves local differences. An immutable fit-time reference anchors the comparison. The claim requires a change in later exploitation under identical observations.

MIRA-Relay is the concrete instantiation of this hypothesis within the MIRA adaptation framework. Its updater changes family residuals and provider biases only when a selected outcome is released; family-balanced probes provide coverage, and a runtime ledger distinguishes execution failure from a wrong prediction. Selection uses released history. A separate post-call verifier interface can inspect the returned output and request review or abstention; this extension is evaluated in E5 so that additional calls cannot be mistaken for an improvement in direct selection.

This draft makes four testable commitments, each paired with a falsification condition in the experimental matrix:

- **Task validity.** Public truth and a concrete provider panel yield input-dependent headroom over a fixed provider without leaking unselected outcomes; this fails if an evaluator-only panel score is the only source of signal.
- **Faithful adaptation.** Selected-only delayed events can be replayed with exact visibility, release clocks, and failure semantics; this fails if an independent checker cannot validate the recorded action, release, and state-hash chain.
- **Mechanistic adaptation.** Shared residual feedback changes later exploitation decisions beyond the same probe schedule with

no update; this fails if all changes come from direct probes or disappear under family/provider permutation.

- **Practical value.** Any improvement in future correctness must survive the strongest legal fixed and matched online controls while reporting harmed decisions, calls, latency, and memory; otherwise the conclusion is limited to a protocol or diagnostic result.

The remainder of the paper defines the task, gives the proposed specification, fixes the benchmark and baseline contracts, and lays out the pre-registered matrix whose empirical cells are intentionally left open.

2 Problem and Task Contract

We study one agent making a sequence of tool calls. Figures 1 and 2 show the same contract at two scales: the first separates the learned relay from execution and evaluation, while the second fixes the event order that determines when feedback can affect a later action. The contract is defined at the granularity of a concrete provider, not a provider family or a post-hoc majority vote.

2.1 Episode, menu, and feedback

At decision tick t, the agent receives a molecule x_t, an endpoint e_t, and an available menu A_t of concrete provider identifiers. It chooses one provider $a_t \in A_t$ before reading the current output panel. The benchmark stores an independent endpoint truth $y_t \in \{0, 1\}$ for evaluation. The selected call returns an output o_t, a runtime status $s_t \in \{\text{ok}, \text{error}\}$, and, when available, a confidence value c_t. We keep the labels that drive the method separate:

$$r_t^{\text{run}} = \mathbf{1}[s_t = \text{ok}],$$

$$r_t^{\text{chem}} = \begin{cases} \mathbf{1}[o_t = y_t], & s_t = \text{ok}, \\ \text{null}, & s_t = \text{error}, \end{cases}$$

$$r_t^{\text{sys}} = \mathbf{1}[s_t = \text{ok} \wedge o_t = y_t].$$

The correctness head is trained only on non-null r^{chem}; the runtime head uses r^{run}; a bandit reward may use r^{sys} with separate failure and chemical-error costs. Thus an execution failure is not silently relabeled as a chemical mistake.

After termination, an independent replay judge records the selected outcome. The outcome becomes visible only at its registered release tick τ_t. The legal history at tick t is

$$H_t = \{(x_s, e_s, a_s, r_s^{\text{sys}}, \tau_s) : s < t,\ \tau_s \le t\}.$$

For example, for molecule `z000282`, the benchmark truth is 1. The call to `admet_ai_1_4_0` returns 0 with status ‘ok‘. The call to `b3clf_dtree_common` returns 1 with status ‘ok‘. Both calls have $r^{\text{run}} = 1$, but their chemical labels differ. A decision at tick 2 cannot read either unselected output, the current truth, or any future terminal record.

Provider parameters use a registry $\mathcal{P}$ fixed at initialization; $A_t \subseteq \mathcal{P}$ is the current candidate menu. MIRA-Relay retains its fallback in every menu. Removing a challenger leaves its stored state intact. For the BBB replay, $|\mathcal{P}| = 33$ throughout the stream. The queue orders releases by due tick and breaks ties by enqueue order; each feedback is consumed once and receipts record the release order explicitly.

For the fixed-delay replay, a decision at tick t terminates, enqueues its feedback, and releases it at

$$\tau_t = t + 1 + D, \qquad D \in \{0, 1, 4\}.$$

Only after this release may the event enter $H_{t'}$ and affect a later decision. For $D = 0$, the release is processed before the next decision tick and never changes the action that caused the event. Unknown truth creates no correctness label and stops the current scoring stream; a refusal creates no selected-provider label. Both remain explicit in the episode ledger.

2.2 Selection and verification interfaces

The pre-call selector and post-call verifier have disjoint interfaces:

$$a_t = \pi_{\text{sel}}(x_t, e_t, A_t, H_t, S_t), \qquad v_t = \pi_{\text{ver}}(o_t, c_t, s_t),$$

where v_t is one of accept, escalate, or refuse. The verifier can request a second provider only after the first call returns. This is an extension interface for E5, not an action performed by the current direct-selection runner. In the running example, a selector may choose ‘b3clf_dtree_common‘; only after its output and confidence are available can the verifier decide whether to escalate.

The online learner maintains a serializable post-release state S_t. At tick t, the release phase first applies exactly the events due at that tick; the selector then reads the resulting state:

$$\begin{aligned} S_t &= U\left(S_{t-1}, \right. \\ &\qquad \left. \{(x_s, e_s, a_s, r_s^{\text{sys}}, \tau_s) : s < t,\ \tau_s = t\}\right), \\ a_t &= \pi_{\text{sel}}(x_t, e_t, A_t, H_t, S_t). \end{aligned}$$

With no due event, U is the identity. Thus a $D = 0$ event from tick t enters S_{t+1} and can affect action $t + 1$, but never action t. No correctness-residual update is allowed for an unselected provider, an unreleased event, an unknown label, or a refusal. A terminal unknown or refusal may still update runtime/availability bookkeeping; fallback feedback never changes residual mean/variance or provider bias. This contract lets a receipt verifier check the visible read set, action, release queue, state-hash chain, and recorded schema/counts without importing the training runner. Complete metric recomputation is left to the E5 transition replayer; this receipt check does not by itself recompute scores, propensities, or the MAP update.

2.3 Estimands and costs

The primary estimand is prequential system success: a selected call must return a valid and correct answer. We also report chemical correctness conditional on valid returns, paired rescued and harmed decisions, failures, and call and update costs. Verification experiments additionally account for escalation, refusal, and unknown truth. Static full-panel accuracy and evaluator-only Oracle accuracy measure task headroom separately from online effects.

3 MIRA-Relay: Proposed Method Specification

This section specifies MIRA-Relay, the mechanism under test. It is a pre-results design, not a claim that the mechanism has passed the acceptance gates.




Figure 1: MIRA-Relay closes the loop from a pre-call choice to a later decision. Molecule, endpoint, eligible menu, and released state enter a fit-only reference plus a family residual and provider bias. One selected call produces a terminal record; the frozen endpoint judge supplies chemical correctness only after termination, while runtime failure follows its own ledger. The selected outcome waits until $\tau_t = t + 1 + D$ and then updates the released state; decisions continue while feedback is pending.

3.1 Cold-start scores and the immutable reference

Let $\phi(x) \in \mathbb{R}^d$ be a frozen molecule representation, $g(a)$ the audited family of provider a, and $K = |\mathcal{P}|$. For each registered provider, a fit-only direct head w_a^0 is trained on the fit partition; the current menu only masks which coordinates can act. Let c be the provider with the highest fit-partition system-success rate (the fit-only Best Fixed provider), and let u_g^0 and b_a^0 be fit-only family residual and provider bias parameters. The cold-start score is

$$z_a^0(x) = (w_a^0)^\top \phi(x) + (u_{g(a)}^0)^\top \phi(x) + b_a^0.$$

The case is concrete: $\phi(\texttt{z000282})$ is a frozen 64-dimensional vector, and its challenger belongs to family `b3clf`. The planned evaluation loads sealed fit values w_a^0, u_g^0, b_a^0; the fit solver is not rerun online.

The fallback score $z_c^0(x)$ is immutable throughout evaluation. This is a safety reference, not a promise of safety: the experiment must still count every decision in which a challenger replaces the reference and is wrong. Providers outside the fit-manifest registry are out of scope; candidate menus are subsets of the registry and the fallback is always reinserted if a caller omits it.

3.2 Reliability surface and bounded evidence choice

The score is a discriminative reliability surface over the current molecule, endpoint, provider, and released evidence. At the first call it produces a provider correctness estimate $q_t(a)$ and a separate runtime estimate $h_t(a)$; after a result is observed, the same surface conditions on the evidence state rather than creating separate "verification" and "complement" heads. For a bounded extension with at most one additional call, let $p_t(y \mid E_t)$ be the endpoint posterior and let ρ be the cost of refusing. The stop loss is

$$R_{\text{stop}}(E_t) = \min\{\rho, 1 - \max_y p_t(y \mid E_t)\}.$$

For a candidate call a, its value is computed by enumerating the possible returned observation o under the fitted outcome model:

$$Q_1(a \mid E_t) = \kappa_a + \sum_o P(o \mid E_t, a) R_{\text{stop}}(E_t \cup \{o\}).$$

The planner chooses ACCEPT, REFUSE, or CALL(a) by minimizing these quantities. The primary E2a task fixes horizon zero; E4/E5 use this one-step extension and report the extra call and refusal costs separately.

3.3 Family-shared residual state

The online state concatenates family residuals and provider biases. At initialization, it is seeded by the fit-only parameters, so $\beta_0 = (u_1^0, \ldots, u_G^0, b_1^0, \ldots, b_K^0)$ and $z_{a,0} = z_a^0$:

$$\beta_t = (u_{1,t}, \ldots, u_{G,t}, b_{1,t}, \ldots, b_{K,t}).$$

For a challenger $a \neq c$, define $q_a(x)$ to contain $\phi(x)$ in the block for family $g(a)$, one in the coordinate for provider a, and zeros elsewhere. Its current score is

$$z_{a,t}(x) = (w_a^0)^\top \phi(x) + q_a(x)^\top \beta_t.$$

A common residual added to every provider would cancel in an argmax and could not change the action. The family-specific block does not cancel: feedback from one selected 'b3clf' provider can change the scores of its sibling providers while leaving other families unchanged. This is the intended transfer path, and the provider bias preserves within-family differences.

3.4 Selected-only diagonal update

When a selected challenger releases the end-to-end label r_t^{sys}, the updater touches only the nonzero coordinates of $q_t = q_{a_t}(x_t)$. For a valid return, r_t^{sys} equals the released 'r_chem' label; a runtime failure contributes $r_t^{\text{sys}} = 0$ while its chemical label remains null. Unknown truth and refusal do not update the correctness residual.

Let (μ_t, ω_t) denote the local mean and diagonal variance for those coordinates. The local Bernoulli MAP logit is the unique root

$$z^* = z_0 + v_t\big(r_t^{\mathrm{sys}} - \sigma(z^*)\big),$$
$$z_0 = (w_{a_t}^0)^\top \phi(x_t) + q_t^\top \mu_t,$$
$$v_t = \sum_j q_{t,j}^2 \omega_{t,j}.$$

with $p^* = \sigma(z^*)$ and $h^* = p^*(1-p^*)$. MIRA-Relay uses a diagonal-precision projection, rather than treating the diagonal of a projected state as the diagonal of a full Laplace inverse. Writing $\lambda_{t,j} = 1/\omega_{t,j}$ for diagonal precision, the update is

$$\mu_{t+1,j} = \mu_{t,j} + \omega_{t,j} q_{t,j}(r_t^{\mathrm{sys}} - p^*),$$
$$\lambda_{t+1,j} = \lambda_{t,j} + h^* q_{t,j}^2,$$
$$\omega_{t+1,j} = 1/\lambda_{t+1,j}.$$

The same ‘z000282‘ case makes the information boundary explicit. If the selected ‘b3clf‘ provider releases $r_t^{\mathrm{sys}} = 1$, only its family block and provider bias are updated; no unselected provider receives a synthetic label. If the provider fails, $r_t^{\mathrm{sys}} = 0$ updates the system-success residual and the independent hazard ledger, while ‘chemical_correct‘ remains null.

The update touches $O(d)$ coordinates per release. Scoring all K registered candidates costs $O(Kd)$, including the fixed direct heads. The online posterior means and diagonal variances together store $2(Gd + K)$ scalars, before the runtime ledger, masks, and state version; the fixed fit-only direct heads w_a^0 are stored separately and are not counted as online state. This is smaller than a full covariance for every provider. For a challenger a, the current score variance is

$$v_{a,t} = \sum_j \phi(x_t)_j^2 \, \omega_{t,j}^{(g(a))} + \omega_t^{(b_a)},$$

where both terms use the state after all due releases. The fixed direct head adds no online variance. The fallback uses its immutable score without an uncertainty bonus. For `z000282`, this sum uses its 64 encoded features and the selected challenger's family and bias variances. These are implementation targets to be measured in the cost table, not assumptions about the final result.

3.5 Result-independent probes and hazard gate

To observe challengers beyond the current exploitation choice, MIRA-Relay reserves a fixed probe probability $\epsilon = 0.20$ before looking at the current outcome. It samples a family uniformly from the eligible challenger families and then a challenger uniformly within that family. If $\mathcal{G}_t$ is the eligible family set and $P_{g,t}$ the eligible providers, the logged propensity is

$$\rho_t(a) = \frac{1}{|\mathcal{G}_t|\,|P_{g(a),t}|}, \qquad \pi_t(a) = \epsilon\rho_t(a) + (1-\epsilon)\mathbf{1}[a = a_t^{\mathrm{exp}}].$$

Here ρ_t is the safe family/provider probe distribution and a_t^{exp} is the exploitation action. A provider in a hard block, family block, or runtime-hazard exclusion set is ineligible. For ineligible providers and the fallback, $\rho_t(a) = 0$. If no challenger is eligible, the fallback branch is explicit: $\pi_t(c) = 1$ and $\pi_t(a) = 0$ for every other provider. Otherwise the displayed mixture is normalized over the eligible family/provider sets. The complete action probability π_t, not only the probe branch probability, is logged. Common random numbers couple schedules across methods but do not imply identical actions when a dynamic safe menu changes. Every decision records the eligible sets, branch and full propensity, scores, gate action, and block reason.

On the non-probe branch, MIRA-Relay uses a fixed logit-space upper-confidence score

$$\mathrm{score}_{a,t} = z_{a,t} + \kappa\sqrt{v_{a,t}},$$

then filters providers whose upper runtime-hazard bound exceeds the fallback bound by a fixed slack. If $F_a^{\mathrm{fit}}, V_a^{\mathrm{fit}}$ are fit-time failure/valid counts and $F_{a,t}^{\mathrm{on}}, V_{a,t}^{\mathrm{on}}$ are released runtime counts, each terminal event counted once at release for the fixed BBB endpoint, the bound is

$$h_{a,t}^U = \mathrm{BetaInv}\Big(1-\delta_h; 1 + F_a^{\mathrm{fit}} + F_{a,t}^{\mathrm{on}}, 1 + V_a^{\mathrm{fit}} + V_{a,t}^{\mathrm{on}}\Big).$$

The reference $h_{c,0}^U$ uses fit counts alone. This preserves the fit-time comparison threshold; fallback outcomes still enter its diagnostic ledger. For example, a released failed challenger call increments $F_{a,t}^{\mathrm{on}}$ once and leaves $V_{a,t}^{\mathrm{on}}$ unchanged. A challenger passes the runtime-hazard filter when $h_{a,t}^U \le h_{c,0}^U + \eta_h$. The constants are fixed as $\epsilon = 0.20$, $\kappa = 1$, $\delta_h = 0.05$, and $\eta_h = 0.02$ in the CPU pre-registration. The runner receipt must record all four values; they cannot be selected by inspecting evaluation outcomes. This branch is a candidate exploitation rule; the hazard filter controls runtime exposure only and is not a chemical-correctness safety guarantee. The experiment will test whether released residuals actually change its decisions.

3.6 Invariants and falsification

The implementation must preserve five invariants: (i) no current truth or unselected output is read before action, (ii) only released selected events update state, (iii) the fallback score is immutable, (iv) system failure and chemical correctness remain separate, and (v) a state snapshot plus event prefix deterministically reconstructs the next action.

Fallback feedback has a separate bookkeeping path: it does not update the residual learner or provider bias, but it may update diagnostic correctness and availability/hazard ledgers and records ‘residual_update=false‘.

The development-only verifier prototype checks lifecycle fields and the recorded state-hash chain; it is not an independent recovery result and does not recompute the score, propensity, or MAP transition. E5/T5 therefore treats a policy-independent transition replayer as a required artifact before claiming full realtime recoverability.

The mechanism is rejected as an adaptive contribution if a same-schedule ProbeNoUpdate control has the same post-release action changes, if changes come only from direct probes, if family/provider permutation leaves the effect unchanged, or if the receipt verifier cannot validate the recorded state-hash and propensity fields. These tests distinguish the proposed feedback-to-exploitation path from a probe schedule, a provider-local update, or a logging artifact.

The science gate requires a gain of at least 0.5 percentage points over each matched control, with a molecule-cluster 95% interval above zero. The controls are ProbeNoUpdate and ProbeIndependentResidual. Action change alone establishes implementation behavior.




Figure 2: The terminal feedback contract. At decision tick t, the selector sees S_t and A_t and chooses one provider before any current output is observed. The terminal record is split into output and runtime status; the frozen endpoint judge then yields chemical correctness only after termination. Runtime failure and chemical correctness form the selected terminal outcome, which waits in a selected-only queue until $\tau_t = t + 1 + D$. The relay update is visible to the first action at or after release; for $D = 0$, this is the next action.

4 Benchmark and Baselines

4.1 Two-layer benchmark contract

The primary benchmark has a public truth layer and a provider routing layer. The truth layer uses the Therapeutics Data Commons (TDC) BBB endpoint and its fixed label semantics and split archive [5]. The development manifest contains 722 BBB molecules with reference labels; 716 have complete cached outputs from the 33-provider Task36 panel. Canonical conflict groups are excluded under the project decision while raw conflict receipts remain available for audit. The old development panel overlaps the official BBB test by 147 canonical molecules and 235 scaffolds, so it cannot be called an untouched confirmation set.

The routing layer turns cached provider outputs into sequential decisions with a fixed registry, a dynamic eligible-menu mask, selected-only feedback, delayed release, and explicit failures. It is a project protocol grounded in public truth. Our primary study uses the fixed provider registry; 716 of 722 development molecules have 33 runtime-ok cells, while six molecules retain 144 explicit error cells. Eligible challengers may change through runtime gates. Provider arrival and version migration require separate protocols. Unknown truth stops the current single-call stream; verification and refusal require the separately specified E5 protocol. hERG and AMES remain extension targets pending endpoint and lineage audits.

4.2 Baselines and fairness

Table 1 fixes the role of each comparator. All deployable methods receive the same molecule, endpoint, menu, feature stratum, initialization permission, selected-only feedback, delay, and call budget. Full-panel labels are allowed only in fit-only warm starts, evaluator-only Oracle controls, or offline audits. The Oracle is never included in a deployable ranking.

The fairness record must include source commit, checkpoint or sealed-fit-state hash, feature and prior, fit-only warm start, feedback likelihood, delay, seed, budget, selection/update latency, state bytes, failure and unknown denominators, and license or audit-only status. Missing fields remain missing; an adapted baseline is not promoted by relabeling it as native.

5 Experimental Protocol and Matrix

The experiments are organized by questions rather than by implementation order. Every result uses raw JSONL, a configuration and input hash, per-event visibility and release fields, a source-tree identity, and an independent recovery script. Results are aggregated by molecule and scaffold cluster; individual event rows are not treated as independent samples.

5.1 Research questions

RQ1 (validity): Does the frozen panel contain context-dependent headroom over the fit-only incumbent?

RQ2 (comparison): Under selected-only delay, does MIRA-Relay improve future correctness at matched cost?

RQ3 (mechanism): Does released family residual feedback change exploitation beyond probes alone?

RQ4 (boundary/cost): How do delay, failures, exposure, verification, latency, memory, and confirmation affect the conclusion?

MIRA denotes the adaptation framework and MIRA-Relay the implementation specified here. FamilyGuard is a mechanism condition within MIRA-Relay; ContextProbe and Provider-Graph Relay are stopped diagnostics and never enter the proposed-method row. Strict common-prior controls share its evaluation contract; historical Replay and adapted routers retain separate comparison strata.

Table 1: Baseline roles under the common routing contract. A row marked "adapted" is reported separately from strict matched comparisons until its likelihood and prior semantics are identical.

Role	Comparator	Question answered
Lower anchor	Random	Is there signal beyond blind selection?
Fixed anchor	Best Fixed	What does a fit-only incumbent achieve?
Privileged upper bound	Oracle	How much panel headroom exists with all outputs visible?
Static control	Frozen selector	Does representation plus fit-time mapping suffice?
Matched online	Online SGD	Does ordinary selected-only updating help under the strict contract?
Separate control	Replay SGD (separate-control)	Does a prior-compatible historical replay provide a useful secondary check?
Contextual control	Greedy LinUCB	Does standard optimism help under the same contract?
Modern adapted	PILOT, BayesianRouter	How do recent router ideas transfer when adapted faithfully?
Evidence controls	Independent / Frozen Joint	Does provider dependence or online updating add value beyond the same evidence model?
Audit-only modern	GraphRouter (audit-only; currently blocked)	Can graph routing be audited without post-hoc tuning?
Task controls	Direct property predictor; confidence threshold	Is gain from routing or from recovering the endpoint / post-call risk?
Proposed method	MIRA-Relay	Does shared residual feedback add exploitation value beyond probe cost?

5.2 Pre-registered matrix

Table 2 is the complete matrix for the first paper build. Cells remain TBD until the corresponding frozen receipt exists. E6 remains blocked until method, baselines, menus, thresholds, and epochs are frozen.

E2a is the strict common-prior comparison; E2b retains Replay as a separate historical control, and E2c reports adapted likelihood/prior strata separately. E3 shares probe randomness, order, and clock; delay may still change actions, so contrasts are whole-policy paired effects. Family-macro results account for related providers. E4a is controlled stress, while E4b is the bounded evidence extension and must use the same call budget across methods. Natural arrival, retirement, version change, and drift remain BLOCKED without a frozen trace.

6 Results: Pre-results Tables

This section reserves the result views; cells remain open until the corresponding receipts close.

Main comparison template. On the frozen E2a receipt, MIRA-Relay will be reported at **[RESULT]** system success versus **[RESULT]** for Frozen, with a paired scaffold-cluster interval of **[RESULT]** and **[RESULT]** additional calls per episode. The strongest matched online control is **[RESULT]**; its difference from MIRA-Relay is **[RESULT]**. We will interpret the result as an adaptation gain only if the interval, failure denominator, and independent recovery all pass the pre-registered gates. Otherwise this paragraph will state the observed boundary and retain the method as a protocol-level result.

7 Error and Cost Analysis

The paper will report errors by provider family, endpoint, scaffold group, runtime status, and feedback visibility. A wrong terminal prediction, a provider execution failure, an unknown truth, and an intentional refusal are different events and remain in separate denominators. For each adaptive method we will show both-correct, both-wrong, rescued, harmed, and switch-away counts relative to the fit-only incumbent. This decomposition is necessary because a small pooled accuracy change can hide a large number of harmful switches.

The cost table will include provider calls, probe rate, selection and update p50/p95, peak serialized state, and recovery time. Python replay time is reported as policy computation cost; it is not presented as provider money, token, or wall-clock service latency. Verification and escalation report their extra-call distribution and break-even utility thresholds. TBD values will be filled only from the raw event ledger.

8 Limitations and Discussion

The benchmark separates public answer semantics from the project routing protocol. This makes the provider-selection question replayable, but it does not make the routing layer a community benchmark by itself. The principal development endpoint is BBB; hERG and AMES remain extensions until their assay semantics, coverage, conflicts, and provider training lineage are closed. The current provider panel also contains related model families, so provider-count improvements cannot be interpreted as independent evidence without family-balanced analysis.

The proposed method is scoped to feedback-adaptive selection. A delayed selected-only replay does not by itself demonstrate natural provider arrival, retirement, version drift, or broad nonstationarity. Those events are controlled stress unless an independent deployment trace supports a stronger claim. An immutable fallback is a reference and guardrail, not a theorem that no switch can be harmful.

The method may fail when probes seldom reach related providers, when a residual update is too small to change the next choice, or when sharing transfers an error in the wrong direction. These alternatives motivate exposure, score-margin, and rescued/harmed analyses. A failed candidate remains evidence for revising the mechanism; it does not establish the project's target improvement or justify replacing that target with a protocol-only conclusion.

Table 2: Pre-registered experiment matrix. "TBD" is an intentional placeholder in this internal draft, not a missing value silently filled from a development diagnostic.

ID / RQ	Setting	Comparators / intervention	Primary measurements	Status
E1 / RQ1	BBB development, scaffold folds, fit-only panel	Random, Best Fixed, Oracle, Frozen	OOF correctness, headroom, family macro, conflict and failure counts	TBD
E2a / RQ2	selected-only online, delay $\{0, 1, 4\}$; strict common-prior logistic	Frozen, Matched Online SGD, MIRA-Relay	prequential correctness, paired CI, calls, update p50/p95	TBD
E2b / RQ2	same task; historical separate-control receipt	Replay SGD only against its own historical Frozen/control	descriptive paired effect, prior lineage, failure and cost fields	TBD
E2c / RQ2	same task; adapted likelihood/prior strata	Gaussian reward-ridge, LinUCB, PILOT, BayesianRouter	within-stratum paired effect, likelihood/prior, cost and missing fields	TBD
E3 / RQ3	same schedule and menu	NoProbeShield vs ProbeNoUpdate vs ProbeIndependentResidual vs MIRA-Relay; family/provider permutation	release-after action change, paired system-success, harmed/rescued, switch-away, runtime failure	TBD
E4a / RQ4	controlled feedback-adaptive events	transient/persistent failures, family-balanced exposure, delays, runtime blocks	recovery time, exposure, failure ledger, delay sensitivity, negative controls	TBD
E4b / RQ4	one-step evidence extension	Independent Evidence, Frozen Joint, MIRA planner, fixed cascade, matched random escalation	accept/call/refuse utility, calls, rescued/harmed, calibration	TBD
E4c / RQ4	natural lifecycle scope, only if separately frozen	provider arrival, retirement, version shift, or observed drift; otherwise BLOCKED	lifecycle-specific recovery and frozen comparison; never shares controlled-event denominator	BLOCKED / TBD
E5 / RQ4	full accounting and cost	confidence threshold, always/never verification, direct-property control	system success; conditional metric only when emitted; calls, refusal utility, unknowns, latency, memory, recovery	TBD
E6 / RQ4	molecule- or scaffold-disjoint confirmation	all frozen deployable methods and controls	pre-registered primary metric and interval; no label feedback to tuning	BLOCKED / TBD

9 Related Work

Tool-using agents learn to call external APIs and execute actions, but their training objectives generally do not impose a selected-only correctness clock [10, 12]. Our task instead treats the provider call as an online decision whose outcome may be delayed and whose correctness is tied to an independently auditable scientific endpoint.

Contextual bandits provide the natural language for choosing an action from a context before observing its reward. LinUCB [7] and contextual Thompson sampling [1] are canonical controls, while warm-start methods study how prior data can reduce the cost of early exploration [8]. Delayed-feedback analyses show that the release clock changes online learning even when the action space is unchanged [6]. MIRA-Relay uses these ideas as baselines and contracts; its proposed difference is the explicit separation of immutable fallback, family-shared residual evidence, runtime hazard, and result-independent probe coverage in a scientific tool menu.

Recent model-routing work studies static or online selection among language models, including budget-aware adaptive routing [9], graph-based selection [3], dual-contrastive routing [2], and benchmark frameworks for multi-model routing [4]. Those systems provide useful modern comparators, but their usual feedback is a preference or task score for the selected response and their provider panels are language-model panels. We retain adapted versions only when their input features, prior, feedback, and budget can be audited under the pharmaceutical contract; GraphRouter is audit-only if its graph input semantics cannot be preserved.

Finally, molecular benchmark work emphasizes public task definitions and reproducible datasets [5, 11]. Pharmaceutical providers are correlated predictors with different training lineages, so the present study reports family sensitivity and training-membership limits rather than treating every cached model as an independent truth source.

10 Conclusion

Adapting scientific tool use requires connecting a released outcome to a better subsequent decision. MIRA-Relay makes that connection testable through shared residuals, a fixed reference, and explicit feedback timing. The experiment matrix separates comparative utility from state changes, probe coverage, and verification cost.

Table 5: One-step evidence decisions. The planner may accept the current posterior, refuse, or call one additional provider. All methods use the same first-call output, call cost, refusal cost, and evidence budget.

Planner	Calls	Refusal rate	System utility	Rescued / harmed
Always accept	TBD	TBD	TBD	TBD
Fixed cascade	TBD	TBD	TBD	TBD
Independent Evidence	TBD	TBD	TBD	TBD
Frozen Joint Evidence	TBD	TBD	TBD	TBD
MIRA one-step planner	TBD	TBD	TBD	TBD

Table 3: Development comparisons by eligibility stratum. N counts scored decisions; calls counts all invocations. Fail/U/R denote execution failures, unknown truth, and refusals. Strict Δ uses the same-receipt Frozen control; other strata must name their own control. Intervals use paired scaffold-cluster resampling. Cells await recovery.

Method	N/ calls	Success	Paired Δ (95% CI)	Fail/U/R	Update p95
Random (anchor)	TBD	TBD	TBD	TBD	TBD
Best Fixed (anchor)	TBD	TBD	TBD	TBD	TBD
Frozen (strict)	TBD	TBD	0	TBD	TBD
Online SGD (strict)	TBD	TBD	TBD	TBD	TBD
MIRA-Relay (candidate)	TBD	TBD	TBD	TBD	TBD
Replay SGD (separate)	TBD	TBD	TBD	TBD	TBD
Greedy LinUCB (adapted)	TBD	TBD	TBD	TBD	TBD
PILOT (adapted)	TBD	TBD	TBD	TBD	TBD
Bayesian Router (adapted)	TBD	TBD	TBD	TBD	TBD

Table 4: Mechanism analysis within each scope and delay. Changes count post-release exploitation changes, excluding direct probes. Rescued/harmed counts use the fit-only incumbent. Paired effects use ProbeNoUpdate as the mechanism control and scaffold-cluster intervals. N counts scored decisions.

Scope / delay	N	Probes	Changes	Rescued / harmed	Paired Δ (95% CI)
NoProbeShield / D	TBD	TBD	TBD	TBD	TBD
ProbeNo Update / D	TBD	TBD	TBD	TBD	TBD
Independent residual / D	TBD	TBD	TBD	TBD	TBD
MIRA-Relay / D	TBD	TBD	TBD	TBD	TBD
Family permutation / D	TBD	TBD	TBD	TBD	TBD

Establishing the target improvement requires completing those comparisons and frozen confirmation.

References

[1] Shipra Agrawal and Navin Goyal. 2013. Thompson Sampling for Contextual Bandits with Linear Payoffs. In *Proceedings of the 30th International Conference on Machine Learning*. 127–135.

[2] Shuhao Chen, Weisen Jiang, Baijiong Lin, James T. Kwok, and Yu Zhang. 2024. RouterDC: Query-Based Router by Dual Contrastive Learning for Assembling Large Language Models. In *Advances in Neural Information Processing Systems*.

[3] Tao Feng, Yanzhen Shen, and Jiaxuan You. 2025. GraphRouter: A Graph-based Router for LLM Selections. In *International Conference on Learning Representations*.

[4] Qitian Jason Hu, Jacob Bieker, Xiuyu Li, Nan Jiang, Benjamin Keigwin, Gaurav Ranganath, Kurt Keutzer, and Shriyash Kaustubh Upadhyay. 2024. RouterBench: A Benchmark for Multi-LLM Routing System. *arXiv preprint arXiv:2403.12031* (2024).

[5] Kexin Huang, Ting Fu, Lucas M. Glass, Marinka Zitnik, Cao Xiao, and Jimeng Sun. 2021. Therapeutics Data Commons: Machine Learning Datasets and Tasks for Drug Discovery and Development. In *Advances in Neural Information Processing Systems, Datasets and Benchmarks Track*.

[6] Pooria Joulani, Andras Gyorgy, and Csaba Szepesvari. 2013. Online Learning under Delayed Feedback. In *Proceedings of the 30th International Conference on Machine Learning*. 1453–1461.

[7] Lihong Li, Wei Chu, John Langford, and Robert E. Schapire. 2010. A Contextual-Bandit Approach to Personalized News Article Recommendation. In *Proceedings of the 19th International Conference on World Wide Web*. 661–670. doi:10.1145/1772690.1772758

[8] Bastian Oetomo, R. Malinga Perera, Renata Borovica-Gajic, and Benjamin I. P. Rubinstein. 2023. Cutting to the Chase with Warm-Start Contextual Bandits. *Knowledge and Information Systems* 65, 9 (2023), 3533–3565.

[9] Pranoy Panda, Raghav Magazine, Chaitanya Devaguptapu, Sho Takemori, and Vishal Sharma. 2025. Adaptive LLM Routing under Budget Constraints. In *Findings of the Association for Computational Linguistics: EMNLP 2025*. 23934–23949. doi:10.18653/v1/2025.findings-emnlp.1301

[10] Timo Schick, Jane Dwivedi-Yu, Roberto Dessi, Roberta Raileanu, Maria Lomeli, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. 2023. Toolformer: Language Models Can Teach Themselves to Use Tools. In *Advances in Neural Information Processing Systems*.

[11] Zhenqin Wu, Bharath Ramsundar, Evan N. Feinberg, Nathan Gomes, Caleb Geniesse, Aneesh S. Pappu, Adele Leswing, and Vijay Pande. 2018. MoleculeNet: A Benchmark for Molecular Machine Learning. *Chemical Science* 9, 2 (2018), 513–530. doi:10.1039/C7SC02664A

[12] Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2023. ReAct: Synergizing Reasoning and Acting in Language Models. In *International Conference on Learning Representations*.