



Conditional Resource Creation

Terraform-Intermediate-Day1 – Module1

Learning Objectives

By the end of this module you will understand:

- How to make Terraform choose between two options automatically
- How to use feature flags to create optional resources only when needed
- How to safely display information about resources that might not exist

Why Do We Need Conditional Logic?

Imagine you're setting up infrastructure for two environments: dev and staging.

Each environment has different needs:

- **dev** is for developers to test code quickly. It doesn't need a database server, uses the smallest (cheapest) instance size, and has small storage.
- **staging** is for testing before release. It needs a database server, uses a larger instance, and has more storage.

The Problem: With basic variables and tfvars, you can parameterize values – but what if you need to skip creating a resource entirely in some environments? Or choose between two completely different values based on a condition?

Why Do We Need Conditional Logic?

The Solution: Conditional expressions let your configuration make decisions automatically - creating or skipping resources, and selecting values based on conditions.

Quick Note: Locals

Before we dive into conditionals, you'll see **local.** references in the examples below. Locals are internal values you define once and reuse throughout your configuration.

```
locals {  
  environment = terraform.workspace # Gets the current workspace name  
  name_prefix = "myapp-${local.environment}"  
}
```

- Define them in a **locals** block
- Reference them with **local.** prefix (e.g., **local.environment**)

Think of locals as a way to calculate a value once and give it a name you can use everywhere.

The Ternary Operator (Inline If-Else)

The ternary operator lets Terraform pick between two options based on a true/false condition.

```
condition ? value_if_condition_is_true : value_if_condition_is_false
```

What Counts as True or False?

The Ternary Operator (Inline If-Else)

In Terraform, conditions evaluate to either true or false:

- **Boolean values:** true is true, false is false
- **Comparisons:** `var.environment == "staging"` is true only when environment equals "staging"
- **Not equal:** `var.environment != "dev"` is true when environment is anything other than "dev"

Example: Choose an instance type based on whether we're in staging:

```
instance_type = var.environment == "staging" ? "t3.small" : "t3.nano"
```

The Ternary Operator (Inline If-Else)

Let's break down each part: `(instance_type = var.environment == "staging" ? "t3.small" : "t3.nano")`

- `var.environment == "staging"` - This is the condition (true when environment equals "staging")
- `?` - This symbol means "if true, use the next value"
- `"t3.small"` - This is the value used when the condition is true
- `:` - This symbol means "otherwise, use this instead"
- `"t3.nano"` - This is the value used when the condition is false

This says: "If environment equals staging, use t3.small. Otherwise, use t3.nano."

Choosing storage size:

```
volume_size = var.environment == "staging" ? 20 : 10
```

This says: "If environment equals staging, use 20 GB. Otherwise, use 10 GB."

Using count to Create or Skip Resources

The count setting controls how many copies of a resource Terraform creates:

- `count = 1` means "create this resource" (one copy)
- `count = 0` means "don't create this resource at all" (zero copies)

The Pattern

We combine `count` with the ternary operator:

```
resource "aws_instance" "db" {  
  count = var.enable_db ? 1 : 0  
  ami = data.aws_ami.amazon_linux.id  
  instance_type = "t3.micro"  
}
```

This says: "If `enable_db` is true, create 1 instance. If false, create 0 instances (skip it)."

How It Works Step by Step

When `var.enable_db = true`:

- Terraform evaluates `true ? 1 : 0`
- The condition is true, so it picks the first value: `1`
- `count = 1` tells Terraform to create the resource

When `var.enable_db = false`:

- Terraform evaluates `false ? 1 : 0`
- The condition is false, so it picks the second value: `0`
- `count = 0` tells Terraform to skip this resource completely

Referencing Resources That Use count

- When you add `count` to a resource, Terraform prepares to potentially create multiple copies (0, 1, 2, or more).
- To handle this, it stores the resource as a list.
- Even with `count = 1`, you get a list containing one item - that's why you need `[0]` to access it:

```
security_group_id = aws_security_group.db[0].id
```

The `[0]` means "get the first item in the list" (lists start counting at 0, not 1).

Warning: If `count = 0`, there is no first item - the list is empty! Trying to access `[0]` would cause an error.

We'll learn how to handle this safely in the "Conditional Outputs" section.

Feature Flags: On/Off Switches for Resources

A feature flag is simply a true/false variable that acts like a light switch - it turns a feature on or off.

Creating a Feature Flag

```
variable "enable_db_instance" {  
    description = "Enable optional database EC2 instance"  
    type = bool  
    default = false  
}
```

This creates an on/off switch called `enable_db_instance`. By default, it's off (`false`).

Using Feature Flags

You can use the same feature flag to control multiple related resources:

```
# Security group - only created when DB is enabled
resource "aws_security_group" "db_sg" {
  count = var.enable_db_instance ? 1 : 0
  name = "${local.name_prefix}-db-sg"
  description = "Security group for database server"
}

# DB instance - only created when DB is enabled
resource "aws_instance" "db" {
  count = var.enable_db_instance ? 1 : 0
  ami = data.aws_ami.amazon_linux.id
  instance_type = "t3.micro"
  vpc_security_group_ids = [aws_security_group.db_sg[0].id]
}
```

Using Feature Flags

Both the security group and the database instance use the same condition (`count = var.enable_db_instance ? 1 : 0`), so they're always created together or skipped together.

Important: When a resource uses `count = 1`, you must reference it with `[0]` to access the first (and only) instance:

```
vpc_security_group_ids = [aws_security_group.db_sg[0].id]
```

Setting Feature Flags in tfvars Files

You can set different values for different environments:

dev.tfvars:

```
enable_db_instance = false
```

Dev doesn't need a database, so the switch is off.

staging.tfvars:

```
enable_db_instance = true
```

Staging doesn't need a database, so the switch is on.

Conditional Outputs: Safely Showing Information

Outputs display information after Terraform runs. But what if you want to show information about a resource that might not exist?

The Problem

If a resource wasn't created (because `count = 0`), trying to access it causes an error:

```
# This FAILS when the database wasn't created
output "db_instance_id" {
  value = aws_instance.db[o].id # Error! There's no [o] because the list is empty
}
```


Conditional Outputs: Safely Showing Information

The Solution:

Use the same condition that controls whether the resource exists:

```
output "db_instance_id" {  
    description = "DB instance ID (shows null if database wasn't created)"  
    value = var.enable_db_instance ? aws_instance.db[o].id : null  
}
```

This says: "If the database is enabled, show the ID. Otherwise, show null (nothing)."

How it works:

- If `enable_db_instance = true`, the database exists, so it's safe to access `[0]`
- If `enable_db_instance = false`, the database doesn't exist, so we show `null` instead of causing an error

Key Takeaways

1. **The ternary operator** (`condition ? value_if_true : value_if_false`) lets Terraform choose between two options automatically
2. **count = 0 or 1** controls whether a resource is created or skipped completely
3. **Feature flags** are on/off switches (true/false variables) that control optional resources
4. **Conditional outputs** must use the same condition as the resource to avoid errors when the resource doesn't exist
5. **Related resources** (like a database and its security group) should use the same switch so they're always created or skipped together

Knowledge Check

Question 1

What does this expression give you when `var.environment = "dev"`?

```
instance_type = var.environment == "staging" ? "t3.small" : "t3.nano"
```

- A. "t3.small"
- B. "t3.nano"
- C. "dev"
- D. Error

Answer: B (t3.nano)

Knowledge Check

Question 2

What happens when you set `count = 0` on a resource?

- A) Creates a zero-sized resource
- B) Creates one resource with empty values
- C) Terraform shows an error
- D) The resource is not created at all

Answer: D `count = 0` means "create zero copies" - the resource is completely skipped and won't exist.

Knowledge Check

Question 3

Why must conditional outputs use the same condition as the resource?

```
resource "aws_instance" "db" {  
    count = var.enable_db ? 1 : 0  
    # ...  
}  
output "db_id" {  
    value = var.enable_db ? aws_instance.db[0].id : null  
}
```

- A) To make the code easier to read
- B) Because `[0]` doesn't exist when `count = 0`, which would cause an error
- C) Because Terraform requires it
- D) To make Terraform run faster

Answer: B - When `count = 0`, the resource list is empty (nothing was created). Trying to get `[0]` (the first item) from an empty list causes an error. The ternary operator checks first, so we only try to access `[0]` when we know the resource exists.