

# Rajalakshmi Engineering College

Name: Sherwin G M  
Email: 240701496@rajalakshmi.edu.in  
Roll no: 240701496  
Phone: 7708605966  
Branch: REC  
Department: I CSE FD  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 1

Attempt : 2  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Janani is a tech enthusiast who loves working with polynomials. She wants to create a program that can add polynomial coefficients and provide the sum of their coefficients.

The polynomials will be represented as a linked list, where each node of the linked list contains a coefficient and an exponent. The polynomial is represented in the standard form with descending order of exponents.

##### ***Input Format***

The first line of input consists of an integer  $n$ , representing the number of terms in the first polynomial.

The following  $n$  lines of input consist of two integers each: the coefficient and the exponent of the term in the first polynomial.

The next line of input consists of an integer m, representing the number of terms in the second polynomial.

The following m lines of input consist of two integers each: the coefficient and the exponent of the term in the second polynomial.

### **Output Format**

The output prints the sum of the coefficients of the polynomials.

### **Sample Test Case**

Input: 3

2 2

3 1

4 0

3

2 2

3 1

4 0

Output: 18

### **Answer**

```
// You are using GCC
```

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
typedef struct Node
```

```
{
```

```
    int data1;
```

```
    int data2;
```

```
    struct Node* next;
```

```
}node;
```

```
void inserting(node*list,int poly1,int poly2)
```

```
{
```

```
    node * newnode=(node*)malloc(sizeof(node));
```

```
    if(!newnode) return;
```

```
    newnode->data1=poly1;
```

```
    newnode->data2=poly2;
```

```
    node* temp=list;
```

```
    while(temp->next!=NULL)
```

```
    {
```

```

        temp=temp->next;
    }
    newnode->next=temp->next;
    temp->next=newnode;
}
int main()
{
    int e1,e2,n1,n2,i;
    scanf("%d",&n1);
    node* head=(node*)malloc(sizeof(node));
    head->next=NULL;
    for(i=0;i<n1;i++)
    {
        scanf("%d %d",&e1,&e2);
        inserting(head,e1,e2);
    }
    scanf("%d",&n2);
    node* head1=(node*)malloc(sizeof(node));
    head1->next=NULL;
    for(i =0;i<n2;i++)
    {
        scanf("%d %d",&e1,&e2);
        inserting(head1,e1,e2);
    }
    int sum=0;
    node* temp=head->next;
    while(temp!=NULL)
    {
        sum+=temp->data1;
        temp=temp->next;
    }
    temp=head1->next;
    while(temp!=NULL)
    {
        sum+=temp->data1;
        temp=temp->next;
    }
    printf("%d",sum);
}

```

**Status :** Correct

**Marks :** 10/10