

Rajalakshmi Engineering College

Name: Sherwin G M
Email: 240701496@rajalakshmi.edu.in
Roll no: 240701496
Phone: 7708605966
Branch: REC
Department: I CSE FD
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 6_COD_Question 3

Attempt : 1
Total Mark : 10
Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

You are the lead developer of a text-processing application that assists writers in organizing their thoughts. One crucial feature is a character-sorting service that helps users highlight the most critical elements of their text.

To achieve this, you decide to enhance the service to sort characters in descending order using the Quick-Sort algorithm. Implement the algorithm to efficiently rearrange the characters, ensuring that it is sorted in descending order.

Input Format

The first line of the input consists of a positive integer value N, representing the number of characters to be sorted.

The second line of input consists of N space-separated lowercase alphabetical characters.

Output Format

The output displays the set of alphabetical characters, sorted in descending order.

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 5

a d g j k

Output: k j g d a

Answer

```
#include <stdio.h>
```

```
#include <string.h>
```

```
// You are using GCC
```

```
void swap(char* a, char* b) {
```

```
    //Type your code here
```

```
    char temp;
```

```
    temp=*a;
```

```
    *a=*b;
```

```
    *b=temp;
```

```
}
```

```
int partition(char arr[], int low, int high) {
```

```
    //Type your code here
```

```
    char pivot=arr[low];
```

```
    int l=low;
```

```
    int u=high;
```

```
    while(l<u)
```

```
    {
```

```
        while(arr[l]>=pivot)
```

```
        {
```

```
            l++;
```

```
        }
```

```

        while(arr[u]<pivot)
        {
            u--;
        }
        if(l<u)
        {
            swap(&arr[l],&arr[u]);
        }
    }
    swap(&arr[low],&arr[u]);
    return u;
}

```

```

void quicksort(char arr[], int low, int high) {
    //Type your code here
    if(low<high)
    {
        int part=partition(arr,low,high);
        quicksort(arr,low,part-1);
        quicksort(arr,part+1,high);
    }
}

```

```

int main() {
    int n;
    scanf("%d", &n);

    char characters[n];

    for (int i = 0; i < n; i++) {
        char input;
        scanf(" %c", &input);
        characters[i] = input;
    }

    quicksort(characters, 0, n - 1);

    for (int i = 0; i < n; i++) {
        printf("%c ", characters[i]);
    }

    return 0;
}

```

Status : Correct

Marks : 10/10